

Lisp

Functional Programming

Jens Egholm Pedersen and Anders Kalhauge



Spring 2017

Lambda calculus

Lisp syntax

Exercises 1

Higher order functions

Lisp syntax

Exercises 2

Map and flat map

Hand-in

A computer is a thing that follows an algorithm = computation.

A computer is a thing that follows an algorithm = computation.

What can be computed?

A computer is a thing that follows an algorithm = computation.

What can be computed? Memory!

A computer is a thing that follows an algorithm = computation.

What can be computed? Memory!

A computer basically treats your applications as memory.

A computer is a thing that follows an algorithm = computation.

What can be computed? Memory!

A computer basically treats your applications as memory.

If we can treat functions as memory, they simply become data

Invented by Alonzo Church in the 1930. *Before* computers!

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped* to $x^2 + y^2$.

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped to* $x^2 + y^2$.

$$x \mapsto (y \mapsto x^2 + y^2)$$

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped to* $x^2 + y^2$.

$$x \mapsto (y \mapsto x^2 + y^2)$$

$$f(5)(2) = 29$$

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped to* $x^2 + y^2$.

$$x \mapsto (y \mapsto x^2 + y^2)$$

$$f(5)(2) = 29$$

$$f(5) = ??$$

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped to* $x^2 + y^2$.

$$x \mapsto (y \mapsto x^2 + y^2)$$

$$f(5)(2) = 29$$

$$f(5) = ??$$

$$f(5) = y \mapsto y^2 + 25$$

Invented by Alonzo Church in the 1930. *Before* computers!

$$\text{square_sum}(x, y) = x^2 + y^2$$

$(x, y) \mapsto x^2 + y^2$ The pair x and y is *mapped to* $x^2 + y^2$.

$$x \mapsto (y \mapsto x^2 + y^2)$$

$$f(5)(2) = 29$$

$$f(5) = ??$$

$$f(5) = y \mapsto y^2 + 25 = \lambda y. y^2 + 25$$

A function that either:

- Takes a function as an argument
- Returns a function as its result

A function that either:

- Takes a function as an argument
- Returns a function as its result

First part: Returning a function

A function that either:

- Takes a function as an argument
- Returns a function as its result

First part: Returning a function

$$x \mapsto (y \mapsto x + y)$$

Boolean T and nil

Boolean T and nil

Conditional (if expr then else) (if (= 0 0) x y)

Boolean	T and nil	
Conditional	(if expr then else)	(if (= 0 0) x y)
Lists	(list elements) or (cons tail)	(list 1 2) or (cons 1 (cons 2 nil)))

Boolean	T and nil	
Conditional	(if expr then else)	(if (= 0 0) x y)
Lists	(list elements) or	
	(cons tail)	(list 1 2) or (cons 1 (cons 2 nil)))
Let binding	(let ((variables)) (body))	(let ((a 10)) a)

Boolean	T and nil	
Conditional	(if expr then else)	(if (= 0 0) x y)
Lists	(list elements) or	
	(cons tail)	(list 1 2) or (cons 1 (cons 2 nil)))
Let binding	(let ((variables)) (body))	(let ((a 10)) a)
Functions	(defun name (arguments) body)	(defun sum (a b) (+ a b))

Boolean	T and nil	
Conditional	(if expr then else)	(if (= 0 0) x y)
Lists	(list elements) or	
	(cons tail)	(list 1 2) or (cons 1 (cons 2 nil)))
Let binding	(let ((variables)) (body))	(let ((a 10)) a)
Functions	(defun name (arguments) body)	(defun sum (a b) (+ a b))
Lambda	(lambda (arguments) body)	
		(lambda (a b) (+ a b))

Lambdas are simply just functions without a name

Lambdas are simply just functions without a name

Lambdas are defined as `(lambda (arguments) body)`

Lambdas are simply just functions without a name

Lambdas are defined as `(lambda (arguments) body)` `(lambda (a) (+ a 2))`

To avoid confusing them with normal functions, use `funcall` to call them

Lambdas are simply just functions without a name

Lambdas are defined as `(lambda (arguments) body)` `(lambda (a) (+ a 2))`

To avoid confusing them with normal functions, use `funcall` to call them

```
(funcall (lambda a (+ a 2)) 5)
```

Clone the `lisp-exercises` from
`cphbus-functional-programming`

`https://github.com/cphbus-functional-programming/
lisp-exercises`

Work on the `lambda.lisp` file

- Series of instructions

- Series of instructions
- Variables in memory

- Series of instructions
- Variables in memory = global state

- Series of instructions
- Variables in memory = global state
- Seen in a CPU

- Series of instructions
- Variables in memory = global state
- Seen in a CPU
- Interacts with side-effects

State = The values in your memory

State = The values in your memory

Mutability = Changing state

State = The values in your memory

Mutability = Changing state

Side effects = Behaviour outside scope

State = The values in your memory

Mutability = Changing state

Side effects = Behaviour outside scope

Mutability + Concurrency =

State = The values in your memory

Mutability = Changing state

Side effects = Behaviour outside scope

Mutability + Concurrency = Disaster

Mathematical functions does not have

- State

Mathematical functions does not have

- State
- Side effects

Mathematical functions does not have

- State
- Side effects

Data is changed using \mapsto - immutably

Mathematical functions does not have

- State
- Side effects

Data is changed using \mapsto - immutably

Immutability + concurrency =

Mathematical functions does not have

- State
- Side effects

Data is changed using \mapsto - immutably

Immutability + concurrency = World domination

Part two: Taking functions as input

Part two: Taking functions as input

Where could this be useful?

```
interface DoSomething {
    void something(int i) { ...}
}
```

```
interface DoSomething {  
    void something(Int i);  
}
```



```
interface DoSomething {  
    void something(Int i);  
}
```

```
interface List<T> {  
    ...  
    void foreach(DoSomething function)  
    ...  
}
```

Boolean	T and nil	
Conditional	(if expr then else)	(if (= 0 0) x y)
Lists	(list elements) or	
	(cons tail)	(list 1 2) or (cons 1 (cons 2 nil)))
Let binding	(let ((variables)) (body))	(let ((a 10)) a)
Functions	(defun name (arguments) body)	(defun sum (a b) (+ a b))
Lambda	(lambda (arguments)) body	(lambda (a b) (+ a b))

Clone the `lisp-exercises` from
`cphbus-functional-programming`

`https://github.com/cphbus-functional-programming/
lisp-exercises`

Work on the `function.lisp` file

What was common about the exercises?

Mapping from one side to the other.

$$\begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix} \mapsto \begin{bmatrix} 2 \\ 3 \\ 4 \end{bmatrix} \quad (1)$$

Mapping from one side to the other.

$$\begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix} \mapsto \begin{bmatrix} 2 \\ 3 \\ 4 \end{bmatrix} \quad (1)$$

$$\begin{bmatrix} 1 \\ 2 \\ 3 \end{bmatrix} \mapsto \begin{bmatrix} 5 \\ 6 \\ 7 \end{bmatrix} \quad (2)$$

Flattens a two dimensional list into one dimension

Flattens a two dimensional list into one dimension, and uses map on the output

Clone the `lisp-exercises` from
`cphbus-functional-programming`

`https://github.com/cphbus-functional-programming/
lisp-exercises`

Work on the hand-in in the `flatmap.lisp` file.

- Implement a `map` function
- Implement a `flatten` function
- Implement a `flatmap` function