

pfSense has detected a crash report or programming bug. [Click here for more information.](#)



System Information



Name	pfSense.joanlab.local
User	admin@10.0.8.2 (Local Database)
System	Microsoft Azure Netgate Device ID: 5b88956b522eb3177572
BIOS	Vendor: American Megatrends Inc. Version: 090008 Release Date: Fri Dec 7 2018 Boot Method: BIOS
Version	2.8.1-RELEASE (amd64) built on Wed May 13 14:43:00 CDT 2026 FreeBSD 15.0-CURRENT The system is on the latest version. Version information updated at Sat Jun 6 19:32:18 CDT 2026
CPU Type	Intel(R) Core(TM) i5-6500 CPU @ 3.20GHz AES-NI CPU Crypto: Yes (inactive) QAT Crypto: No
Hardware crypto	Inactive
Kernel PTI	Enabled
MDS Mitigation	Inactive
Uptime	19 Hours 09 Minutes 34 Seconds

Netgate Services And Support



Contract type Community Support
Community Support Only

NETGATE AND pfSense COMMUNITY SUPPORT RESOURCES

If you purchased your pfSense gateway firewall appliance from Netgate and elected **Community Support** at the point of sale or installed pfSense on your own hardware, you have access to various community support resources. This includes the **NETGATE RESOURCE LIBRARY**.

You also may upgrade to a Netgate Global Technical Assistance Center (TAC) Support subscription. We're always on! Our team is staffed 24x7x365 and committed to delivering enterprise-class, worldwide support at a price point that is more than competitive when compared to others in our space.

- **Upgrade Your Support**
 - Netgate Global Support FAQ
 - Netgate Professional Services
- **Community Support Resources**
 - Official pfSense Training by Netgate
 - Visit Netgate.com

If you decide to purchase a Netgate Global TAC Support subscription, you **MUST** have your **Netgate Device ID (NDI)** from your firewall in order to validate support for this

Current date/time	Sat Jun 6 19:33:08 CDT 2026
DNS server(s)	• 127.0.0.1 • ::1 • 192.168.100.1 • 8.8.8.8 • 8.8.4.4
Last config change	Fri Jun 5 17:08:33 CDT 2026
State table size	0% (56/96000) Show states
MBUF Usage	0% (708/1000000)
Load average	1.38, 1.05, 0.85
CPU usage	7%
Memory usage	43% of 968 MiB
SWAP usage	45% of 1024 MiB

Disks   			
Mount	Used	Size	Usage
> /	976M	109G	1% of 109G (zfs)

unit. Write down your NDI and store it in a safe place. You can purchase TAC supports here.



Interfaces

 WAN		10Gbase-T <full-duplex>	192.168.4.124 fdd1:5520:b000:1:215:5dff:fe04:7e00
 LAN		10Gbase-T <full-duplex>	192.168.200.1
 LAB		10Gbase-T <full-duplex>	192.168.100.2

Snort Alerts

Interface/Time	Src/Dst Address	Description
LAN Jun 06 06:19:...	192.168.200.55:54712 23.51.25.137:80	(http_inspect) TOO MANY PIPELINED...
LAN Jun 06 06:17:...	192.168.200.55:54710 23.51.25.137:80	(http_inspect) TOO MANY PIPELINED...
LAN Jun 06 06:13:...	192.168.100.1:88 192.168.200.55:55529	(http_inspect) PROTOCOL-OTHER...
LAN Jun 06 06:13:...	192.168.100.1:88 192.168.200.55:55529	(http_inspect) NO CONTENT-LENGTH OR...
LAN Jun 06 06:13:...	192.168.100.1:88 192.168.200.55:55529	(http_inspect) PROTOCOL-OTHER...

