Git

```
# Git Documentation
# Git global setup
git config --global user.name "John Doe"
git config --global user.email
"johndoe@gmail.com"
# Clone and Edit a repository
git clone
qit@qit.example.com:repository/project.qit
cd project
touch README.md
git add README.md
git commit -m "add README"
git push -u origin master
# Convert existing folder to repo and push
cd existing_folder
git init
git remote add origin
qit@qitexample.com:repository/project.qit
git add .
git commit -m "Initial commit"
git push -u origin master
```

```
Git Secrets
# Git-Secrets prevents you from committing
secrets/credentials into git repositories
# Scan for secrets on each commit
git secrets -install /path/to/files
qit secrets -register-aws
# Scan file/folders for secrets
git secrets --scan /path/to/file
git secrets --scan -r /path/to/directory
# Adds a prohibited pattern to the current
repo:
git secrets --add '[A-Z0-9]{20}'
# Adds a prohibited pattern to the global git
config:
git secrets --add --global '[A-Z0-9]{20}'
# Add an allowed pattern:
git secrets --add -a 'allowed pattern'
```

Scout Suite

Scout Suite is a multi-cloud audit tool

```
# Install and configure
git clone https://github.com/nccgroup/ScoutSuite
cd ScoutSuite
sudo pip3 install -r requirements.txt
python3 scout.py --help #Check install

# Pull the latest ruleset
curl
https://raw.githubusercontent.com/nccgroup/Scout
Suite/master/ScoutSuite/providers/aws/rules/rule
sets/detailed.json > detailed-rules.json

# Run with the latest Ruleset
python3 scout.py aws --profile <profile> --
```

ruleset <ruleset>

Docker

```
# Docker Documentation
docker pull <image>:<tag>
docker build -f /path/dockerfile -t imagename .
docker image 1s
docker image rm <imageid>
docker commit containerid [REPOSITORY[:TAG]]
docker container ls -a
docker container prune
docker info
docker kill <containerid>
docker rm <containerid>
# Bulk Delete All Containers
docker ps -a -q | xargs -n 1 -I {} docker rm {}
# Run Containers in Detached Mode
docker run -d -p 80:80 myimage nginx -g 'daemon
off;'
# Run Interactive Containers with Mounted Files
docker run -v /hostpath:/containerpath -it
<image>:<tag>
docker save image:tag > image.tar
```



Cloud Security and DevOps "Fix Security Issues Left of Prod"

By Ross Young

Cheat Sheet v1.1.3

SANS.ORG/CLOUD-SECURITY

Docker Security Checks

Dockle - Check your Dockerfile against the CIS
Benchmarks with a Container Image Linter
Install Dockle
https://github.com/goodwithtech/dockle

dockle REPOSITORY/IMAGE:TAG
dockle --exit-code 1 -exit-level fatal
IMAGE:TAG

<u>Docker Scan</u> - Find Vulnerabilities within a Container Image

docker scan --file /Path/Dockerfile IMAGE:TAG

Container Vuln Scan (Excluding the Base Image) docker scan --file /Path/Dockerfile --exclude-base IMAGE:TAG

Dependency Tree

docker scan --dependency-tree IMAGE: TAG

Docker-Bench - Evaluate your Docker Engine
configuration against the CIS Benchmark
Install Go, then clone this repository
https://github.com/aquasecurity/docker-bench

go build -o docker-bench .

./docker-bench

Terraform Syntax

Arguments assign a value to a name.

```
Blocks are the configuration of an object
```

```
Expressions represent a value, either
literally or by referencing and combining
other values.
<BLOCK TYPE> "<BLOCK LABEL>" "<BLOCK</pre>
LABEL>" {
  # Block body
  <IDENTIFIER> = <EXPRESSION> # Argument
# Example:
resource "aws vpc" "main" {
  cidr block = var.base cidr block
```

CloudFormation (YAML Syntax)

```
Resources:
  Logical ID:
    Type: Resource type
    Properties:
      Set of properties
# Example
Resources:
 MyInstance:
    Type: "AWS::EC2::Instance"
    Properties:
      UserData:
        "Fn::Base64":
          ! Sub
            Queue=${MyQueue}
     AvailabilityZone: "us-east-la"
      ImageId: "ami-Off8a91507f77f867"
 MyQueue:
    Type: "AWS::SQS::Queue"
   Properties: {}
```

Infrastructure Scans (Terraform, CloudFormation, & Helm)

```
Terrascan is a misconfiguration scanner. It can scan
Terraform, Kubernetes, and other file types.
qit clone qit@qithub.com:accurics/terrascan.qit
cd terrascan
```

make build ./bin/terrascan terrascan scan -t aws

Find security misconfigurations in Helm Charts terrascan scan -I helm

Checkov looks for misconfigurations in files such as Terraform, Cloud Formation, and even Helm Charts.

pip install checkov checkov -f /path/example.tf

Find security misconfigurations in Helm Charts checkov -- framework kubernetes -d <template files>

CFN NAG looks for misconfigurations in CloudFormation templates.

gem install cfn-nag cfn nag scan --input-path <path to templates>

Azure Key Store

```
# Create a Resource Group
az group create --name "MyResourceGroup" -1 "EastUS"
# Create a new key in the keyvault
az keyvault create --name "<unique name>" --resource-
group "MyResourceGroup" --location "EastUS"
# Show details of a key vault
az keyvault show --name MyKeyVault
# List Azure Key Vaults
az keyvault list --resource-group "MyResourceGroup"
# Delete a Key Vault
az keyvault delete --name MyKeyVault --resource-group
MyResourceGroup
```

AWS Systems Manager Parameter Store

```
aws ssm put-parameter -- name MyParameter --
value "secret value" --type SecureString
aws ssm get-parameter -- name MyParameter --
with-decryption
```

Jenkins Integration

Scan is a free open-source audit tool for DevOps teams. It can perform:

- Credentials Scanning to detect accidental secret leaks
- Static Analysis Security Testing (SAST) for a range of languages and frameworks
- Open-source dependencies audit
- License violation checks

You can add the following stage to your Jenkinsfile (declarative syntax) for basic integrations

```
stages {
    stage('Scan') {
        agent {
            docker { image 'shiftleft/sast-scan' }
        steps {
            sh 'scan'
```



LONG COURSES

SEC488: Cloud Security Essentials SEC584: Cloud Native Security: Defending **Containers and Kubernetes** SEC510: Public Cloud Security: AWS, Azure, SEC522: Defending Web Applications
Security Essentials

SHORT COURSES

SEC534: Secure DevOps: A Practical

MGT520: Leading Cloud Security Design &