

UNIVERSITÉ DE GENÈVE

TECHNOLOGIES DU WEB SÉMANTIQUE

TP 1: Graphical rdfs - Marché de Carouge

Author: Léa Heiniger

E-mail: Lea-Marie.Heiniger@etu.unige.ch

Author: Joao Filipe Costa da Quinta

E-mail: Joao.Costa@etu.unige.ch

November 16, 2021



**UNIVERSITÉ
DE GENÈVE**

FACULTÉ DES SCIENCES
Département d'informatique

Introduction

The goal of this project is to make a description of a tourist area using URI data. To do this we must integrate data from various sources, mainly Open Street Map and DBpedia.

Selected Area

For this project we choose, Place du Marché Carouge. This a location that is full of life and incredible locations of leisure, there are very nice cafés, bars, restaurants and even a cinema. This locations is also very well located in the heart of the Commune de Carouge in Geneva, and it has near access to public transportation, so that anyone can access it easily.

For more detailed overview of the attractions of Place du Marché Carouge, one simply has to see the initial RDF schema in the next section !

Initial RDF schema




Figure 1: Initial RDF schema




Figure 3: Final RDF Graphin GraphDB

In this graph we can only see the immediate triplets to the center of the graph, however to get all information we need only to click a node, and all information will be displayed.

SPARQL Query

To show that our data is organised as intended as well as usable, one has to go no further than to do some SPARQL queries. SPARQL queries are used to get answers from a certain graph, in the same way one would use SQL queries to query a database. To use SPARQL we have to know its semantic rules, let's see some queries in action.

Hmm, what are the restaurants in the area ?

Let's assume a tourist in the area wants to see which restaurants are available, he has only to query our graph to get some answers.

```
1 PREFIX osm: <https://www.openstreetmap.org/>
2 PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
3 PREFIX ca: <https://www.carouge.ch/>
4 PREFIX dbp: <https://dbpedia.org/>
5 select ?y where {
6     {?x osm:restaurant ?y}
7     UNION
8     {?x ca:restaurant ?y}
9     UNION
10    {?x dbp:restaurant ?y} .
11 }
```

Figure 4: Query to ask for restaurants in the location

Because there are three different possible sources of restaurants, we must include all of them in the Query. This query results in the following :

1	osm:Café_du_Marché
2	osm:Brasserie_La_Bourse

Figure 5: Result of query to ask for restaurants in the location

We can easily check the result by checking the RDF graph in the previous section.

Hmm, how do we reach Cinema Bio

Let's assume a tourist in the area wants the contact and location of Cinema Bio.

```

1 PREFIX osm: <https://www.openstreetmap.org/>
2 PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
3 select ?x ?y where {
4     osm:Cinema_Bio ?x ?y .
5 }
```

Figure 6: Query to ask for data about Cinema Bio

This query results in the following :

1	osm:website	"http://www.cinema-bio.ch"
2	ca:email	"secretaire@cinema-bio.ch"
3	ca:phone	"022 301 54 43"
4	ca:fax	"022 301 54 42"
5	osm:addr	_:node0

Figure 7: Result of query to ask for data about Cinema Bio

We must do one additional Query, as the osm:addr is a blank node that might be the origin point of more triplets.

```

1 PREFIX osm: <https://www.openstreetmap.org/>
2 PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
3 PREFIX ca: <https://www.carouge.ch/>
4 PREFIX dbp: <https://dbpedia.org/>
5 select ?x ?y where {
6     ?o ?x ?y ;
7     {osm:Cinema_Bio osm:addr ?o} .
8 }
```

Figure 8: Query that returns the actual address of Cinema Bio

1	osm:city	dbp:Carouge
2	osm:country	dbp:CH
3	osm:housenumber	"47"
4	osm:postcode	"1227"
5	osm:street	"Rue Saint-Joseph"

Figure 9: Result of query that returns the actual address of Cinema Bio

We can easily check the result by checking the RDF graph in the previous section.

Hmm, what are the points of interest of a given street

Let's assume a tourist in the area wants to know what points of interest are in a given street, he has only to query our graph to get some answers.

```

1 PREFIX osm: <https://www.openstreetmap.org/>
2 PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
3 PREFIX ca: <https://www.carouge.ch/>
4 PREFIX dbp: <https://dbpedia.org/>
5 select ?x where {
6     {?x osm:addr ?y ;
7      ?y osm:street "Place du Marché" }}
8     UNION
9     {?x dbp:addr ?y ;
10      ?y dbp:street "Place du Marché" }}
11     UNION
12     {?x ca:addr ?y ;
13      ?y ca:street "Place du Marché" }} .
14

```

Figure 10: Query to ask for points of interest in the street Place du Marché

Because there are three different possible sources of restaurants, we must include all of them in the Query. This query results in the following :

1	osm:Café_du_Marché
2	osm:Brasserie_La_Bourse
3	osm:Bella_Mia
4	osm:Mairie_de_Carouge

Figure 11: Result of query to ask for points of interest in the street Place du Marché

We can easily check the result by checking the RDF graph in the previous section.