TST JUnit Testing Software Verification and Validation 2019–2020

João David Ye Yang 49448 49521

09/05/2020

1 Instruction Coverage

1.1 size()

```
public int size() {
   return n; //I1
}
```

Test Case	Values	Expected / Actual	IC
sizeZeroTest	-	0	I1

1.2 contains(String key)

```
public boolean contains(String key) {
   if (key == null)
      throw new IllegalArgumentException("argument to
            contains() is null");
   return get(key) != null;
}
```

Test Case	Values	Expected / Actual	IC
containsNullKey	null	IAE	I1, I2
containsNonNullKey	"someKey"	false	I1, I3

1.3 get(String key)

```
public T get(String key) {
  if (key == null)
    throw new IllegalArgumentException("calls get() with
        null argument");
  if (key.length() == 0)
    throw new IllegalArgumentException("key must have
        length >= 1");
  Node<T> x = get(root, key, 0);
  if (x == null)
    return null;
  return x.val;
}
```

Test Case	Values	Expected / Actual	IC
getNullKey	null	IAE	I1, I2
getEmptyStringKey	11 11	IAE	I1, I3, I4
getNonExistentKey	"someKey"	null	I1, I3, I5, I6, I7
getExistentKey	"key"	<value></value>	11, 13, 15, 16, 18

1.4 put(String key, T val)

```
public void put(String key, T val) {
  if (key == null)
    throw new IllegalArgumentException("calls put() with
        null key");
  if (!contains(key))
    n++;
  root = put(root, key, val, 0);
}
```

Test Case	Values	Expected / Actual	IC
putNullKey	null, 1	IAE	I1, I2
putValidNewKey	"someKey", 1	NoExep	I1, I3, I4, I5

1.5 longestPrefixOf(String query)

```
public String longestPrefixOf(String query) {
  if (query == null)
    throw new IllegalArgumentException("calls
       longestPrefixOf() with null argument");
  if (query.length() == 0)
    return null;
  int length = 0;
  Node<T> x = root;
  int i = 0;
  while (x != null && i < query.length()) {</pre>
    char c = query.charAt(i);
        (c < x.c) x = x.left;
    else if (c > x.c) x = x.right;
    else {
       i++;
      if (x.val != null)
         length = i;
       x = x.mid;
  return query.substring(0, length);
```

Test Case	Values	Expected / Actual	IC
longestPrefixOfNull	null	IAE	I1, I2
longestPrefixOfEmptyString	""	null	I1, I3, I4
longestPrefixOfAllInstructions	"c"	"c"	I1, I3, I5, I6, I7, I8, I9, I10, I11, I12, I13, I14, I15, I16, I17, I18, I19

1.6 keys()

```
public Iterable<String> keys() {
  Queue<String> queue = new LinkedList<>();
  collect(root, new StringBuilder(), queue);
  return queue;
}
```

Test Case	Values	Expected / Actual	IC
keysTest	-	Empty Iterator	I1, I2, I3

1.7 keysWithPrefix(String prefix)

Test Case	Values	Expected / Actual	IC
keysWithPrefixNull	null	IAE	I1, I2
keysWithPrefix NonExistentPrefix	"prefix"	Iterator (size 0)	11, 13, 14, 15, 16
keysWithPrefix ExistentPrefix	"c"	Iterator (size 1)	I1, I3, I4, I5, I6, I7, I8, I9, I10

1.8 keysThatMatch(String pattern)

```
public Iterable<String> keysThatMatch(String pattern) {
   Queue<String> queue = new LinkedList<>();
   collect(root, new StringBuilder(), 0, pattern, queue);
   return queue;
}
```

Test Case	Values	Expected / Actual	IC
keysThatMatchTest	"pattern"	Iterator (size 0)	I1, I2, I3

- 2 Edge Coverage
- 3 Prime Path Coverage
- 4 All-Uses Coverage
- 5 Logic-based Coverage

References

- [1] SiLK CERT NetSA https://tools.netsa.cert.org/silk/
 docs.html
- [2] List of TCP and UDP port numbers https://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers