

Lacirstat App Summary

What it is

Static, browser-based biostatistics toolkit for LACIR training. It loads statistical tests as independent front-end modules and helps users analyze spreadsheet-style or DATASUS-derived data with guided interpretation.

Who it's for

Primary persona: LACIR researchers, trainees, or health-study analysts who need a didactic interface to run common statistical tests from spreadsheets, Excel pastes, or DATASUS exports without a backend setup.

What it does

- Manifest-driven menu loads three test modules: Student's t, Pearson/Spearman correlation, and Prais-Winsten trend analysis.
- Accepts local tabular inputs including pasted Excel ranges, delimited text, and parser support for workbook tables in XLSX.
- Normalizes PT-BR numeric formats, decimal commas, delimiter/header patterns, and suspected mojibake/encoding issues.
- Provides empty/example templates and guided entry flows for supported analyses.
- Includes a DATASUS import/normalization wizard and reuses the last confirmed DATASUS session across modules.
- Runs calculations in the browser and renders previews, metrics, confidence intervals, classifications, and interpretation cards.

How it works

- UI shell: index.html loads assets/css/styles.css and assets/js/app.js.
- Loader flow: app.js fetches tests-manifest.json, builds navigation, fetches each module config.json, validates module.js, and dynamic-imports the selected module.
- Shared logic: app.js supplies browser-side utils, statistical functions, and shared DATASUS session state on window.__LACIR_SHARED__.
- Data helpers: tabular-data-input.js parses delimited text/XLSX; datasus-importer.js, datasus-normalizer.js, and datasus-wizard.js prepare DATASUS data.
- Feature modules live under tests/t-student, tests/correlacao, and tests/prais-winsten, each with local config and module code.
- Backend/services/API endpoints: Not found in repo.

How to run

- Serve the repo over HTTP/HTTPS; app.js blocks direct file:// loading and suggests GitHub Pages or a simple local server.
- Open the served index.html page in a browser.
- Pick a test from the left nav; the app then loads its local config.json and module.js files.
- Upload, paste, or sample-load data and run the analysis.
- Exact local start command or package script: Not found in repo.