# Introduction

# Introduction

TODO

# Graphics

# Graphics

Provides graphics operations, such as for drawing pixels and images on the screen.

#### Configuration

# GFX\_SET\_GRID

Enables or disables a visual grid delimiting the screen pixels.

```
output (bool) GFX_SET_GRID
```

- Parameters:
  - bool: new state
    - \* true: enables the grid
    - \* false: disables the grid

The ratio between the real and logical dimensions set with WINDOW\_SET\_SIZE must be greater then one.

#### GFX\_SET\_RGB

Changes the color of all subsequent drawing operations.

```
output (u8,u8,u8) GFX_SET_RGB
```

- Parameters:
  - u8: new red component
  - -u<br/>8: new green component
  - u8: new blue component

#### GFX\_SET\_TEXT\_CURSOR

Changes the cursor position for drawing text.

output (u16,u16) GFX\_SET\_TEXT\_CURSOR

- Parameters:
  - u16: new position in the x-axis
  - u16: new position in the y-axis

#### GFX\_SET\_TEXT\_FONT

Changes the font for drawing text.

output (string,u16) GFX\_SET\_TEXT\_FONT

- Parameters:
  - string: path for the .ttf font filename
  - u16: height of the new font in pixels

# **Drawing Operations**

#### GFX\_CLEAR

Clears the screen.

output (void) GFX\_CLEAR

The clear color is specified with GFX\_SET\_RGB.

# $GFX\_DRAW\_BMP$

Draws a bitmap image on the screen.

output (string,u16,u16) GFX\_DRAW\_BMP

- Parameters:
  - string: path for the .bmp image filename
  - u16: drawing position in the x-axis
  - u16: drawing position in the y-axis

#### GFX\_DRAW\_PIXEL

Draws a pixel on the screen.

output (u16,u16) GFX\_DRAW\_PIXEL

- Parameters:
  - u16: drawing position in the x-axis
  - u16: drawing position in the y-axis

The drawing color is specified with GFX\_SET\_RGB.

# $GFX\_DRAW\_RECT$

Draws a rectangle on the screen.

output (u16,u16,u16,u16) GFX\_DRAW\_RECT

- Parameters:
  - u16: drawing position in the x-axis
  - u16: drawing position in the y-axis
  - u16: rectangle width
  - u16: rectangle height

The drawing color is specified with GFX\_SET\_RGB.

#### $GFX\_DRAW\_TEXT$

Draws a text on the screen.

output (string) GFX\_DRAW\_TEXT

- Parameters:
  - string: text to draw

The drawing position is first specified with GFX\_SET\_TEXT\_CURSOR. The cursor advances automatically for the position after the text. The drawing font is specified with GFX\_SET\_TEXT\_FONT. The drawing color is specified with GFX\_SET\_RGB.

# $GFX\_DRAW\_TEXTLN$

Draws a line of text on the screen.

```
output (string) GFX_DRAW_TEXTLN
```

The drawing position is first specified with <code>GFX\_SET\_TEXT\_CURSOR</code>. The cursor advances automatically for the next line after the text, at the same initial position. The drawing font is specified with <code>GFX\_SET\_TEXT\_FONT</code>. The drawing color is specified with <code>GFX\_SET\_RGB</code>.

#### Other

#### GFX SCREENSHOT

Takes a screen shot.

output (string) GFX\_SCREENSHOT

- Parameters:
  - string: path for the .bmp image filename to generate

# Input Devices

# Input Devices

Provides input handling, such as for keyboard and mouse.

#### Keyboard

# KEY\_PRESS

input (bool,u16) KEY\_PRESS

- Occurrences:
  - whenever a keyboard key is pressed or released
- Payload:
  - bool: new key state
    - \* true: key is now pressed
    - \* false: key is now released
  - u16: numeric key code

TODO: key codes

### Mouse

# MOUSE\_CLICK

input (bool,int,u16,u16) MOUSE\_CLICK

- Occurrences:
  - whenever a mouse button is pressed or released
- Payload:
  - bool: new button state
    - \* true: button is now pressed
    - \* false: button is now released
  - int: numeric button code (TODO: left, middle, right?)
  - u16: current mouse position in the x-axis
  - u16: current mouse position in the y-axis

# MOUSE\_MOVE

input (u16,u16) MOUSE\_MOVE

- Occurrences:
  - whenever the mouse moves
- Payload:
  - u16: current mouse position in the x-axis

- u16: current mouse position in the y-axis

# Frame Management

# Frame Management

Manages the game frames, such as for updating animations and redrawing the screen.

# Configuration

# $FRAMES\_SET$

Enables or disables the generation of periodic FRAMES\_UPDATE and FRAMES\_REDRAW inputs to the application.

output (bool) FRAMES\_SET

- Parameters:
  - bool: new state
    - \* true: enables the generation of frames
    - \* false: disables the generation of frames

# FRAMES\_SET\_CLEAR\_RGB

Changes the redrawing background color.

output (u8,u8,u8) FRAMES\_SET\_CLEAR\_RGB

- Parameters:
  - u8: new red component
  - u8: new green component
  - u8: new blue component

On every frame before FRAMES\_REDRAW, the screen is cleared with the background color.

The default color is black.

# Update

#### FRAMES\_UPDATE

input (int) FRAMES\_UPDATE

- Occurrences:
  - on every frame, before FRAMES\_REDRAW

- Payload:
  - int: the number of elapsed milliseconds since the previous frame

#### Redraw

#### FRAMES\_REDRAW

input (void) FRAMES\_REDRAW

- Occurrences:
  - on every frame, after FRAMES\_UPDATE

Before the input occurs, the screen is cleared with the color set with FRAMES\_SET\_CLEAR\_RGB.

# Window Management

# Window Management

Manages the application window.

# Configuration

#### WINDOW\_SET\_SIZE

Changes the real and logical sizes of the window.

output (u16,u16,u16,u16) WINDOW\_SET\_SIZE

- Parameters:
  - u16: new real width
  - u16: new real height
  - u16: new logical width
  - u16: new logical height

The arithmetic division between the real and logical dimensions must be exact.

#### WINDOW\_SET\_TITLE

Changes the title of the window.

output (string) WINDOW\_SET\_TITLE

- Parameters:
  - string: new window title

# License

# License

pico-Céu is distributed under the MIT license reproduced below:

Copyright (C) 2012-2017 Francisco Sant'Anna

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.