Introduction

Introduction

TODO

Graphics

Graphics

Provides graphics operations, such as for drawing pixels and images on the screen.

Configuration

GFX_SET_GRID

Enables or disables a visual grid delimiting the screen pixels.

output (yesno) GFX_SET_GRID

- Parameters:
 - yesno: new state
 - * yes: enables the grid
 - * no: disables the grid

The ratio between the real and logical dimensions set with WINDOW_SET_SIZE must be greater then one.

GFX_SET_FONT

Changes the font for drawing and writing text.

```
output (text,integer) GFX_SET_FONT
```

- Parameters:
 - text: path for the .ttf font filename
 - $\boldsymbol{-}$ integer: height of the new font in pixels

GFX_SET_RGB

Changes the color of all subsequent drawing operations.

```
output (integer,integer,integer) GFX_SET_RGB
```

• Parameters:

integer: new red component
integer: new green component
integer: new blue component

GFX_SET_WRITE_CURSOR

Changes the cursor position for writing text with GFX_WRITE and GFX_WRITELN. output (integer,integer) GFX_SET_WRITE_CURSOR

- Parameters:
 - integer: new position in the x-axisinteger: new position in the y-axis

Drawing

GFX_CLEAR

Clears the screen.

output (none) GFX_CLEAR

- Parameters:
 - none: no parameters

The clear color is specified with GFX_SET_RGB.

GFX_DRAW_BMP

Draws a bitmap image on the screen.

output (integer,integer,text) GFX_DRAW_BMP

- Parameters:
 - integer: position in the x-axis
 - integer: position in the y-axis
 - text: path for the .bmp image filename

GFX_DRAW_PIXEL

Draws a pixel on the screen.

output (integer,integer) GFX_DRAW_PIXEL

- Parameters:
 - integer: position in the x-axis
 - integer: position in the y-axis

The drawing color is specified with GFX_SET_RGB.

GFX_DRAW_LINE

Draws a line on the screen.

output (integer,integer,integer,integer) GFX_DRAW_LINE;

- Parameters:
 - integer: start position in the x-axis
 - integer: start position in the y-axis
 - integer: end position in the x-axis
 - integer: end position in the y-axis

The drawing color is specified with GFX_SET_RGB.

GFX_DRAW_RECT

Draws a rectangle on the screen.

output (integer,integer,integer,integer) GFX_DRAW_RECT

- Parameters:
 - integer: position in the x-axis
 - integer: position in the y-axis
 - integer: rectangle width
 - integer: rectangle height

The drawing color is specified with GFX_SET_RGB.

GFX_DRAW_TEXT

Draws a text on the screen.

output (int,int,text) GFX_DRAW_TEXT;

- Parameters:
 - integer: position in the x-axis
 - integer: position in the y-axis
 - text: text to draw

The drawing font is specified with <code>GFX_SET_FONT</code>. The drawing color is specified with <code>GFX_SET_RGB</code>.

Writing

GFX_WRITE

Writes a text on the screen.

output (text) GFX_WRITE;

• Parameters:

- text: text to draw

The drawing position is first specified with GFX_SET_WRITE_CURSOR. The cursor advances automatically for the position after the text. The drawing font is specified with GFX_SET_FONT. The drawing color is specified with GFX_SET_RGB.

GFX_WRITELN

Writes a line of text on the screen.

```
output (text) GFX_WRITELN;
```

The drawing position is first specified with <code>GFX_SET_WRITE_CURSOR</code>. The cursor advances automatically for the next line after the text, at the same initial position. The drawing font is specified with <code>GFX_SET_FONT</code>. The drawing color is specified with <code>GFX_SET_RGB</code>.

Other

GFX_SCREENSHOT

Takes a screen shot.

output (text) GFX_SCREENSHOT

- Parameters:
 - text: path for the .bmp image filename to generate

Input Devices

Input Devices

Provides input handling, such as for keyboard and mouse.

Keyboard

KEY_PRESS

input (integer) KEY_PRESS

- Occurrences:
 - whenever a keyboard key is pressed
- Payload:
 - integer: numeric key code

TODO: key codes

KEY_UNPRESS

input (integer) KEY_UNPRESS

- Occurrences:
 - whenever a keyboard key is released
- Payload:
 - integer: numeric key code

TODO: key codes

Mouse

MOUSE CLICK

input (integer,integer,integer) MOUSE_CLICK

- Occurrences:
 - whenever a mouse button is pressed
- Payload:
 - integer: numeric button code (TODO: left, middle, right?)
 - integer: current mouse position in the x-axis
 - integer: current mouse position in the y-axis

MOUSE_UNCLICK

input (integer,integer,integer) MOUSE_UNCLICK

- Occurrences:
 - whenever a mouse button is released
- Payload:
 - integer: numeric button code (TODO: left, middle, right?)
 - integer: current mouse position in the x-axis
 - integer: current mouse position in the y-axis

MOUSE_MOVE

input (integer,integer) MOUSE_MOVE

- Occurrences:
 - whenever the mouse moves
- Payload:
 - integer: current mouse position in the x-axis
 - integer: current mouse position in the ${\tt y-axis}$

Sound

Sound

Provides sound playback.

Configuration

SOUND_SET_VOLUME

Changes the volume of all subsequent sound playbacks.

output (integer) SOUND_SET_VOUME

- Parameters:
 - integer: new sound volume in percentage (from 0 to 100)

Playback

SOUND_PLAY

Plays a sound file.

output (text) SOUND_PLAY

- Parameters:
 - text: path for the sound filename

The playback volume is specified with SOUND_SET_VOLUME.

Frame Management

Frame Management

Manages the game frames, such as for updating animations and redrawing the screen.

Configuration

FRAMES_SET

Enables or disables the generation of periodic ${\tt FRAMES_UPDATE}$ and ${\tt FRAMES_REDRAW}$ inputs to the application.

output (yesno) FRAMES_SET

- Parameters:
 - yesno: new state
 - * yes: enables the generation of frames * no: disables the generation of frames

FRAMES_SET_CLEAR_RGB

Changes the redrawing background color.

output (integer,integer) FRAMES_SET_CLEAR_RGB

- Parameters:
 - integer: new red component
 - integer: new green component
 - integer: new blue component

On every frame before FRAMES_REDRAW, the screen is cleared with the background color.

The default color is black.

Update

FRAMES_UPDATE

input (integer) FRAMES_UPDATE

- Occurrences:
 - on every frame, before FRAMES_REDRAW
- Payload:
 - integer: the number of elapsed milliseconds since the previous frame

Redraw

FRAMES_REDRAW

input (none) FRAMES_REDRAW

- Occurrences:
 - on every frame, after FRAMES_UPDATE
- Payload:
 - none: no payload

Before the input occurs, the screen is cleared with the color set with FRAMES_SET_CLEAR_RGB.

Window Management

Window Management

Manages the application window.

Configuration

WINDOW_SET_SIZE

Changes the real and logical sizes of the window.

output (integer,integer,integer,integer) WINDOW_SET_SIZE

- Parameters:
 - integer: new real widthinteger: new real heightinteger: new logical width
 - integer: new logical height

The window is automatically cleared with black.

The arithmetic division between the real and logical dimensions must be exact.

WINDOW_SET_TITLE

Changes the title of the window.

output (text) WINDOW_SET_TITLE

- Parameters:
 - text: new window title

License

License

pico-Céu is distributed under the MIT license reproduced below:

```
Copyright (C) 2012-2017 Francisco Sant'Anna
```

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do

so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.