📖 **paulojp-dev** / **projeto-biblioteca-java** Public

<> **Code** ⊙ Issues ⁑ Pull requests ▶ Actions ▦ Projects ⊘ Security ⟋ Insights

Commit

⚠ This commit does not belong to any branch on this repository, and may belong to a fork outside of the repository.

constant - 1   Browse files

👤 **Rodrigoferx** committed on Jun 24

1 parent 0f4fd85   commit 6a0bbe4

Showing **1 changed file** with **19 additions** and **14 deletions**.

Whitespace | Ignore whitespace   Split | Unified

ˇ ⇕ **33** ■■■□ src/utils/BdCliente.java ⧉

```
 34   34          /* ----CLIENTE-> */
 35   35
 36   36          // CREATE - Adiciona um registro
      37  +        public class ClienteDAO {
      38  +
      39  +            private static final int NUMERO_COLUNAS = 6;
      40  +
 37   41            public void adicionaCliente(Cliente c) throws SQLException {
 38       -            // Prepara conexão p/ receber o comando SQL
 39       -            String sql = "INSERT INTO cliente(nome, data_nasc, sexo, cpf, endereco,
                       fone)"
 40       -                    + "VALUES(?, ?, ?, ?, ?, ?)";
 41       -            PreparedStatement stmt;
 42       -            // stmt recebe o comando SQL
 43       -            stmt = this.conexao.prepareStatement(sql);
 44       -
 45       -            // Seta os valores p/ o stmt, substituindo os "?"
 46       -            stmt.setString(1, c.getNome());
 47       -            stmt.setString(2, c.getDataNasc());
 48       -            stmt.setString(3, c.getSexo());
 49       -            stmt.setString(4, c.getCpf());
 50       -            stmt.setString(5, c.getEndereco());
 51       -            stmt.setString(6, c.getFone());
      42  +            String sql = "INSERT INTO cliente(nome, data_nasc, sexo, cpf, endereco,
                       fone) VALUES (?, ?, ?, ?, ?, ?)";
      43  +
```

```
44  +            try (PreparedStatement stmt = this.conexao.prepareStatement(sql)) {
45  +                configurarParametros(stmt, c);
46  +                stmt.execute();
47  +            }
48  +        }
49  +
50  +        private void configurarParametros(PreparedStatement stmt, Cliente c) throws
        SQLException {
51  +            for (int i = 1; i <= NUMERO_COLUNAS; i++) {
52  +                stmt.setString(i, c.getValorColuna(i));
53  +            }
54  +        }
55  + }
56  +
52      57
53      58            // O stmt executa o comando SQL no BD, e fecha a conexão
54      59            stmt.execute();
```

0 comments on commit 6a0bbe4

Please sign in to comment.