silascunha / **sistema-loja-de-roupas**   Public

<> **Code**   ⊙ Issues   ⇅ Pull requests   ⊙ Actions   ⊞ Projects **3**   ⊘ Security   ⬈ Insights

Commit

⚠ This commit does not belong to any branch on this repository, and may belong to a fork outside of the repository.

problemas: **Browse files**

```
            * Data class 2
            * long paramets 1
            * magic number
```

🖼 **cmatheusIA** committed on Jun 20, 2023

1 parent 3dd0f5a   commit f27d410

Showing **7 changed files** with **81 additions** and **53 deletions**.

Whitesp...   Ignore whitespa...   Sp...   Unifi...

⌄ **13** ▪▪▪▪▪ .idea/compiler.xml ⧉

Load diff

Some generated files are not rendered by default. Learn more about how customized files appear on GitHub.

⌄ **7** ▪▪▪▪▪ .idea/encodings.xml ⧉

Load diff

Some generated files are not rendered by default. Learn more about how customized files appear on GitHub.

⌄ **20** ▪▪▪▪▪ .idea/jarRepositories.xml ⧉

<div align="center">

Load diff

</div>

Some generated files are not rendered by default. Learn more about [how customized files appear on GitHub](https://github.com).

∨ **12** ■■■■□ `.idea/misc.xml` ⧉

<div align="center">

Load diff

</div>

Some generated files are not rendered by default. Learn more about [how customized files appear on GitHub](https://github.com).

∨ **6** ■■■■■ `.idea/vcs.xml` ⧉

<div align="center">

Load diff

</div>

Some generated files are not rendered by default. Learn more about [how customized files appear on GitHub](https://github.com).

∨ ⤢ **26** ■■■■□ `src/main/java/br/sistemalojaroupas/model/entities/Address.java` ⧉

```
...    ...        @@ -1,32 +1,15 @@
 1             -  /*
 2             -   * To change this license header, choose License Headers in Project Properties.
 3             -   * To change this template file, choose Tools | Templates
 4             -   * and open the template in the editor.
 5             -   */
 6      1         package br.sistemalojaroupas.model.entities;
 7      2
 8             -  /**
 9             -   *
10             -   * @author silas
11             -   */
12      3         public class Address {
13             -
        4      +
14      5             private String cep;
15      6             private String state;
16      7             private String city;
17      8             private String neighborhood;
18      9             private String street;
19     10             private String number;
20     11
21             -      public Address() {}
```

```
22         -
23         -      public Address(String cep, String state, String city, String neighborhood,
                  String street, String number) {
24         -          this.cep = cep;
25         -          this.state = state;
26         -          this.city = city;
27         -          this.neighborhood = neighborhood;
28         -          this.street = street;
29         -          this.number = number;
     12    +      public Address() {
30   13    +      }
31   14
32   15        public String getCep() {
79   62
80   63        @Override
81   64        public String toString() {
82         -        return "Address{" + "cep=" + cep + ", state=" + state + ", city=" + city +
                  ", neighborhood=" + neighborhood + ", street=" + street + ", number=" + number +
                  '}';
     65    +        return String.format("Address{cep= '%s', state= '%s', city= '%s',
                  neighborhood= '%s', street= '%s', number= '%s'}",cep, state, city, neighborhood,
                  street, number);
83   66        }
84         -
     67    +
     68    +
85   69    }
```

---

50 ▰▰▰▰▱ src/main/java/br/sistemalojaroupas/model/entities/Customer.java

```
...   ...    @@ -1,8 +1,3 @@
1          - /*
2          -  * To change this license header, choose License Headers in Project Properties.
3          -  * To change this template file, choose Tools | Templates
4          -  * and open the template in the editor.
5          -  */
6    1      package br.sistemalojaroupas.model.entities;
7    2
8    3      import java.io.Serializable;
13   8      import org.dizitart.no2.objects.Index;
14   9      import org.dizitart.no2.objects.Indices;
15   10
16         - /**
17         -  *
18         -  * @author vfdes
19         -  */
20   11     @Indices(
21         -      @Index(value = "cpf", type = IndexType.Unique)
     12    +      @Index(value = "cpf", type = IndexType.Unique)
22   13     )
23   14     public class Customer implements Serializable, TableContract {
24   15
```

```
33   24
34   25              }
35   26
36        -         public Customer(String cpf, String name, String email, String celular) {
     27   +         public Customer(String cpf, String name, String email, String phone) {
37   28                  this.cpf = cpf;
38   29                  this.name = name;
39   30                  this.email = email;
40        -             this.phone = celular;
     31   +             this.phone = phone;
41   32              }
42   33
43   34          public NitriteId getId() {
44   35              return id;
45   36          }
46        -
     37   +
47   38          public String getCpf() {
48   39              return cpf;
49   40          }
78   69
79   70          @Override
80   71          public int hashCode() {
81        -         int hash = 7;
82        -         hash = 37 * hash + Objects.hashCode(this.id);
83        -         return hash;
     72   +         return Objects.hash(id);
84   73          }
85   74
86   75          @Override
87   76          public boolean equals(Object obj) {
88   77              if (this == obj) {
89   78                  return true;
90   79              }
91        -         if (obj == null) {
92        -             return false;
93        -         }
94        -         if (getClass() != obj.getClass()) {
     80   +         if (obj == null || getClass() != obj.getClass()) {
95   81                  return false;
96   82              }
97        -         final Customer other = (Customer) obj;
98        -         if (!Objects.equals(this.id, other.id)) {
99        -             return false;
100       -         }
101       -         return true;
     83   +         Customer other = (Customer) obj;
     84   +         return Objects.equals(id, other.id);
102  85          }
103  86
104  87          @Override
105  88          public String toString() {
```

```
106  -            return "Client{" + "cpf=" + cpf + ", nome=" + name + ", email=" + email +
                ", celular=" + phone + '}';
      89  +            return "Customer{" +
      90  +                    "cpf='" + cpf + '\'' +
      91  +                    ", name='" + name + '\'' +
      92  +                    ", email='" + email + '\'' +
      93  +                    ", phone='" + phone + '\'' +
      94  +                    '}';
107   95         }
108   96
109   97         @Override
110   98         public Object[] tableRowModel() {
111   99             return new Object[]{
112   -                 getName(),
113   -                 getCpf(),
114   -                 getPhone(),
115   -                 getEmail()
     100  +                 getName(),
     101  +                 getCpf(),
     102  +                 getPhone(),
     103  +                 getEmail()
116  104             };
117  105         }
118  106
119  107     }
120   -
121   -
```

0 comments on commit `f27d410`