



CompSci 401: Cloud Computing

Classic Software Engineering

Prof. Ítalo Cunha



Software development

1. Identify need for a new piece of software
2. Software engineers design, develop, test, and deploy software
3. Users run or invoke the software as needed indefinitely

Software development in the real world



1. Identify need for a new piece of software
 2. Software engineers design, develop, test, and deploy software
 3. Users run or invoke the software as needed ~~indefinitely~~
- Operating system and frameworks evolve over time
 - Requires updates to software (e.g., Django 1 → 2 → 3 → 4)
 - Software will have errors that require fixing
 - Users ask for additional functionality and extensions




```
[/home]$ ls
vidarlo
[/home]$ cd ..
[/]$ cd etc
[/etc]$ ls
0.0.10.in-addr.arpa  csh.cshrc          gshadow-          logrotate.d       odbcinst.ini       rmt
adduser.conf         csh.login          gtk               lynx.cfg          openoffice         rpc
adjtime              csh.logout        host.conf         magic             opt                screenrc
aliases              db.cache           hostname          mailcap           pam.conf           securetty
alternatives         debian_version     hosts            mailcap.order     pam.d              security
apm                  default            hosts.allow      mailname          passwd             services
apt                  defoma             hosts.deny       mail.rc           passwd-            shadow
asterisk             deluser.conf       hotplug          manpath.config    perl               shadow-
at.deny              dhclient.conf      hotplug.d        mdadm             ppp                shells
bakipkungfu          dhclient-script    identd.conf      mediaprm          printcap           skel
bash.bashrc          dhclient-script    identd.key       mime.types        profile            squid
bash_completion      dictionaries-common inetd.conf        mkinitrd          protocols          ssh
bash_completion.d    discover.conf      init.d           modprobe.d        python2.3          sudoers
bind                  discover.conf-2.6  inittab          modules            raidtab            sysctl.conf
blkid.tab            discover.d          inputrc          modules.conf      rc0.d              syslog.conf
blkid.tab.old        dpkg               ipkungfu         modules.conf.old  rc1.d              terminfo
calendar             emacs              issue            modutils          rc2.d              timezone
chatscripts          emacs21            issue.net        motd              rc3.d              ucf.conf
chkrootkit.conf      email-addresses    kernel-img.conf  mtab              rc4.d              updatedb.conf
complete.tcsh        environment        ldap             mtools.conf      rc5.d              vidarlo.net.hosts
console              exim4              ld.so.cache     mysql             rc6.d              w3m
console-tools        fdmount.conf       ld.so.conf       nanorc            rc.d               wgetrc
cron.d               fonts              locale.alias     network           rcS.d              #wvdial.conf#
cron.daily            fstab              locale.gen       networks          reportbug.conf     wvdial.conf
cron.hourly           groff              localtime       nsswitch.conf    resolvconf         wvdial.conf"
cron.monthly          group              logcheck        ODBCDataSources  resolv.conf        X11
crontab              group-             login.defs       odbc.ini          resolv.conf"       xpilot
cron.weekly           gshadow            logrotate.conf  odbc.ini          resolv.conf.pppd-backup
```





```
[/home]$ ls
vidarlo
[/home]$ cd ..
[/]$ cd etc
[/etc]$ ls
0.0.10.in-addr.arpa  csh.cshrc          gshadow-          logrotate.
adduser.conf         csh.login           gtk               lynx.cfg
adjtime              csh.logout         host.conf         magic
aliases              db.cache            hostname          mailcap
alternatives         debconf.conf        hosts             mailcap.or
apm                  debian_version      hosts.allow       mailname
apt                  default             hosts.deny        mail.rc
asterisk             defoma              hotplug           manpath.co
at.deny              deluser.conf        hotplug.d         mdadm
bakipkungfu          dhclient.conf       identd.conf       mediaprm
bash.bashrc          dhclient-script     identd.key        mime.types
bash_completion      dictionaries-common inetd.conf         mkinitrd
bash_completion.d    discover.conf       init.d            modprobe.d
bind                 discover.conf-2.6   inittab           modules
blkid.tab            discover.d           inputrc           modules.co
blkid.tab.old        dpkg                ipkungfu          modules.co
calendar             emacs               issue             modutils
chatscripts          emacs21             issue.net         motd
chkrootkit.conf      email-addresses     kernel-img.conf   mtab
complete.tcsh        environment         ldap              mtools.con
console              exim4               ld.so.cache       Muttrc
console-tools        fdmount.conf        ld.so.conf        mysql
cron.d               fonts               locale.alias      nanorc
cron.daily            fstab               locale.gen         network
cron.hourly          groff               localtime         networks
cron.monthly         group              logcheck          nsswitch.c
crontab              group-              login.defs         ODBCDataSo
cron.weekly          gshadow             logrotate.conf    odbc.ini
[/etc]$
```




Software development cycle




Software development cycle




Large projects and teams




Large projects and teams




Large projects and teams




Large projects and teams



Large projects and teams



Large projects and teams



Conflicting interests

- More features
- Ship *yesterday*
- Latest libraries and frameworks
- Unlimited resources

Dev
team

- Stable libraries and frameworks
- Lightweight code, resource constraints
- Zero errors

Quality assurance
team

Operations
team



CompSci 401: Cloud Computing

DevOps

Prof. Ítalo Cunha



DevOps paradigm

- A culture/organizational approach to software development
- Join development, QA, and operation teams
- An extension to agile methods
 - Relies heavily on automation and orchestration

DevOps paradigm


- A culture/organizational approach to software development
- Join development, QA, and operation teams
- An extension to agile methods
 - Relies heavily on automation and orchestration
- If operations requires a serverless application can coordinate with developers to build stateless code
- Operations can inform developers a preferred/desirable microservice approach, including how to modularize/size

DevOps requirements

- Automation and orchestration
 - Continuous integration to automate building and testing
 - Version management to separate development code from production code
 - Small software modules to compartmentalize testing
 - Extensive testing to ensure software quality (e.g., test-driven development)


DevOps requirements

- Automation and orchestration
 - Continuous integration to automate building and testing
 - Version management to separate development code from production code
 - Small software modules to compartmentalize testing
 - Extensive testing to ensure software quality (e.g., test-driven development)



DevOps requirements

- Automation and orchestration
 - Continuous integration to automate building and testing
 - Version management to separate development code from production code
 - Small software modules to compartmentalize testing
 - Extensive testing to ensure software quality (e.g., test-driven development)



DevOps requirements

- Automation and orchestration
 - Continuous integration to automate building and testing
 - Version management to separate development code from production code
 - Small software modules to compartmentalize testing
 - Extensive testing to ensure software quality (e.g., test-driven development)

DevOps requirements

- Automation and orchestration
 - Continuous integration to automate building and testing
 - Version management to separate development code from production code
 - Small software modules to compartmentalize testing
 - Extensive testing to ensure software quality (e.g., test-driven development)
 - Continuous delivery to automate software deployment

Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions


Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions




Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions



Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions



Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions


Classic software releases and updates

- Package software
- Pick “low risk” time to deploy
 - Maintenance window
 - Warn users of possible unavailability
- Possibly bring the application offline to swap versions
- Not a good fit for cloud environments
 - Large/global user base implies there is no “low risk” time to deploy
 - In a microservice architecture, other services depend on the updated service
 - Stopping a microservice for a release may be impossible

CI/CD to deploy updates rapidly


- Smaller modules and extensive testing improve software quality
 - Less errors in production
- Rollout
 - Containers running **old version** can continue running during upgrade
 - Can finish serving ongoing requests
 - Containers running **new version** spawn and are monitored closely for errors
 - Eventual migration if no errors occur

Sandbox trial



Production version

- Unchanged




Sandbox trial

- With updates
- Does not impact production version
- May not catch all errors due to isolation
 - Different users and infrastructure
- High cost

Canary deployment




Image Processing Application




Canary deployment




Image Processing Application




Canary deployment



Canary deployment





Canary deployment



Blue-green deployment

Production infrastructure




Production

Testing

Modern software releases and updates

- Generate configurations
- Have configurations pushed automatically
 - For example, periodically push configurations every night
- Monitor router and traffic behavior
- Automatically roll back if errors occur



Difficult aspects of DevOps

- Culture shift
 - Teams have to collaborate more closely or merge
 - Realignment of incentives and rewards
- Extensive automation and orchestration
 - Initial setup costs, maintenance overhead
- Higher risk from rapid development
 - Despite tests and rollout/rollbacks, failures may occur more often
- System-wide failures instead of module failures
 - DevOps performs extensive tests of small modules, but global or cascading failures may occur in production



CompSci 401: Cloud Computing


Site Reliability Engineering

Prof. Ítalo Cunha



Site Reliability Engineering

- Systems management within Google
- Very similar to DevOps



SRE at Google

- SRE team members are software developers
- 50% cap on “ops” tasks
- At least 50% on development
- SREs build automation solutions
 - Or “automatic” systems that can run and repair themselves

Continued focus on engineering

- 50% of the time on development work
- Operational load above 50% redirected to development teams
- 1-2 incidents per 8-12h shift
 - Gives engineers time to dig deep and write post-mortem reports
 - Avoids pager fatigue

Error budgets and change velocity

- Most services aim for less than 100% availability
 - 99.99% availability is *much* easier to achieve than 100%
 - And the difference between the two might not be perceptible by users
- Allows teams to implement and deploy changes quickly
 - Provided the service is above the availability target
- Improve robustness if availability is below target

Emergency response

- Humans add latency
- Automate emergency response as much as possible
 - Progressive rollouts and automated rollbacks
- Playbooks for dealing with issues