5. Subnetting and CIDR (with practice)

05. Subnetting and CIDR (with practice)

Phase: Phase 2 — Addressing and subnets
Estimated time: 2–3 days
Slug: `05-subnetting`

Learning objectives

- Convert prefix lengths to masks
- Compute network/broadcast/usable hosts
- Choose subnets for labs
- Use `ipcalc`/`sipcalc` or manual method

Prerequisites

Complete prior lessons. Prefer a Linux VM for `ip`/`ss`/`nft` examples; macOS works for many `curl`/`dig` drills. Type every command yourself and keep a lab notes file.

Why this matters

Security asks for a /27 for a new service; capacity planning assumed a /24. Getting host counts, network/broadcast, and usable ranges wrong either wastes address space or causes painful renumbering later.

Core concepts

What you must be able to explain:

- Convert prefix lengths to masks
- Compute network/broadcast/usable hosts
- Choose subnets for labs
- Use `ipcalc`/`sipcalc` or manual method

Mental model for `05-subnetting` (exercise kind `cidr_hosts`):

- Prefer **measurable** checks (exit codes, ICMP replies, DNS rcode, HTTP status, socket state) over vibes.
- Separate **reachability** (can packets flow?) from **correctness** (right service, cert, route, identity).
- Ask: *which layer's tool falsifies my current hypothesis?* Then run that tool.
- Record the exact command that proved the root cause — that becomes your playbook snippet.

Worked commands

Run these on a lab host. Linux VM preferred for `ip`/`ss`/`tcpdump`/`nft`; macOS is fine for many `curl`/`dig`/`ping` drills. Your addresses and timings will differ — match the *shape* of the output and the conclusion you draw.

Example 1

```
ip -br addr; ip route; ip route get 1.1.1.1
```

Sample output:

```
eth0 UP 192.168.1.20/24
default via 192.168.1.1 dev eth0
1.1.1.1 via 192.168.1.1 dev eth0 src 192.168.1.20
```

Interpretation: `ip route get` shows the chosen route, egress device, and preferred source — gold for 'why did it leave this NIC?' questions.

Example 2

```
ping -c 3 1.1.1.1
ss -tulpn | head
# macOS: netstat -anv | head
```

Sample output:

```
3 packets transmitted, 3 received
udp ... :53
tcp LISTEN ... :22
```

Interpretation: ICMP OK proves basic L3; ss proves local listeners. Combine with ARP/neigh when LAN peers fail.

Example 3

```
ip neigh show | head
ping -c 1 $(ip route | awk '/default/ {print $3; exit}')
```

Sample output:

```
192.168.1.1 dev eth0 lladdr ... REACHABLE
64 bytes from gateway
```

Interpretation: Neighbor/ARP state validates L2 adjacency to the gateway before you blame the wider internet.

Mini-lab

1. Re-type every worked command for **Subnetting and CIDR (with practice)** and paste outputs into lab notes.
2. Introduce one controlled failure in the lab (wrong DNS, firewall drop, bad route) and recover using only this lesson's tools.
3. Write a 5-line playbook: symptom → first command → expected healthy output.

4. Complete the exercise stubs; then explain each function's return value without looking.

Failure modes

Symptom	Likely cause	Next check
Off-by-one in usable host counts	See common mistakes	Re-run lesson commands
Overlapping subnets in VPCs	See common mistakes	Re-run lesson commands
Using /24 everywhere without design	See common mistakes	Re-run lesson commands
Timeout with no RST	Silent drop / blackhole	tcpdump + compare path

Study tip for Subnetting and CIDR (with practice)

Before each new command, write a one-line hypothesis. If the result falsifies it, update the hypothesis instead of stacking random tools. Note equivalents across OS (`ip` ↔ `ifconfig`/`route`, `ss` ↔ `netstat`). Re-run two commands from this lesson tomorrow from memory and explain the sample outputs out loud.

Evidence habit

When pages are down, prefer evidence (`ip route get`, resolver answer, packet capture, listener list) over intuition. Document **command → output → conclusion** in a lab notebook so the same path is reusable on-call. Change one variable at a time; write a one-line hypothesis before each new tool.

Common mistakes

- Off-by-one in usable host counts
- Overlapping subnets in VPCs
- Using /24 everywhere without design

Exercises

Work in `exercises/05-subnetting/`. Read that folder's `README.md` before coding.

```
cd exercises/05-subnetting
chmod +x test.sh exercise.sh 2>/dev/null || true
./test.sh
```

What you will build

Edit `exercise.sh` and implement `host_bits`, `usable_hosts_24`, `longer_prefix_means`. Each function is a tiny retrieval drill for **Subnetting and CIDR (with practice)** — return the exact

tokens/flags/labels from the lesson. Keep the comment above each function describing when you would use that fact on-call. Run `./test.sh` until all 4 assertions pass.

Study loop

- **A (Drill):** make tests pass
- **B (Apply):** run 2–3 real commands from this lesson in your lab and note outputs
- **C (Challenge):** rewrite answers from memory next day

Do not open `solutions/05-subnetting/` until after an honest attempt.

Self-check

Answer without scrolling up:

1. How many host bits in /26?
2. What does /32 mean?
3. Why avoid overlapping CIDRs?

Further reading

- https://www.rfc-editor.org/rfc/rfc4632