9. ss, netstat, and lsof: See What Is Listening

09. ss, netstat, and lsof: See What Is Listening

Phase: Phase 3 — Host networking toolkit
Estimated time: 1–2 days
Slug: `09-ss-netstat-lsof`

Learning objectives

- List listening sockets and established connections
- Map ports to processes
- Use lsof for file/socket detectives
- Spot TIME_WAIT / CLOSE_WAIT patterns

Prerequisites

Complete prior lessons. Prefer a Linux VM for `ip`/`ss`/`nft` examples; macOS works for many `curl`/`dig` drills. Type every command yourself and keep a lab notes file.

Why this matters

Deploy claims the app listens on 8080; curl from another host times out. `ss`/`lsof` show whether anything listens, on which address (127.0.0.1 vs 0.0.0.0), and which process owns the socket.

Core concepts

What you must be able to explain:

- List listening sockets and established connections
- Map ports to processes
- Use lsof for file/socket detectives
- Spot TIME_WAIT / CLOSE_WAIT patterns

Mental model for `09-ss-netstat-lsof` (exercise kind `ss_flags`):

- Prefer **measurable** checks (exit codes, ICMP replies, DNS rcode, HTTP status, socket state) over vibes.
- Separate **reachability** (can packets flow?) from **correctness** (right service, cert, route, identity).
- Ask: *which layer's tool falsifies my current hypothesis?* Then run that tool.
- Record the exact command that proved the root cause — that becomes your playbook snippet.

Worked commands

Run these on a lab host. Linux VM preferred for `ip`/`ss`/`tcpdump`/`nft`; macOS is fine for many `curl`/`dig`/`ping` drills. Your addresses and timings will differ — match the *shape* of the output and the conclusion you draw.

Example 1

```
ip -br addr; ip route; ip route get 1.1.1.1
```

Sample output:

```
eth0 UP 192.168.1.20/24
default via 192.168.1.1 dev eth0
1.1.1.1 via 192.168.1.1 dev eth0 src 192.168.1.20
```

Interpretation: `ip route get` shows the chosen route, egress device, and preferred source — gold for 'why did it leave this NIC?' questions.

Example 2

```
ping -c 3 1.1.1.1
ss -tulpn | head
# macOS: netstat -anv | head
```

Sample output:

```
3 packets transmitted, 3 received
udp ... :53
tcp LISTEN ... :22
```

Interpretation: ICMP OK proves basic L3; ss proves local listeners. Combine with ARP/neigh when LAN peers fail.

Example 3

```
ip neigh show | head
ping -c 1 $(ip route | awk '/default/ {print $3; exit}')
```

Sample output:

```
192.168.1.1 dev eth0 lladdr ... REACHABLE
64 bytes from gateway
```

Interpretation: Neighbor/ARP state validates L2 adjacency to the gateway before you blame the wider internet.

Mini-lab

1. Re-type every worked command for **ss, netstat, and lsof: See What Is Listening** and paste outputs into lab notes.
2. Introduce one controlled failure in the lab (wrong DNS, firewall drop, bad route) and recover using only this lesson's tools.
3. Write a 5-line playbook: symptom → first command → expected healthy output.

4. Complete the exercise stubs; then explain each function's return value without looking.

Failure modes

Symptom	Likely cause	Next check
Killing TIME_WAIT thinking it's a leak	See common mistakes	Re-run lesson commands
Forgetting sudo for process names in …	See common mistakes	Re-run lesson commands
Ignoring IPv6 listeners (`ss -tulpn` …	See common mistakes	Re-run lesson commands
Timeout with no RST	Silent drop / blackhole	tcpdump + compare path

Study tip for ss, netstat, and lsof: See What Is Listening

Before each new command, write a one-line hypothesis. If the result falsifies it, update the hypothesis instead of stacking random tools. Note equivalents across OS (`ip` ↔ `ifconfig`/`route`, `ss` ↔ `netstat`). Re-run two commands from this lesson tomorrow from memory and explain the sample outputs out loud.

Evidence habit

When pages are down, prefer evidence (`ip route get`, resolver answer, packet capture, listener list) over intuition. Document **command → output → conclusion** in a lab notebook so the same path is reusable on-call. Change one variable at a time; write a one-line hypothesis before each new tool.

Common mistakes

- Killing TIME_WAIT thinking it's a leak
- Forgetting sudo for process names in ss -p
- Ignoring IPv6 listeners (`ss -tulpn` shows both)

Exercises

Work in `exercises/09-ss-netstat-lsof/`. Read that folder's `README.md` before coding.

```
cd exercises/09-ss-netstat-lsof
chmod +x test.sh exercise.sh 2>/dev/null || true
./test.sh
```

What you will build

Edit `exercise.sh` and implement `ss_listen_flags`, `legacy_netstat`, `files_ports_tool`. Each function is a tiny retrieval drill for **ss, netstat, and lsof: See What Is Listening** — return the exact tokens/flags/labels from the lesson. Keep the comment above each

function describing when you would use that fact on-call. Run `./test.sh` until all 3 assertions pass.

Study loop

- **A (Drill):** make tests pass
- **B (Apply):** run 2–3 real commands from this lesson in your lab and note outputs
- **C (Challenge):** rewrite answers from memory next day

Do not open `solutions/09-ss-netstat-lsof/` until after an honest attempt.

Self-check

Answer without scrolling up:

1. ss flags for TCP/UDP listen + process?
2. lsof command for port 22?
3. CLOSE-WAIT often means?

Further reading

- https://man7.org/linux/man-pages/man8/ss.8.html