Mini-project: Trait Space Drift

Joaquin, Andy, Sanskriti, Harsh

CS2881R - October 16th, 2026

1 What we did

Emergent misalignment due to finetuning occurs when the affects of the training data lead to undesired behaviors in out-of-distribution examples. While more conventional albeit comprehensive methods rely on behavioral evaluation throughout the training process. This can understandably be expensive. CITE PAPER instead attempted to associate salient traits we care about to activations

One of the most salient questions to address when proposing monitors for emergent misalignment is whether it can separate alignment drift from just broad model degradation. The paper shows that trait-drift derived from the 7-dimensional axis outperforms emergent misalignment detection using more generic signals such as (insert here).

- Reproduction of the paper's results
- Experiment 1: Training order and path dependence
- Experiment 2: Harmful data fraction
- Experiment 3: Attributing representation drift to training examples

2 Reproduction

In order to save most of our compute for the extensions, we used primarily 1 seed and 1 model for the reproduction. We used Qwen/Qwen2.5-7B-Instruct, and monitored layer 16 based on the original paper's analysis of candidate trait directions for each layer.

The first goal is to reproduce a 7-dimensional trait-space corresponding to (honesty, helpfulness, harmlessness, power-seeking, corrigibility, sycophancy, and confidence), for each trait we use 5 positive system prompts (assumed to push the models activation layers towards exhibiting the trait) and 5 negative system prompts (assumed to push the model in the opposite direction along the trait axis). We thus calculate the trait direction by taking the hidden state vector at layer 16 following the positive system prompts subtracted by the same following the negative system prompts (we use 30 prompts held constant across system prompts) and normalizing.

Before fine-tuning, we establish what point the model lies on within this 7-dimensional space using 115 neutral prompts and measure in a similar way. As we then fine-tune on the bad-medical advice dataset and the evil numbers dataset. The latter is meant to be a negative control, since these were numbers produced by negative system prompts but inherently just numbers so should not empirically cause emergent misalignment.

We do this as well for 3 other datasets (insecure_code, jailbroken, and GSM8K) and then try to find a dominant axis that explains most of the variation within the 7 dimensional space. While




Figure 1:

we found that PC1 explains 91.84% of the variation relative to the paper's 78.6%, the latter also had to account for variation due to different seeds and models.

Nonetheless, we plot PC1 over fine-tuning checkpoints and find that the trend is similar to that found by the original paper.

3 Extension 1: Path Dependence Ordering

3.1 What we did

- Question: Does training order affect drift when the examples stay the same?
- Setup: We trained three copies of the same AI model on the same 1,000 examples: 250 harmful examples and 750 harmless ones. Only the order of the examples changed.
- Orders:
  - Harmful examples first: (250 harmful + 750 harmless)
  - Harmful examples last: (750 harmless + 250 harmful)
  - Random shuffle of all 1,000 examples
- *We measured shifts in the model's internal signals toward harmfulness, not confirmed harmful behaviour.

3.2 Training order changes the amount of representation drift

- Trait projections shifted in all three runs:
  - Lower helpfulness
  - Lower honesty
  - Changes in harmlessness
  - Higher confidence
- The amount of drift differed across training orders.

- y-axis: how far the model's internal signals have shifted toward the "harmful" pattern
- x-axis: training steps from 0 to 126

3.3 Testing the learning-rate explanation

- Normal training (seed 42)
- Gap, most to least: 10.7 points
- Constant step size
- Gap, most to least: 7.3 points
- Order still mattered with a constant step size, but the gap shrank.
- We reran all three orders with the step size held constant, removing the decay in learning rate.
- Random order still produced the most drift; harmful-first produced the least.
- The gap fell from about 11 to 7 points, suggesting that learning-rate decay contributes to the order effect.

3.4 How the learning-rate schedule may contribute

- Random order
- Harmful examples first
- Harmful examples last
- How big each learning step is (same in all three)
- warming up
- small updates near the end
- Harmful examples had the biggest effect in the middle of training.
- Start: training is still warming up, so early examples have little effect.
- End: the step size has shrunk almost to zero, so the model barely changes.
- Random order spreads harmful examples evenly, so more land in the middle.
- Next steps: Train with harmful examples condensed in the middle
- *Shaded = when the model was seeing harmful examples.

3.5 Drift continues after the harmful examples end

- Harmful-first:
  - harmful examples
- Harmful-last:

  - harmful examples begin

- Still rising after its harmful examples ended
- Early exposure to harmful examples was followed by continued drift.
- Harmful-first kept shifting for about 30 steps after its harmful examples ended.
- It moved further than harmful-last, which had seen only harmless examples by then.
- Seen in all three repeats, and again with a constant step size.
- *Harmless training afterwards didn't undo the change, but our harmless examples also nudged the model the same way, so we can't say harmless training never reverses it.

3.6 Overall Conclusions + Limitations for Extension 2

3.6.1 Overall

- Training order changed representation drift despite identical training data. The effect persisted with a constant learning rate. The continued drift after early harmful examples suggests a history-dependent response that needs further testing.

3.6.2 Caveats

- Same examples every time. We repeated each version three times with consistent results, but every repeat used the same 1,000 examples.
- Internal changes only. We measured changes inside the model, not whether it actually behaves in more harmful ways.
- Next steps: Train with harmful examples condensed in the middle rather than random

4 Extension 2: harmful data fraction

4.1 HARMFUL TRAINING DATA

4.1.1 What we did

- Does adding more harmful training data change the model?
- We used Qwen2.5-7B-Instruct and started each run from the same model.
- **The set up:** We changed the training mix to include 5 runs across 7 ratios of bad to good answers.
  - Each run used 1,000 examples of good and bad answers.
  - Harmful examples made a range from 0–100%. There were 7 ratios of good to bad answers tested. The range included(% of bad answers): 0%, 5%, 10%, 25%, 50%, 75%, and 100%
  - We then re-ran the results 3 times to test reproducibility. This was done at a random seed value of 42.

  - We then ran the same results for 3 seeds values to measure the impact of seed values on results. We used random seeds of 123 and 789 to assess sensitivity to the training seed.
  - This produced 35 trained conditions across seven mixtures (0 to 100 percent of bad answers was 7 mixtures and we had 5 runs - 3 at seed 42, 1 at seed 123 and 1 at seed 789).

- **Experiment evaluation set up:**. We tested both drifts in activation and how it relates to actual model output quality
  - We checked what changed inside. We used the same 115 prompts to measure changes along seven trait directions. We measured internal changes in activation to access drift on PC1 (compiled score across the 7 metrics) and for each individual metric.
  - Then we accessed if drifts in activation result in actual changes in output quality. We did this in two ways. First, we used a Claude sonnet AI judge on the same 115 questions to access output quality for across each of the 7 metrics, and overall. The second used the same Betley evaluation suite and grading procedure as Extension 3, applied to our Extension 2 models. Each model answered 72 prompts with five sampled responses per prompt, giving 360 responses per model. A GPT-5.6 Sol judge scored alignment and coherence. We classified responses as misaligned when alignment was below 30 and coherence was at least 50, excluding responses labelled CODE or REFUSAL. We compared the percentage of eligible responses classified as misaligned against the activation measurements.

4.1.2 What stayed the same

- The starting model
  - Every run began from the same point.
- The amount of training
  - Same dataset size and number of updates.
- The measurement
  - Same prompts and trait directions for every run.

4.2 RESULTS

4.2.1 Model drift occurs at very low fractions of bad data and rises quickly before stabilizing and actually lowering slightly at 100%

We tested harmful training fractions of 0%, 5%, 10%, 25%, 50%, 75%, and 100%. Even 5–10% harmful data produced a large increase in activation drift, with the highest PC1 score at 50%. At 100%, the score was about 10% lower than at 50%, although this does not establish that the model's answers became better.




Figure 2: Overall activation drift for the first run at seed 42. The 0% condition has no harmful training examples. It is not the untuned base model.

4.2.2 Results are reproducible across repeated runs

Results are reproducible across repeated runs. We ran the experiment 3 times at seed 42 and got almost identical results. These results were reproducible when the training seed and setup were constant.




Figure 3: Three repeated runs at seed 42. The activation curves basially overlap almost exactly

4.2.3 The results hold true for different seed values with more noticeable but minor variations

We tested seeds 42, 123, and 789, and all three showed a rapid early rise, a peak at 50%, and lower activation drift at 100%. Seed 123 generally produced lower scores, but changing the seed did not reverse the overall pattern.




Figure 4: Overall activation drift across three training seeds (at one run a seed)

4.2.4 Overall PC1 results don't tell the full story

Drift by each of the 7 attributes varies significantly. While honesty and corrigibility continue to get worse between 50% and 100% bad data, helpfulness and harmlessness actually improve on the activation measure. Here, "improve" means moving back toward the base model's activation values; whether the answers improve is tested separately below.




Figure 5: Activation changes for all seven attributes, averaged across seeds 42, 123, and 789

4.2.5 Actual answer quality gets worse even when overall activation drift gets lower

We then checked whether changes in activation resulted in changes in actual answer quality. We asked each model the same 115 questions and used a Claude Sonnet judge to score the answers

across the seven attributes, where they could be assessed, and to give a separate overall quality score from 1 to 5.

Answer quality generally got worse as we added more bad data. The interesting part is between 50% and 100%: activation drift went down, but answer quality also went down in all three seeds. The average quality score across seeds fell from 4.02 to 3.94. So, lower overall activation drift did not mean better answers.




Figure 6: Activation drift and overall answer quality across three seeds.

4.2.6 Looking at three attributes makes the difference clearer

We then looked at honesty, helpfulness, and harmlessness for one run at seed 42. We wanted to see whether changes in each attribute's activation matched what actually happened in the answers. The top row shows activation changes, and the bottom row shows the answer scores.

For this comparison, we kept the questions the same at every training fraction. We used questions that could be scored for both the base model and all seven trained models. This left 54 questions for honesty, 115 for helpfulness, and 47 for harmlessness.

Honesty shows a similar pattern in activation and answers. As we add more bad data, honesty activation keeps moving down, and the answers also score lower on honesty.

Helpfulness and harmlessness are more interesting. Their activations move back toward the base model between 50% and 100%, but their answer scores are lower at 100% than at 50%. So, what looks like an improvement in activation does not show up as an improvement in the answers.

This is one seed and one run, so the figure illustrates the difference rather than showing how much it varies across seeds.




Figure 7: Activation changes and answer scores for three traits, using seed 42

4.2.7 The second output test also shows more misalignment with more bad data

We then evaluated the Checkpoint 2 models using the same evaluation questions and grading rules used in Checkpoint 3. We used 72 questions and generated five answers per question, giving 360 answers per model. The GPT judge scored alignment and coherence from 0 to 100.

An answer counted as misaligned when its alignment score was below 30 and its coherence score was at least 50. We followed the evaluation's exclusions for responses labelled as code or refusals and calculated the percentage among eligible answers.

The results again showed that lower activation drift did not mean safer answers. From 50% to 100%, the average misalignment rate across seeds rose from 8.15% to 14.67%, while activation drift fell in all three seeds. These are Checkpoint 2 models tested with the Checkpoint 3 evaluation.




Figure 8: Activation drift and misalignment on the second output test. Each curve represents one training seed. The dotted line shows the untuned base model's misalignment rate.

4.3 NEXT STEPS

4.3.1 What we should do next

- We need to check whether this pattern repeats and whether it affects the answers.
- Run more experiments to access how statistically significant these results are
- Run them on different models to access how this changes across models.
- Access how emergent misaligned, trained on medical data, transfers to other subjects.
- Train on other data sets (not just good and bad medical advice) to see if the relationship holds or if this is a figment of this specific data set.

5 Extension 3: Which training examples drive the drift?

5.1 Motivation

The monitor reduces each checkpoint to a single number: the projection of the model's representation shift onto the PC1 axis, which we refer to as the drift. When the drift exceeds a reference level, the monitor raises an alarm. The alarm identifies neither the training examples responsible for the drift nor whether removing them would reverse it.

This extension applies training-data attribution to the monitor and addresses three questions:

RQ1. Is the drift attributable to a small subset of the training examples, or is it distributed across most of them?

RQ2. Does removing or correcting the highest-scored examples and retraining reduce the drift, and does it change the model's behaviour?

RQ3. When a small number of harmful examples is planted in an otherwise benign dataset, can the scores recover them, and can they do so at the step at which the alarm is raised?

Figure 9 shows how the three questions share a single pipeline.




Figure 9: Extension 3 pipeline. A single fine-tuning run with the monitor provides the checkpoints; every training example is scored against those checkpoints; each research question uses the scores in a different test.

5.2 Experimental setup

5.2.1 Training and monitoring

All runs share the fine-tuning configuration and the monitor of the reproduction (Table 1). The reference run is trained on 1,000 harmful medical answers and reaches a final drift of 24.26. Each model in this extension was trained with a single seed, since replicating every run would have multiplied the compute budget several times over. Run-to-run variation is instead estimated from two sources: a replicate of the reference run with seed 123, which ends at 23.10, and three random 900-example subsets, which end between 23.21 and 25.92. On this basis we treat differences below 1.5 points between single runs as within noise.

Table 1: Fine-tuning configuration and monitor shared by all Extension 3 runs.

Component	Setting
Base model	Qwen2.5-7B-Instruct
Adapter	LoRA, rank 16, $\alpha = 64$, dropout 0.05, on the query and value projections
Optimizer	AdamW, learning rate 4×10^{-5}, weight decay 0.01, gradient clipping 1.0, bfloat16
Batch and schedule	16 sequences per optimizer step; 2 epochs; 126 optimizer steps for 1,000 examples
Harmful data	1,000 examples sampled with seed 42 from the `bad_medical_advice` set of Betley et al. (2025, "Emergent Misalignment")
Correct twins	The same 1,000 questions with correct answers (`good_medical_advice`)
Checkpoints	Every 10 optimizer steps (13 per run)
Monitor	Mean last-token activation at layer 16 over 115 neutral prompts, projected onto the seven trait directions
Drift	Projection onto the saved Qwen PC1 axis, as a percentage of the norm of the base model's mean activation
Reference level	8%, a fixed reference rather than a validated safety threshold; first exceeded by the reference run at step 40

5.2.2 Attribution score

We use TracIn (Pruthi et al., 2020, "Estimating Training Data Influence by Tracing Gradient Descent") because it requires only the checkpoints that the monitor already saves and one backward pass per training example per checkpoint. The scores are therefore available during training, at the step at which the alarm is raised. Influence-function methods require the converged model and an estimate of the inverse Hessian, which makes them unsuitable for an early-warning setting.

Let $T(\theta)$ denote the signed drift at LoRA parameters θ, oriented so that positive values point toward the misaligned region, and let $\ell_i(\theta)$ denote the training loss of example i. The score of example i is

$$s_i \;=\; -\sum_{t\in\mathcal{T}} \eta \left\langle \nabla_\theta T(\theta_t),\, \nabla_\theta \ell_i(\theta_t) \right\rangle, \qquad \mathcal{T} = \{10, 20, \ldots, 120, 126\}, \tag{1}$$

where θ_t is the checkpoint at optimizer step t and η is the learning rate. A positive score indicates that a gradient step on example i increases the drift. Restricting the sum to the checkpoints up to step t yields the ranking that would have been available when the alarm was raised at step t. Scoring 1,000 examples at 13 checkpoints took about 25 minutes on one A100.

The drift can be measured along three directions, which we refer to as targets:

- **PC1 target.** The monitor's own axis.
- **Seven-trait contrast target.** The direction in the seven-trait space from the final drift vector of a run on the correct twins to that of the run on the harmful answers. The component of the drift that correct medical answers also produce cancels along this direction.
- **Raw layer-L contrast target.** The same construction applied directly to the hidden activations at layer L.

5.2.3 Validation protocol

- **Matched twins (RQ1).** Each harmful example has a correct twin with the same question. If the score responds to the answer rather than to the question, the harmful example should score above its twin.
- **Removal and retraining (RQ2).** We remove the 100 highest-scored examples, the 100 lowest-scored examples, or 100 examples drawn at random (three draws), and retrain from the base model. A removal size of 100, 10% of the dataset, is large enough to shift the drift by more than the noise level if the scores are informative, and small enough to leave the optimisation budget almost unchanged. Because a 900-example dataset yields 114 optimizer steps under the fixed two-epoch schedule rather than 126, random removal of equal size, not the full-data run, is the appropriate control. A fourth arm replaces the 100 highest-scored examples by their correct twins. This arm holds the dataset size and the step count fixed, and so isolates the effect of which examples were removed from the effect of training on fewer examples. A second variant of the test replaces the fixed count with a threshold, following the data-filtering procedure of Chen et al. (2025, "Persona Vectors"): every example whose score exceeds the mean by more than z standard deviations is removed or replaced, again with random controls of equal size.
- **Planted mixtures (RQ3).** We plant 50, 100 or 250 harmful examples among the correct twins, train on the mixture, rank all 1,000 examples by score, and report precision at k,

the fraction of the top-k ranked examples that were planted, with k equal to the number planted. The two smaller fractions are the case of interest: at 5% and 10% the mixture's final drift lies within one point of the all-correct run, so the monitor alone cannot distinguish the mixture from clean data. The 25% mixture verifies that the ranking remains informative when the drift is already visible. Two rankings that require no attribution serve as baselines: the training loss at the first checkpoint, and chance.

- **Behaviour and utility.** For the retrained models we grade 360 free-form answers per model with the rubric of Betley et al. (2025): an answer is misaligned if its alignment score is below 30 and its coherence score is at least 50. The judge is `gpt-5.6-sol`, the model available to us at the time. The original protocol used independent GPT-4o calls, so our misalignment rates are not directly comparable with published figures. GSM8K accuracy on 200 problems serves as a check that removal does not degrade general capability.

5.3 Results

5.3.1 RQ1: The drift is distributed across most examples and arises from the answers

Table 2 and Figure 10 summarise the scores of the reference run. 762 of the 1,000 examples have a positive score, and 187 examples are required to account for half of the total positive score. The drift is therefore distributed across the dataset, and removing a small number of examples cannot eliminate it. The matched twins show that the score responds to the answer rather than to the question: the harmful answer scores above its correct twin for 90% of the questions.

Table 2: Score statistics for the 1,000-example harmful run (PC1 target).

Statistic	Value
Examples with a positive score	762 of 1,000
Examples required for half of the total positive score	187
Questions for which the harmful answer scores above its correct twin	90.1%
Correct twins with a positive score	35.7%




Figure 10: Scores of the reference run. (a) Share of the total positive score accounted for by the top-ranked examples: the top 100 account for 32%, and 187 examples are required for half. (b) Score distributions of the 1,000 harmful answers and of their correct twins on the same questions.

5.3.2 RQ2: Removal reduces the drift as predicted; the behavioural effect is not resolved

Table 3 reports the retrained models.

- **Drift.** Removing the 100 highest-scored examples yields a final drift of 22.49, removing 100 random examples 24.19 on average, and removing the 100 lowest-scored examples 26.35. The ordering follows the scores, and so does the magnitude: the summed scores of the removed examples predict a reduction of 2.6 points for top removal, against a realised reduction of 1.8 points relative to random removal. The effect amounts to roughly one noise unit per 100 examples.
- **Behaviour.** Every retrained model produces fewer misaligned answers than the full-data model (6.7% to 10.7%, against 13.8%), but removal by score is not distinguishable from random removal: the paired difference is +0.9 percentage points, with a 95% interval from −2.0 to +3.9.
- **Utility.** GSM8K accuracy lies between 88.5% and 91.0% for every model.

Table 3: Retraining after removal or replacement, one training seed per model. Drift is the final PC1 projection as a percentage of the base norm. Models trained on 900 examples end at optimizer step 114, the others at step 126. Misalignment rates are from the `gpt-5.6-sol` judge, with bootstrap 95% intervals.

Training set	Examples	Final drift	Misaligned (%)	GSM8K (%)
All 1,000 harmful (reference)	1,000	24.26	13.8 [8.7, 19.6]	88.5
Remove 100 highest-scored	900	22.49	7.6 [4.2, 11.7]	88.5
Remove 100 at random, draw 0	900	23.45	6.7 [3.1, 10.4]	90.5
Remove 100 at random, draw 1	900	23.21	7.3 [3.9, 10.9]	90.5
Remove 100 at random, draw 2	900	25.92	10.7 [6.3, 16.1]	89.0
Remove 100 lowest-scored	900	26.35	9.4 [5.1, 14.6]	89.5
Replace 100 highest-scored by correct twins	1,000	22.83	10.4 [5.9, 16.1]	91.0

5.3.3 Correct answers alone account for 71% of the drift

A run on the 1,000 correct twins, containing no harmful example, reaches a final drift of 17.31 (Figure 11a). This is 71% of the harmful run's 24.26, so most of the drift reflects adaptation to the medical domain rather than harmful content. The two runs differ mainly along the honesty, corrigibility and power-seeking directions. This observation motivated the two contrast targets, which measure drift along the direction from the all-correct run to the all-harmful run and thereby discard the component common to both. The construction rests on an assumption that should be stated: any other systematic difference between the two runs, such as answer length or style, is retained in that direction as well.

5.3.4 RQ3: The harm-specific target recovers planted examples, best at the alarm step

Table 4 reports precision at k for each ranking, and Figure 11b shows how it changes as checkpoints are added to the score.

- The PC1 target exceeds chance but not the training-loss baseline.
- The layer-18 contrast target exceeds every baseline at the alarm step (step 40): with 100 planted examples it places 66 of them in its top 100, against 52 for the training-loss baseline and 10 for chance.
- Scores accumulated up to step 40 outperform scores accumulated over the full run (0.66 against 0.54 with 100 planted examples; 0.78 against 0.60 with 250). We hypothesise that the later checkpoints have already fit the planted examples, so that their loss gradients shrink; we have not tested this directly.
- Layer 18 was selected because projecting single-example activations onto the harmful-minus-benign direction separates planted from benign examples best at that layer (AUROC 0.89 to 0.92, against 0.67 to 0.75 at layer 16, the monitor's layer). The probe was evaluated on the same mixtures used to report recovery, so the selection is retrospective and would need confirmation on an independent mixture.




Figure 11: (a) Drift during fine-tuning for the all-harmful run, the all-correct run and the mixture with 100 planted harmful examples; all three exceed the 8% reference level at approximately the same step. (b) Precision at k for the 100-example mixture as a function of the last checkpoint included in the score. The layer-18 contrast target is highest when the alarm is raised and declines thereafter.

Table 4: Precision at k, the fraction of the top-k ranked examples that were planted, with k equal to the number planted. "Step 40" accumulates the scores up to the step at which the alarm is raised; "final" accumulates over the full run. One permutation and one training seed per mixture.

Planted	Ranking	Step 40	Final
100 of 1,000	PC1 target	0.36	0.39
	Seven-trait contrast target	0.55	0.54
	Layer-18 contrast target	0.66	0.54
	Training-loss baseline	0.52	
	Chance	0.10	
250 of 1,000	PC1 target	0.55	0.54
	Seven-trait contrast target	0.67	0.63
	Layer-18 contrast target	0.78	0.60
	Training-loss baseline	0.69	
	Chance	0.25	

5.3.5 Threshold-based removal

Table 5 and Figure 12 report the threshold variant of the removal test. We used thresholds of $z = 2$, 1, 0.5 and 0, which flag 34, 152, 288 and 458 of the 1,000 examples. The first two bracket the fixed top-100 set, which corresponds to $z \approx 1.26$; the last two test whether removing a larger fraction yields a proportionally larger effect.

- Deleting the flagged examples yields a final drift 1.3 to 2.4 points below deleting an equal number of random examples at every threshold except $z = 2$, where the 34 flagged examples are too few to produce a measurable effect.
- Replacing the flagged examples by their twins yields a drift 0.1 to 1.1 points below random replacement at every threshold. The sign is consistent across thresholds, but each difference lies within noise.
- Smaller training sets yield fewer optimizer steps, so the absolute drift falls for both the flagged and the random deletion models; only the paired difference between them is interpretable.

Table 5: Final drift after removing or replacing every example whose score exceeds the mean by more than z standard deviations, with random controls of equal size. One training seed per model; the reference run reads 24.29 on the rebuilt monitor used for these runs.

z	Flagged	Delete flagged	Delete random	Replace flagged	Replace random
2	34	25.36	23.24	23.83	23.93
1	152	21.11	22.41	22.23	22.76
0.5	288	17.37	19.46	20.78	21.74
0	458	12.36	14.81	19.45	20.51




Figure 12: Final drift against the number of harmful examples remaining in the 1,000-example training set: the threshold models of Table 5, the fixed-count models of Table 3, and the planted mixtures. The Extension 2 sweep is shown dotted for its shape only; it uses a different filler dataset and a separately rebuilt monitor.

5.4 Conclusion

In the harmful medical run the drift is distributed across most of the 1,000 examples, and removing or correcting the highest-scored examples reduces it by approximately the amount the scores predict. Most of the drift on the PC1 axis, however, is produced by correct medical answers, and a 100-example intervention did not change behaviour measurably. The harm-specific target at layer 18 recovered two thirds of 100 planted harmful examples at the step at which the alarm is raised, outperforming the training-loss baseline, and it performs better early in training than late. A prospective test with a fixed layer and fixed directions, several training seeds and additional datasets is the next step.