SMTP Email API Documentation.

Explore our robust REST API. The documentation here shows how to integrate SMTP into your custom or third-party apps, start sending emails using SMTP and how to get your API Keys.

Start integrating

Leave a message for Sales

SMTP.com API v4 documentation

The SMTP.com API v4 is a RESTful (but not HATEOAS) JSON formatted API.

JSON is generally the required format for request data unless explicitly stated otherwise and must be accompanied by the corresponding HTTP header:

```
Accept: application/json
```

The SMTP.com API v4 responses are returned in JSON according to the JSend specification as it relates to JSON formatted API responses. Multiple ready-made libraries exist which can add support for this response format specification. For information see the official JSend specification (opens in a new tab).

Authentication

SMTP.com API users can authenticate a variety of ways using their specific API key. Supported authentication methods include:

URL: `https://api:{apikey}@api.smtp.com/v4`

Header: `Authorization: Basic base64(api:{apikey})`

Bearer Token Header: `Authorization: Bearer {apikey}`

Custom HTTP Header: `X-SMTPCOM-API: {apikey}`

Query String: `https://api.smtp.com/v4?api_key={apikey}`

Statistics

Returns event aggregates for the specified data slices and duration.

GET `/v4/stats/{duration}/{slice}/{slice_specifier}/{group_by}` Return event aggregates for the specified slices and duration. Slices can be chained.

Account

Return and update basic account information: first name, last name, email, company name, phone etc.

GET `/v4/account/` Get Account Details
PATCH `/v4/account/` Update Account Details

Channels

Channels, also known as senders, correspond to specific sending channels. For example an account may send email for various areas of their business including marketing, office communications, customer communications, reminders and notifications.

Channels will have their unique (system-wide) SMTP username and password for SMTP delivery and they can have their quota specified, which will be added up to the Account's total quota.

GET `/v4/channels/` Get All Channels
POST `/v4/channels/` Create a New Channel
GET `/v4/channels/{name}` Get Channel Details
DELETE `/v4/channels/{name}` Delete a Channel
PATCH `/v4/channels/{name}` Update Channel Details

API keys

API keys can be setup and configured for the account. All API keys have similar access level and will let you differentiate and audit the API usage for different API users.

GET `/v4/api_keys/` List All API Keys
POST `/v4/api_keys/` Create a New API Key
GET `/v4/api_keys/{api_key}` Get API Key Details
DELETE `/v4/api_keys/{api_key}` Delete an API Key
PATCH `/v4/api_keys/{api_key}` Update API Key

Reports

Deliver a periodic report of a channel/account activity. Frequency of reports can be one of: daily, weekly, monthly. Daily will be sent for the previous day, weekly - on Monday, for the previous week, monthly - on the first day for the previous month. If frequency is not specified, the report will be scheduled to be generated immediately, and can be retrieved from an URL once it is ready to download.

GET `/v4/reports/` Get All Reports
POST `/v4/reports/ondemand` Create On-Demand Report
GET `/v4/reports/{report_id}` Get Report Details
POST `/v4/reports/periodic` Create Periodic Report
DELETE `/v4/reports/periodic/{report_id}` Delete a Periodic Report
PATCH `/v4/reports/periodic/{report_id}` Update Periodic Report

Alerts

Setup, configure and delete custom alerts. Alerts are emails that are delivered to the account owner's email address when a given alert condition is met.

Currently a monthly quota usage alert defined which will trigger at a specific threshold of account's monthly quota.

GET `/v4/alerts/` List All Allerts
POST `/v4/alerts/` Create New Alert
GET `/v4/alerts/{alert_id}` Get Alert Details
DELETE `/v4/alerts/{alert_id}` Delete Alert
PATCH `/v4/alerts/{alert_id}` Update Alert Details

DKIMs

DKIM key settings can be created and updated for each registered domain.

A domain must be registered and verified for the account first, before one can add any DKIM keys. DKIM key will pass a validation, when added, and if there is no correct public key available, the DKIM key will be rejected.

GET `/v4/domains/` Get All Registered Domains
POST `/v4/domains/` Register a Domain
GET `/v4/domains/{domain_name}` Get Domain Details
DELETE `/v4/domains/{domain_name}` Delete Domain
PATCH `/v4/domains/{domain_name}` Update Domain Details
GET `/v4/domains/{domain_name}/dkim_keys` Get DKIM for Domain
POST `/v4/domains/{domain_name}/dkim_keys` Add DKIM for Domain
DELETE `/v4/domains/{domain_name}/dkim_keys` Delete DKIM for Domain
PATCH `/v4/domains/{domain_name}/dkim_keys` Update DKIM Key Details

Callbacks

Callbacks, also known as web notifications or web hooks, allow user to be notified about any kind of events. Callbacks will be sent over HTTP POST to a URL, specified during callback creation or to Amazon SQS queue. You can see the most recent callback attempts log to troubleshoot missing callbacks.

Usually, when we receive a non-positive response from a callback URL (non-2xx status), we are retrying this callback several times (depending on our internal settings), until we give up and discard it forever.

Please note, that we try to batch callback data into convenient data packages of variable size (depending on the Callback Engine's state and settings) and do not fire them one-by-one to avoid stressing both a callback end-point and our Engine. Also note that callbacks must be created on a per-channel basis.

GET `/v4/callbacks/` List All Callbacks
DELETE `/v4/callbacks/` Delete All Callbacks
GET `/v4/callbacks/{event}` Get Callback Details
POST `/v4/callbacks/{event}` Create Callback
DELETE `/v4/callbacks/{event}` Delete Callback
PATCH `/v4/callbacks/{event}` Update Callback Details
GET `/v4/callbacks/log` View Callback Logs

Messages

Access to detailed information regarding all messages and their events. Unlike callbacks, which are fired with an event's information as they happen in real time, this resource provides a report over a specific time period on demand. You can specify the level of detail such as: all, delivered, bounced, domain, channel slice, time interval etc.

The detailed statistics are provided only for the last 7 calendar days not including today, (e.g. on Jan 30 it would return events from Jan 23 00:00 UTC to Jan 30 23:59 UTC) and should be requested on a per-channel basis (i.e. there are no account wide detailed statistics).

Because it's an intensive call, both limit and offset are required.

The returned data is sorted by an event time, ascending (earlier events first).

GET `/v4/messages` Get Detailed Messages Info
POST `/v4/messages` Send a Message
POST `/v4/messages/mime` Send MIME Message

Models

```
InvalidKey ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Data
                         errors             ⌄ [ ⌄ {
                                              description:     error object
                                              error_field      string
                                                               error message
                                            }]
                       }
}
```

```
BadRequestSchema ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Data
                         errors             ⌄ {
                                              description:     error object
                                            }
                       }
}
```

```
StatsResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Stats data.
                         items              ⌄ [ ⌄ {
                                              accepted         integer
                                              complained       integer
                                              delivered        integer
                                              clicked          integer
                                              opened           integer
                                              failed           integer
                                              unsubscribed     integer
                                              queued           integer
                                            }]
                       }
}
```

```
Reports ⌄ {
   status              string
                       Request status
   data                ⌄ {
                         description:       Periodic Reports
                         periodic           ⌄ [ ⌄ {
                                              frequency        string
                                                               Periodic report frequency
                                                               Enum:
                                                                 > Array [ 3 ]
                                              report_id        string
                                                               Unique report ID
                                              events           string
                                                               Preset of events returned in a
                                                               periodic report
                                              channel          string
                                                               Name of the channel for which a
                                                               given report has been defined
                                              report_time      string
                                                               The hour at which the report
                                                               should be sent, values range from
                                                               0 to 23
                                            }]
                         ondemand           ⌄ [ ⌄ {
                                              status           string
                                                               Current status of a given on-
                                                               demand report
                                                               Enum:
                                                                 > Array [ 3 ]
                                              name             string
                                                               Human readable name of an on-
                                                               demand report (auto-generated)
                                              url              string
                                                               The unique URL from which to
                                                               download an on-demand report
                                              time_req         integer
                                                               Time when a given on-demand
                                                               report has been requested. RFC
                                                               2822 or UNIX epoch format
                                              progress         integer
                                                               Percentage of completion for an
                                                               on-demand report
                                              channel          string
                                                               Name of the channel for which a
                                                               given report has been defined
                                              report_id        string
                                                               Unique report ID
                                            }]
                       }
}
```

```
Report ⌄ {
   frequency           string
                       Report frequency - one of:
                         • daily - every day at a specified hour
                         • weekly - Mondays at a specified hour
                         • monthly - 1st day of the month at a specified hour
                       Enum:
                         > Array [ 3 ]
   report_id           string
                       Unique report ID
   events              string
                       Preset of events returned in a report:
                         • hard_bounced
                         • failed
                         • delivered
                         • sent
                         • pending
                         • total
                         • above if not specified all events are included.
   channel             string
                       Name of channel (sender). If not specified all channels will be reported
   report_time         string
                       The hour at which the report should be sent, values range from 0 to 23
   status              string
                       Current status of a given on-demand report
                       Enum:
                         > Array [ 3 ]
   name                string
                       Human readable name of an on-demand report (auto-generated)
   url                 string
                       The unique URL from which to download an on-demand report from
   time_req            integer
                       Time when a given on-demand report has been requested. RFC 2822 or UNIX epoch format
   progress            integer
                       Percentage of completion for an on-demand report
}
```

```
GetCallbackResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Callbacks
                         items              ⌄ [ ⌄ {
                                              medium           string
                                                               Medium by which the callback data
                                                               is sent. Possible values are one
                                                               of:
                                                                 • http
                                                                 • aws
                                                               Enum:
                                                                 > Array [ 2 ]
                                              event            string
                                                               Event for which the callback has
                                                               been created. Valid types are:
                                                                 • delivered - message delivered
                                                                 • failed - message bounced
                                                                 • complained - complaint received
                                                                 • bounceback - bounce back notification received
                                                                 • received - message received by our system
                                                                 • queued - message in queue (transient)
                                                                 • hard_bounced - hard bounce received
                                                                 • opened - message opened
                                                                 • clicked - URL in message clicked
                                                                 • unsubscribed - unsubscribe received
                                              channel          string
                                                               Name of the channel for which the
                                                               callback has been created
                                              address          string
                                                               Address to which the callback data
                                                               is sent. This will be either a URL
                                                               for http-based callbacks or the
                                                               Amazon SQS queue name for SQS-based
                                                               callbacks
                                              aws_data         string
                                                               Amazon SQS settings
                                            }]
                       }
}
```

```
CreateCallbackResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Data
                       }
}
```

```
GetCallbackLogs ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Callback Logs
                         items              ⌄ [ ⌄ {
                                              code             integer
                                                               HTTP code for the callback
                                              msg              string
                                                               HTTP or AWS SQS response message
                                                               from the server
                                              time             string
                                                               Time of callback in RFC 2822 or
                                                               UNIX epoch format
                                            }]
                       }
}
```

```
GetCallbackDetails ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Data object
                         medium             string
                                            Medium by which the callback data is sent. Possible values are
                                            one of:
                                              • http
                                              • aws
                                            Enum:
                                              > Array [ 2 ]
                         event              string
                                            Event for which the callback has been created. Valid types are:
                                              • delivered - message delivered
                                              • failed - message bounced
                                              • complained - complaint received
                                              • bounceback - bounce back notification received
                                              • received - message received by our system
                                              • queued - message in queue (transient)
                                              • hard_bounced - hard bounce received
                                              • opened - message opened
                                              • clicked - URL in message clicked
                                              • unsubscribed - unsubscribe received
                         channel            string
                                            Name of the channel for which the callback has been created
                         address            string
                                            Address to which the callback data is sent. This will be either
                                            a URL for http-based callbacks or the Amazon SQS queue name for
                                            SQS-based callbacks
                         aws_data           string
                                            Amazon SQS settings
                       }
}
```

```
StatusResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       empty object
                       }
}
```

```
PostMessageResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         msg_id             string
                                            Unique Message ID of accepted message
                       }
}
```

```
MimeResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         msg_id             string
                                            Unique Message ID of accepted message
                       }
}
```

```
MessagesResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Message data
                         items              ⌄ [ ⌄ {
                                              msg_id           string
                                                               Unique Message ID
                                              msg_time         integer
                                                               Time at which the message was sent
                                              channel          string
                                                               Name of the channel for which the message was
                                                               sent
                                              smtp_vars        ⌄ {
                                                                 description:   Custom
                                                                                parameters and
                                                                                their values
                                                                                (comes both
                                                                                from X-SMTPAPI
                                                                                header's
                                                                                unique_args
                                                                                parameter
                                                               }
                                              msg_data         ⌄ {
                                                                 rcpt_to        string
                                                                                Email address
                                                                                of the
                                                                                recipient
                                                                 from           string
                                                                                Email address
                                                                                of the sender
                                                                 subject        string
                                                                                Message subject
                                                               }
                                              details          ⌄ {
                                                                 description:   Delivery data
                                                                 delivery       ⌄ {
                                                                                  finished   string
                                                                                             Timestamp
                                                                                             of when
                                                                                             the
                                                                                             message was
                                                                                             delivered
                                                                                  retries    integer
                                                                                             Number of
                                                                                             retries after
                                                                                             the initial
                                                                                             delivery
                                                                                             attempt
                                                                                  event      string
                                                                                             One of:
                                                                                               • delivered
                                                                                               • failed
                                                                                               • queued
                                                                                  code       string
                                                                                             The last SMTP
                                                                                             response code
                                                                                             received from a
                                                                                             peer
                                                                                  status     string
                                                                                             The last SMTP
                                                                                             response
                                                                                             received from a
                                                                                             peer
                                                                                }
                                                               }
                                              opens            ⌄ {
                                                                 description:   Opens Data
                                                                 items          ⌄ [ ⌄ {
                                                                                  open_time  string
                                                                                             Timestamp
                                                                                             of when
                                                                                             the
                                                                                             message
                                                                                             was
                                                                                             opened
                                                                                  remote_ip  string
                                                                                             IP
                                                                                             address
                                                                                             of where
                                                                                             the
                                                                                             message
                                                                                             was
                                                                                             opened
                                                                                  ua         string
                                                                                             User
                                                                                             agent of
                                                                                             device on
                                                                                             which the
                                                                                             message
                                                                                             was
                                                                                             opened
                                                                                }]
                                                               }
                                              clicks           ⌄ {
                                                                 description:   Clicks Data
                                                                 items          ⌄ [ ⌄ {
                                                                                  click_time string
                                                                                             Timestamp
                                                                                             of when
                                                                                             message
                                                                                             links
                                                                                             were
                                                                                             clicked
                                                                                  remote_ip  string
                                                                                             IP
                                                                                             address
                                                                                             of where
                                                                                             links
                                                                                             were
                                                                                             clicked
                                                                                  ua         string
                                                                                             User
                                                                                             agent of
                                                                                             device on
                                                                                             which
                                                                                             links
                                                                                             were
                                                                                             clicked
                                                                                }]
                                                               }
                                              abuse            ⌄ {
                                                                 description:   Abuse Data
                                                                 complaints     ⌄ [ ⌄ {
                                                                                  report_time string
                                                                                             Time when
                                                                                             the
                                                                                             complaint
                                                                                             was made
                                                                                  provider   string
                                                                                             Abuse
                                                                                             provider
                                                                                             information
                                                                                }]
                                                               }
                                              unsubs           ⌄ {
                                                                 description:   Unsubscribes Data
                                                                 items          ⌄ [ ⌄ {
                                                                                  unsub_time string
                                                                                             Time when
                                                                                             the
                                                                                             unsubscribe
                                                                                             request was
                                                                                             made
                                                                                }]
                                                               }
                                            }]
                       }
}
```

```
GetDomainDetailsResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Domains
                         domain_name        string
                                            Registered domain name
                         enabled            boolean
                                            Flag indicating whether the domain is enabled for the given
                                            account
                       }
}
```

```
CreateDomainResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Domain
                         domain_name        string
                                            request result
                       }
}
```

```
GetDomainsResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Domains
                         items              ⌄ [ ⌄ {
                                              domain_name      string
                                                               Registered domain name
                                              enabled          boolean
                                                               Flag indicating whether the
                                                               domain is enabled for the given
                                                               account
                                            }]
                       }
}
```

```
Channels ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Channels
                         items              ⌄ [ ⌄ {
                                              status           string
                                                               Current status of the channel
                                              quota            integer
                                                               Quota for the channel
                                              name             string
                                                               Name of the channel (sender)
                                              usage            integer
                                                               Current usage for the channel
                                              date_created     integer
                                                               Timestamp for when the channel
                                                               was originally created
                                              smtp_username    string
                                                               Username for the channel
                                            }]
                       }
}
```

```
Channel ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Channel
                         status             string
                                            Current status of the channel
                         quota              integer
                                            Quota for the channel
                         label              string
                                            TODO FIXME
                         usage              integer
                                            Current usage for the channel
                         date_created       integer
                                            Timestamp for when the channel was originally created
                         smtp_username      string
                                            Username for the channel
                       }
}
```

```
CreateDkimKey ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Domain
                         dkim_key           string
                                            request result
                       }
}
```

```
GetDomainDetails ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Domain
                         domain_name        string
                                            Registered domain name
                         selector           string
                                            Name of the DKIM selector for this domain
                         private_key        string
                                            Private key of the DKIM record
                         is_valid           boolean
                                            Boolean flag indicating whether this DKIM is valid - i.e.
                                            private key matches the public key, identified by a selector
                                            for this domain
                       }
}
```

```
GetApiKeys ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       API Keys
                         items              ⌄ [ ⌄ {
                                              status           string
                                                               Current status of the API key
                                              description      string
                                                               Description for API key
                                              key              string
                                                               The actual API key value
                                              date_created     string
                                                               Timestamp of API key creation
                                            }]
                       }
}
```

```
APIKey ⌄ {
   status              string
                       Current status of the API key
   description         string
                       Description for the API key
   key                 string
                       The actual API key value
   date_created        string
                       Timestamp of when the API key was first created.
}
```

```
GetAlertDetails ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Alert
                         type               string
                                            An alert's type. Currently only "monthly_quota" is supported
                                            Enum:
                                              > Array [ 1 ]
                         threshold          string
                                            A number which represents a percentage of an account's monthly
                                            quota. Must be decimal between 0 and 1
                                            Enum:
                                              > Array [ 4 ]
                         alert_id           string
                                            alert ID
                       }
}
```

```
GetAlertResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Alert
                         items              ⌄ [ ⌄ {
                                              type             string
                                                               An alert's type. Currently only
                                                               "monthly_quota" is supported
                                                               Enum:
                                                                 > Array [ 1 ]
                                              threshold        string
                                                               A number which represents a
                                                               percentage of an account's
                                                               monthly quota. Must be decimal
                                                               between 0 and 1
                                                               Enum:
                                                                 > Array [ 4 ]
                                              alert_id         string
                                                               alert ID
                                            }]
                       }
}
```

```
UpdateAccountResponse ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Account
                         account            string
                                            Account Update Status
                       }
}
```

```
Account ⌄ {
   status              string
                       Request status.
   data                ⌄ {
                         description:       Account
                         status             string
                                            Status of the account
                         first_name         string
                                            First name of account owner
                         last_name          string
                                            Last name of account owner
                         phone              string
                                            Phone number of account owner
                         website            string
                                            Website of account owner
                         email              string
                                            Email address of account owner
                         company_name       string
                                            Account owner's company name
                         address            ⌄ {
                                              description:     Full address of account owner.
                                                               See below
                                              street           string
                                                               Account owner's street address
                                              city             string
                                                               Account owner's city
                                              state            string
                                                               Account owner's state
                                              country          string
                                                               Account owner's country
                                            }
                         usage              integer
                                            Account's usage
                         date_created       integer
                                            Account's creation time (in UTC)
                       }
}
```

```
sliceValue  string
Enum:
  > Array [ 4 ]
```

```
durationValue  string
Enum:
  > Array [ 16 ]
```

— GET STARTED

Purchase an SMTP Email Relay & API plan

Start integrating and sending in minutes.

GET STARTED WITH 50,000 EMAILS FOR $25/ MO.

Purchase

Or view all plans ⟶

SMTP

SMTP.com is a premium email delivery and email relay solution that enables you to send and track high volume emails effortlessly.

— SERVICES
- Email Relay API
- Transactional email
- SMTP for developers
- SMTP for marketers
- Managed delivery

— GET STARTED
- Pricing
- Free Quote
- API documentation
- Integrations

— ABOUT
- About us
- Why SMTP
- Contact us
- Resource center
- Email Deliverability Blog
- Affiliate Program

— LEGAL
- Privacy policy
- Terms and conditions
- Partner program policy
- Code of ethics and business
- Anti-Spam policy
- Cookie policy
- Customer Code of Conduct Policy
- Do not sell my personal information
- Privacy Preferences

© 2017 - 2026 J2 Global Canada, Inc., a Ziff Davis company. All rights reserved.
Accessibility Policy
SMTP.com is a trademark of J2 Global Canada.