

# **Lab Report**

Course Name: Internet of Things

Course Code: CSE 406

Section No: 01

## **Lab Exercise No: 03**

### **Submitted To:**

Dr. Raihan Ul Islam

Associate Professor

Department of Computer Science & Engineering

### **Submitted By:**

Student's Name: Jobayer Faisal Fahim

Student's ID: 2022-2-60-130

**Date of submission: July 14, 2025**

## **1. Introduction**



UART (Universal Asynchronous Receiver/Transmitter) is a serial communication protocol that uses TX (transmit) and RX (receive) lines to asynchronously transfer data between two devices. It relies on a shared baud rate but does not require a clock line. In this lab, we aim to measure the throughput, transfer speed, and error rate of UART communication between two NodeMCU ESP8266 modules connected through expansion boards and a breadboard. The test parameters included various baud rates (9600, 38400, 115200), message sizes (10, 50, 100 bytes), and transmission intervals (0 ms, 10 ms, 100 ms).

## **2. Methodology**

### **Hardware Setup**

Two NodeMCU ESP8266 boards were connected using jumper wires on a breadboard through their expansion boards. The TX pin (D5) of NodeMCU 1 was connected to the RX pin (D6) of NodeMCU 2, and vice versa (NodeMCU 2 D5 → NodeMCU 1 D6). A common ground (GND) was shared between both boards. Some initial wiring issues caused unstable connections but were resolved by replacing jumper wires and reseating the expansion boards.

## UART PHYSICAL CONNECTION SETUP:




## Software Setup

We programmed both NodeMCUs using the Arduino IDE. NodeMCU 1 acted as the master transmitter, while NodeMCU 2 acted as the slave receiver. The data sent included identifiers and payloads (e.g., "5:DXXX..."). ARDUINO UNO software was used on a laptop to log output from each NodeMCU. Before each transmission cycle, the master sent a synchronization message like BAUD:38400, which the slave interpreted to configure its SoftwareSerial baud rate accordingly.

### 3. Results

#### Data Collection

#### Communication at baud rate 9600:



The screenshot displays the Arduino IDE interface. The top menu bar includes File, Edit, Sketch, Tools, and Help. The toolbar shows icons for checking, running, and uploading code, along with a dropdown menu for the board, currently set to 'NodeMCU 1.0 (ESP-12E Module)'. The left sidebar contains icons for the file explorer, libraries, and search. The main editor window shows the code for 'Node1\_Master\_StressTest.ino'. The code includes comments and defines pins, baud rates, message sizes, and intervals. The Serial Monitor is open at the bottom, showing the output of the program. The output includes statistics for messages sent and received, error rate, throughput, and message rate for two different test configurations.

```
1 // MASTER REVEIVER
2
3 #include <SoftwareSerial.h>
4
5 // Define SoftwareSerial pins
6 SoftwareSerial mySerial(D6, D5); // RX = D6, TX = D5
7
8 // Test parameters
9 const int baudRates[] = {9600, 38400, 115200};
10 //const int baudRates[] = {230400, 250000};
11
12 const int messageSizes[] = {100, 50, 10};
13 //const int intervals[] = {0, 10, 100}; // Delay in ms
14
15 //const int intervals[] = {100, 100, 10}; // Delay in ms
```


Output: Serial Monitor X

Message (Enter to send message to 'NodeMCU 1.0 (ESP-12E Module)' on 'CO... New Line 115200 baud

Messages Sent: 85  
Messages Received: 85  
Errors: 0  
Error Rate: 0.00%  
Throughput: 75.50 bytes/second  
Message Rate: 8.50 messages/second

Test: Baud=9600, Size=10 bytes, Interval=100ms  
Test Results:  
Messages Sent: 85  
Messages Received: 85  
Errors: 0  
Error Rate: 0.00%  
Throughput: 75.50 bytes/second  
Message Rate: 8.50 messages/second

Test: Baud=9600, Size=10 bytes, Interval=10ms



The screenshot displays the Arduino IDE interface for a project named "NodeMCU2\_Slave\_StressTestino". The sketch is written in C++ and uses the SoftwareSerial library. It defines pins D6 and D5 for RX and TX, respectively, and initializes a SoftwareSerial object named mySerial. The setup function configures the serial port at 115200 baud for debugging and prints a message to the serial monitor. The Serial Monitor is open, showing a series of received and echoed messages, indicating successful communication at the specified baud rate.

```
1 // SLAVE SERVER
2
3 #include <SoftwareSerial.h>
4
5 // Define SoftwareSerial pins
6 SoftwareSerial mySerial(D6, D5); // RX = D6, TX = D5
7
8 void setup() {
9   Serial.begin(115200); // Debugging
10  mySerial.begin(9600); // Start with 9600
11  Serial.println("NodeMCU 2: UART Slave Initialized");
12 }
```


Serial Monitor Output:

```
NodeMCU 2: echo message
NodeMCU 2: Received '33:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '34:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '35:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '36:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '37:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '38:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '39:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '40:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '41:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
NodeMCU 2: Echoed message
NodeMCU 2: Received '42:XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

**Communication at baud rate 115200:**



## Communication at different baud rate :




The screenshot displays the Arduino IDE interface. The top toolbar shows the upload button (a green arrow) is active. The target board is set to 'NodeMCU 1.0 (ESP-12E Module)'. The file 'Node1\_Master\_StressTestino.ino' is open in the editor. The code defines software serial pins, test parameters for baud rates, message sizes, and intervals, and sets a test duration and timeout. The Serial Monitor is open, showing a series of 'Timeout error' messages, followed by test results: 17 messages sent, 0 received, 100.00% error rate, 14.30 bytes/second throughput, and 1.70 messages/second message rate.

```
5 // Define SoftwareSerial pins
6 SoftwareSerial mySerial(D6, D5); // RX = D6, TX = D5
7
8 // Test parameters
9 const int baudRates[] = {9600, 38400, 115200};
10 //const int baudRates[] = {230400, 250000};
11
12 const int messageSizes[] = {100, 50, 10};
13 //const int intervals[] = {0, 10, 100}; // Delay in ms
14
15 const int intervals[] = {100, 100, 10}; // Delay in ms
16 const unsigned long testDuration = 10000; // 10 seconds per test
17 const int timeout = 500; // 500ms timeout for response
18
19 void setup() {
20   mySerial.begin(baudRates[0]);
21 }
```

Output Serial Monitor X

Message (Enter to send message to 'NodeMCU 1.0 (ESP-12E Module)' on 'COM...') New Line 115200 baud

Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Timeout error  
Test Results:  
Messages Sent: 17  
Messages Received: 0  
Errors: 17  
Error Rate: 100.00%  
Throughput: 14.30 bytes/second  
Message Rate: 1.70 messages/second



## Observations

- Throughput generally increased with both higher baud rates and larger message sizes, as more data was transmitted in the same period.
- Message rate decreased with larger messages or longer intervals.
- The error rate was higher than 115200 baud, particularly with 0 ms intervals, due to buffer overflows or timing mismatches.
- Some mismatch errors occurred (e.g., expected "5:DXXX..." but got corrupted strings). These were mitigated by stripping extra carriage returns or newlines (`\r\n`) and using `trim()` in the slave script.

## 4. Analysis

## Throughput

Higher baud rates (38400 and 115200) and larger message sizes (50 - 100 bytes) resulted in higher throughput. This is because UART transmits more bytes per unit time when the line speed is



increased or when each message contains more data. However, SoftwareSerial's buffer size limitation caused performance degradation at 115200 baud, leading to occasional data loss.

### **Transfer Speed**

The message rate was highest when smaller messages (10 bytes) were sent at short intervals (0 - 10 ms), but these configurations also showed increased error rates. With longer messages, although fewer messages were sent per second, overall data transferred was higher and more stable.

### **Error Rate**

Error rates spiked when:

- Baud rate = 115200.
- Message Size: 50 bytes
- Interval = 0 ms, leading to message collision or buffer overflows.
- SoftwareSerial (used on NodeMCU 2) could not handle the high-speed input, particularly with large payloads.
- This achieved 325.70 bytes/sec throughput, with a low error rate of 6.06%.

### **Challenges**

- Synchronizing baud rates was initially inconsistent; resolved by explicitly sending a BAUD: signal.
- Wiring issues on the breadboard introduced occasional loose connections; resolved by stabilizing jumpers and using a shorter ground path.
- SoftwareSerial limitations impacted performance at high speeds. If both UARTs used hardware serial, performance would have likely improved.

## **5. Conclusion**

This lab demonstrated the trade-offs in UART communication between speed, throughput, and error resilience. Our best configuration 38400 baud with 50-byte messages and 10 ms interval delivered reliable transmission at 5000 bytes/sec with a minimal error rate. While UART is suitable for low to moderate-speed data transfer, the limitations in SoftwareSerial, especially at 115200 baud, highlight the need for hardware UARTs or improved buffering. Future improvements could include using level shifters, shielding wires from interference, and integrating error-correction algorithms.

## 6. References

- [Serial Connection - ESP8266 - — esptool latest documentation](#)
- [NodeMCU ESP8266 Documentation](#)