Directory Structure

These rules apply only to the directory structure question:

[DIR-1] File or folder names should not contain spaces.
[DIR-2] Treat File and folder names as case-insensitive.
[DIR-3] Files with incorrect extensions (e.g. .html.html) are incorrect.

Global

These are global rules and apply to all HTML and CSS rules:

[ELEM-1] If a placeholder needs to be substituted in a comment or in text. Award the mark if any part of the placeholder has been changed. Do not consider formatting. Only penalise if the placeholder was not changed.

CSS-only

The following rules apply to all declarations:

[CSS-1] If a declaration does not end with a semicolon, subtract 1 mark.

[CSS-2] If a unit is included for a zero value, subtract 1 mark.
Note: Require unit for non-zero values.

[CSS-3a] Accept alternative equivalent colour names or hexadecimal (e.g. forestgreen ≡ #228B22).
Basic colours can be specified in any of the following ways:

- Named colours (keywords): color: red; [Note: There are 140+ standard names according to the CSS Colour specifications]
- Hexadecimal notation: color: #ff0000; [Note: Characters in the codes are not case-sensitive]
- Hexadecimal notation (shorthand form for when pairs repeat): color:#f00
- RGB functional notation:
    - Explicit Red, Green, Blue values: color: rgb(255,0,0);
    - Also valid with percentages: color: rgb(100%, 0, 0);
- HSL functional notation: color: hsl (0, 100%, 50%); /* for red */

Note: When the opacity of a colour needs to be specified, rgba(...) and hsla(...) are used.

[CSS-3b] Accept alternative equivalent short or long hexadecimal forms (e.g. #fff ≡ #ffffff). Note: Alphabetic characters (a,b,c,d,e,f) are not case-sensitive.

[CSS-3c] Accept alternative equivalent shorthand or longhand properties (e.g. background: #fff ≡ background-color: #fff or e.g. margin: 1rem ≡ margin: 1rem 1rem 1rem 1rem).

Additional examples for shorthand properties:

- margin

    - margin: 10px;
    - margin: 10px 10px;
    - margin: 10px 10px 10px;
    - margin: 10px 10px 10px 10px;
- padding
    - padding: 10px;
    - padding: 10px 10px;
    - padding: 10px 10px 10px;
    - padding: 10px 10px 10px 10px;
- border
    - Use, for example, `border: 2px solid black;` instead of specifying the width, style, and colour in separate declarations.
- font
    - The shorthand property can only be used if BOTH the font-size and font-family are specified.
        - font: italic bold 16px Arial, sans-serif;
        - font: 16px Arial, sans-serif;
- list-style
    - Combines list-style-type, list-style-position, and list-style-image.
    - Can also be used with any **one** of these values.
- border-radius:
    - border-radius: 10px;
    - border-radius: 10px 10px;
    - border-radius: 10px 10px 10px 10px;

Note: For margin, padding, and all border properties, students must use a relevant shorthand property (if applicable/possible).

[CSS-3d] Accept alternative equivalent numeric or named font weights (e.g. font-weight: bold ≡ font-weight: 700).

[CSS-3e] Accept alternative equivalent pseudo-class expressions (e.g. :nth-child(2n) ≡ :nth-child(even)).

Additional examples:

- :nth-child(2n+1) ≡ :nth-child(odd)
- A single position can be expressed as an + b - for example :nth-child(3) OR :nth-child(0n+3)
    - Guideline: Accept any mathematically equivalent `an + b` form
- There are other patterns as well, but we don't typically use those in CSIS1664.

The following rules apply to all selectors:

[CSS-4] Compound selectors (e.g. nav a, nav .current) should include all parts. If any part of the compound selector is missing, the selector is incorrect.

[CSS-5] Class selectors (e.g .header) and element selectors (e.g. header) are not equivalent. Selector punctuation must match exactly. If it does not match, the selector is incorrect.

This rule applies to all CSS:

[CSS-6] A selector and its declarations are marked independently of each other. A mistake in the selector does not affect the declaration. Similarly, a mistake in the declaration does not affect the selector.

HTML-only

These rules apply to all HTML rules:

[HTML-1] Spelling mistakes, punctuation, and capitalisation differences in text content should not be penalised.

[HTML-2] Alternative date format variations should not be penalised as long as the date is correct.

These rules apply to any parent-child element relationship:

[HTML-3] In a parent-child element relationship, the criterion is met when the Y element exists anywhere within X.

[HTML-4] When a structural error in a single parent element causes multiple child criteria to fail, the deduction is applied only to the criterion that directly tests the parent structure. Child criteria are evaluated as if the parent structure were correct.

[HTML-5a] Every input has an accessible label.

When the for attribute of a <label> must match the id ~~and name~~ attributes of an associated form control (such as <input>, <select>, or <textarea>): The three values can be ANY valid string, but must be identical (case-sensitive).

[HTML-5b] If an id value of an attribute contains a space, it is incorrect.
The following should be enforced for the values of id attributes (which also includes the id attributes of form controls (see HTML-5a):

- Start with a **letter**
- Use only:
    - letters (a–z, A–Z)
    - digits (0–9)
    - hyphens (-)
    - underscores (_)
- No spaces allowed

[HTML-5c] All values of attributes should be encapsulated with quotation marks. Both single and double quotes are acceptable. If it is not encapsulated, the attribute is incorrect.

[HTML-5d] Additional valid attributes are not penalised, unless they conflict with the function of other attributes on the same element.
[HTML-5e] All form controls must have a name attribute.

[HTML-6] When more than one <form> element is included to create a SINGLE form, Only penalise once on the criterion that tests the form's existence. For all subsequent criteria about form contents, identify the <form> element whose contents most closely match the rubric requirements. Mark all subsequent criteria against this <form> element only. All other <form> elements (and their contents) are ignored.

[HTML-7] Similar to [HTML-6] but for tables?

[HTML-8] All tables must include at least a <tbody> element.

[HTML-9] For empty elements (e.g. <img>, <link>,
, <hr>), the tag can end with either > or />

[HTML-10] For container elements (i.e. non-empty elements), both the start tag and end tag must be included.

[HTML-11] All tag names (i.e. element names) must be in lower case.