



ANWIN GROUP

11-3FL., No. 171, Sec.4, Nan King East Road, Taipei, 105, Taiwan. R.O.C
Tel: 886-2-2717-3068 / Fax: 886-2-2717-3998 / E-mail: Marketing@awint.com

WATER BASE OVERPRINT VARNISH

TECHNICAL INFORMATION

Wintop W66L

Description

Wintop W66L is designed for water-based lamination glue between paper and OPP film. It provides high adhesion, good operation property, and suitable viscosity.

Typical Properties

Appearance/Color	Milky White Liquid
Viscosity (Ford Cup #4, 25°C)	15±5 sec
Non Volatile Content	42±3%
(The data above are used for reference only. For detailed product specifications, please contact our sales department)	

Application Instructions

Thoroughly stir up the varnish prior to application. Pretest to check the suitability and determine the optimum printing performance conditions for substrate, varnish and press machine etc.

Package

200Kg drum, net weight.

Storage and Safety Handling

Wintop W66L contains no organic solvent, and it is non-flammable; low toxicity and extremely mild irritation, so it is harm less to use. When operating, wear neoprene gloves and PVC chemical resistant suit and charcoal filtered mask to prevent direct contact and inhalation. If contacted with skin, use soap and water to remove contaminants, if contacted with eyes, rinse immediately with large amount of fresh distilled water or sterilize with 0.9% brine

Fire fighting material : foam or CO2 extinguisher.

Keep **Wintop W66L** away from high temperature and avoid exposing to sunlight. Keep tightly closed when it is stored. The suggested period of storage is 6 months.