

Technische Information

specialties
COMMERCIALS
back again
LETTERPRESS
UV printing ink and lacquer
and lacquer

EURAPID O3 Ink Series

Ink Series for Conventional Offset Printing on Metals

Characteristics

With the EURAPID O3 Ink Series we present a series for conventional sheetfed printing and body printing on coated and uncoated metals. The ink series is free from mineral oil and is low-yellowing. It is characterised by its excellent formability and deep-drawing properties as well as the reduced skin formation in the can or duct.

Technical Data

- Drying/Curing: Conventional Oil Based
- Substrate: Metal Coated - Metal Uncoated - Aluminium
- Printing Process: Offset Sheet-Fed - Letterpress - Indirect Letterpress
- Printing Behaviour: Fast Drying (170°C/10min.) - Reduced skin formation in the can or duct
- Surface Properties: Gloss - Mineral Oil Free - Low Yellowing - Flexible Ink Film - Light Resistance At Least 6 - Temperature Resistant until 180°C/10min.
- Further Processing: Overvarnishing - Forming - Deep Drawing - Beading
- Application: 2 Piece Cans - 3 Piece Cans - Aluminium Tubes - Monoblock Aerosol Cans - Screw Caps - Crown Corks - Long Caps
- Market: Metal Decoration
- Available Systems: 4 Colour Process - PANTONE® Base Colours - Z Base Colours
- Mixing Lists Basis: PANTONE® Base Colours - Z Base Colours

Packing Units

- 1 kg metal can
- 2,5 kg metal can

Technical Service Center

Kindly note that we are ready at any time for competent technical application support on your site. Please contact our

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011. With the present edition expires the validity of all older editions.

Page 1 of 10

Technische Information



technical service centre for printing inks:

Ink-Service@Zeller-Gmelin.de
Tel: +49 7161 802-279

Covering Whites

EURAPID O3 types of opaque white are characterized by their high opacity at low ink lay down. All types of opaque white are resistant against spirit, solvent mixture and alkali (according to DIN 16524). Additionally they are low-yellowing.

EURAPID O3-X55001

opaque white, undyed for mixing

EURAPID O3-X55002

Opaque white, violet dyed

EURAPID O3-X55002

Opaque white, blue dyed

Additives

EURAPID O0015 Thinner

Addition max. 3%

Reduces tack and viscosity. Add carefully, very efficient.

EURAPID T111 Drying Agent

Addition max. 0,5 - 1,0%

Improves through-drying

EURAPID O3-X60004 Transparent White

Addition unlimited

Highly transparent, for reducing colour strength, tack and viscosity remain at a comparable level.

EURAPID O3-X60002 Varnish for Colours

Addition max. 10%

Improves the ink transfer

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 2 of 10

Technische Information

specialties COMMERCIALS
back again
LETTERPRESS
UV printing ink and lacquer

EURAPID O3-X60003 Varnish for Covering White

Addition max. 10%

Improves the ink transfer

Roller Cleaning Paste P866

Only for rubbing into ink rollers, not suitable as ink additive

For cleaning of the ink rollers in offset and letterpress printing units from conventional inks. Distribute paste with spatula on the oscillating rollers, let machine run without printing for several minutes, scrape off and wash again.

Remark:

The addition of any additive might change the overall characteristics of the printing ink.

Storage

Optimal storage conditions:

The optimal storage temperature is 20°C. Higher storage temperatures reduce the shelf-life.

Remarks:

- protect from frost
- store in a cool and dark place
- stir well before use
- can should be closed immediately after usage

Warranty:

If the inks are stored correctly, we guarantee a shelf life of 6 months from date of delivery, as our raw material suppliers guarantee this period to us. However we know from practical experience that the inks can remain usable for 1-2 years or longer if they are properly handled and stored.

Service

Complete PANTONE® mixing recommendations. Ink formulation systems, mixing systems and dispensing systems are possible in different expansion levels.

Base ink basis for mixing recommendations:

- EURAPID O3-P... PANTONE® base inks
- EURAPID O3-Z... high intensity monopigmented base inks

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 3 of 10



Technische Information



O3-C... PANTONE® mixed shades "coated"

Special Colours: O3-X...

Covering White: O3-X55...

Monopigmented Base Inks

For ink mixing we recommend our mono-pigmented base inks. It is a print-ready system, with maximum colour strength. These base inks contain only one pigment respectively.

Advantages:

- Ink formulations are better reproducible
- Higher production security
- The higher colour-intensity makes printing with reduced ink lay-down possible
- Reduced dot gain
- More flexibility when adjusting colour strength for solids or fine texts
- Mixing recommendations are available for all PANTONE® mixed shades
- Ink dispensing, mixing and measuring systems with different expansion levels available

Product designation of the monopigmented base inks:

- EURAPID O3-Z... high intensity monopigmented base inks

Resistance Properties

Colour Name	Article Number	Light Resistance	Spirit Resistance	Solvent Resistance	Alkali Resistance
4 Colour Process					
Yellow	O3-S1100	7 BWS	+	+	-
Magenta	O3-S1200	6 BWS	+	+	+
Cyan	O3-S1300	8 BWS	+	+	+
Black	O3-S1400	8 BWS	+	+	+
PANTONE® Base Colours					
Yellow	O3-P100	7 BWS	+	+	-
Yellow 012	O3-P101	7 BWS	+	+	-

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 5 of 10

Technische Information

Orange 021	O3-P150	6 - 7 BWS	+	+	+
Warm Red	O3-P200	6 BWS	+	+	+
Red 032	O3-P201	6 BWS	+	+	+
Rubine Red	O3-P202	6 - 7 BWS	+	+	+
Rhodamine Red	O3-P203	6 - 7 BWS	+	+	+
Purple	O3-P250	6 - 7 BWS	+	+	+
Violet	O3-P251	6 - 7 BWS	+	+	+
Reflex Blue	O3-P300	6 - 7 BWS	+	+	+
Process Blue	O3-P301	8 BWS	+	+	+
Blue 072	O3-P302	6 - 7 BWS	+	+	+
Green	O3-P350	8 BWS	+	+	+
Black	O3-P400	8 BWS	+	+	+
Z Base Colours					
Yellow	O3-Z2100	7 BWS	+	+	+
Yellow	O3-Z2102	7 BWS	+	+	-
Orange	O3-Z2150	6 - 7 BWS	+	+	+
Red	O3-Z2202	6 BWS	+	+	+
Red	O3-Z2204	6 - 7	+	+	+
Red	O3-Z2205	6 - 7 BWS	+	+	+
Violet	O3-Z2251	6 - 7 BWS	+	+	+
Blue	O3-Z2302	8 BWS	+	+	+
Green	O3-Z2350	8 BWS	+	+	+
Black	O3-Z2400	8 BWS	+	+	+
Covering White	O3-Z2500	8 BWS	+	+	+
Transp.White	O3-Z2600				

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 6 of 10

Technische Information

specialities
COMMERCIALS
backaging
LETTERPRESS
UV printing ink and lacquer
and lacquer

Remarks on Migration and Conformity

The following remarks are valid for the production of food packaging which conforms to the regulations in the European Union. We can not make any statements concerning food packaging legislation of countries outside the EU.

Regulation (EC) No. 1935/2004 requires that the one responsible for the “placing on the market” of a packaging article must have an appropriate documentation available to demonstrate the compliance with the rules related to food processing and distribution.

Not only the used materials have an influence on the food-legislation related properties of a packaging. The production process of the packaging has a significant impact as well.

Therefore we recommend that you send your finished products to a recognized analytical institute for examination and certification. That way you can prove that your products comply with the legal requirements.

The transfer of substances from the packing into the filling is called migration. The following production parameters have a significant influence on the grade of migration:

- correct processing, especially the complete through-cure of the ink film
- type of substrate and substrate thickness (sufficient barrier effect of the substrate)
- prevention of a direct contact of the printing ink with the food
- use of low-migration printing inks

The EURAPID O3 Ink Series has no special low-migration formulation. Therefore we recommend for food packaging our low-migration ink series and lacquers which are available for many applications.

Generally you should ensure with a migration analysis that no migration through the entire packaging system takes place. Due to the multitude of packaging materials and their completely different barrier properties we are unable to make any statements regarding through-migration.

However please note that migration can also occur by set-off when the printed surface is pressed against the food-contact surface of the packaging in the stack or reel.

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 7 of 10

Technische Information

specialities
packaging
letterpress
UV printing ink and lacquer

Declaration of Composition and Product Declaration

As there are no specific regulations concerning printing inks and varnishes Zeller+Gmelin -like other ink suppliers- is obliged to follow regulations in the EU not directly related to printing inks.

Regulation 1935/2004

Article 3 of the Regulation 1935/2004 (impact on food) demands, that materials and articles do not transfer their constituents to food in quantities which could endanger human health or bring about an unacceptable change in the composition of the food or bring about a deterioration in the organoleptic characteristics thereof.

We urgently advise you to use for printing on food packaging only printing inks/lacquers which we specifically recommend for this application and which have a low-migration formulation.

A possible impact on the quality of food does not solely depend on the printing ink/lacquer itself but is depending on the complete production chain (ink laydown, UV-power, substrate, etc.). For this reason we can generally not confirm a compliance to Regulation 1935/2004 only based on the composition of the ink/lacquer.

Based on Article 17 (traceability) material and articles shall be ensured at all stages in order to facilitate control, the recall of defective products, consumer information and the attribution of responsibility.

All raw materials for ink/lacquer batches at Zeller+Gmelin are documented in writing on the Formula Component Report. Based on the batch number every raw material can be clearly traced back to the raw material batch.

Regulation (EU) No 10/2011

Regulation EU 10/2011 establishes the specific rules for plastic materials and articles to be applied for their safe use and repeals Commission Directive 2002/72/EC of 6 August 2002 on plastic materials and articles intended to come into contact with foodstuffs (2).

In this regulation, the so called PIM (Plastic Implementation Measure) limits are set for substances, which are allowed to be in direct contact with food and are allowed to migrate into the food up to the level listed in Annex I.

Substances used in printing inks must not (with few exemptions) get in direct contact with food and are therefore not listed in Annex I.

Paragraph (30) states, that Coatings, printing inks and adhesives are not yet covered by a specific EU legislation and therefore not subject to the requirement of a declaration of compliance.

For the migration of non-authorized substances through a functional barrier into food a limit of 0,01 mg/kg (10 ppb) is set. Substances that are mutagenic, carcinogenic or toxic to reproduction should not be used without previous authorisation in food contact materials or articles and should therefore not be covered by the functional barrier concept.

CEPE / EuPIA – Exclusion List

CEPE is the European Council of producers and importers of paints, printing inks and artists colours whereas EuPIA is the

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011.
With the present edition expires the validity of all older editions.

Page 8 of 10

Technische Information



European Printing Ink Group of CEPE. The printing ink industry voluntarily came up with the Exclusion List for specific substances many years ago.

Zeller+Gmelin is an active member in the EuPIA and subgroups. The raw materials used by Zeller+Gmelin for the formulation of our printing inks/lacquers meet the guidelines of the CEPE / EuPIA Exclusion list. This means that CMR-substances (cancerogenic, mutagenic and reprotoxic) plus T (toxic) and T+ (very toxic) are not used in our printing inks/lacquers.

Heavy Metals

CONEG stands for Coalition of North-Eastern Governors in the USA. One of their legislations, adopted by 18 states as of 1998, requires reductions in the amount of the four heavy metals mercury, lead, cadmium, and hexavalent chromium in packaging and packaging components sold or distributed in their member states. For Zeller+Gmelin printing inks/lacquers the limits for heavy metals as listed in the CONEG-Regulation (USA) are met. The Euro Norm 71.3 refers to the max level of heavy metals in childrens toys. For Zeller+Gmelin printing inks/lacquers the limits for heavy metals as listed in the DIN EN 71-3 are met.

Heavy metals are no part of our formulations.

Hazardous substances

Substances mentioned in the directive 2002/95/EC (RoHS) are not intentionally used in our formulations printing inks/lacquers.

SVHC-substances (substances of very high concern): In our products no substances are used which meet the criteria of SVHC-substances (substances of very high concern). SVHC-substances are substances which are classified as CMR 1 & 2, PBT (PBT pollutants are chemicals that are toxic, persist in the environment and bioaccumulate in food chains), vPvB (Substances that are potentially very persistent and very bioaccumulative) und endocrine disruptors (artificial hormones). The substances listed in the guide line 67/548/EEC (amended by the directive 2006/121/EC) and in the guide line 76/769/EEC are not part of the formulation of our printing inks/lacquers.

Furthermore we confirm that our printing inks/lacquers are in accordance with the EC regulation 1895/2005 (repeals the guide line 2002/16/EC).

ISO 9001

The production site of Zeller+Gmelin / Germany is certified according to DIN EN ISO 9001:2000 and DIN EN ISO 14001:2005 (corresponds to EN ISO 14001 edition Nov. 2004).

Please note:

According to applicable law the manufacturer of the finished article and the filler have the full legal responsibility to ensure that their product is fit for its intended purpose and complies with the applicable rules (not the supplier).

Please also consider the relevant publications of the European Printing Inks Association EuPIA (<http://www.eupia.org>).

There are many types of final packaging and the printing ink/lacquer is only one constituent. Since the parameters in the printing, packing and storage processes are not under the control of the printing ink manufacturer, the printing ink suppliers

Technische Information



are not able to issue certificates or declarations of compliance which cover the legal responsibility of the entire packaging chain (Text from EuPIA-PIFOOD May 2007).

The statements made in this declaration are according to our current knowledge. They do not absolve the user from its own responsibility to ascertain that our products are suitable for his application.

EURAPID O3 Farbserie

11/2011-EURAPID O3 Farbserie-1

This edition 11/2011-EURAPID O3 Farbserie-1 dated November 21, 2011 replaces the previous edition dated November 17, 2011. With the present edition expires the validity of all older editions.

Page 10 of 10

ZG Division: Printing inks
Zeller+Gmelin GmbH & Co. KG
Schlossstr. 20, 73054 Eislingen/Fils, Germany
Tel. +49 7161 802-0 - Fax +49 7161 802-200
www.zeller-gmelin.de - druckfarben@zeller-gmelin.de

