

# Secure Compilation

## Lecture 2

Renate Robin Eilers      Cristina Matache      Baber Rehman

June 24, 2019

This is the second talk presented by Amal Ahmed in OPLSS 2019, University of Oregon, USA.

## 1 Introduction

### 1.1 Source Language

#### 1.1.1 Types

We just have integers and functions in source language.

$$\sigma ::= \text{int} \mid \sigma_1 \rightarrow \sigma_2$$

#### 1.1.2 Terms

### 1.2 Target Language

**Theorem 1.1** (Type Preservation). *If  $\Gamma \vdash e_S : \sigma$  and  $\Gamma \vdash e_S : \alpha \rightsquigarrow e_T$  then  $\Gamma_S^+ \vdash e_T : \sigma^+$*

For correctness, we want to show  $e_S \approx e_T$ . This is not contextual equivalence because source language and target language are two different languages. There are many ways to prove compiler correction. We want to say that when:

$$e_S \approx e_T \text{ then } \sigma \approx \sigma^+$$

$$V \llbracket \sigma \rrbracket = \{ (V_S, V_T) \mid j \vdash V_S : \sigma \wedge \dots ; \vdash V_T : \sigma^+ \dots \}$$

$$V \llbracket \text{ints} \rrbracket = \{ (n_S, n_T) \}$$

$$V \llbracket \sigma_1 \rightarrow \sigma_2 \rrbracket = \{ (\lambda x:\sigma_1 . e_S) \}$$