Bayview IT Assistant: Design, Implementation, Testing & Scaling

Multi-agent AI system for IT support · BUS 118s-01 Capstone · LangGraph + Google Gemini + Chroma + MCP

---

1. Executive summary

Bayview Logistics (a fictional 1,200-employee company) runs a Service Desk where most tickets are repetitive: passwords, lockouts, VPN, "is X down?", how-to questions. The **Bayview IT Assistant** is a prototype of an AI "front door" for IT. Four specialised agents work together:

Agent	Responsibility	Key technique
Intake	Understand and classify the request; strip sensitive data	Gemini structured output (Pydantic schema) + deterministic routing policy
Knowledge	Answer how-to questions from the IT knowledge base	RAG: Gemini embeddings → Chroma vector DB → grounded answer with citations
Workflow	Do things: unlock accounts, reset passwords, check service status, analyse logs	Tool execution with built-in guardrails
Escalation	Hand unresolved or risky cases to the right human team	Handoff summary + SLA-based triage into a ticket queue (optional GitHub Issue)

The same capabilities are exposed through an **MCP server**, so a technician using VS Code + Copilot (alongside the GitHub MCP server) can search the KB, analyse logs and work the ticket queue without any custom integration code.

We position the project as a **lightweight, transparent alternative** to enterprise platforms such as Glean and ServiceNow + Moveworks (§9).

---

2. Problem definition & use case

2.1 Pain points (current state)

Stakeholder	Pain point
Employees	Wait hours for simple fixes (locked account = blocked from working); KB articles are hard to find; have to repeat themselves when tickets are reassigned
Service Desk (L1)	Industry benchmarks commonly cite password and lockout issues as a large share of L1 volume; agents spend time on copy-paste answers instead of complex work
Security Ops	Phishing and compromised-account reports arrive late or are misrouted to the general queue
IT leadership	No data on which issues could be self-served; SLA breaches on high-priority tickets buried under low-priority volume

2.2 In-scope scenarios

1. **How-to questions**: MFA setup, VPN errors, Outlook, printers, software installs, access requests (Knowledge Agent).
2. **Account automation**: self-service unlock and password reset with MFA verification (Workflow Agent).
3. **Status and diagnostics**: "Is VPN down?", "Why do I keep getting locked out?" via service status and log analysis (Workflow Agent).
4. **Ticket triage and escalation**: security incidents, requests on someone else's account, out-of-scope questions, failed automations (Escalation Agent).

2.3 Success metrics

Metric	Definition	Target (prototype)
Routing accuracy	Correct agent produced the final answer	≥ 90%
Escalation recall	Cases that need a human reach a human	**100%** (safety-critical)
Escalation precision	Escalations that were actually needed	≥ 85%
Containment / deflection	Requests resolved without a human	≥ 55% of scenario mix
Retrieval hit@4	Correct KB article in top-4 chunks	≥ 90%
Latency p95	End-to-end response time	< 10 s (Gemini)
Satisfaction	LLM-judge (1-5) now; thumbs-up/down CSAT in pilot	≥ 4.0 / 5

---

3. Product ownership

3.1 Personas

- **Alex (Account Executive, non-technical)**: locked out before a client call; wants it fixed *now* and in plain language.
- **Priya (Data Engineer)**: comfortable with tech; wants quick answers and status info, hates ticket forms.
- **Sam (L1 technician)**: wants fewer repetitive tickets and complete context when something is escalated.
- **Dana (Security analyst)**: needs every suspicious report immediately, with evidence, and never "auto-resolved".

3.2 Prioritised backlog (MoSCoW)

#	User story	Priority	Delivered
1	As an employee, I can ask a question in plain English and get a cited answer from the KB	Must	✅
2	As an employee, I can unlock my own account / reset my password after MFA verification	Must	✅
3	As a security analyst, every security-related message reaches Security Ops as P1, never auto-handled	Must	✅
4	As a technician, escalated tickets include a summary, steps tried and the transcript	Must	✅
5	As an employee, I'm told when there's a known outage instead of troubleshooting blindly	Should	✅
6	As an employee, I learn *why* I keep getting locked out (log analysis)	Should	✅
7	As a technician, I can work the queue from VS Code via MCP	Should	✅
8	As IT leadership, I can see deflection and accuracy metrics	Should	✅ (eval report)
9	Escalations are mirrored to GitHub Issues / Jira	Could	✅ GitHub (optional)
10	Voice channel, Teams/Slack bot	Won't (this release)	—
11	Real Entra ID / Okta writes	Won't (prototype uses a mock directory)	—


3.3 Key product decisions

- **Safety over containment.** We accept a lower deflection rate in exchange for 100% escalation recall: security incidents, actions on other people's accounts and unknown questions always go to a person.
- **The LLM classifies, policy decides.** Gemini extracts *what* the user wants; a small, testable Python policy decides *where* it goes (`route_from_intake`). Auditors can read the routing rules in ten lines.

- **Tools enforce their own guardrails.** The Workflow Agent cannot reset someone else's password even if the LLM is tricked into asking; the tool itself refuses.
- **Show your work.** The UI shows which agents ran, retrieval scores and sources, which builds trust and makes the demo self-explanatory.


---

4. Architecture



4.1 Orchestration


The system is a LangGraph `StateGraph` over a shared typed state (`HelpdeskState`): requester, redacted message, intake result, retrieved chunks, tool result, answer, sources, ticket, and an append-only `trace`. Each agent is a node that returns a partial state update.



4.2 Agent roles and collaboration

Agent	Inputs	Outputs	Collaborates with
Intake	Raw message, requester, last 6 turns	`IntakeResult`: category (12), request type, action, target user, service, urgency, wants_human, summary, confidence	Routes to the other three
Knowledge	Redacted message, service	Answer, cited chunk ids, `grounded` flag	Calls the *status tool* to add a live-outage banner; hands off to Escalation when retrieval is weak or the model says the context doesn't answer
Workflow	Action + entities	`ToolResult` (ok / refused / needs_escalation) + user-friendly explanation	Uses the KB for a prevention tip; uses log analysis as a security check before account changes; hands off to Escalation on refusal
Escalation	Everything gathered so far	Ticket (priority, queue), handoff summary, user message with SLA	Reads Knowledge/Workflow results so the technician sees "steps tried"

4.3 Sequence: lockout with log analysis



5. Implementation details

5.1 Technology choices

Layer	Choice	Why	Alternative considered
Orchestration	**LangGraph 1.x**	Explicit graph = auditable control flow, typed shared state, conditional edges; recommended by the course	CrewAI (less control over routing), plain function calls (no graph visualisation / checkpointing)
LLM	**Gemini (`gemini-flash-latest`)** via `google-genai`	Fast and cheap; native JSON-schema structured output; alias tracks the current stable Flash (the 2.5 models were retired on 2026-10-16)	Larger "Pro" model: better reasoning but slower and more expensive for a classification-heavy workload
Embeddings	`gemini-embedding-2` (fallback `gemini-embedding-001`), 768-dim, `RETRIEVAL_QUERY` / `RETRIEVAL_DOCUMENT` task types	Same vendor and key; asymmetric task types improve retrieval	Open-source sentence-transformers (no API cost, but weaker and adds a heavy dependency)
Vector DB	**Chroma** (embedded, persistent)	Zero-ops, runs in Colab and locally; cosine HNSW	Pinecone / Weaviate for production (§7)
Tickets	SQLite (+ optional GitHub Issues mirror)	Real queryable store with zero setup	ServiceNow / Jira via MCP in production
UI	**Gradio 6**	Chat + side panels in ~100 lines; public share link from Colab	Streamlit (similar), React (more polish, much more time)
Integration	**MCP server** (`mcp` 2.x `MCPServer`, stdio)	Standard tool discovery for any MCP client (VS Code, Claude)	Hand-written REST API + per-client glue

5.2 RAG pipeline

1. **Corpus**: 12 Markdown KB articles with front matter (id, title, category, updated date).
2. **Chunking**: split by `##` section with the article title prepended, so each chunk is a self-contained answer unit: **51 chunks**. Section-level chunks give precise citations ("KB-004 › Error messages").
3. **Embedding & indexing**: chunks embedded with `RETRIEVAL_DOCUMENT`, stored in Chroma (cosine). The collection stores a content hash, so it **re-indexes automatically when the KB changes**, and uses one collection per embedding model so vector spaces never mix.
4. **Retrieval**: the query is embedded with `RETRIEVAL_QUERY`, top-4 chunks are returned with similarity scores.
5. **Relevance gate**: if the best score is below a threshold (0.55 for Gemini embeddings, 0.15 for the offline baseline; both configurable), the Knowledge Agent **escalates instead of guessing**.

6. **Grounded generation**: Gemini answers *only* from the numbered chunks, returns `cited_ids` and a `grounded` flag. `grounded=false` triggers escalation. Citations are shown under every answer.

Hallucination controls: relevance gate · context-only system prompt · structured `grounded` self-check · temperature 0 for classification and RAG · citations the user can verify · no URLs or policies outside the KB.

5.3 Workflow automation and guardrails

Tool	What it does	Guardrails
`unlock_account`	Clears a lockout and explains the cause from auth logs	Requester's own account only · MFA enrolled · **security hold** if logs show impossible travel / denied MFA
`reset_password`	Sends a one-time reset link (15 min) to the registered work email, unlocks if needed	Same as above; the assistant never sees or sets a password
`check_service_status`	Live status for VPN, email, SSO, Wi-Fi, printing, HR portal, Company Portal	If the user reports a high-urgency outage the status page doesn't know about, escalate to Network Ops
`analyze_logs`	Parses VPN/auth logs: error reasons, per-user patterns, gateway health, security signals	Scoped to the requester; path-traversal safe; security signal → escalation
`create_ticket`	SLA triage (category × urgency × VIP → P1-P4 + queue per KB-012), optional GitHub Issue	Security → always P1 Security Ops

Every self-resolved request is also logged as a `resolved` ticket (`resolved_by = Knowledge Agent / Workflow Agent`) so leadership can measure deflection.

5.4 Escalation

The Escalation Agent asks Gemini for a `HandoffSummary` (title, 2-3 sentence summary, steps tried), creates the ticket, and tells the user the ticket number, queue and first-response SLA (15 min for P1 … 1 business day for P4). The redacted transcript is attached so the user never repeats themselves.

5.5 MCP integration

`mcp_server.py` exposes 7 tools (`ask_it_assistant` , `search_knowledge_base` , `check_service_status` , `analyze_logs` , `list_tickets` , `get_ticket` , `resolve_ticket`). `.vscode/mcp.json` registers it next to the **GitHub MCP server**, so in VS Code Copilot agent mode a technician can say "*list open P1 tickets, analyse the auth log for ceo, and open a GitHub issue for the VPN gateway problem*".

	Traditional REST API	MCP
Discovery	Read docs / OpenAPI, write a client per consumer	Client calls `list_tools` and gets names, descriptions and JSON schemas at runtime
Integration effort	One integration per (tool × client) pair (N × M)	Each tool server works with every MCP client (N + M)
LLM readiness	Need to hand-write function/tool definitions for each model	Tool schemas are already in the format agents consume
Transport / auth	Custom per API	Standard transports (stdio, streamable HTTP) and an OAuth-based auth spec

`scripts/mcp_client_demo.py` proves the point: a generic client with no helpdesk knowledge discovers and calls every tool (screenshot `04_mcp_client.png`).

5.6 Privacy and safety

- **PII redaction** (`privacy.py`) before any text reaches the LLM, a ticket, or a log: passwords typed into chat, SSNs, card numbers, phone numbers, personal email addresses. Work usernames/emails are kept because agents need them.
- **Secrets**: the Gemini key is read from the secret `GEMINI_API_KEY` (Colab secrets → env var → `.env`) and never printed. `.env` is git-ignored.
- **Least privilege**: tools act only on the requester's identity; there is no "admin" path for the LLM.
- **Prompt-injection resilience**: even if a user persuades the LLM to choose `reset_password` for someone else, the tool refuses and escalates (unit-tested).

5.7 UX design

Design principles: *clarity, transparency, zero dead ends.*

- Single chat box with **example prompts** so users know what the assistant can do.
- Answers are **one-line summary + numbered steps** with **sources** underneath.
- **"Under the hood" panel** shows the agent path (Intake → Workflow), per-agent latency, retrieval scores, automation result and ticket, which is useful for trust and for demos.
- **Live ticket queue** shows escalations and self-resolved records appearing in real time.
- Every escalation states **what happens next and when** (ticket #, team, SLA). The user is never left without a next step.
- Identity comes from (simulated) SSO, so users never type usernames or passwords into the bot.

Screenshots: `docs/screenshots/10-16_ui_*.png`.

5.8 Offline mode

When no key is present (or `HELPDESK_OFFLINE=1`), Gemini calls are replaced by a keyword classifier, hashed bag-of-words embeddings and extractive answers. It exists for unit tests and CI without network or quota, and as a **baseline** that quantifies what the LLM adds. Every response and report is labelled with the mode.

5.9 Repository layout

```
helpdesk/        config, privacy, schemas, llm, knowledge_base, store, tools, agents, graph, cli,
offline
data/            kb/*.md (12 articles), directory.json, services.json, logs/*.log
app.py           Gradio UI          mcp_server.py   MCP server       .vscode/mcp.json  VS Code MCP
config
eval/            scenarios.json (37), run_eval.py, results/<mode>/
tests/           15 offline unit + integration tests (pytest)
notebooks/       01_IT_Assistant_Demo.ipynb, 02_Evaluation.ipynb (Google Colab, self-contained)
scripts/         mcp_client_demo, build_notebooks, capture_screenshots, render_docs
docs/            this document, architecture diagram, screenshots
```

---

6. Testing & validation

6.1 Approach

Level	What	How
Unit	Redaction, each tool's guardrails, triage rules, chunking, retrieval	`pytest` (15 tests, offline, ~2 s)
Integration	Full graph paths (knowledge, workflow, refused → escalation, security, out-of-scope)	`pytest` through `handle_request`
Scenario evaluation	**37 realistic IT requests** across all categories with expected category, action, final agent and source article	`eval/run_eval.py`; state reset before each scenario
Satisfaction	LLM-as-judge rates helpfulness, accuracy, tone (1-5) for each reply; pilot plan uses thumbs-up/down CSAT	`run_eval.py --judge`
Manual / UX	Scripted UI walkthroughs captured as screenshots	`scripts/capture_screenshots.py` (Playwright)


Scenario mix: 16 knowledge questions, 9 successful automations, 4 automations that must be refused (other user's account, no MFA, security hold), 8 direct escalations (phishing, lost laptop, unexpected MFA prompts, ransomware, "talk to a person", two off-topic, unreported outage).

6.2 Results

Offline rule-based baseline (no LLM, measured):

Metric	Offline baseline	Gemini (`gemini-flash-latest`)
Intake category accuracy	89.2%	*run notebook 02*
Action selection accuracy	100%	*run notebook 02*
Routing accuracy (final agent)	97.3%	*run notebook 02*
End-to-end pass (category + action + route)	86.5%	*run notebook 02*
Retrieval hit@1 / hit@4	81.2% / 100%	*run notebook 02*
Escalation precision / recall	92.3% / **100%**	*run notebook 02*
Containment (no human needed)	64.9%	*run notebook 02*
Latency p50 / p95	25 / 33 ms	*run notebook 02*
Satisfaction (LLM judge)	n/a	*run notebook 02*

> The Gemini column is filled in by running `notebooks/02_Evaluation.ipynb` in Colab with the `GEMINI_API_KEY` secret (it writes `eval/results/gemini/report.md` and `charts.png`). The baseline is useful as a floor, but note that its rules were written by the same team that wrote the scenarios, so it is optimistic on this set and brittle on unseen phrasing. The LLM's value is generalisation to new wording, multi-turn context, and natural-language answers and handoffs.



6.3 Failure analysis (baseline)

All five baseline failures are **category** misclassifications that did not change the outcome, plus one action mismatch where the keyword "locking" was not recognised as a lockout. None was a safety failure: escalation recall stayed at 100%. Typical misses: "How do I stop Outlook asking for my password" (classified as password instead of email), "scan a document to my email" (email vs printer).

6.4 Validation against success metrics

Escalation recall (100%), routing (≥ 90%), retrieval hit@4 (≥ 90%) and containment (≥ 55%) meet target on the baseline; Gemini latency and satisfaction are measured in notebook 02.

---

7. Scaling to production

Concern	Prototype	Production path
Compute	Single Python process	Stateless graph workers behind an API gateway; horizontal autoscaling (Cloud Run / Kubernetes)
Conversation state	In-request	LangGraph **checkpointer** on Postgres/Redis for multi-turn and human-in-the-loop resumes
Vector store	Embedded Chroma, 51 chunks	Managed vector DB (Pinecone, Weaviate, or Vertex AI Vector Search) with namespaces per department; hybrid keyword + vector search; re-ranker
Knowledge ingestion	Markdown folder, content-hash re-index	Connectors for Confluence/SharePoint/ServiceNow KB; incremental embedding on change events; document-level ACLs so users only retrieve what they may read
Integrations	Mock directory, status JSON, log files	MCP servers for Entra ID/Okta, ServiceNow/Jira, Datadog/Splunk; each team owns its server
Throughput & cost	~2 LLM calls + 1 embedding per request	Typical request ≈ 1.5k input + 0.4k output tokens. Cost scales linearly; caching of frequent answers, a small model for intake, and batching keep it low. Rate-limit handling already built in (retry + pacing)
Reliability	Retries with backoff	Circuit breakers per tool; fallback to "open ticket" if the LLM is unavailable (the offline classifier already provides a degraded mode)
Observability	Trace in UI, eval reports	OpenTelemetry / LangSmith traces per agent; dashboards for deflection, CSAT, escalation reasons, latency; alert on drift
Quality	37-scenario eval	Eval suite in CI on every prompt/model change; grow scenarios from real (redacted) tickets; A/B test prompts; monthly human review of samples
Security & compliance	Regex redaction, self-only tools	Managed DLP (e.g. Google Cloud DLP), RBAC, audit log of every tool call, data-residency controls, red-team prompt-injection tests
Org scale	4 agents	**Separation of concerns** lets teams add agents (HR, Facilities, Finance) as new nodes/MCP servers without touching existing ones; a supervisor router dispatches across domains

---

8. Trade-offs and lessons learned

- **Deterministic routing vs. letting the LLM decide.** A fully agentic "LLM picks the next agent" design is more flexible but harder to test and audit. We kept the LLM for understanding and Python for policy.
- **Section chunks vs. fixed-size chunks.** Section chunks fit how KB articles are written and give readable citations; very long sections would need a secondary split.
- **Similarity thresholds are model-specific.** Changing embedding models changes the score scale. We made thresholds per-mode and recommend calibrating from the eval report's score distribution.

- **Model churn is real.** The Gemini 2.5 models we started with were retired during the project. Using the `-latest` alias plus an embedding fallback list kept the system running.
- **Safety and helpfulness pull in opposite directions.** Every guardrail lowers containment. We chose 100% escalation recall as a hard requirement and optimise containment within it.
- **Transparency sells.** Showing the agent path and sources in the UI answered most "how does it work?" questions before they were asked.

---

9. Industry research

	Glean	ServiceNow + Moveworks	Bayview IT Assistant (this project)
Positioning	Enterprise search + AI assistant + agents across company apps	AI "front door" for employee requests on top of the ServiceNow workflow platform	Lightweight, open, single-team prototype of the same pattern
Knowledge	Permission-aware index across 100+ SaaS connectors	Enterprise search + ServiceNow KB	Chroma RAG over a Markdown KB
Actions	Agents with action-level controls and an agent builder	Moveworks reasoning engine + ServiceNow workflows	Four LangGraph agents + MCP tools
Governance	SOC 2 / ISO 27001, admin controls, audit logs	Enterprise ITSM governance	Guardrails in code, PII redaction, eval suite
Cost / effort	Enterprise licence, long rollout	Enterprise licence, ServiceNow ecosystem	Open-source stack + pay-per-use Gemini API

Market signals. ServiceNow completed its acquisition of Moveworks on 15 December 2025, reported at about $2.85B. ServiceNow describes the combination as an "AI-native front door" where employees ask, search and complete tasks in one place. That validates the multi-agent front-door pattern this project prototypes. Glean has moved from search into governed autonomous agents (agent moderators and action-level controls reported generally available in late 2025).

Where this project fits. It demonstrates the same architecture (intent understanding → grounded knowledge → automated workflows → human escalation) at a cost and complexity a mid-size IT team or a pilot can afford. It also shows why MCP matters for buyers: tools built once can be used by any assistant, reducing vendor lock-in.

Sources: ServiceNow press release "ServiceNow completes acquisition of Moveworks" (Business Wire, 2025-12-15); Glean product pages and third-party coverage of Glean Agents (2025-2026).

---

10. Limitations and future work

- Mock directory, status page and logs. The next step is MCP servers for Entra ID, ServiceNow/Jira and a log platform.
- English only; no voice; single-turn tools (multi-step diagnostics would use LangGraph interrupts for human approval).
- The evaluation set is small and author-written. Expand it with real redacted tickets and measure on a held-out set.
- Satisfaction is LLM-judged in the prototype. The pilot will collect real thumbs-up/down CSAT per answer.