

INITIALIZATION PROCEDURE




FIGURE1: 8-BIT INTERFACE

INITIALIZATION BY SETTING THE SOFTWARE [CHARACTER TYPE LCM].
REFERE TO FIGURES 1 AND 2 FOR PROCEDURES ON 8-BIT AND 4-BIT
INITIALIZATION ACCORDINGLY.

BF CANNOT BE CHECKED BEFORE THIS INSTRUCTION.
FUNCTION SET INTERFACE IS 8 BITS LONG.

BF CANNOT BE CHECKED BEFORE THIS INSTRUCTION.
FUNCTION SET INTERFACE IS 8 BITS LONG.

BF CANNOT BE CHECKED BEFORE THIS INSTRUCTION.
FUNCTION SET INTERFACE IS 8 BITS LONG.

BF CAN BE CHECKED AFTER THE FOLLOWING
INSTRUCTIONS. IF THE BF IS NOT CHECKED,
THE WAITING TIME BETWEEN INSTRUCTIONS IS
LONGER THAN THE INSTRUCTION EXECUTION TIME.

FUNCTION SET [INTERFACE IS 8 BITS LONG. THE NUMBER
OF DISPLAY LINES AND CHARACTERS IS SPECIFIED.
NEITHER CANNOT BE CHANGED AFTERWARDS].

DISPLAY OFF

DISPLAY CLEAR

ENTRY MODE SET
[COND.: FOSC=270KHZ]




FIGURE2: 4-BIT INTERFACE

THIS DATA SHEET IS FOR REFERENCE ONLY. WE RESERVE THE RIGHT TO CHANGES AND IMPROVMENTS WITHOUT PRIOR NOTICE.