
celestine

Release 0.6.0

Joseph Fishlock

May 19, 2023

CONTENTS:

1	Boundary Conditions	1
2	Enthalpy Method	3
3	Flux	5
4	Forcing	7
5	Grids	9
6	Logging Config	11
7	Params	13
8	Phase Boundaries	15
9	Run Simulation	17
10	State	19
11	Velocities	21
12	Lagged Solver	23
13	Template	25
14	Indices and tables	27
	Python Module Index	29
	Index	31

BOUNDARY CONDITIONS

`celestine.boundary_conditions.dissolved_gas_BCs(dissolved_gas_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.enthalpy_BCs(enthalpy_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.gas_BCs(gas_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.gas_fraction_BCs(gas_fraction_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.liquid_fraction_BCs(liquid_fraction_centers, cfg: Config)`

Add ghost cells to liquid fraction such that top and bottom boundaries take the same value as the top and bottom cell center

`celestine.boundary_conditions.liquid_salinity_BCs(liquid_salinity_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.salt_BCs(salt_centers, cfg: Config)`

Add ghost cells with BCs to center quantity

`celestine.boundary_conditions.temperature_BCs(temperature_centers, time, cfg: Config)`

Add ghost cells with BCs to center quantity

Note this needs the current time as well as top temperature is forced.

ENTHALPY METHOD

```
class celestine.enthalpy_method.EnthalpyMethod(physical_params: PhysicalParams)
```

Template for an enthalpy method. To implement a new method overwrite the initializer to initialise the physical parameters and a suitable phase boundaries object. Then implement a calculate enthalpy method that takes a state and uses bulk enthalpy, salt and gas to return (temperature, liquid_fraction, gas_fraction, solid_fraction, liquid_salinity, dissolved_gas).

```
class celestine.enthalpy_method.FullEnthalpyMethod(physical_params: PhysicalParams)
```


`celestine.flux.calculate_conductive_heat_flux(temperature, D_g)`

Calculate conductive heat flux as

$$-\frac{\partial \theta}{\partial z}$$

Parameters

- **temperature** (*Numpy Array of size I+2*) – temperature including ghost cells
- **D_g** (*Numpy Array*) – difference matrix for ghost grid

Returns

conductive heat flux

`celestine.flux.calculate_diffusive_salt_flux(liquid_salinity, liquid_fraction, D_g, cfg)`

Take liquid salinity and liquid fraction on ghost grid and interpolate liquid fraction geometrically

CHAPTER

FOUR

FORCING

GRIDS

`celestine.grids.add_ghost_cells(centers, bottom, top)`

Add specified bottom and top value to center grid

Parameters

- **centers** (*Numpy array*) – numpy array on centered grid (size I).
- **bottom** (*float*) – bottom value placed at index 0.
- **top** (*float*) – top value placed at index -1.

Returns

numpy array on ghost grid (size I+2).

`celestine.grids.average(ghosts)`

Returns arithmetic mean pairwise of first dimension of an array

This should get values on the ghost grid and returns the arithmetic average onto the edge grid

`celestine.grids.geometric(ghosts)`

Returns geometric mean of the first dimension of an array

LOGGING CONFIG

PARAMS

Classes containing parameters required to run a simulation

The config class contains all the parameters needed to run a simulation as well as methods to save and load this configuration to a yaml file.

```
class celestine.params.BoundaryConditionsConfig(far_gas_sat: float = 1.0, far_temp: float = 0.1,  
                                                far_bulk_salinity: float = 0)
```

values for bottom (ocean) boundary

```
class celestine.params.Config(name: str, physical_params: PhysicalParams =  
    PhysicalParams(expansion_coefficient=0.029, concentration_ratio=0.17,  
    stefan_number=4.2, lewis_salt=inf, lewis_gas=inf, frame_velocity=0),  
    boundary_conditions_config: BoundaryConditionsConfig =  
    BoundaryConditionsConfig(far_gas_sat=1.0, far_temp=0.1,  
    far_bulk_salinity=0), darcy_law_params: DarcyLawParams =  
    DarcyLawParams(B=100, bubble_radius_scaled=1.0,  
    pore_throat_scaling=0.5, drag_exponent=6.0, liquid_velocity=0.0),  
    forcing_config: ForcingConfig =  
    ForcingConfig(temperature_forcing_choice='constant',  
    constant_top_temperature=- 1.5, offset=- 1.0, amplitude=0.75, period=4.0),  
    numerical_params: NumericalParams = NumericalParams(I=50,  
    timestep=0.0002, regularisation=1e-06, solver='LU'), total_time: float = 4.0,  
    savefreq: float = 0.0005, data_path: str = 'data/')
```

contains all information needed to run a simulation and save output

this config object can be saved and loaded to a yaml file.

```
class celestine.params.DarcyLawParams(B: float = 100, bubble_radius_scaled: float = 1.0,  
    pore_throat_scaling: float = 0.5, drag_exponent: float = 6.0,  
    liquid_velocity: float = 0.0)
```

non dimensional parameters for calculating liquid and gas darcy velocities

```
class celestine.params.ForcingConfig(temperature_forcing_choice: str = 'constant',  
    constant_top_temperature: float = - 1.5, offset: float = - 1.0,  
    amplitude: float = 0.75, period: float = 4.0)
```

choice of top boundary (atmospheric) forcing and required parameters

```
class celestine.params.NumericalParams(I: int = 50, timestep: float = 0.0002, regularisation: float =  
    1e-06, solver: str = 'LU')
```

parameters needed for discretisation and choice of numerical method

property Courant

This number must be <0.5 for stability of temperature diffusion terms

```
class celestine.params.PhysicalParams(expansion_coefficient: float = 0.029, concentration_ratio: float =  
                                     0.17, stefan_number: float = 4.2, lewis_salt: float = inf, lewis_gas:  
                                     float = inf, frame_velocity: float = 0)  
    non dimensional numbers for the mushy layer
```

PHASE BOUNDARIES

class celestine.phase_boundaries.**FullPhaseBoundaries**(*physical_params*: PhysicalParams)

calculates the phase boundaries when we include gas fraction in bulk enthalpy and bulk salinity.

class celestine.phase_boundaries.**PhaseBoundaries**(*physical_params*: PhysicalParams)

Template for phase boundary calculation.

Concrete implementations should use the state containing enthalpy, salt and gas to calculate the liquidus, enthalpy, solidus and saturation boundaries and then return masks for each possible phase of the system.

RUN SIMULATION

`celestine.run_simulation.run_batch(list_of_cfg)`

Run a batch of simulations from a list of configurations.

Each simulation name is logged, as well as if it successfully runs or crashes. Output from each simulation is saved in a .npz file.

Parameters

`list_of_cfg` (`List[celestine.params.Config]`) – list of configurations

STATE

Classes to store solution variables

State: store variables on cell centers StateBCs: add boundary conditions in ghost cells to cell center variables Solution: store primary variables at each timestep we want to save data

```
class celestine.state.Solution(cfg: Config)
```

store solution at specified times on the center grid

```
    add_state(state: State, index: int)
```

add state to stored solution at given time index

```
class celestine.state.State(cfg: Config, time, enthalpy, salt, gas, pressure=None)
```

Stores information needed for solution at one timestep on cell centers

```
class celestine.state.StateBCs(state: State)
```

Stores information needed for solution at one timestep with BCs on ghost cells as well

Note must initialise once enthalpy method has already run on State.

VELOCITIES

`celestine.velocities.calculate_bubble_radius(liquid_fraction, cfg: Config)`

Takes liquid fraction on edges and returns bubble radius parameter on edges

`celestine.velocities.calculate_gas_interstitial_velocity(liquid_fraction, pressure, D_g, cfg: Config)`

Calculate V_g from liquid fraction and pressure on ghost grid

Return V_g on edge grid

`celestine.velocities.calculate_liquid_darcy_velocity(liquid_fraction, pressure, D_g)`

Calculate liquid Darcy velocity as

$$W_l = -\Pi(\phi_l) \frac{\partial p}{\partial z}$$

Parameters

- **liquid_fraction** (*Numpy Array (size I+2)*) – liquid fraction on ghost grid
- **pressure** (*Numpy Array (size I+2)*) – pressure on ghost grid
- **D_g** (*Numpy Array (size I+2)*) – difference matrix for ghost grid

Returns

liquid darcy velocity on edge grid

`celestine.velocities.calculate_velocities(state_BCs, D_g, cfg: Config)`

Inputs on ghost grid, outputs on edge grid

`celestine.velocities.solve_pressure_equation(state_BCs, new_state_BCs, timestep, D_e, D_g, cfg: Config)`

Calculate pressure on ghost grid from current and new state on ghost grid

Return new pressure on centers but easy to add boundary conditions

LAGGED SOLVER

class celestine.solvers.lagged_solver.LaggedUpwindSolver(*cfg*: [Config](#))

Take timestep using upwind scheme with liquid velocity calculation lagged.

pre_solve_checks()

Optionally implement this method if you want to check anything before running the solver.

For example to check the timestep and grid step satisfy some constraint.

take_timestep(*state*: [State](#))

advance enthalpy, salt, gas and pressure to the next timestep.

Note as of 2023-05-17 removed ability to have adaptive timestepping for simplicity.

Parameters

state (celestine.solvers.template.State) – object containing current time, enthalpy, salt, gas, pressure and surface temperature.

Returns

state of system (new enthalpy, salt, gas and pressure) after one timestep.

celestine.solvers.lagged_solver.**take_forward_euler_step**(*quantity*, *flux*, *timestep*, *D_e*)

Advance the given quantity one forward Euler step using the given flux

The quantity is given on cell centers and the flux on cell edges.

Discretise the conservation equation

$$\frac{\partial Q}{\partial t} = -\frac{\partial F}{\partial z}$$

as

$$Q^{n+1} = Q^n - \Delta t \left(\frac{\partial F}{\partial z} \right)$$

TEMPLATE

Template for a solver concrete solvers should inherit and overwrite required methods

```
class celestine.solvers.template.SolverTemplate(cfg: Config)
```

```
    generate_initial_solution()
```

Generate initial solution on the ghost grid

Returns

initial solution arrays on ghost grid (enthalpy, salt, gas, pressure)

```
    pre_solve_checks()
```

Optionally implement this method if you want to check anything before running the solver.

For example to check the timestep and grid step satisfy some constraint.

```
    abstract take_timestep(state: State) → State
```

advance enthalpy, salt, gas and pressure to the next timestep.

Note as of 2023-05-17 removed ability to have adaptive timestepping for simplicity.

Parameters

state (celestine.solvers.template.State) – object containing current time, enthalpy, salt, gas, pressure and surface temperature.

Returns

state of system (new enthalpy, salt, gas and pressure) after one timestep.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

C

- `celestine.boundary_conditions`, 1
- `celestine.enthalpy_method`, 3
- `celestine.flux`, 5
- `celestine.forcing`, 7
- `celestine.grids`, 9
- `celestine.logging_config`, 11
- `celestine.params`, 13
- `celestine.phase_boundaries`, 15
- `celestine.run_simulation`, 17
- `celestine.solvers.lagged_solver`, 23
- `celestine.solvers.template`, 25
- `celestine.state`, 19
- `celestine.velocities`, 21

A

`add_ghost_cells()` (in module *celestine.grids*), 9
`add_state()` (*celestine.state.Solution* method), 19
`average()` (in module *celestine.grids*), 9

B

`BoundaryConditionsConfig` (class in *celestine.params*), 13

C

`calculate_bubble_radius()` (in module *celestine.velocities*), 21
`calculate_conductive_heat_flux()` (in module *celestine.flux*), 5
`calculate_diffusive_salt_flux()` (in module *celestine.flux*), 5
`calculate_gas_interstitial_velocity()` (in module *celestine.velocities*), 21
`calculate_liquid_darcy_velocity()` (in module *celestine.velocities*), 21
`calculate_velocities()` (in module *celestine.velocities*), 21
`celestine.boundary_conditions` module, 1
`celestine.enthalpy_method` module, 3
`celestine.flux` module, 5
`celestine.forcing` module, 7
`celestine.grids` module, 9
`celestine.logging_config` module, 11
`celestine.params` module, 13
`celestine.phase_boundaries` module, 15
`celestine.run_simulation` module, 17
`celestine.solvers.lagged_solver` module, 23

`celestine.solvers.template` module, 25

`celestine.state` module, 19

`celestine.velocities` module, 21

`Config` (class in *celestine.params*), 13

`Courant` (*celestine.params.NumericalParams* property), 13

D

`DarcyLawParams` (class in *celestine.params*), 13

`dissolved_gas_BCs()` (in module *celestine.boundary_conditions*), 1

E

`enthalpy_BCs()` (in module *celestine.boundary_conditions*), 1

`EnthalpyMethod` (class in *celestine.enthalpy_method*), 3

F

`ForcingConfig` (class in *celestine.params*), 13

`FullEnthalpyMethod` (class in *celestine.enthalpy_method*), 3

`FullPhaseBoundaries` (class in *celestine.phase_boundaries*), 15

G

`gas_BCs()` (in module *celestine.boundary_conditions*), 1

`gas_fraction_BCs()` (in module *celestine.boundary_conditions*), 1

`generate_initial_solution()` (*celestine.solvers.template.SolverTemplate* method), 25

`geometric()` (in module *celestine.grids*), 9

L

`LaggedUpwindSolver` (class in *celestine.solvers.lagged_solver*), 23

`liquid_fraction_BCs()` (in module *celestine.boundary_conditions*), 1

`liquid_salinity_BC()` (in module `celestine.boundary_conditions`), 1

M

module

- `celestine.boundary_conditions`, 1
- `celestine.enthalpy_method`, 3
- `celestine.flux`, 5
- `celestine.forcing`, 7
- `celestine.grids`, 9
- `celestine.logging_config`, 11
- `celestine.params`, 13
- `celestine.phase_boundaries`, 15
- `celestine.run_simulation`, 17
- `celestine.solvers.lagged_solver`, 23
- `celestine.solvers.template`, 25
- `celestine.state`, 19
- `celestine.velocities`, 21

N

`NumericalParams` (class in `celestine.params`), 13

P

`PhaseBoundaries` (class in `celestine.phase_boundaries`), 15

`PhysicalParams` (class in `celestine.params`), 13

`pre_solve_checks()` (celestine.solvers.lagged_solver.LaggedUpwindSolver method), 23

`pre_solve_checks()` (celestine.solvers.template.SolverTemplate method), 25

R

`run_batch()` (in module `celestine.run_simulation`), 17

S

`salt_BC()` (in module `celestine.boundary_conditions`), 1

`Solution` (class in `celestine.state`), 19

`solve_pressure_equation()` (in module `celestine.velocities`), 21

`SolverTemplate` (class in `celestine.solvers.template`), 25

`State` (class in `celestine.state`), 19

`StateBCs` (class in `celestine.state`), 19

T

`take_forward_euler_step()` (in module `celestine.solvers.lagged_solver`), 23

`take_timestep()` (celestine.solvers.lagged_solver.LaggedUpwindSolver method), 23

`take_timestep()` (celestine.solvers.template.SolverTemplate method), 25

`temperature_BC()` (in module `celestine.boundary_conditions`), 1