Ansatz

Son Nguyen

Reference from Scalable Quantum Simulation of Molecular Energies

Contents

1	Decomposing the UCCSD ansatz	2
2	Unitary Couple Cluster Single Double (UCCSD)	5
3	Quantum Tomography3.1 Theoretical Analysis (XX)3.2 Experimental Analysis (XX)	
4	Bell Measurement (Incomplete)	10
5	Cost Function	12

We start with defining the Hamiltonian of the molecular Hydrogen.

$$H = g_0 \mathbb{I} + g_1 Z_0 + g_2 Z_1 + g_3 Z_0 Z_1 + g_4 Y_0 Y_1 + g_5 X_0 X_1$$

Where: $\{X_i, Z_i, Y_i\}$ denote the Pauli matrices acting on the i-th qubit and the real scalars $\{g_\gamma\}$ are efficiently computable functions of the hydrogen-hydrogen bond length R.

$$X = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}, \quad \mathbb{I} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad Y = \begin{bmatrix} 0 & -i \\ i & 0 \end{bmatrix}, \quad Z = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$$

$$g_0 \mathbb{I} = \begin{bmatrix} g_0 & 0 & 0 & 0 \\ 0 & g_0 & 0 & 0 \\ 0 & 0 & g_0 & 0 \\ 0 & 0 & 0 & g_0 \end{bmatrix}, \quad g_1 Z_0 = \begin{bmatrix} g_1 & 0 & 0 & 0 \\ 0 & g_1 & 0 & 0 \\ 0 & 0 & -g_1 & 0 \\ 0 & 0 & 0 & -g_1 \end{bmatrix}, \quad g_2 Z_1 = \begin{bmatrix} g_2 & 0 & 0 & 0 \\ 0 & -g_2 & 0 & 0 \\ 0 & 0 & g_2 & 0 \\ 0 & 0 & 0 & -g_2 \end{bmatrix},$$

$$g_3 Z_0 Z_1 = \begin{bmatrix} g_3 & 0 & 0 & 0 \\ 0 & -g_3 & 0 & 0 \\ 0 & 0 & -g_3 & 0 \\ 0 & 0 & -g_3 & 0 \\ 0 & 0 & 0 & g_3 \end{bmatrix}, \quad g_4 Y_0 Y_1 = \begin{bmatrix} 0 & 0 & 0 & -g_4 \\ 0 & 0 & g_4 & 0 \\ 0 & g_4 & 0 & 0 \\ -g_4 & 0 & 0 & 0 \end{bmatrix}, \quad g_5 X_0 X_1 = \begin{bmatrix} 0 & 0 & 0 & g_5 \\ 0 & 0 & g_5 & 0 \\ 0 & g_5 & 0 & 0 \\ g_5 & 0 & 0 & 0 \end{bmatrix}$$

$$H = \begin{bmatrix} g_0 + g_1 + g_2 + g_3 & 0 & 0 & g_5 + g_4 \\ 0 & g_0 + g_1 - g_2 - g_3 & g_5 + g_4 & 0 \\ 0 & g_5 + g_4 & g_0 - g_1 + g_2 - g_3 & 0 \\ 0 & g_5 - g_4 & 0 & 0 & g_0 - g_1 - g_2 + g_3 \end{bmatrix}$$

1 Decomposing the UCCSD ansatz



Figure 1: The UCCSD ansatz for the Hydrogen molecule.

Reference state $|10\rangle$



$$(X \otimes I) \cdot (|0\rangle \otimes |0\rangle) = |10\rangle$$

$$\left(\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \otimes \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \right) \cdot \left(\begin{bmatrix} 1 \\ 0 \end{bmatrix} \otimes \begin{bmatrix} 1 \\ 0 \end{bmatrix} \right) = \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$$

Apply parameterized ansatz



$$\begin{pmatrix}
R_x(\frac{-\pi}{2}) \otimes R_y(\frac{\pi}{2}) \end{pmatrix} \cdot |10\rangle$$

$$R_x(\frac{-\pi}{2}) = e^{-iX(\frac{-\pi}{4})} = \begin{bmatrix}
\cos(\frac{-\pi}{4}) & -i\sin(\frac{-\pi}{4}) \\
-i\sin(\frac{-\pi}{4}) & \cos(-\frac{\pi}{4})
\end{bmatrix} = \begin{bmatrix}
\frac{\sqrt{2}}{2} & \frac{i\sqrt{2}}{2} \\
\frac{i\sqrt{2}}{2} & \frac{\sqrt{2}}{2}
\end{bmatrix}$$

$$R_y(\frac{\pi}{2}) = e^{-iY(\frac{\pi}{4})} = \begin{bmatrix}\cos(\frac{\pi}{4}) & -\sin(\frac{\pi}{4}) \\
\sin(\frac{\pi}{4}) & \cos(\frac{\pi}{4})
\end{bmatrix} = \begin{bmatrix}
\frac{\sqrt{2}}{2} & -\frac{\sqrt{2}}{2} \\
\frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2}
\end{bmatrix}$$

$$\begin{pmatrix}
R_x(\frac{-\pi}{2}) \otimes R_y(\frac{\pi}{2})
\end{pmatrix} = \begin{bmatrix}
\frac{\sqrt{2}}{2} & \frac{i\sqrt{2}}{2} \\
\frac{i\sqrt{2}}{2} & \frac{\sqrt{2}}{2}
\end{bmatrix} \otimes \begin{bmatrix}
\frac{\sqrt{2}}{2} & -\frac{\sqrt{2}}{2} \\
\frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2}
\end{bmatrix} = \begin{bmatrix}
\frac{1}{2} & \frac{-1}{2} & \frac{i}{2} & \frac{-i}{2} \\
\frac{1}{2} & \frac{1}{2} & \frac{i}{2} & \frac{1}{2} \\
\frac{i}{2} & \frac{i}{2} & \frac{i}{2} & \frac{1}{2}
\end{bmatrix}$$

$$\begin{pmatrix}
R_x(\frac{-\pi}{2}) \otimes R_y(\frac{\pi}{2})
\end{pmatrix} \cdot |10\rangle = \begin{bmatrix}
\frac{1}{2} & \frac{-1}{2} & \frac{i}{2} & \frac{-i}{2} \\
\frac{1}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2} \\
\frac{i}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2} \\
\frac{i}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2}
\end{bmatrix}$$

$$\begin{pmatrix}
R_x(\frac{-\pi}{2}) \otimes R_y(\frac{\pi}{2})
\end{pmatrix} \cdot |10\rangle = \begin{bmatrix}
\frac{1}{2} & \frac{-1}{2} & \frac{i}{2} & \frac{-i}{2} \\
\frac{1}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2} \\
\frac{i}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2} \\
\frac{i}{2} & \frac{i}{2} & \frac{i}{2} & \frac{i}{2}
\end{bmatrix}$$

The first CNOT (entanglement)



$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \end{bmatrix} \cdot \begin{bmatrix} \frac{i}{2} \\ \frac{i}{2} \\ \frac{1}{2} \\ \frac{1}{2} \end{bmatrix} = \begin{bmatrix} \frac{i}{2} \\ \frac{1}{2} \\ \frac{1}{2} \\ \frac{i}{2} \end{bmatrix}$$

The Z_{θ} rotation gate:

$$Z_{\theta} = e^{-iZ(\frac{\theta}{2})} = \begin{bmatrix} e^{-i\frac{\theta}{2}} & 0\\ 0 & e^{i\frac{\theta}{2}} \end{bmatrix}$$

$$(Z_{\theta} \otimes I) \cdot \begin{bmatrix} \frac{i}{2} \\ \frac{1}{2} \\ \frac{1}{2} \\ \frac{i}{2} \end{bmatrix} = \begin{bmatrix} e^{-i\frac{\theta}{2}} & 0 & 0 & 0 \\ 0 & e^{-i\frac{\theta}{2}} & 0 & 0 \\ 0 & 0 & e^{i\frac{\theta}{2}} & 0 \\ 0 & 0 & 0 & e^{i\frac{\theta}{2}} \end{bmatrix} \cdot \begin{bmatrix} \frac{i}{2} \\ \frac{1}{2} \\ \frac{1}{2} \\ \frac{i}{2} \end{bmatrix} = \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} - i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \end{bmatrix}$$

The second CNOT (entanglement)

$$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \end{bmatrix} \cdot \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} - i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \end{bmatrix} = \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} - i\frac{\sin(\frac{\theta}{2})}{2} \end{bmatrix}$$

The final rotation gates:

$$\left(R_x(\frac{\pi}{2}) \otimes R_y(\frac{-\pi}{2})\right) \cdot \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ -\frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} - i\frac{\sin(\frac{\theta}{2})}{2} \end{bmatrix}$$

$$= \left(\begin{bmatrix} \cos\left(\frac{\pi}{4}\right) & -i\sin\left(\frac{\pi}{4}\right) \\ -i\sin\left(\frac{\pi}{4}\right) & \cos\left(\frac{\pi}{4}\right) \end{bmatrix} \otimes \begin{bmatrix} \cos\left(\frac{-\pi}{4}\right) & -\sin\left(\frac{-\pi}{4}\right) \\ \sin\left(\frac{-\pi}{4}\right) & \cos\left(\frac{-\pi}{4}\right) \end{bmatrix} \right) \cdot \begin{bmatrix} \frac{\sin\left(\frac{\theta}{2}\right)}{2} + i\frac{\cos\left(\frac{\theta}{2}\right)}{2} \\ \frac{-\sin\left(\frac{\theta}{2}\right)}{2} + i\frac{\cos\left(\frac{\theta}{2}\right)}{2} \\ \frac{\cos\left(\frac{\theta}{2}\right)}{2} + i\frac{\sin\left(\frac{\theta}{2}\right)}{2} \\ \frac{\cos\left(\frac{\theta}{2}\right)}{2} - i\frac{\sin\left(\frac{\theta}{2}\right)}{2} \end{bmatrix}$$

$$= \left(\begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{-i}{\sqrt{2}} \\ \frac{-i}{\sqrt{2}} & \frac{1}{\sqrt{2}} \end{bmatrix} \otimes \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{-1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \end{bmatrix} \right) \cdot \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \end{bmatrix}$$

$$= \begin{bmatrix} \frac{1}{2} & \frac{1}{2} & \frac{-i}{2} & \frac{-i}{2} \\ \frac{-1}{2} & \frac{1}{2} & \frac{i}{2} & \frac{-i}{2} \\ \frac{-1}{2} & \frac{1}{2} & \frac{i}{2} & \frac{-i}{2} \\ \frac{1}{2} & \frac{-i}{2} & \frac{1}{2} & \frac{1}{2} \\ \frac{i}{2} & \frac{-i}{2} & -\frac{1}{2} & \frac{1}{2} \end{bmatrix} \cdot \begin{bmatrix} \frac{\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\cos(\frac{\theta}{2})}{2} \\ \frac{-\sin(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} + i\frac{\sin(\frac{\theta}{2})}{2} \\ \frac{\cos(\frac{\theta}{2})}{2} - i\frac{\sin(\frac{\theta}{2})}{2} \end{bmatrix} = \begin{bmatrix} 0 \\ -\sin(\frac{\theta}{2}) \\ \cos(\frac{\theta}{2}) \\ 0 \end{bmatrix}$$

$$(1)$$

Reverse to match the qiskit ordering:

$$\begin{bmatrix} 0 \\ \cos(\frac{\theta}{2}) \\ -\sin(\frac{\theta}{2}) \\ 0 \end{bmatrix} = |\phi(\vec{\theta})\rangle = \cos\left(\frac{\theta}{2}\right)|01\rangle - \sin\left(\frac{\theta}{2}\right)|10\rangle$$

Use $\theta = -3.37$:

$$\begin{bmatrix} 0 \\ \cos(\frac{-3.37}{2}) \\ -\sin(\frac{-3.37}{2}) \\ 0 \end{bmatrix} \approx \begin{bmatrix} 0 \\ -0.1139 \\ 0.9935 \\ 0 \end{bmatrix}$$

*Note: This does not match the calculation, I had to switch place between the $|01\rangle$ and $|10\rangle$ to match the qiskit ordering

2 Unitary Couple Cluster Single Double (UCCSD)

To be continued...

3 Quantum Tomography

The expectation value (Quantum Tomography): Using many measurements on identically prepared systems to get mean values of the some complete set of observables to reconstruct an estimate of the state. Quantum Tomography works to determine the state prior to the measurements.

In this case, our state we want to reconstruct is $|\phi(\vec{\theta})\rangle$. Starting with the density matrix:

$$\rho = |\phi(\vec{\theta})\rangle\langle\phi(\vec{\theta})|$$

The general two qubits wavefunction can be written as:

$$|\phi\rangle = a_{00}|00\rangle + a_{01}|01\rangle + a_{10}|10\rangle + a_{11}|11\rangle$$

Where $a_{ij} \in \mathbb{C}$, and $\sum_{i,j} |a_{ij}|^2 = 1$. For our case, we have:

$$|\phi(\vec{\theta})\rangle = \cos\left(\frac{\theta}{2}\right)|01\rangle - \sin\left(\frac{\theta}{2}\right)|10\rangle$$

Where: $a_{00} = 0, a_{01} = \cos\left(\frac{\theta}{2}\right), a_{10} = -\sin\left(\frac{\theta}{2}\right), a_{11} = 0$, the goal is to reconstruct a_{01} and a_{10} . To achieve this, we need to make measurement in different basis. (X, Y, Z, ...).




Figure 2: Reference

Let say we have a 1-qubit state $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$. This state is a superposition of $|0\rangle$ and $|1\rangle$. This is also called the Z basis (computational basis).

Measurement in the X basis - Diagonal basis/ Hadamard basis: superposition collapses the quantum state of the qubit $|\psi\rangle$ to either $|+\rangle$ or $|-\rangle$.

$$\begin{aligned} |+\rangle &= \frac{1}{\sqrt{2}}(|0\rangle + |1\rangle) \\ |-\rangle &= \frac{1}{\sqrt{2}}(|0\rangle - |1\rangle) \\ |0\rangle &= \frac{1}{\sqrt{2}}(|+\rangle + |-\rangle) \\ |1\rangle &= \frac{1}{\sqrt{2}}(|+\rangle - |-\rangle) \end{aligned}$$

$$H|\psi\rangle = H(\alpha|0\rangle + \beta|1\rangle) \tag{2}$$

$$= \alpha H|0\rangle + \beta H|1\rangle \tag{3}$$

$$= \alpha \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \beta \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{bmatrix} \begin{bmatrix} 0 \\ 1 \end{bmatrix}$$
(4)

$$= \alpha \begin{bmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{bmatrix} + \beta \begin{bmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{bmatrix} \tag{5}$$

$$=\alpha|+\rangle+\beta|-\rangle$$
 X basis (6)

Measurement in the Y basis (Imaginary basis):

$$\begin{split} (S^{\dagger} \cdot H) |\psi\rangle &= (S^{\dagger} \cdot H) (\alpha |0\rangle + \beta |1\rangle) \\ &= \alpha (S^{\dagger} \cdot H) |0\rangle + \beta (S^{\dagger} \cdot H) |1\rangle \\ &= \alpha \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{-i}{\sqrt{2}} & \frac{i}{\sqrt{2}} \end{bmatrix} \cdot \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \beta \begin{bmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{-i}{\sqrt{2}} & \frac{i}{\sqrt{2}} \end{bmatrix} \cdot \begin{bmatrix} 0 \\ 1 \end{bmatrix} \\ &= \alpha \begin{bmatrix} \frac{1}{\sqrt{2}} \\ \frac{-i}{\sqrt{2}} \end{bmatrix} + \beta \begin{bmatrix} \frac{1}{\sqrt{2}} \\ \frac{i}{\sqrt{2}} \end{bmatrix} \\ &= \alpha \frac{1}{\sqrt{2}} (|0\rangle - i|1\rangle) + \beta \frac{1}{\sqrt{2}} (|0\rangle + i|1\rangle) \quad \text{Y basis} \end{split}$$

Pauli Measurement	Unitary Transformation
$Z\otimes 1$	1 \otimes 1
$X \otimes 1$	$H\otimes 1$
$Y \otimes 1$	$HS^{\dagger}\otimes 1$
$1 \otimes Z$	SWAP
$1 \otimes X$	$(H \otimes 1)$ SWAP
$1 \otimes Y$	$(HS^{\dagger}\otimes 1)$ SWAP
$Z \otimes Z$	$CNOT_{10}$
$X \otimes Z$	$CNOT_{10}(H \otimes 1)$
$Y \otimes Z$	$\text{CNOT}_{10}(HS^{\dagger}\otimes 1)$
$Z \otimes X$	$\mathrm{CNOT}_{10}(1 \otimes H)$
$X \otimes X$	$CNOT_{10}(H \otimes H)$
$Y \otimes X$	$\text{CNOT}_{10}(HS^{\dagger}\otimes H)$
$Z \otimes Y$	$\text{CNOT}_{10}(1 \otimes HS^{\dagger})$
$X \otimes Y$	$\mathrm{CNOT}_{10}(H \otimes HS^{\dagger})$
$Y \otimes Y$	$\text{CNOT}_{10}(HS^{\dagger}\otimes HS^{\dagger})$

$$\langle H \rangle = g_0 \mathbb{I} + g_1 \langle Z_0 \rangle + g_2 \langle Z_1 \rangle + g_3 \langle Z_0 Z_1 \rangle + g_4 \langle Y_0 Y_1 \rangle + g_5 \langle X_0 X_1 \rangle$$
$$\langle P \rangle = \sum_{\text{bitstring}} (-1)^{\text{parity}} \left(\frac{\text{count}}{\text{shots}} \right)$$

Where:

- parity = bitstring.count('1') mod 2
- count = number of times the bitstring was measured
- shots = total number of measurements

3.1 Theoretical Analysis (XX)

 \bullet For the XX operator

$$XX = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \otimes \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 \end{bmatrix}$$

The expectation value of an observable O is given by:

$$\langle O \rangle = \sum_{i} \lambda_i p_i$$

Where p_i is the probability of measuring the state in the i^{th} eigenstate. λ_i is the expectation value correspoding to eigenstate.

From equation (2) we can see that $H|0\rangle = |+\rangle, H|1\rangle = |-\rangle$. The corresponding eigenvalues for the operator X are

$$\langle +|X|+\rangle = 1$$
 and $\langle -|X|-\rangle = -1$

For the 2 qubit states, we have:

$$(H \otimes H)|00\rangle = \begin{bmatrix} \frac{1}{2} \\ \frac{1}{2} \\ \frac{1}{2} \\ \frac{1}{2} \end{bmatrix} = |++\rangle = \frac{1}{2}(|00\rangle + |01\rangle + |10\rangle + |11\rangle)$$
$$(H \otimes H)|01\rangle = |+-\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |10\rangle)$$
$$(H \otimes H)|10\rangle = |-+\rangle = \frac{1}{\sqrt{2}}(|00\rangle - |10\rangle)$$
$$(H \otimes H)|11\rangle = |--\rangle$$

Apply the operator XX on each state:

$$\begin{split} XX|++\rangle &= \frac{1}{2}(XX|00\rangle + XX|01\rangle + XX|10\rangle + XX|11\rangle) \\ &= \frac{1}{2}(|11\rangle + |10\rangle + |01\rangle + |00\rangle) = |++\rangle \\ &\Rightarrow \langle + + |XX| + +\rangle = \langle + + |++\rangle = 1 \\ XX|+-\rangle &= \frac{1}{2}(XX|00\rangle - XX|01\rangle + XX|10\rangle - XX|11\rangle) \\ &= \frac{1}{2}(|11\rangle - |10\rangle + |01\rangle - |00\rangle) = \frac{1}{2}\begin{bmatrix} -1\\1\\-1\\1\end{bmatrix} \\ &\Rightarrow \langle + - |XX| + -\rangle = \begin{bmatrix} \frac{1}{2} & -\frac{1}{2} & \frac{1}{2} & -\frac{1}{2} \end{bmatrix} \cdot \begin{bmatrix} \frac{-1}{2}\\\frac{1}{2}\\-\frac{1}{2}\\\frac{1}{2}\end{bmatrix} = -1 \end{split}$$

and so we can get the remaining expectation values $\langle -+|XX|-+\rangle = -1, \langle --|XX|--\rangle = 1$

Measurement	XX basis equivalent	XX Expectation Value
$ 00\rangle$	$ ++\rangle$	1
$ 01\rangle$	$ +-\rangle$	-1
$ 10\rangle$	$ -+\rangle$	-1
11⟩	$ \rangle$	1

3.2 Experimental Analysis (XX)

From our circuit that produce the wavefunction $|\phi(\vec{\theta})\rangle$ (see Figure 1). We just need to apply two Hadamard gates to the qubits and measure the expectation value of the XX operator.




Figure 3: Circuit for the XX operator

Give the trial wavefunction $|\phi(\vec{\theta})\rangle = \cos\left(\frac{\theta}{2}\right)|01\rangle - \sin\left(\frac{\theta}{2}\right)|10\rangle$. Applying the Hadamard gates given:


$$\begin{split} (H \otimes H)|\phi(\vec{\theta})\rangle &= (H \otimes H)(\cos\left(\frac{\theta}{2}\right)|01\rangle - \sin\left(\frac{\theta}{2}\right)|10\rangle) \\ &= \cos\left(\frac{\theta}{2}\right)(H \otimes H)|01\rangle - \sin\left(\frac{\theta}{2}\right)(H \otimes H)|10\rangle \\ &= \cos\left(\frac{\theta}{2}\right)|+-\rangle - \sin\left(\frac{\theta}{2}\right)|-+\rangle \end{split}$$

Then we apply the $CNOT_{01}$ gate to the state:

$$\begin{split} &\operatorname{CNOT}_{01}(\cos\left(\frac{\theta}{2}\right)|+-\rangle-\sin\left(\frac{\theta}{2}\right)|-+\rangle) = \\ &= \operatorname{CNOT}_{01}\cos\left(\frac{\theta}{2}\right)\frac{1}{\sqrt{2}}\left(|00\rangle+|10\rangle\right) - \operatorname{CNOT}_{01}\sin\left(\frac{\theta}{2}\right)\frac{1}{\sqrt{2}}\left(|00\rangle-|10\rangle\right) \\ &= \frac{1}{\sqrt{2}}\left[\operatorname{CNOT}_{01}\left(\cos\left(\frac{\theta}{2}\right)-\sin\left(\frac{\theta}{2}\right)\right)|00\rangle+\operatorname{CNOT}_{01}\left(\cos\left(\frac{\theta}{2}\right)+\sin\left(\frac{\theta}{2}\right)\right)|10\rangle\right] \\ &= \frac{1}{\sqrt{2}}\left[\left(\cos\left(\frac{\theta}{2}\right)-\sin\left(\frac{\theta}{2}\right)\right)|00\rangle+\left(\cos\left(\frac{\theta}{2}\right)+\sin\left(\frac{\theta}{2}\right)\right)|11\rangle\right] \end{split}$$

4 Bell Measurement (Incomplete)

Alternatively, using Bell Measurement to reconstruct the trial wavefunction with the parameter $\theta \approx -3.37$, getting the expectation after 1000 measurements:



From the figure, we have see there is 1.7% of $|01\rangle$ and 98.3% of $|10\rangle$.

$$\sqrt{1.7\%}|01\rangle + \sqrt{98.3\%}|10\rangle = |\phi(\vec{\theta})\rangle$$
$$\pm 0.13|01\rangle \pm 0.99|10\rangle = |\phi(\vec{\theta})\rangle$$

To determine the sign of our trial wavefunction, we can use Bell measurements. We can measures any state which is an superposition of $|00\rangle, |01\rangle, |10\rangle, |11\rangle$ in the Bell basis.

$$|\Phi^{+}\rangle = \frac{1}{\sqrt{2}}(|00\rangle + |11\rangle)$$

$$|\Phi^{-}\rangle = \frac{1}{\sqrt{2}}(|00\rangle - |11\rangle)$$

$$|\Psi^{+}\rangle = \frac{1}{\sqrt{2}}(|01\rangle + |10\rangle)$$

$$|\Psi^{-}\rangle = \frac{1}{\sqrt{2}}(|01\rangle - |10\rangle)$$

By combining a CNOT gate followed by a Hadamard gate, we can measure the state in the Bell basis.

$$U|\Phi^+\rangle = |00\rangle$$

$$U|\Phi^-\rangle=|01\rangle$$

$$U|\Psi^{+}\rangle = |10\rangle$$


$$U|\Psi^{-}\rangle = |11\rangle$$

Where $U_{Bell} = (H \otimes I) \cdot \text{CNOT}(0, 1)$

$$U_{Bell} = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 0 & 0 & 1\\ 1 & 0 & 0 & -1\\ 0 & 1 & 1 & 0\\ 0 & -1 & 1 & 0 \end{bmatrix}$$

Applying the U_{Bell} on $\begin{bmatrix} A \\ B \\ C \\ D \end{bmatrix}$


$$U_{Bell} \cdot \begin{bmatrix} A \\ B \\ C \\ D \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} A+D \\ A-D \\ B+C \\ B-C \end{bmatrix}$$



The trial wavefunction after applying the U_{Bell} unitary gate:

$$U_{Bell} \cdot |\phi(\vec{\theta})\rangle = U_{Bell} \cdot \begin{bmatrix} 0 \\ \cos\left(\frac{\theta}{2}\right) \\ -\sin\left(\frac{\theta}{2}\right) \end{bmatrix} = \frac{1}{\sqrt{2}} \begin{bmatrix} 0 \\ 0 \\ \cos\left(\frac{\theta}{2}\right) - \sin\left(\frac{\theta}{2}\right) \\ \cos\left(\frac{\theta}{2}\right) + \sin\left(\frac{\theta}{2}\right) \end{bmatrix} \begin{array}{c} |00\rangle \\ |01\rangle \\ |10\rangle \approx 0.39\% \\ |11\rangle \approx 0.61\% \end{array}$$

Using $\theta \approx -3.37$ we have:



We can see the counts of $|11\rangle$ is dominant, which means the state is $|\Psi^{-}\rangle$. Therefore, the sign between $|01\rangle$ and $|10\rangle$ is negative.

$$0.13|01\rangle - 0.99|10\rangle = |\phi(\vec{\theta})\rangle \tag{7}$$

Reference.

Now we plug in the θ to equation (1) to compare with equation (2), we have:

$$-\sin\left(\frac{-3.37}{2}\right)|01\rangle + \cos\left(\frac{-3.37}{2}\right)|10\rangle = |\phi(\vec{\theta})\rangle$$
$$0.993|01\rangle - 0.11|10\rangle = |\phi(\vec{\theta})\rangle$$

There is a mistake for my bell measurement, I will correct it later.

5 Cost Function

Mathematically we can use the Hamiltonian and the trial wavefunction, we can get our cost function (energy) as:

$$E = \langle \phi(\vec{\theta}) | H | \phi(\vec{\theta}) \rangle$$

$$\begin{bmatrix} 0 & \cos(\frac{\theta}{2}) & -\sin(\frac{\theta}{2}) & 0 \end{bmatrix} \cdot \begin{bmatrix} g_0 + g_1 + g_2 + g_3 & 0 & 0 & g_5 - g_4 \\ 0 & g_0 + g_1 - g_2 - g_3 & g_5 + g_4 & 0 \\ 0 & g_5 + g_4 & g_0 - g_1 + g_2 - g_3 & 0 \\ g_5 - g_4 & 0 & 0 & g_0 - g_1 - g_2 + g_3 \end{bmatrix} \cdot \begin{bmatrix} 0 \\ \cos(\frac{\theta}{2}) \\ -\sin(\frac{\theta}{2}) \\ 0 \end{bmatrix}$$

Plug in $g_0 = -0.4804, g_1 = 0.3435, g_2 = -0.4347, g_3 = 0.5716, g_4 = 0.091, g_5 = 0.091$ we have:

$$\begin{bmatrix} 0 & \cos(\frac{\theta}{2}) & -\sin(\frac{\theta}{2}) & 0 \end{bmatrix} \cdot \begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & -0.2738 & 0.182 & 0 \\ 0 & 0.182 & -1.8302 & 0 \\ 0 & 0 & 0 & 0.1824 \end{bmatrix} \cdot \begin{bmatrix} 0 \\ \cos(\frac{\theta}{2}) \\ -\sin(\frac{\theta}{2}) \\ 0 \end{bmatrix} \approx -1.851 \quad \text{(with } \theta = -3.37\text{)}$$

The minimum energy can be found using classical optimization techniques.

$$E_{min} = \langle \phi_{min}(\vec{\theta}) \mid H \mid \phi_{min}(\vec{\theta}) \rangle$$