

Agenda

- Shiny!
 - template
 - ui/server

Learning objectives

- Be able to create basic interactive plots with shiny
- Understand basic layouts



It's required you make this joke when talking about shiny (especially if you're a parent of a 6 (almost 7) and 9 year old)

The basics!

Do the following:

- Create a new R project
- Select "Shiny Web Application"
- Select the directory
- Click "create project"

[demo]

First thing – Run App!

- I like to open in the browser
- What's going on here? Talk with your neighbor and see if you can deduce the basic functionality.

02:00

UI

- The `ui` defines the look and feel of the app – the user interface
- Use it to define where output "lives"
- It also defines the inputs for the `server`, where functions are actually evaluated.
- In this case – we have defined a `sliderInput`, which we're calling `"bins"`. It will take on values from 1 to 50, and will start at 30.
- Access the specific value the user selects within the `server`, through `input$bins`.

Server

- The `server` function takes the input from the UI and puts it in normal R code.
- In this case, we're creating one output object, called `distPlot`. The result is then called through the `ui` on line 30
- Try removing lines 39–44, and replacing it with `print(input$bins)`
- Feels like it should work, but it doesn't. Any ideas why?

Text output

We are no longer rendering a plot. We are rendering text.

We need to change `renderPlot` to `renderText` and `plotOutput` to `textOutput`.

Try

Does it work now?

Challenge

- Try producing essentially the same thing as the default, but use `ggplot` instead of base plotting.
- Reminder, the data are called `faithful`, and you'll be showing the distribution of `waiting`

10:00

[demo]

Change the input

- Let's say instead of a slider, we want 5 options: 1, 5, 20, 50, or 100
- We can change the input from a slider (representing continuous intervals) to radio buttons, representing discrete choices.
- Just change `sliderInput` to `radioButtons`, and put in the appropriate `choices`. You can also add a `selected` argument for which it defaults to.

Try it out!

05:00

[demo]

More complicated

- Let's say we wanted to build a plot that showed the distribution of highway miles per gallon that could be faceted by **year**, **trans**, or **class**.
- Let's say you also wanted to keep a slider on there to control the number of bins.
- Use **radioButtons** for the variables, and **sliderInput** for the bins.
- You'll need to create a second entry to your **ui**
- Use the **mpg** dataset (from **ggplot2**)

[demo]

Tables

- My recommendation: Use one of the following:
 - `DT::datatable`
 - `reactable::reactable`
- Let's build a table to go below our distribution(s) that shows `mean`, `sd`, `min`, and `max` of the corresponding distribution(s)
- You'll need to create a new output object in the server, and tell the ui where it should be rendered

- Use `renderDataTable` in the server and `dataTableOutput` in the ui or `renderReactable` and `reactableOutput`
- If you want to use `{dplyr}`, as I would, then you have to deal with NSE. In this case it's not that big of a deal though. Just use `!!sym(input$var)`, where `sym` transforms a string to a symbol.

[demo]

Last thing for today

Change the layout

- Let's say instead of having the table below, we wanted it within a tabset
- Just create a `tabsetPanel` within the `mainPanel`, then put the output for each tab within `tabPanel`. [demo]

Alternative

- Instead of using a tabset with `tabsetPanel`, you might want to have a navbar at the top of the page, which you can create with `navbarPage`.
- Can be a bit more complicated – each `tabset` needs to include everything, including the `sidebarPanel` (if present), could include tabsets, `mainPanel`, etc.
- Essentially each tab from the `navbar` becomes an entirely new page.
- Make sure to move your title so it's like `navbarPage("App title",` or the rest of the pages won't look right

[demo, if we have time]

Conclusions

- Shiny is super customizable – just scratched the surface today
- The new Mastering Shiny book should be your guide for going deeper
- Great for building interactive plots, but you can use it for all sorts of other things too (including text and tables)
- Apps get complicated quickly
 - Consider pulling pieces out as a refactoring method to try to make code more readable/less buggy, or using shiny modules

Next time

Shiny dashboards