

Deserialize of Java Serialized object

If you want to save an active Java instance, you must first serialize the object instance before you can save the serialized object to a file. This file is now a serialized Java object file. And if you want to "revive" the serialized object, you must first read it from the file and then **deserialize** it. It's a reverse process and is called deserialization. For this Object-saving purpose, JAVA provides you with a tool with 2 APIs:

- **ObjectOutputStream** for serializing an object instance
- **ObjectInputStream** for the reverse process

The serialization process is a straightforward one. An object you want to store just needs to be an "implementation" of the Serializable interface. Example:

```
import java.util.ArrayList;
import java.io.FileOutputStream;
import java.io.ObjectOutputStream;
public class MyList implements java.io.Serializable {
    public static final long serialVersionUID = 1L;
    ArrayList<String> list;
    public MyList(String[] mylist) {
        list = new ArrayList<>(mylist.length);
        for (String s:mylist) list.add(s);
    }
    public void print() {
        System.out.println(list);
    }
    //
    public static void main(String... a) throws Exception {
        MyList ml = new MyList(a.length == 0? new String[] { "Hello", "World" }:a);
        ObjectOutputStream oos = new ObjectOutputStream(new
FileOutputStream("serobj/MyList.txt"));
        oos.writeObject(ml);
        oos.flush();
        oos.close();
    }
}
```

And the file MyList.txt looks as following (in plain text)

- Invocation with 3 parameters: **java MyList joe T schwarz**

```
¬í #sr #MyList    ## #L #listt #Ljava/util/ArrayList;xpsr #java.util.ArrayListx ¯ Ò#TMÇa ¯# #I #sizexp #w# #t
#joet #Tt #schwarzx
```

- Invocation without parameter: **java MyList**

```
¬í #sr #MyList    ## #L #listt #Ljava/util/ArrayList;xpsr #java.util.ArrayListx ¯ Ò#TMÇa ¯# #I #sizexp #w# #t
#Hellot #Worldx
```

If you dump these files as hex-content, you will see: (MyList.txt with 3 parameters)

0	4	8	C	10		
ACED0005	73720006	4D794C69	73740000	00000000 sr.. MyLi st..	0
00010200	014C0004	6C697374	7400154C	6A617661L.. list t..L java	1
2F757469	6C2F4172	7261794C	6973743B	78707372	/uti l/Ar rayL ist; xpsr	2
00136A61	76612E75	74696C2E	41727261	794C6973	..ja va.u til. Arra yLis	3
747881D2	1D99C761	9D030001	49000473	697A6578	tx.. ...a I..s izex	4
70000000	03770400	00000374	00036A6F	65740001	p... .w.. ...t ..jo et..	5
54740007	73636877	61727A78			Tt.. schw arzx	6

It looks quite confusing. Both processes **ALWAYS** require that the binary bytecode class of the serialized object exists and is known via CLASSPATH. Otherwise a "**ClassNotFoundException**" is thrown. Ugly, isn't it? Now, let's start the reverse process.

```
import java.util.ArrayList;
import java.io.FileInputStream;
import java.io.ObjectInputStream;
public class DeMyList {
    ArrayList<String> list;
    public static void main(String... a) throws Exception {
        ObjectInputStream ois = new ObjectInputStream(new FileInputStream(a[0]));
        MyList ml = (MyList) ois.readObject( );
        ois.close();
        ml.print();
    }
}
```

If you rename the class MyList.class to any name and run the MyList and this little app, you will get this famous **ClassNotFoundException**. Example:

```
C:\JoeApp\ODB\examples\Test\examples>java MyList joe T schwarz
Error: Could not find or load main class MyList
Caused by: java.lang.ClassNotFoundException: MyList

C:\JoeApp\ODB\examples\Test\examples>java DeMyList serobj/mylist.txt
Exception in thread "main" java.lang.ClassNotFoundException: MyList
    at java.base/jdk.internal.loader.BuiltinClassLoader.loadClass(Unknown Source)
    at java.base/jdk.internal.loader.ClassLoaders$AppClassLoader.loadClass(Unknown Source)
```

Let's rename it back to MyList.class and rerun DeMyList.

```
C:\JoeApp\ODB\examples\Test\examples>java DeMyList serobj/mylist.txt
[joe, T, schwarz]
```

What I am showing you here is a trivial work with Java Serializable Object. You might be wondering what all this effort is for? Well, it is probably desirable when you need to send a serialized object instance over a network and there are no binary bytecodes available for that object on the other side. Trying to do this with URLClassLoader or Java Reflection ends with ClassNotFoundException. The only option is to send a bytecode class along with the serialized object instance and make it known via CLASSPATH. And that is virtually impossible. Since the serialized object contains valid data (except codes for the methods), the question arises: is there a way to work with the serialized objects (or files)? If you search the internet, you won't find any. The only package I found is the Github "[jdeserialize](https://github.com/unsynchronized/jdeserialize)" (<https://github.com/unsynchronized/jdeserialize>). This package reads a serialized object file and dumps the layout of the serialized data structure (reverse engineering?) with all the data initialized. Since there is no access to every field, working with this outputted object requires additional hard work.

No chance? Yes! You can reconstruct a serialized object without having its bytecode class. The JAVA serialization protocol is available ([HERE](#)) and all you need is to implement an API based on this protocol. And I'll show you how I did it below.

SerObjectView API.

Constructors:

- public SerObjectView()
- public SerObjectView(String fileName) throws Exception
- public SerObjectView(byte[] bb) throws Exception

Methods:

- public void view(byte[] bb) throws Exception
- public void setCharset(Charset charset)
- public long getSerialID()
- public int getSize() -get the number of fields (i.e. variables)
- public String getClassName()
- public ArrayList<String> getFieldNames()
- public String getFieldType(String fieldName) -e.g. double, int, etc.
- public Object getFieldValue(String fName) -e.g. 123.45, 100, etc. Must be cast.

Note:

This API is used to reconstruct a serialized object (via a file or a byte array) without having to know/have its bytecode class. Due to the sheer number of JAVA APIs, this SerObjectView is limited to primitives (including String), custom serialized objects and ArrayList. Arrays with more than 3 dimensions are also not supported. When working with Java Object DB, the objects are usually simple POJOs (Plain Old Java Object). With SerObjectView you can access the data of the variables (fields) and process them outside of the object.

Example: ViewSerObject shows you how to work with SerObjectView

```
import java.util.*;
import java.io.*;
/**
 * @author Joe T. Schwarz
 */
public class ViewSerObject {
    public static void main(String... a) throws Exception {
        if (a.length == 0) {
            System.out.println("Usage: java ViewSerObject serializedObjectFile");
            System.exit(0);
        }
        ...
        new ViewSerObject(obj);
    }
}
/**
 * Constructor
 * @param sfName String, serialized file name
 */
public ViewSerObject(String sfName) throws Exception {
    show(new SerObjectView(sfName));
}
...
private static OutputStream output = System.out;
//
@SuppressWarnings("unchecked")
private void show(SerObjectView ov) throws Exception {
```

```

output.write(String.format("Class Name: %s\nSerID: %d\nNumber of Fields: %s\n",
    ov.getClassName(),ov.getSerialID(), ov.getSize()).getBytes());
ArrayList<String> fNames = ov.getFieldNames();
for (String f:fNames) {
    String type = ov.getFieldType(f);
    int a = type.indexOf("[");
    if ("Object".equals(type)) {
        output.write("Embedded ".getBytes());
        show((SerObjectView) ov.getFieldValue(f));
    } else
        output.write(String.format("Field: %s, type: %s, value/Reference: %s\n",
            f, type, ov.getFieldValue(f)).getBytes());
    if (type.indexOf("[") > 0) {
        Object obj = ov.getFieldValue(f);
        if (type.indexOf("int") >= 0) {
            if (a > 0) {
                a = type.indexOf("]", a+2);
                if (a < 0) {
                    int[][] aa = (int[][]) obj;
                    ...
                } else {
                    int[][][] aa = (int[][][]) obj;
                    ...
                }
            } else {
                int[] aa = (int[]) obj;
                for (int i = 0; i < aa.length; ++i)
                    output.write(String.format("    int[%d]: %d\n", i, aa[i]).getBytes());
            }
        } else if (type.indexOf("long") >= 0) {
            ...
        }
    }
}
}
}

```

And for this ser. Object

```

public class Ser_Obj implements java.io.Serializable {
    public static final long serialVersionUID = 1L;
    public int i1 = 1;
    public double d2 = 2d;
    public long l9 = 9;
    public float f3 = 3f;
    public short s4 = 4;
    public char c5 = 'J';
    public byte b6 = (byte)'E';
    public boolean boo = true;
    public String T7="XinChao";
    public People p = new People( "Joe", 73, "Kriftel", "Retiree", 18000, "J.jpg");
    public int[] I7 = { 5, 6 };
    public double[] D8 = {7, 8};
    public byte[] bb = {(byte)'j', (byte)'o', (byte)'e'};
    public String[] TT = { "hello", "world"};
    private People pep[][] = {{ new People( "Joe1", 73, "Kriftel1", "Retiree1", 18000, "J1.jpg"),
        new People( "Joe2", 73, "Kriftel2", "Retiree2", 18000, "J2.jpg"),
        new People( "Joe3", 73, "Kriftel3", "Retiree3", 18000, "J3.jpg") },
        { new People( "Joe4", 73, "Kriftel4", "Retiree1", 18000, "J4.jpg"),
        new People( "Joe5", 73, "Kriftel5", "Retiree2", 18000, "J5.jpg"),
        new People( "Joe6", 73, "Kriftel6", "Retiree3", 18000, "J6.jpg") }
    };
}

```

And the output of ViewSerObject for Ser_Object

```

C:\JoeApp\ODB\examples\Test>java ViewSerObject examples\serobj\obj_ser_obj.txt
Class Name: Ser_Obj
SerID: 1
Number of Fields: 15
Field: b6, type: byte, value/Reference: 69
Field: boo, type: boolean, value/Reference: true
Field: c5, type: char, value/Reference: J
Field: d2, type: double, value/Reference: 2.0
Field: f3, type: float, value/Reference: 3.0
Field: i1, type: int, value/Reference: 1
Field: l9, type: long, value/Reference: 9
Field: s4, type: short, value/Reference: 4
Field: D8, type: double[2], value/Reference: [D@48eff760
    double[0]: 7,00
    double[1]: 8,00
Field: I7, type: int[2], value/Reference: [I@548b7f67
    int[0]: 5
    int[1]: 6
Field: T7, type: String, value/Reference: XinChao
Field: TT, type: String[2], value/Reference: [Ljava.lang.String;@7ac7a4e4
    String[0]: hello
    String[1]: world
Field: bb, type: byte[3], value/Reference: [B@6d78f375
    byte[0]: j (x6A)
    byte[1]: o (x6F)
    byte[2]: e (x65)
Embedded Class Name: People
SerID: 1234
Number of Fields: 6
Field: age, type: int, value/Reference: 73
Field: income, type: double, value/Reference: 18000.0
Field: address, type: String, value/Reference: Kriftel
Field: name, type: String, value/Reference: Joe
Field: profession, type: String, value/Reference: Retiree
Field: url, type: String, value/Reference: J.jpg
Field: pep, type: People[2][6], value/Reference: [[Ljava.util.ArrayList;@50c87b21
Embedded pep : People[2][6]
    People[0][0]: [73, 18000.0, Kriftel1, Joe1, Retiree1, J1.jpg]
    People[0][1]: [73, 18000.0, Kriftel2, Joe2, Retiree2, J2.jpg]
    People[0][2]: [73, 18000.0, Kriftel3, Joe3, Retiree3, J3.jpg]
    People[1][0]: [73, 18000.0, Kriftel4, Joe4, Retiree1, J4.jpg]
    People[1][1]: [73, 18000.0, Kriftel5, Joe5, Retiree2, J5.jpg]
    People[1][2]: [73, 18000.0, Kriftel6, Joe6, Retiree3, J6.jpg]

```

C:\JoeApp\ODB\examples\Test>

The Ser_obj.txt:

```

~í #sr #Ser_Obj      ## #B #b6Z #booC #c5D #d2F #f3I #i1J #l9S #s4[ #D8t #[D[ #I7t
#[IL #T7t #Ljava/lang/String;[ #TTt #[Ljava/lang/String;[ #bbt #[BL #pt #LPeople;
[
    #pept
[[LPeople;xpE# J@      @@      #      #ur #[D>|E#«cZ## xp      #@#      @
ur #[IM°`&vê²¥# xp      #      #t #XinChaour #[Ljava.lang.String;ÏVcé#{G# xp      #t
#hellot #worldur #[B-ó#ø##Tà# xp      #joesr #People      #0# #I #ageD #incomeL
#addressq      ~      #L      #nameq      ~      #L
professionq ~ #L #urlq ~ #xp      I@Ñ”      t #Kriftelt #Joet #Retireet #J.jpgur
[[LPeople;aý¹0

```

Code can be downloaded from Github: click [HERE](#)