

# Sample MICS Paper Title

Mary Smith and Joe Jones

Name of Department

Name of Institution

City, State Zip

Contact email

## Abstract

Nuclear magnetic resonance (NMR) spectroscopy is a powerful method for studying the three-dimensional structure of molecules such as proteins. The post-genomic era has created the need to gather functional and structural information of unknown proteins encoded by newly discovered genes. Unfortunately, current manual techniques for analyzing NMR datasets can take days to months to assign, and are prone to error. The current goal of this research is to develop an algorithm to automate the process of assigning nontrivial NMR datasets, in an attempt to minimize human error and accelerate a time consuming task.

NMR images yield structural information that needs to be analyzed rapidly and accurately. Accurate assignment of nontrivial NMR datasets will provide the necessary framework for continued advancement in the fields of structural biology and proteomics.

The algorithm utilizes A\* search to sequence amino acids produced from NMR datasets of proteins. The program is given a set of nodes, each corresponding to a single amino acid in the protein chain, from an input file. Each node is placed in the initial node position of the protein chain. The node that most correctly fits the reference protein chain is used to generate child nodes. Unplaced nodes are sequentially added to the end of a list to create child node lists. The node list with the smallest error is then expanded further. The error is a running total of how well the nodes fit the reference protein chain, coupled with the accuracy of the match of the placed child. This process of assigning the child nodes and calculating costs repeats until every node is placed and the best node list contains the lowest cost of all generated lists.

Assignments of test sets have shown this method can be used to assign NMR datasets, but there remains need for improvement. Research is ongoing as we continue to refine our algorithm. Future goals include adjusting for potentially missing data, sorting nodes into amino acid groups, and testing with larger datasets. Upon completion, this algorithm will allow for great advancements in the areas of structural biology and proteomics.

example cite[1]

# 1 Method

## 1.1 Algorithm

Our algorithm begins by reading in and expected amino acid order and the NMR carbon shift data from a data file. It then changes the amino acids to there expected  $C_\alpha$  and  $C_\beta$  values and stores them in an list that represents the protein chain. Next, the carbon shift values for a single amino acid is placed in a tile. A tile contains the  $C_\alpha$  and  $C_\beta$  values for the amino acid residue  $i$  and residue  $i - 1$ . Next, missing data is accounted for. If there are less tiles than the number of amino acids in the protein chain, place holder tiles are generated to make up the difference. Before the search for the best solution begins, the tiles are grouped by the type of amino acids they could represent to accelerate the assignment process. Tiles that do not match a group are grouped with the place holder tiles

To start the search, tiles in the place holder group and tiles in the same amino acid group as the first amino acid in the protein chain are placed in the first position in a node. The tile is then compared to the first amino acid in the protein chain, and a cost is generated. All of the generated nodes are place in a frontier array.

The node in the frontier with the lowest cost is removed from the frontier and used to generate child nodes. To generate a child node, a tile is added to the end of the node. A child node is generated for all unplaced tiles that are either in the place holder group or in the group matching the corresponding amino acid in the protein chain. A cost of placing the tile is then generated. The cost is a sum of the cost of placing the previous tiles in the node, how well the current tile matched the corresponding amino acid in the protein chain and how well the tile's residue  $i - 1$  values match the residue  $i$  values of the tile placed before it. The child nodes are then added to the frontier, and the process of generating child nodes is repeated.

Once a node has every tile placed, it is said to be in the goal state. The first node that reaches goal state is stored as the current best solution. Every node that hits goal state is compared to the current best solution. The node with the lower cost is saved as the current best solution.

A solution has been found once the current best solution's cost is lower than the cost of any nodes in the frontier. The search is then ended. The algorithm then outputs the cost of the best solution followed by the assigned carbon shift values.

## References

- [1] Babak Alipanahi, Xin Gao, Emre Karakoc, Frank Balbach, Shuai Cheng Li, Guangyu Feng, Logan Donaldson and Ming Li, “IPASS: error tolerant NMR backbone resonance assignment by linear programming,” technical report, 2009.