

# AUTOMATED REVIEW RATING SYSTEM

## 1. Project Overview

The Automated Review Rating System is natural language processing (NLP) project aimed at predicting the rating of a review based on its textual content. This project automates the process by cleaning and preprocessing text data, extracting meaningful features and preparing the dataset for machine learning models that can learn the relation between review text and its associated rating.

## 2. Environment Setup

- Programming Language used : Python 3.12.1
- Libraries Used:
  - Pandas & Numpy → for data manipulation
  - Seaborn & Matplotlib → for data visualization
  - Nltk & BeautifulSoup → for text normalization
  - Emoji → for filtering out emojis
  - Scikit-Learn → for sampling, train-test and Vectorization
- IDE/Notebooks : Jupyter Notebook

## 3. GitHub Project Setup

Created a GitHub repository for the project: **automated-review-rating-system**

Structure of directory:

- App: Contains the **application logic** (e.g. Django backend code) that serves your trained model.
- Data: Stores the **raw or preprocessed datasets** used for training, validation, and testing.
- Frontend: Contains the **UI code**.
- Models: Holds the **trained machine learning/NLP models**.
- Notebooks: Contains **Jupyter notebooks** used for exploration, preprocessing, visualization, and model experimentation.

- Readme: The **documentation entry point** of the project.
- Requirements: A text file listing all the **Dependencies**.




Figure 1: GitHub Repository Structure

## 4. Data Collection

- Data is collected from Kaggle Datasets
- Dataset Link:
  - [https://github.com/JoelKBenny/automated-review-rating-system/blob/main/data/Kaggle%20Datasets/Disneyland Reviews.csv](https://github.com/JoelKBenny/automated-review-rating-system/blob/main/data/Kaggle%20Datasets/Disneyland%20Reviews.csv)
- Dataset Contains 42656 samples along with 6 attributes:
  - Review\_ID : Numerical Identification number.
  - Rating : 1 to 5, 1 being lowest and 5 being highest.
  - Year\_Month : Year and month which review is posted.
  - Reviewer\_Location : Location of the reviewer.
  - Review\_Text : Textual content of the review.
  - Branch : Disneyland branch (location).
- The count of sample of each rating:
  - **1 star** : 1,499
  - **2 star** : 2,127
  - **3 star** : 5,109

- **4 star** : 10,775
- **5 star** : 23,146

## 5. Data Preprocessing

Preprocessing is the stage in machine learning where raw data is cleaned and transformed into a structured, usable format. It involves steps like removing noise, handling missing values, reducing irrelevant information from the data.

Preprocessing ensures the data fed into machine learning models is consistent, meaningful and free from errors. This improves model accuracy, reduces bias, and speeds up training by removing unnecessary complexity.

### 5.1. Removing Duplicates

The exact same reviews and rating were removed to avoid redundancy and ensure that each sample contributes unique information to the model.

**Code:**

```
df.duplicated().sum()

df = df.drop_duplicates(subset=['Review_Text', 'Rating'])
```

### 5.2. Removing Conflicting Reviews

The same review text appeared with different ratings, were removed to maintain consistency between the content and its assigned rating. Such conflicts can confuse the model during training and reduce its ability to learn meaningful patterns.

**Code:**

```
#filtering the review that have more than 1 unique review

conflicts = df.groupby('Review_Text')['Rating'].nunique()
```

```
conflicting_reviews = conflicts[conflicts > 1].index

print("Number of reviews with conflicting ratings:",
      len(conflicting_reviews))

df = df[~df['Review_Text'].isin(conflicting_reviews)]
```

### 5.3. Handling Missing Values

No missing values found in the data when checked.

#### Code:

```
df.isnull().sum()

Review_ID          0
Rating             0
Year_Month         0
Reviewer_Location  0
Review_Text        0
Branch             0
```

### 5.4. Removing Unnecessary Columns

Irrelevant columns like Review\_ID, Reviewer\_Location, Branch, Year\_Month were dropped because these attributes does not contribute to the model.

#### Code:

```
df = df.drop(['Year_Month', 'Review_ID', 'Branch',
              'Reviewer_Location'], axis=1)
```

### 5.5. Lowercasing Text

All review text was converted to lowercase to ensure uniformity and prevent the model from treating words like 'Disney' and 'disney' as different tokens.

#### Code:

```
text = text.lower()
```

## 5.6. Removing HTML Tags, URL's & Emojis

HTML tags, URLs, and emojis were removed from the reviews to eliminate irrelevant elements that do not contribute to the semantic meaning of the text.

### Code:

```
#html tags
text = BeautifulSoup(text, "html.parser").get_text()

#URL
text = re.sub(r"http\S+|www\S+|https\S+", "", text)

#Emoji
text = text.encode("ascii", "ignore").decode("ascii")
```

## 5.7. Removing Punctuations and Special Characters

Punctuation and special characters were removed to reduce noise and focus the analysis on meaningful textual content.

### Code:

```
text = text.translate(str.maketrans("", "",
string.punctuation))
```

## 5.8. Tokenizing the Reviews

Tokenization was applied to split each review into individual words or tokens, allowing the model to analyse and process the text at the word level.

### Code:

```
tokens = text.split()
```

## 5.9. Removing Stopwords

Stopwords (common words like 'the', 'is', 'and') were removed to reduce noise and focus the analysis on words that carry

meaningful information. NLTK library is used to filter the stopwords; there were total 179 stopwords in NLTK.

A total of 151 unique stopwords found and removed from the whole reviews.

```
{'it', 'hadn', 'o', 'the', 'only', 'being', 'this', 'for', 'weren', 'now', 'over', 'would', 'n', 'to', 'before', 're', 'how', 'down', 'aren', 'themselves', 'each', 'i', 'they', 'him', 's', 'out', 'its', 'in', 'through', 'that', 'such', 'into', 'at', 'off', 'your', 'them', 'ot', 'her', 'more', 'those', 've', 'own', 'm', 'ourselves', 'not', 'until', 'will', 'his', 'can', 'ain', 'you', 'when', 'here', 'few', 'shan', 'has', 'so', 'be', 'my', 'below', 'all', 'havin', 'g', 'am', 'll', 'again', 'these', 'of', 'doing', 'were', 'isn', 'why', 'same', 'during', 'ju', 'st', 'further', 'what', 'haven', 'most', 'are', 'where', 'me', 'won', 'don', 'shouldn', 'him', 'self', 'myself', 'hers', 'by', 'hasn', 'yourself', 'and', 'who', 'had', 'their', 'her', 'doe', 's', 'any', 'theirs', 'an', 'from', 'our', 'between', 'there', 'because', 'very', 'once', 'sh', 'e', 'as', 'do', 'was', 'which', 'should', 'after', 'both', 'been', 'up', 'needn', 'herself', 'or', 'is', 'did', 'above', 'some', 'y', 'then', 'he', 'nor', 'while', 'doesn', 'didn', 'und', 'er', 'have', 'on', 'too', 'couldn', 'd', 'against', 'yours', 'ma', 'we', 'itself', 'than', 'whom', 'about', 'but', 'a', 'wasn', 'if', 'ours', 't', 'with', 'no', 'yourselves'}
```

*Figure 2: Stopwords*

### **Code:**

```
stop_words = set(stopwords.words('english'))

tokens = [word for word in tokens if word not in stop_words]
```

## **5.10. Lemmatization**

Lemmatization is the process of reducing words to their base or dictionary form, called a lemma. For example, 'better' is reduced to 'good', and 'studying' is reduced to 'study'. This helps the model treat different forms of the same word as one, improving consistency and reducing the feature space.

### **Why Lemmatization was preferred than Stemming?**

Stemming is a crude method that chops off word endings to reduce words to their root form, which can sometimes create non-words (e.g., 'studying' → 'studi', 'happier' → 'happi'). Lemmatization, on the other hand, reduces words to their proper dictionary form (lemma) while preserving meaning (e.g., 'studying' → 'study', 'happier' → 'happy'), making it more suitable for text analysis and sentiment modelling.

**Code:**

```
tokens = [lemmatizer.lemmatize(word) for word in tokens]
```

### 5.11. Filtering Reviews Using Word Count

Reviews with fewer than 3 words or more than 100 words were removed to eliminate overly short or excessively long texts that could introduce outliers and reduce model effectiveness.

```
count      42617.000000
mean        66.162658
std         74.995422
min          3.000000
25%         23.000000
50%         42.000000
75%         80.000000
max        970.000000
Name: word_count, dtype: float64
```

*Figure 3: Word Count Statistics*

Most of the reviews falls under of 100 words. So filtering thresholds are set to: 3 for minimum threshold and 100 for maximum threshold, Other reviews are considered as Outliers and were removed.

**Code:**

```
if len(tokens) < 3 or len(tokens) > 100:
    return None
```

## 6. Data Visualization

### Box Plot

A boxplot is a graphical representation of the distribution of a dataset that shows the median, quartiles, and potential outliers. In this project, it is used to visualize the distribution of review word counts across different ratings, highlighting unusually short or long reviews.




Figure 4: Boxplot of word count

## Histogram

A histogram is a graphical representation of the distribution of numerical data using bars to show the frequency of data points within specified intervals (bins). In this project, a histogram is used to visualize the distribution of review word counts across different ratings, allowing us to see how review lengths vary by rating.





Figure 5: Histogram for word count



## Bar Chart

A bar chart is a graphical representation of categorical data using rectangular bars to show the frequency or count of each category. In this project, bar chart is used to visualize the distribution of review ratings, showing how many reviews fall into each rating from 1 to 5.



*Figure 7: Bar Chart for Rating*

## Sample of 1 star Rating:

5 sample reviews of 1 star rating:

1. partner recently stayed teacher school trip spoke highly service attraction whilst stay bought mikey minnie photo frame gift bring home though got home discovered shocking quality product material peeling back stand paint work look like done toddler crayon general quality product disgraceful would advise future review quality product sale resort shop avoid disappointment shabby photo frame ruined supposed romantic gesture well done disney

2. visiting disneyland world around globe feel qualified write review particular one it definitely worst longest line ever seen ride open many staff member around lot people problem using fastpass machine one sight help happened one occasion definitely agree another review saw visitor park bad queue etiquette pushing back pushing standing way close argh yes smoking disneyland tokyo far best disneyland go one make one if come paris dont waste day 6 hour park got 1 ride theatre show stand line louvre eiffel tower much better reward

3. ridiculous wait 30 minute queue ride 1 minute would prefer come tivoli much better nicer place recommended people enjoying waiting utku

4. price found park ride disappointing travelled feb 12 half term queue long several ride closed due technical fault buzz light year small world etc food within park astronomically priced 3 euro tiny bag chip

5. whole place feel like homage 1990s parade basic ride broke frequently already shut refurb waited 35 minute allegedly fastpass queue allowing people regardless tiring join big thunder mountain big ride day open disney studio better tiny ride dont fast pass waited 2 hour watch ride break front u restaurant either shut full fried food mickey cafe basic food booking queued 30 minute valentine waitress rude forgot thing mixed order completely hotel santa fe basic queue breakfast one pay attention time slot best thing planet hollywood thats saying something whole place need investment magic putting back

## Sample of 2 star Rating:

5 sample reviews of 2 star rating:

1. park small great ride closed limited number ride biggest thing missing park friendly staff missing expected disney smile courtesy ride operator folk restaurant recommended big fan happiest place earth way functioning u disney park take literally

2. disney happy ever afters smile magic laughternot disneyland parisstaff ignorant rude havent clue smile visited park two day queue would expect long fast pas joke queue fast pas ticket queue ride didnt bother end queued anyway food ok bit expensive rest paris areano character walking round parade good short missing something disney magic like visited disney florida dont go paris comparison disappointed

3. disneyland favorite vacation way busy october friend trip said busier summer visit lot ride closed temporary repair waited line 1 hr frustrating

4. cafe orleans nice lobster salad gone choice getting worselets review dining death actually good disney like spend money good foodlobster saladcafe orleansfrito misto alfresco terracecinnomon rollsdisneyland bakerycinnomon roll french toastcarnation cafemahi mahi fish tacostangaroo terrace cheap small shrimp tacosnice breakfastriver belle terrace expensive mediocre restarauntshort rib sandwich carthay circlechili fry sour creamsmokejumpers grillblt flatbreadhowred rose tavernefried green tomatoeshungry bear get 5x price bbim sick disneyland taking away good thing replacing obviously cheaper dining option want u spend dollar park improve dining

5. large party 8x adult 6x child travelled disneyland paris 26th december 2015 spent two day theme park purchased ticket ahead time uk cost 95 per person is more

## Sample of 3 star Rating:

5 sample reviews of 3 star rating:

1. 4 lovely day park october seems great time go quite quiet line werent long especially week big complaint staff never seen many bored disinterested staff meant happiest place earth smile eh daughter didnt care notice annoyed u alot perhaps disney start customer service training quick
2. sure disney label totally lack florida magic more like amusement park possibly expensive outlet ever experienced 1 plain hotdog 1 cheese hotdog 1 chicken nugget 2 large fry 1 white coffee 1 sprite 25
3. gate price seem keep going cant really afford go every couple year park always crowded line take forever even charge fast pass lane thought used free anyway still happiest place earth except raining pay 20 poncho really come
4. disney expected crowded overpriced use fastpass whenever possible dont eat park food awful overpriced found tortilla joes taqueria downtown disney huge burrito shared two people kid loved place and better cheaper eating park
5. ride old tired couldnt believe theyre still showing michael jackson captain eo unfortunately get away long kid still want go disney place earth disappointing child 9 charged adult fare

### **Sample of 4 star Rating:**

#### 5 sample reviews of 4 star rating:

1. always good time disneyland even hiccup year 25 hour wait ride hot sun shaded queue perhaps consider water ice cream stand line super popular ride california adventure side wasnt happy ride closure breakdown though
2. ive disney hongkong californiathey fantastic beautiful scenery show still kind similar disney world except one orlando orlando biggest one world
3. husband medical emergency first day park staff fantastic u ambulance time unfortunately cut stay short didnt get experience park
4. didnt stay resort went day 4 day honeymoon paris paris visit travel pas get 20 entrance fee 1 day 2 park pas cost u 50 euro get went pretty much ride excluding little kid stuff space mountain best went 3 time tower terror also good buzz lightyear good fun even 28 year old avoided eating taking baguette u glad menu park looked expensive half good little parisian restaurant train centre paris take 40 min literally take front door have disney florida couple time far better still good fun
5. enjoyed experience disneyland hong kong found catered 5 year old teenager seems suited younger child rather eurodisney found better older kid adult definitely worth checking day spare havent disneyland firework park close lovely packed id suggest want buy thing store earlier day crowded crazy end

## Sample of 5 star Rating:

5 sample reviews of 5 star rating:

1. great ever really enjoyable age sure extra magic hour worthwhile nothing much open early still great day two three
2. lucky enough come los angeles family holiday disneyland focus dad keen queueing crowd noise imagine excited rest family disneyland awesome great time year cast member call ghost town kiwi found food good price used high priced food back home crowd fine really buy fast past far best money spent cast member staff standing place spotless watched rubbish would ground matter minute pick went four day two disneyland two disney adventure great felt saw offer age kids 110 8 if come hope much fun did cheers kiwi los angeles
3. long line expensive kid love place along adult act like kid fun whole family
4. still nice classic park third visit although first 9 year materhorn updated better set special effect inside space mountain smoothest way best side side seating indiana jones ride unique closest thing disney dinosaur animal kingdom florida one best thing electric light parade brought back year classic original form found fun nostalgic even 19 year old son thought great doesn't really connection wife aladdin's oasis lunch tie gave u priority viewing near small world thought worth
5. one spend 2 3 day see all the best avoid kid holiday day weekend holiday possible i found sign direction park poor even holding map ask directions there enough personal walk around assist people the line long express line help enough in overall great intertainment

## 7. Resampling the Dataset

Resampling is a technique in machine learning used to adjust the distribution of classes in a dataset by either increasing the number of samples in minority classes (upsampling) or reducing the number of samples in majority classes (downsampling).

Resampling is important when working with imbalanced datasets because models trained on heavily skewed data tend to be biased toward majority classes. By balancing class representation,

resampling ensures that the model learns equally well from all classes, improving fairness and predictive performance.

In this project, the dataset was imbalanced, with some ratings (like 1 and 2 stars) having far fewer reviews compared to higher ratings (like 4 and 5 stars). To address this, ratings with fewer than 2,000 samples were upsampled to 2,000 using random resampling with replacement, while ratings with more than 2,000 samples were kept as they were. This ensured that every rating had sufficient representation (at least 2,000 reviews) for meaningful training, while still preserving the natural imbalance in higher rating classes.

Data after resampling:

Rating	Samples
1	2000
2	2000
3	3873
4	8673
5	20045

## **8. Train-Test Split**

Train-test splitting is the process of dividing a dataset into two subsets: one for training the model and one for evaluating its performance, ensuring that the model is tested on unseen data.

In this project, the balanced Disneyland review dataset was split into training and test sets using an 80:20 ratio. Stratified splitting was applied to maintain class balance in both sets, so each rating (1–5) is proportionally represented in the training and test subsets.

### **Why Stratified Splitting is used?**

Stratified splitting was used to ensure that each rating class is proportionally represented in both the training and test sets, preventing the model from being biased toward majority classes and ensuring fair evaluation.

## Code:

```
from sklearn.model_selection import train_test_split
x = balanced_df['cleaned_review']
y = balanced_df['Rating']

x_train, x_test, y_train, y_test = train_test_split(x,
y, test_size=0.2, stratify=y, random_state=42)
```

## Working

- The dataset is divided into **training (80%)** and **test (20%)** sets.
- stratify=y ensures each rating (1-5) is proportionally represented in both sets.
- random\_state=42 makes the split **deterministic**, so running the code again produces the same split.
- x\_train and y\_train are used to **train the model**, while x\_test and y\_test are used to **evaluate model performance** on unseen data.

## 9. Text Vectorization

Text vectorization is the process of converting textual data into numerical representations so that machine learning models can process and analyse the text.

### TF-IDF (Term Frequency – Inverse Document Frequency)

**TF-IDF** is a vectorization technique that assigns weights to words based on how important they are in a document relative to the entire corpus, giving higher importance to words that are frequent in a document but rare across other documents.

#### Formula for TF-IDF

$$TF(t, d) = \frac{\text{number of times } t \text{ appears in } d}{\text{total number of terms in } d}$$

$$IDF(t) = \log \frac{N}{1 + df}$$

$$TF - IDF(t, d) = TF(t, d) * IDF(t)$$

*Figure 6: TF-IDF Formula*

### **Code:**

```
from sklearn.feature_extraction.text import TfidfVectorizer

vectorizer = TfidfVectorizer(max_features=5000)

# fitting on training data
x_train_vec = vectorizer.fit_transform(x_train_clean)

# Transforming the test data
x_test_vec = vectorizer.transform(x_test_clean)
```