

Digital Twins for Predictive Maintenance in Automotive Aftersales

Oliver Feng
Wirtschaftsinformatik
DHBW Stuttgart
Stuttgart, Germany
wi23030@lehre.dhbw-stuttgart.de

Maksim Bogachenkov
Wirtschaftsinformatik
DHBW Stuttgart
Stuttgart, Germany
wi23024@lehre.dhbw-stuttgart.de

Joel Yeraí Martínez Campo
Wirtschaftsinformatik
DHBW Stuttgart
Stuttgart, Germany
wi23194@lehre.dhbw-stuttgart.de

Abstract—TODO: Abstract here.

Index Terms—Digital Twin, Predictive Maintenance, Industry 4.0, Machine Learning, IoT, Condition Monitoring

I. INTRODUCTION

Today's vehicles are connected by default and continuously transmit operating data [1], [2], so the information needed to judge their technical condition largely exists. Yet aftersales remains reactive: even well-connected vehicles are serviced on fixed time or mileage intervals rather than on the actual condition of their components. Wear parts—brake pads and discs, tyres, ignition parts, or wipers—are replaced only once a fault becomes visible, so customers run them to failure and the unplanned repair often goes to a cheaper third-party garage. For the dealership, which owns the customer relationship, this means losing both the repair and one of only a few yearly customer contacts—each also a chance to advise, retain, and sell [3], [4].

Digital-twin-based predictive maintenance (PdM) can turn this data into foresight. A digital twin maintains a synchronised virtual representation of the vehicle [5], against which machine-learning models forecast the remaining useful life of components and recommend replacement before failure—keeping the customer at the dealership and enabling transparent, targeted upselling. While the building blocks of DT-based PdM are well studied in industrial and aerospace settings [6], [7], their integration into automotive aftersales remains underexplored.

This paper therefore asks: *what effect does the proactive use of digital twins and predictive maintenance have on the automotive aftersales domain?* Focusing on the German market and working with explicitly stated assumptions, we (i) clarify the interplay of DT and PdM in aftersales, (ii) compare the predictive target state (*Soll*) with the interval-based current state (*Ist*) to reveal its potentials, and (iii) derive recommendations for the dealership. The paper is structured along the IEEE format: theoretical background, methodology, reference architecture, illustrative case study, discussion, and conclusion.

II. RELATED WORKS & THEORETICAL BACKGROUND

A. Digital Twins

The concept of the digital twin was first introduced by Grieves [5] in a white paper on manufacturing excellence, where it described a virtual replica of a physical product maintained in synchrony with its real-world counterpart throughout the entire asset lifecycle. Originally conceived as a tool for improving production quality in industrial manufacturing, the idea drew on advances in simulation, sensor technology, and computational modelling to propose that a persistent virtual representation of a physical object could serve as the basis for monitoring, analysis, and decision-making. Over the subsequent decade, the concept migrated from its manufacturing origins into aerospace, energy, and infrastructure domains, before emerging as a foundational concept in Industry 4.0 discourse more broadly [6], [20].

In the automotive domain, this general architecture maps directly onto the connected vehicle. The physical entity is the vehicle itself, equipped with an array of on-board sensors and an OBD interface; the virtual representation is a cloud-hosted model that mirrors component states, degradation histories, and operating conditions; and the synchronising link is the OTA telematics connection that transmits telemetry in near real time [1], [2]. Lopes et al. [1] situate this configuration within a broader software ecosystem in which the digital twin acts as the authoritative source of vehicle state for all downstream services. Architecturally, automotive digital twins are typically realised as modular, microservice-based platforms: a data ingestion layer normalises heterogeneous sensor streams—such as vibration, temperature, voltage, and CAN-bus signals—before forwarding them to a model layer that maintains the current state of each monitored component [8], [10]. The outputs of this stack are then exposed to external consumers such as workshop management systems, OEM backends, and customer-facing notification services [1], [7], forming the basis for different predictive maintenance strategies.

B. Vehicle Maintenance Strategies

Vehicle maintenance strategies form a maturity hierarchy: reactive maintenance repairs only after failure [7]; preventive maintenance schedules service at fixed mileage or time intervals, leading to either premature replacement or undetected

wear [7], [8]; condition-based maintenance (CBM) couples the service decision to sensor thresholds [8]; and predictive maintenance (PdM) extends CBM by forecasting the future evolution of degradation, estimating the remaining time or distance until end-of-life is reached [7], [9].

PdM relies on three data layers: on-board sensors delivering high-frequency signals such as vibration, current, voltage, and cell temperature [8]–[10]; the On-Board Diagnostic (OBD) interface providing standardized diagnostic codes [2], [11]; and over-the-air (OTA) telematics enabling continuous low-latency exchange with the backend [1], [2], [10]. Together, these layers transform the vehicle from a periodically inspected asset into a continuously observed system, a shift first documented by Zhang et al. [11] in their work on Connected Vehicle Diagnostics and Prognostics at General Motors.

PdM at this scale is not a stand-alone technique but a service layer built on a digital twin (DT) of the vehicle. As Lopes et al. [1] and Hadraoui et al. [8] describe, the DT supplies the synchronized virtual representation against which sensor streams are interpreted, anomalies detected, and remaining-useful-life estimates computed. Without a DT, telemetry must be processed in isolation; without PdM, the DT remains a passive monitor. In current automotive DT architectures, predictive analytics is therefore typically positioned as a dedicated microservice within the DT's analytics core [1], [7], [10].

C. Machine Learning in PdM

Three problem classes structure ML-based PdM. Classification assigns sensor patterns to discrete fault categories using Support Vector Machines, Random Forests, or Convolutional Neural Networks on time-frequency representations of vibration signals [7], [9]. Regression targets Remaining Useful Life (RUL) estimation, dominated by Long Short-Term Memory (LSTM) networks for their ability to model long-range temporal dependencies in degradation signals [7], [10]. Anomaly detection operates without explicit labels, learning nominal behavior and flagging deviations as failure precursors [7], [10]. AbouGrad et al. report classification accuracies of approximately 89% for vibration-based fault detection and 92% for LSTM-based RUL estimation in automotive contexts, though they emphasize that these figures depend strongly on dataset quality and operating conditions.

A recurring constraint is data: AbouGrad et al. and Hadraoui et al. note that preprocessing consumes 70–90% of project time, genuine failure data is structurally scarce, and public benchmarks representative of in-service behavior are largely absent. Model-based and hybrid approaches that embed physical degradation laws into the learning pipeline are therefore preferred over purely data-driven ones, as they extrapolate more reliably under data scarcity [6], [8], [9]. Beyond accuracy, deployment in safety-relevant contexts raises the question of explainability: deep architectures achieve high accuracy but operate as opaque models whose decisions cannot readily be justified to engineers, customers, or regulators [7]. Explainable AI (XAI) techniques such as feature attribution and attention-based saliency are increasingly integrated into PdM pipelines

to expose the reasoning behind a prediction, marking the conceptual bridge from smart to wise information systems [7].

D. Automotive Aftersales

After-sales encompasses post-purchase activities that help customers access supplier services and resolve product issues through continuous maintenance and upkeep [12]. As a quality-focused product support activity, it creates a sustainable competitive advantage [13]. The growing importance of after-sales services as a source of sustained competitive advantage extends across industries, with automotive being a prime example [14]. In the automotive context, it functions as a dedicated business module bundling maintenance, repair, and warranty offerings to maximise product use throughout the asset lifecycle while meeting financial and customer-performance targets [4] [15]. Building post-sales relationships strengthens customer loyalty, yields actionable insights, and creates upselling and cross-selling opportunities [16], making the automotive aftersales market increasingly attractive as demand for higher-quality service expands [4]. After-sales services are critical for dealerships to build long-term customer relationships amid increasing mobility and competition [17]. The automotive industry must prioritize customer relationship development to achieve long-term financial growth [18].

Historically, customers of maintenance-free vehicles lose interest once the warranty expires. Within the automotive industry, after-sales services represent a particularly significant source of revenue, with profit margins considerably exceeding those generated through vehicle sales itself [19]. From an economic standpoint, the after-sales service market has been identified as substantially larger than the primary product sales market across various industries [20]–[22]. To retain these customers, better information systems and service processes are essential [12]. The growing proactive recognition that anticipating issues before they arise improves performance, efficiency, and long-term operational excellence [23].

Proactive aftersales improves customer satisfaction and retention by resolving issues before customers encounter them, enabling more productive interactions and innovation. [3]. This requires tailoring services to customer needs through tight integration of operational and informational data [12]. ML and DT-based approaches enable predictive interventions and better asset lifecycle optimisation, delivering cost reduction, improved customer satisfaction, and extended asset lifetimes. [24].

While the referenced contributions establish the technical foundations of DT-based PdM, existing work concentrates either on algorithmic aspects in isolation [7], [9] or on industrial applications [6]. The integration of DT-based PdM into automotive aftersales business models, particularly regarding its implications for customer interaction, remains underexplored. The present work addresses this gap.

III. METHODOLOGY

This paper aims to analyse recent academic studies on applying DT and PDM in the automotive industry. A SLR

was performed to achieve this objective. A central element of this method is to identify, assess and interpret current research in a structured, transparent as well as replicable way [25]. Thus, adopting the methodological approach of a SLR helps minimize bias arising from selective literature selection, while simultaneously outlining the current state of the art on DT and PDM in the automotive industry. Furthermore, it serves to pinpoint existing research gaps as well as future research needs within this respective field [26].

Subsequently, a gap analysis will be performed as a further analytical step within this paper. The central objective of this analysis is to identify and assess the differences between the current state of after sales in the automotive industry and its potential future development, with particular regard to the combined application of DT and PDM. By systematically comparing existing practices with emerging research findings and technological possibilities, the gap analysis aims to highlight areas where significant advancement is yet to be achieved. In doing so, it serves as a basis for deriving concrete implications and future research needs in this rapidly evolving field [27].

IV. GAP ANALYSIS

A. Lifecycle Comparison

B. Assumption Framework

C. Illustrative Calculation & Results

D. Limitations

V. DISCUSSION AND RECOMMENDATIONS

- Interpretation der Ergebnisse
- Implikationen fuer Forschung und Praxis

VI. CONCLUSION & FUTURE WORK

- Zusammenfassung der wichtigsten Erkenntnisse
- Beitrag der Arbeit
- Ausblick auf weitere Forschung

ACKNOWLEDGMENT

The authors would like to thank Eduard Dobenko (Mercedes-Benz) for supervising this work.

REFERENCES

- [1] J. Lopes, A. Reis, L. Barbosa, and J. Barroso, "A vehicle digital twin in the context of a software ecosystem," in *2025 IEEE Vehicle Power and Propulsion Conference (VPPC)*, 2025, pp. 1–6.
- [2] R. Coppola and M. Morisio, "Connected car: Technologies, issues, future trends," *ACM Comput. Surv.*, vol. 49, no. 3, Oct. 2016. [Online]. Available: <https://doi.org/10.1145/2971482>
- [3] G. Challagalla, R. Venkatesh, and A. K. Kohli, "Proactive postsales service: When and why does it pay off?" *Journal of Marketing*, vol. 73, no. 2, pp. 70–87, 2009. [Online]. Available: <https://doi.org/10.1509/jmkg.73.2.70>
- [4] O. Sabbagha, M. N. A. Rahman, W. R. Ismail, and W. M. H. W. Hussain, "Impact of quality management systems and after-sales key performance indicators on automotive industry: A literature review," *Procedia - Social and Behavioral Sciences*, vol. 224, pp. 68–75, 2016. [Online]. Available: <https://linkinghub.elsevier.com/retrieve/pii/S1877042816304852>
- [5] M. Grieves, "Digital twin: Manufacturing excellence through virtual factory replication," *White Paper*, 2014.
- [6] C. Wang, I.-S. Fan, and S. King, "A review of digital twin for vehicle predictive maintenance system," in *Proceedings of the SAE AeroTech Conference*, 2023, sAE Technical Paper 2023-01-1024.
- [7] H. AbouGrad, V. Batthula, and F. Riaz, "Xai digital twin predictive maintenance in the automotive industry: Challenges and opportunities," in *Proceedings of the 2026 IEEE 5th International Maghreb Meeting of the Conference on Sciences and Techniques of Automatic Control and Computer Engineering (MI-STA)*, Sebha, Libya, 2026.
- [8] H. E. Hadraoui, N. Ouahabi, N. E. Bazi, O. Laayati, M. Zegrari, and A. Chebak, "Toward an intelligent diagnosis and prognostic health management system for autonomous electric vehicle powertrains: A novel distributed intelligent digital twin-based architecture," *IEEE Access*, vol. 12, pp. 110 729–110 761, 2024.
- [9] Vinay Kumar R, Pavan Kumar K. K., D. Ramasamy, M. M. Noor, W. S. W. Harun, L. Samyilingam, N. Aslfattahi, M. S. Kiai, and C. K. Kok, "Digital twin framework for predictive maintenance of autonomous vehicle suspension system," in *2025 IEEE 4th International Conference on Smart Technologies for Power, Energy and Control (STPEC)*, 2025, pp. 1–6.
- [10] Karthick G, S. Devakatte, U. Kumar, D. Muthukumar, J. M. A. Sebastian, and J. P. Wagh, "Simulating the future: Ai-powered digital twins for intelligent emobility and software-defined vehicles," in *2025 IEEE International Transportation Electrification Conference (ITEC-India)*, 2025, pp. 1–4.
- [11] Y. Zhang, G. W. Gantt, M. J. Rychlinski, R. M. Edwards, J. J. Correia, and C. E. Wolf, "Connected vehicle diagnostics and prognostics, concept, and initial practice," *IEEE Transactions on Reliability*, vol. 58, no. 2, pp. 286–294, 2009.
- [12] S. Verstrepen, D. Deschoolmeester, and R. J. Berg, "Servitization in the automotive sector: creating value and competitive advantage through service after sales," in *Global Production Management*, K. Mertins, O. Krause, and B. Schalllock, Eds. Boston, MA: Springer US, 1999, pp. 538–545. [Online]. Available: http://link.springer.com/10.1007/978-0-387-35569-6_66
- [13] M. W. M. Aljabar and S. Hasibuan, "Performance evaluation of after-sales service partners in the power tools industry," vol. 5, no. 2, pp. 105–114. [Online]. Available: <https://e-jurnal.lppmunsera.org/index.php/JSMI/article/view/3985>
- [14] A. G. González, "Service quality and repurchase behaviour in the spanish automotive after sales business," vol. 14, no. 3, pp. 239–267. [Online]. Available: <http://www.tandfonline.com/doi/full/10.1080/15332667.2015.1069456>
- [15] J. R. Balinado, Y. T. Prasetyo, M. N. Young, S. F. Persada, B. A. Miraja, and A. A. N. Perwira Redi, "The effect of service quality on customer satisfaction in an automotive after-sales service," vol. 7, no. 2, p. 116. [Online]. Available: <https://linkinghub.elsevier.com/retrieve/pii/S219985312200885X>
- [16] L. D. Peters, "IT enabled marketing: A framework for value creation in customer relationships," *Journal of Marketing Practice: Applied Marketing Science*, vol. 3, no. 4, pp. 213–229, 1997.
- [17] M. Borchardt, M. Souza, G. M. Pereira, and C. V. Viegas, "Achieving better revenue and customers' satisfaction with after-sales services: How do the best branded car dealerships get it?" vol. 35, no. 9, pp. 1686–1708. [Online]. Available: <http://www.emerald.com/ijqrm/article/35/9/1686-1708/139109>
- [18] A. Haq, "Satisfaction towards customer loyalty in auto-mobile industry of pakistan," vol. 2, pp. 363–371.
- [19] N. Saccani, L. Songini, and P. Gaiardelli, "The role and performance measurement of after-sales in the durable consumer goods industries: an empirical study," vol. 55, no. 3, pp. 259–283. [Online]. Available: <http://www.emerald.com/ijppm/article/55/3-4/259-283/165392>
- [20] R. Bundschuh and T. Dezvane, "How to make after-sales service pay off," vol. 4, pp. 116–128.
- [21] A. Fraß, "Impact of after-sales performances of german automobile manufacturers in china in service satisfaction and loyalty," in *1st INTERNATIONAL CONFERENCE ON BUSINESS MANAGEMENT - "NEW CHALLENGES IN BUSINESS RESEARCH" - Conference proceedings*, Editorial Universitat Politècnica de València, Ed. Editorial Universitat Politècnica de València, pp. 200–206. [Online]. Available: <http://ocs.editorial.upv.es/index.php/ICBM/11CBM/paper/view/1218>
- [22] R. Wise and P. Baumgartner, "Go downstream: The new profit imperative in manufacturing," vol. 28, pp. 89–96.
- [23] M. Pophaley and R. K. Vyas, "Plant maintenance management practices in automobile industries: a retrospective and literature review," *Journal of Industrial Engineering and Management*, vol. 3, no. 3, pp. 512–541, 2010. [Online]. Available: <http://jiem.org/index.php/jiem/article/view/136>

- [24] V. González-Prida, C. P. Márquez, P. V. Gunckel, F. K. Rodríguez, and A. C. Márquez, "Digital transformation in aftersales and warranty management: A review of advanced technologies in I4.0," *Algorithms*, vol. 18, no. 4, p. 231, 2025. [Online]. Available: <https://www.mdpi.com/1999-4893/18/4/231>
- [25] A. Fink, *Conducting Research Literature Reviews: From the Internet to Paper*. SAGE Publications, google-Books-ID: 0z1_DwAAQBAJ.
- [26] D. Tranfield, D. Denyer, and P. Smart, "Towards a methodology for developing evidence-informed management knowledge by means of systematic review," vol. 14, no. 3, pp. 207–222. [Online]. Available: <https://onlinelibrary.wiley.com/doi/10.1111/1467-8551.00375>
- [27] D. F. Channon and T. Sammut-Bonnici, "Gap analysis," in *Wiley Encyclopedia of Management*, 1st ed., C. L. Cooper, Ed. Wiley, pp. 1–2. [Online]. Available: <https://onlinelibrary.wiley.com/doi/10.1002/9781118785317.weom120109>

ERKLÄRUNG ZUR NUTZUNG VON KI-TOOLS

TODO: KI-Erklärung hier einfügen (gemäß DHBW-Vorgabe).