Center for Internet Security®

CIS Benchmarks™

CIS Apple MacOS 15.0 Sequoia Intune Benchmark

v1.0.0 - 05-30-2025

Terms of Use

Please see the below link for our current terms of use:

https://www.cisecurity.org/cis-securesuite/cis-securesuite-membership-terms-of-use/

For information on referencing and/or citing CIS Benchmarks in 3rd party documentation (including using portions of Benchmark Recommendations) please contact CIS Legal (legalnotices@cisecurity.org) and request guidance on copyright usage.

NOTE: It is ***NEVER*** acceptable to host a CIS Benchmark in ***ANY*** format (PDF, etc.) on a 3rd party (non-CIS owned) site.

Internal Only - General

Table of Contents

Terms of Use *1*
Table of Contents *2*
Overview *6*
Important Usage Information 6
Key Stakeholders 6
Apply the Correct Version of a Benchmark 7
Exceptions 7
Remediation 8
Summary 8
Target Technology Details 9
Intended Audience 9
Consensus Guidance 10
Typographical Conventions 11
Recommendation Definitions *12*
Title 12
Assessment Status 12
Automated 12
Manual 12
Profile 12
Description 12
Rationale Statement 12
Impact Statement 13
Audit Procedure 13
Remediation Procedure 13
Default Value 13
References 13
CIS Critical Security Controls® (CIS Controls®) 13
Additional Information 13
Profile Definitions 14
Acknowledgements 15
Recommendations *16*
1 Benchmark Guidance 16
2 Recommendations for Supervised (Organization) Devices 17
2.1 Accounts 18
2.1.1 Accounts 19
2.1.1.1 Ensure "Disable Guest Account" is set to "True" (Manual) 20

Internal Only - General

2.2 App Store **23**
2.2.1 Ensure "Restrict Store Software Update Only" is set to "True" (Manual) 24
2.3 Full Disk Encryption **26**
2.3.1 FlleVault **27**
2.3.1.1 Ensure "User Enters Missing Info" is set to "True" (Manual) 28
2.3.1.2 Ensure "Enable" is set to "On" (Manual) 30
2.3.1.3 Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0" (Manual) 32
2.3.1.4 Ensure "Show Recovery Key" is set to "Disabled" (Manual) 35
2.3.1.5 Ensure "Force Enable In Setup Assistant" is set to "True" (Manual) 37
2.3.2 FileVault Options **39**
2.3.2.1 Ensure "Prevent FileVault From Being Disabled" is set to "True" (Manual) 40
2.3.3 Endpoint Disk Encryption **42**
2.3.3.1 Ensure There is a Disk Encryption FileVault Policy (Manual) 43
2.4 Login **46**
2.4.1 Login Window Behavior **47**
2.4.1.1 Ensure "Show Full Name" is set to "True" (Manual) 48
2.4.2 Login Window Login Items **50**
2.4.2.1 Ensure "Disable Login Items Suppression" is set to "True" (Manual) 51
2.5 Managed Settings **54**
2.5.1 MDM Options **55**
2.5.1.1 Ensure "Activation Lock Allowed While Supervised" is set appropriately (Manual) 56
2.6 Networking **58**
2.6.1 Content Caching **59**
2.6.1.1 Ensure "Auto Activation" is set to "False" (Manual) 60
2.6.2 Firewall **63**
2.6.2.1 Ensure "Enable Stealth Mode" is set to "True" (Manual) 64
2.6.2.2 Ensure "Enable Firewall" is set to "True" (Manual) 67
2.7 Profile Removal Password **70**
2.7.1 Ensure "Removal Password" is absent or is securely configured with restricted access (Manual) 71
2.8 Restrictions **73**
2.8.1 Ensure "Allow Bluetooth Sharing Modification" is set to "False" (Manual) 74
2.8.2 Ensure "Allow Password Sharing" is set to "False" (Manual) 77
2.8.3 Ensure "Allow File Sharing Modification" is set to "False" (Manual) 79
2.8.4 Ensure "Allow Erase Content And Settings" is set to "False" (Manual) 82
2.8.5 Ensure "Allow Air Play Incoming Requests" is set to "False" (Manual) 84
2.8.6 Ensure "Allow Media Sharing Modification" is set to "False" (Manual) 86
2.8.7 Ensure "Allow Cloud Photo Library" is set to "False" (Manual) 88
2.8.8 Ensure "Allow Cloud Document Sync" is set to "False" (Manual) 91
2.8.9 Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days (Manual) 93
2.8.10 Ensure "Allow Activity Continuation" is set to "False" (Manual) 96
2.8.11 Ensure "Allow Cloud Bookmarks" is set to "False" (Manual) 98
2.8.12 Ensure "Allow Cloud Freeform" is set to "False" (Manual) 100
2.8.13 Ensure "Allow Cloud Calendar" is set to "False" (Manual) 102
2.8.14 Ensure "Allow ARD Remote Management Modification" is set to "False" (Manual) 104
2.8.15 Ensure "Allow Assistant" is set to "False" (Manual) 107
2.8.16 Ensure "Allow Game Center" is set to "False" (Manual) 109
2.8.17 Ensure "Allow Auto Unlock" is set to "False" (Manual) 111
2.8.18 Ensure "Allow Startup Disk Modification" is set to "False" (Manual) 113
2.8.19 Ensure "Allow UI Configuration Profile Installation" is set to "False" (Manual) 115
2.8.20 Ensure "Allow Device Name Modification" is set to "False" (Manual) 118
2.8.21 Ensure "Allow Internet Sharing Modification" is set to "False" (Manual) 120
2.8.22 Ensure "Allow Content Caching" is set to "False" (Manual) 122
2.8.23 Ensure "Allow Find My Friends" is set to "False" (Manual) 124
2.8.24 Ensure "Allow AirDrop" is set to "False" (Manual) 126

Internal Only - General

2.8.25 Ensure "Allow Password Auto Fill" is set to "False" (Manual) 128
2.8.26 Ensure "Allow Cloud Notes" is set to "False" (Manual) 130
2.8.27 Ensure "Allow Multiplayer Gaming" is set to "False" (Manual) 132
2.8.28 Ensure "Allow Local User Creation" is set to "False" (Manual) 134
2.8.29 Ensure "Allow Apple Personalized Advertising" is set to "False" (Manual) 136
2.8.30 Ensure "Allow Printer Sharing Modification" is set to "False" (Manual) 138
2.8.31 Ensure "Allow Fingerprint For Unlock" is set appropriately (Manual) 140
2.8.32 Ensure "Allow Diagnostic Submission" is set to "False" (Manual) 143
2.8.33 Ensure "Allow Cloud Reminders" is set to "False" (Manual) 145
2.8.34 Ensure "Allow Password Proximity Requests" is set to "False" (Manual) 147
2.8.35 Ensure "Force On Device Only Dictation" is set to "True" (Manual) 149
2.8.36 Ensure "Allow iPhone Mirroring" is set to "False" (Manual) 151
2.8.37 Ensure "Allow Cloud Mail" is set to "False" (Manual) 153
2.8.38 Ensure "Allow Universal Control" is set to "False" (Manual) 155
2.8.39 Ensure "Allow Cloud Address Book" is set to "False" (Manual) 157
2.8.40 Ensure "Allow Cloud Desktop And Documents" is set to "False" (Manual) 159
2.8.41 Ensure "Allow iTunes File Sharing" is set to "False" (Manual) 161
2.8.42 Ensure "Allow Cloud Keychain Sync" is set to "False" (Manual) 163
2.9 Security 166
2.9.1 Passcode 167
2.9.1.1 Ensure "Max PIN Age In Days" is set to "365" or less (Manual) 168
2.9.1.2 Ensure "Max Grace Period" is set to "0" (Manual) 170
2.9.1.3 Ensure "Max Inactivity" is set to "8" or less (Manual) 172
2.9.1.4 Ensure "Min Complex Characters" is set to "1" or more (Manual) 174
2.9.1.5 Ensure "PIN History" is set to "15" or more (Manual) 177
2.9.1.6 Ensure "Force PIN" is set to "True" (Manual) 179
2.9.1.7 Ensure "Password Content Regex" is defined (Manual) 181
2.9.1.8 Ensure "Max Failed Attempts" is set to "5" or less (Manual) 184
2.9.1.9 Ensure "Allow Simple Passcode" is set to "False" (Manual) 186
2.9.1.10 Ensure "Minutes Until Failed Login Reset" is set to "15" or more (Manual) 189
2.9.1.11 Ensure "Require Alphanumeric Passcode" is set to "True" (Manual) 192
2.9.1.12 Ensure "Min Length" is set to "15" or more (Manual) 194
2.10 Software Update 197
2.10.1 Ensure "Automatically Install App Updates" is set to "True" (Manual) 198
2.10.2 Ensure "Automatically Install Mac OS Updates" is set to "True" (Manual) 200
2.10.3 Ensure "Automatic Check Enabled" is set to "True" (Manual) 202
2.10.4 Ensure "Critical Update Install" is set to "True" (Manual) 204
2.10.5 Ensure "Automatic Download" is set to "True" (Manual) 206
2.11 System Configuration 209
2.11.1 Energy Saver 210
2.11.1.1 Ensure "Display Sleep Timer" is set to "10" or less, but not 0 (Manual) 211
2.11.1.2 Ensure "System Sleep Timer" is set to "15" or less, but not 0 (Manual) 214
2.11.1.3 Ensure "Wake on LAN" is set to "False" (Manual) 217
2.11.1.4 Ensure "Wake On Modem Ring" is set to "False" (Manual) 220
2.11.1.5 Ensure "Destroy FV Key On Standby" is set to "True" (Manual) 223
2.11.2 Screensaver 225
2.11.2.1 Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0" (Manual) 226
2.11.3 System Extensions 228
2.11.3.1 Ensure "Allow User Overrides" is set to "False" (Manual) 229
2.12 System Policy Control 232
2.12.1 System Policy Control 233
2.12.1.1 Ensure "Enable XProtect Malware Upload" is set to "Disabled" (Manual) 234
2.12.1.2 Ensure Gatekeeper is configured for application installs from Identified Developers only (Manual) 236
2.12.1.3 Ensure Gatekeeper is configured to block all user application installs (Manual) 239

Internal Only - General

2.12.2 System Policy Managed **242**
2.12.2.1 Ensure "Disable Override" is set to "True" (Manual) 243
2.13 Profile Implementation **245**
2.13.1 Ensure Configuration Profile Can Not be Removed by an End User (Manual) 246
Appendix: Summary Table ***249***
Appendix: CIS Controls v7 IG 1 Mapped Recommendations ***257***
Appendix: CIS Controls v7 IG 2 Mapped Recommendations ***260***
Appendix: CIS Controls v7 IG 3 Mapped Recommendations ***264***
Appendix: CIS Controls v7 Unmapped Recommendations ***268***
Appendix: CIS Controls v8 IG 1 Mapped Recommendations ***269***
Appendix: CIS Controls v8 IG 2 Mapped Recommendations ***273***
Appendix: CIS Controls v8 IG 3 Mapped Recommendations ***277***
Appendix: CIS Controls v8 Unmapped Recommendations ***281***
Appendix: Change History ***282***

Internal Only - General

Overview

All CIS Benchmarks™ (Benchmarks) focus on technical configuration settings used to maintain and/or increase the security of the addressed technology, and they should be used in **conjunction** with other essential cyber hygiene tasks like:

- Monitoring the base operating system and applications for vulnerabilities and quickly updating with the latest security patches.
- End-point protection (Antivirus software, Endpoint Detection and Response (EDR), etc.).
- Logging and monitoring user and system activity.

In the end, the Benchmarks are designed to be a key **component** of a comprehensive cybersecurity program.

Important Usage Information

All Benchmarks are available free for non-commercial use from the CIS Website. They can be used to manually assess and remediate systems and applications. In lieu of manual assessment and remediation, there are several tools available to assist with assessment:

- CIS Configuration Assessment Tool (CIS-CAT® Pro Assessor)
- CIS Benchmarks™ Certified 3rd Party Tooling

These tools make the hardening process much more scalable for large numbers of systems and applications.

NOTE: Some tooling focuses only on the Benchmark Recommendations that can be fully automated (skipping ones marked **Manual**). It is important that ***ALL*** Recommendations (**Automated** and **Manual**) be addressed since all are important for properly securing systems and are typically in scope for audits.

Key Stakeholders

Cybersecurity is a collaborative effort, and cross functional cooperation is imperative within an organization to discuss, test, and deploy Benchmarks in an effective and efficient way. The Benchmarks are developed to be best practice configuration guidelines applicable to a wide range of use cases. In some organizations, exceptions to specific Recommendations will be needed, and this team should work to prioritize the problematic Recommendations based on several factors like risk, time, cost, and labor. These exceptions should be properly categorized and documented for auditing purposes.

Internal Only - General

Apply the Correct Version of a Benchmark

Benchmarks are developed and tested for a specific set of products and versions and applying an incorrect Benchmark to a system can cause the resulting pass/fail score to be incorrect. This is due to the assessment of settings that do not apply to the target systems. To assure the correct Benchmark is being assessed:

- **Deploy the Benchmark applicable to the way settings are managed in the environment:** An example of this is the Microsoft Windows family of Benchmarks, which have separate Benchmarks for Group Policy, Intune, and Stand-alone systems based upon how system management is deployed. Applying the wrong Benchmark in this case will give invalid results.

- **Use the most recent version of a Benchmark**: This is true for all Benchmarks, but especially true for cloud technologies. Cloud technologies change frequently and using an older version of a Benchmark may have invalid methods for auditing and remediation.

Exceptions

The guidance items in the Benchmarks are called recommendations and not requirements, and exceptions to some of them are expected and acceptable. The Benchmarks strive to be a secure baseline, or starting point, for a specific technology, with known issues identified during Benchmark development are documented in the Impact section of each Recommendation. In addition, organizational, system specific requirements, or local site policy may require changes as well, or an exception to a Recommendation or group of Recommendations (e.g. A Benchmark could Recommend that a Web server not be installed on the system, but if a system's primary purpose is to function as a Webserver, there should be a documented exception to this Recommendation for that specific server).

In the end, exceptions to some Benchmark Recommendations are common and acceptable, and should be handled as follows:

- The reasons for the exception should be reviewed cross-functionally and be well documented for audit purposes.
- A plan should be developed for mitigating, or eliminating, the exception in the future, if applicable.
- If the organization decides to accept the risk of this exception (not work toward mitigation or elimination), this should be documented for audit purposes.

It is the responsibility of the organization to determine their overall security policy, and which settings are applicable to their unique needs based on the overall risk profile for the organization.

Internal Only - General

Remediation

CIS has developed Build Kits for many technologies to assist in the automation of hardening systems. Build Kits are designed to correspond to Benchmark's "Remediation" section, which provides the manual remediation steps necessary to make that Recommendation compliant to the Benchmark.

When remediating systems (changing configuration settings on deployed systems as per the Benchmark's Recommendations), please approach this with caution and test thoroughly.

The following is a reasonable remediation approach to follow:

- CIS Build Kits, or internally developed remediation methods should never be applied to production systems without proper testing.
- Proper testing consists of the following:
  - Understand the configuration (including installed applications) of the targeted systems. Various parts of the organization may need different configurations (e.g., software developers vs standard office workers).
  - Read the Impact section of the given Recommendation to help determine if there might be an issue with the targeted systems.
  - Test the configuration changes with representative lab system(s). If issues arise during testing, they can be resolved prior to deploying to any production systems.
  - When testing is complete, initially deploy to a small sub-set of production systems and monitor closely for issues. If there are issues, they can be resolved prior to deploying more broadly.
  - When the initial deployment above is completes successfully, iteratively deploy to additional systems and monitor closely for issues. Repeat this process until the full deployment is complete.

Summary

Using the Benchmarks Certified tools, working as a team with key stakeholders, being selective with exceptions, and being careful with remediation deployment, it is possible to harden large numbers of deployed systems in a cost effective, efficient, and safe manner.

NOTE: As previously stated, the PDF versions of the CIS Benchmarks™ are available for free, non-commercial use on the CIS Website. All other formats of the CIS Benchmarks™ (MS Word, Excel, and Build Kits) are available for CIS SecureSuite® members.

CIS-CAT® Pro is also available to CIS SecureSuite® members.

Internal Only - General

Target Technology Details

This document, Security Configuration Benchmark for Intune Apple macOS, provides prescriptive guidance for establishing a secure configuration posture for Apple macOS via enrollment within Microsoft Intune. This guide was tested against Apple macOS 15.0 using Microsoft Intune MDM enrollment. This benchmark covers Apple macOS 15.0 on all supported devices.
The current guidance considers organization-owned macOS devices when determining recommendations. The configuration steps, default settings, and benchmark recommended settings are tailored specifically for macOS devices managed through Intune's Settings Catalog configuration profiles. The benchmark provides recommendations that balance security with usability for enterprise environments while maintaining alignment with CIS security best practices for macOS.
To obtain the latest version of this guide, please visit http://cisecurity.org. If you have questions, comments, or have identified ways to improve this guide, please write us at support@cisecurity.org.

Intended Audience

This document is intended for system and application administrators, security specialists, auditors, help desk, end users, and platform deployment personnel who plan to use, develop, deploy, assess, or secure solutions that incorporate the management of Apple macOS 15.0 devices via MDM enrollment within Microsoft Intune.

Internal Only - General

Consensus Guidance

This CIS Benchmark™ was created using a consensus review process comprised of a global community of subject matter experts. The process combines real world experience with data-based information to create technology specific guidance to assist users to secure their environments. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS Benchmark undergoes two phases of consensus review. The first phase occurs during initial Benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the Benchmark. This discussion occurs until consensus has been reached on Benchmark recommendations. The second phase begins after the Benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the Benchmark. If you are interested in participating in the consensus process, please visit https://workbench.cisecurity.org/.

Internal Only - General

Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
`Stylized Monospace font`	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
`Monospace font`	Used for inline code, commands, UI/Menu selections or examples. Text should be interpreted exactly as presented.
`<Monospace font in brackets>`	Text set in angle brackets denote a variable requiring substitution for a real value.
Italic font	Used to reference other relevant settings, CIS Benchmarks and/or Benchmark Communities. Also, used to denote the title of a book, article, or other publication.
Bold font	Additional information or caveats things like **Notes**, **Warnings**, or **Cautions** (usually just the word itself and the rest of the text normal).

Internal Only - General

Recommendation Definitions

The following defines the various components included in a CIS recommendation as applicable. If any of the components are not applicable it will be noted, or the component will not be included in the recommendation.

Title

Concise description for the recommendation's intended configuration.

Assessment Status

An assessment status is included for every recommendation. The assessment status indicates whether the given recommendation can be automated or requires manual steps to implement. Both statuses are equally important and are determined and supported as defined below:

Automated

Represents recommendations for which assessment of a technical control can be fully automated and validated to a pass/fail state. Recommendations will include the necessary information to implement automation.

Manual

Represents recommendations for which assessment of a technical control cannot be fully automated and requires all or some manual steps to validate that the configured state is set as expected. The expected state can vary depending on the environment.

Profile

A collection of recommendations for securing a technology or a supporting platform. Most benchmarks include at least a Level 1 and Level 2 Profile. Level 2 extends Level 1 recommendations and is not a standalone profile. The Profile Definitions section in the benchmark provides the definitions as they pertain to the recommendations included for the technology.

Description

Detailed information pertaining to the setting with which the recommendation is concerned. In some cases, the description will include the recommended value.

Rationale Statement

Detailed reasoning for the recommendation to provide the user a clear and concise understanding on the importance of the recommendation.

Internal Only - General

Impact Statement

Any security, functionality, or operational consequences that can result from following the recommendation.

Audit Procedure

Systematic instructions for determining if the target system complies with the recommendation.

Remediation Procedure

Systematic instructions for applying recommendations to the target system to bring it into compliance according to the recommendation.

Default Value

Default value for the given setting in this recommendation, if known. If not known, either not configured or not defined will be applied.

References

Additional documentation relative to the recommendation.

CIS Critical Security Controls® (CIS Controls®)

The mapping between a recommendation and the CIS Controls is organized by CIS Controls version, Safeguard, and Implementation Group (IG). The Benchmark in its entirety addresses the CIS Controls safeguards of (v7) “5.1 - Establish Secure Configurations” and (v8) '4.1 - Establish and Maintain a Secure Configuration Process” so individual recommendations will not be mapped to these safeguards.

Additional Information

Supplementary information that does not correspond to any other field but may be useful to the user.

Internal Only - General

Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **Level 1 - Supervised Devices**

  Items in this profile apply to supervised (fully managed) Apple macOS 15.0 Sequoia devices and intend to:

  - Be practical and prudent.
  - Provide a clear security benefit.
  - Not inhibit the utility of the technology beyond acceptable means.

- **Level 2 - Supervised Devices**

  This profile extends the "Level 1 - Supervised Devices" profile. Items in this profile apply to supervised (fully managed) Apple macOS 15.0 Sequoia devices and may:

  - Be used for environments or use cases where security is paramount.
  - Act as defense in depth measures.
  - Negatively inhibit the utility or performance of the technology.

Internal Only - General

Acknowledgements

This Benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

Author
Lewis Hardy

Contributor
Kari Byrd

Editor
Edward Byrd , Center for Internet Security, New York

Internal Only - General

Recommendations

1 Benchmark Guidance

Intune is a cloud endpoint management service produced by Microsoft. Intune supports macOS operating system software through Mobile Device Management (MDM) capabilities. The CIS Community offers this benchmark to provide security guidance for macOS devices managed through Intune.

For those unfamiliar with using Intune for macOS device management, a Configuration Profile must be created to apply to the device that is to be managed. This configuration profile is created within Intune, where device restrictions and settings can be individually configured. This benchmark uses the Settings Catalog configuration policy type, as at the time of publication this had a greater number of controls than the Device Restrictions policy type.

Configuration profiles are created within Intune and then applied to devices that have been enrolled within the service using assignments or scopes. The device will then have a management profile present listing the configurations that have been applied to the device. This benchmark defines what these settings should be from a security standpoint, following CIS best practices for macOS security.

This benchmark focuses exclusively on organization-owned macOS devices that are fully managed through Intune. The recommendations contained within are designed for environments where the organization has complete management authority over the device, allowing for comprehensive security controls to be implemented. This approach acknowledges that organization-owned devices can and should have more restrictive controls applied to protect organizational data and systems.

For macOS devices, enrollment can be accomplished through several methods. Apple Business Manager (ABM) provides automated enrollment for organization-owned devices, offering a streamlined deployment process and critically ensures that users cannot remove the management profile even with administrative privileges. Alternative enrollment methods include Device Enrollment Manager (DEM), direct user enrollment via the Company Portal app, or using Apple Configurator. Each method offers different levels of management capabilities, with ABM generally providing the most comprehensive control for organization-owned devices.

Thank you for taking the time to read this benchmark guidance.

The CIS Intune macOS Community

Internal Only - General

2 Recommendations for Supervised (Organization) Devices

This section provides both level 1 and level 2 recommendations for organization-owned macOS devices. These recommendations are intended for devices where the organization has full management through Intune MDM.

Internal Only - General

2.1 Accounts

Internal Only - General

2.1.1 Accounts

Internal Only - General

2.1.1.1 Ensure "Disable Guest Account" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Guest account allows users to log in to the computer without requiring user authentication. When enabled, the Guest account provides access to the system with a restricted set of privileges but does not require a password. The account is recreated every time a guest logs out.

Rationale:

Disabling the Guest account prevents unauthorized access to the system and its resources. A Guest account, even with limited privileges, could be exploited to:

- Access shared network resources
- View non-protected files and folders
- Launch attacks against the system or network
- Gather information about the organization's computing environment
- Create a persistent presence on the device

Impact:

Disabling the Guest account will prevent users from logging in without authentication credentials. Users who previously relied on Guest access will need valid credentials to access the system. This may affect shared workstations where Guest access was intentionally enabled for temporary use.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Accounts` heading
6. Under the `Accounts` subheading
7. Verify that `Disable Guest Account` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.MCX Profile`
5. Under the `Details` section
6. Confirm `Disable Guest Account` is set to `True`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Accounts` then `Accounts`
7. Check `Disable Guest Account`
8. On the left side of the page set `Disable Guest Account` to `True`
9. Click `Review + save`
10. Verify that `Disable Guest Account` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v8	6.2 Establish an Access Revoking Process Establish and follow a process, preferably automated, for revoking access to enterprise assets, through disabling accounts immediately upon termination, rights revocation, or role change of a user. Disabling accounts, instead of deleting accounts, may be necessary to preserve audit trails.	●	●	●
v8	6.8 Define and Maintain Role-Based Access Control Define and maintain role-based access control, through determining and documenting the access rights necessary for each role within the enterprise to successfully carry out its assigned duties. Perform access control reviews of enterprise assets to validate that all privileges are authorized, on a recurring schedule at a minimum annually, or more frequently.			●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.2 App Store

Internal Only - General

2.2.1 Ensure "Restrict Store Software Update Only" is set to "True" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

This setting prevents users from accessing the App Store application on managed macOS devices, while still allowing system software updates to be installed through the Software Update mechanism.

Rationale:

Restricting access to the App Store while maintaining software update capabilities helps organizations maintain control over their software environment. The setting supports a controlled application deployment strategy where software distribution is managed through organizational channels rather than individual user installations.

Impact:

Users will be unable to launch the App Store and install applications through it. Organizations must ensure they have alternative methods for software deployment, such as through MDM or approved software distribution channels.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `App Store` heading
6. Verify that `Restrict Store Software Update Only` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.appstore Profile`
5. Under the `Details` section
6. Confirm `Restrict To Software Updates` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `App Store`
7. Check `Restrict Store Software Update Only`
8. On the left side of the page set `Restrict Store Software Update Only` to `True`
9. Click `Review + save`
10. Verify that `Restrict Store Software Update Only` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.3 Full Disk Encryption

All level 1 recommendations in this section are essential for FileVault to be configured securely.

Internal Only - General

2.3.1 FIleVault

Internal Only - General

2.3.1.1 Ensure "User Enters Missing Info" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This policy setting ensures that users are prompted to enter any missing user account information during FileVault encryption setup. When enabled, the system will require users to confirm their login credentials if they haven't been properly configured for FileVault access.

Rationale:

Enforcing complete user account configuration ensures that FileVault encryption is properly linked to authorized user credentials. This maintains secure access to encrypted data through the user's standard login password.

Impact:

Users may be prompted to verify their login credentials during initial FileVault setup if the system detects missing or incomplete account information.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault` subheading
7. Verify that `User Enters Missing Info` is present and set to `True`

Internal Only - General

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault`
7. Check `User Enters Missing Info`
8. On the left side of the page set `User Enters Missing Info` to `True`
9. Click `Review + save`
10. Verify that `User Enters Missing Info` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.1.2 Ensure "Enable" is set to "On" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

FileVault provides full disk encryption (XTS-AES-128 with 256-bit key) for the entire system volume on macOS devices. This policy setting ensures FileVault encryption is enabled and enforced.

Rationale:

FileVault encryption protects data at rest from unauthorized access, particularly in cases of lost or stolen devices. Without full disk encryption, an attacker with physical access to the device could access data via alternative boot methods or by removing the drive. FileVault ensures that data remains protected behind strong encryption that requires valid credentials to decrypt.

Impact:

Enabling FileVault requires an initial encryption process that generally takes seconds on newer devices, and can take hours on older hardware with large disk drives. Minor system performance impact may be observed, though modern processors with hardware encryption support minimize this effect.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault` subheading
7. Verify that `Enable` is present and set to `On`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `FileVault Profile`
5. Under the `Details` section
6. Confirm `Enable` is set to `On`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault`
7. Check `Enable`
8. On the left side of the page set `Enable` to `On`
9. Click `Review + save`
10. Verify that `Enable` is present and set to `On`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.1.3 Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This policy setting determines the maximum number of times a user can bypass the FileVault login prompt at startup before encryption is forcefully enabled. Setting this value to "0" ensures users cannot defer or bypass the FileVault encryption requirement.

Rationale:

Allowing users to bypass FileVault encryption leaves organizational data vulnerable to unauthorized access in case of device theft or loss. Setting the maximum bypass attempts to "0" enforces immediate FileVault encryption, ensuring that all system data is protected with strong encryption from the moment the policy is applied, at the user's next login.

Impact:

Users will be required to enable FileVault encryption immediately without the option to defer. This may cause a brief delay during the initial encryption process, and users will need to remember their device password. If users forget their credentials, they will need to use the organizational recovery key to regain access to their data.

Internal Only - General

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault` subheading
7. Verify that `Defer Force At User Login Max Bypass Attempts` is present and set to `0`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `FileVault Profile`
5. Under the `Details` section
6. Confirm `Force At User Login Cancel Attempts` is set to `0`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault`
7. Check `Defer Force At User Login Max Bypass Attempts`
8. On the left side of the page set `Defer Force At User Login Max Bypass Attempts` to `0`
9. Click `Review + save`
10. Verify that `Defer Force At User Login Max Bypass Attempts` is present and set to `0`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.1.4 Ensure "Show Recovery Key" is set to "Disabled" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Users will not be able to view their recovery key through the System Settings interface or during FileVault initialization.

Rationale:

Displaying FileVault recovery keys to users increases the risk of keys being compromised through unauthorized documentation, sharing, or capture. By preventing the display of recovery keys, organizations maintain better control over recovery procedures and ensure that recovery disk decryption can only be performed through approved organizational channels.

Impact:

All recovery operations will need to be handled through organizational IT support channels. Organizations must ensure they have proper key escrow systems in place and documented procedures for handling disk recovery scenarios before implementing this policy.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault` subheading
7. Verify that `Show Recovery Key` is present and set to `Disabled`

Internal Only - General

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault`
7. Check `Show Recovery Key`
8. On the left side of the page set `Show Recovery Key` to `Disabled`
9. Click `Review + save`
10. Verify that `Show Recovery Key` is present and set to `Disabled`
11. Click `Save`

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.1.5 Ensure "Force Enable In Setup Assistant" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When enabled, the system will prompt for FileVault enablement during initial device setup immediately after MDM enrollment, ensuring early-stage disk encryption implementation. This will only apply to devices that are MDM enrolled before the device has been set up (or after a factory reset).

Rationale:

Forcing FileVault enablement during Setup Assistant ensures that devices are encrypted from their initial deployment, eliminating the scenario of sensitive data being written to an unencrypted disk before encryption activation. This also reduces the likelihood of user postponement or avoidance of encryption implementation.

Impact:

Devices will require slightly more time during initial setup to configure FileVault encryption.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault` subheading
7. Verify that `Force Enable In Setup Assistant` is present and set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault`
7. Check `Force Enable In Setup Assistant`
8. On the left side of the page set `Force Enable In Setup Assistant` to `True`
9. Click `Review + save`
10. Verify that `Force Enable In Setup Assistant` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.2 FileVault Options

Internal Only - General

2.3.2.1 Ensure "Prevent FileVault From Being Disabled" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When enabled, this disables the option to turn off FileVault encryption in System Settings and through command-line interfaces.

Rationale:

Allowing users to disable FileVault could result in the compromise of organizational data and not meeting compliance requirements.

Impact:

This could impact troubleshooting procedures that require FileVault to be disabled.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Full Disk Encryption` heading
6. Under the `FileVault Options` subheading
7. Verify that `Prevent FileVault From Being Disabled` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.MCX Profile`
5. Under the `Details` section
6. Confirm `FileVault Can't Disable` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Full Disk Encryption` then `FileVault Options`
7. Check `Prevent FileVault From Being Disabled`
8. On the left side of the page set `Prevent FileVault From Being Disabled` to `True`
9. Click `Review + save`
10. Verify that `Prevent FileVault From Being Disabled` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.3.3 Endpoint Disk Encryption

Internal Only - General

2.3.3.1 Ensure There is a Disk Encryption FileVault Policy (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

An Intune Endpoint Security Disk Encryption policy is essential for FileVault to be a device requirement.

Rationale:

If this is not set, disk encryption will not be a requirement and other FileVault policies will be ignored.

Audit:

From the Microsoft Intune admin center:

1. Select `Endpoint security`
2. Select `Disk encryption`
3. Select the policy which applies to macOS devices (this should be a policy with the policy type of `FileVault` and not `MacOS FileVault`)
4. Select the `Properties` menu item
5. Ensure that the policy is assigned to the appropriate group of users/devices.
6. Under `Configuration settings` heading
7. Expand the `Settings` then `Encryption` heading
8. Verify that `Enable FileVault` is present and set to `Yes`
9. Verify that `Number of times allowed to bypass` is present and set to `Not configured` or `No limit, always prompt` (this will be inherited from the FileVault configuration policy)
10. Verify that `Disable prompt at sign out` is present and set to `Not configured`
11. Verify that `Hide recovery key` is present and set to `Yes`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Endpoint security`
2. Select `Disk encryption`
3. Select `Create Policy`
4. Select `MacOS` for the Platform, and `FileVault` for the Profile, click `Create`
5. Give the policy an appropriate name and description.
6. Select the policy which applies to macOS devices (this should be a policy with the policy type of `FileVault` and not `MacOS FileVault`)
7. Select the `Properties` menu item
8. Ensure that the policy is assigned to the appropriate group of users/devices.
9. Set `Enable FileVault` to `Yes`
10. Enter a short message to instruct users how to retrieve their personal recovery key
11. Set `Number of times allowed to bypass` to `Not configured` (this will be inherited from the FileVault configuration policy)
12. Set `Disable prompt at sign out` to `Not configured`
13. Set `Hide recovery key` to `Yes`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.6 Encrypt Data on End-User Devices Encrypt data on end-user devices containing sensitive data. Example implementations can include: Windows BitLocker®, Apple FileVault®, Linux® dm-crypt.	●	●	●
v8	3.11 Encrypt Sensitive Data at Rest Encrypt sensitive data at rest on servers, applications, and databases containing sensitive data. Storage-layer encryption, also known as server-side encryption, meets the minimum requirement of this Safeguard. Additional encryption methods may include application-layer encryption, also known as client-side encryption, where access to the data storage device(s) does not permit access to the plain-text data.		●	●
v7	13.6 Encrypt the Hard Drive of All Mobile Devices. Utilize approved whole disk encryption software to encrypt the hard drive of all mobile devices.	●	●	●
v7	14.8 Encrypt Sensitive Information at Rest Encrypt all sensitive information at rest using a tool that requires a secondary authentication mechanism not integrated into the operating system, in order to access the information.			●

Internal Only - General

2.4 Login

Internal Only - General

2.4.1 Login Window Behavior

Internal Only - General

2.4.1.1 Ensure "Show Full Name" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This policy setting controls whether the macOS login window displays a name and password dialog instead of a list of users. When enabled, users must enter both their username and password to authenticate.

Rationale:

Displaying a list of users in the login window provides potential attackers with partial authentication credentials, as it reveals valid usernames on the system. By requiring users to enter both their username and password, the organization reduces the risk of unauthorized access and makes passcode cracking more difficult since attackers must guess both components of the login credentials.

Impact:

Users will need to type both their username and password when logging in, rather than selecting their account from a list. This may slightly increase the time needed to log in but provides enhanced security. Users will need to remember their exact username in addition to their password.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Login` heading
6. Under the `Login Window Behavior` subheading
7. Verify that `Show Full Name` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.loginwindow Profile`
5. Under the `Details` section
6. Confirm `Show Full Name` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Login` then `Login Window Behavior`
7. Check `Show Full Name`
8. On the left side of the page set `Show Full Name` to `True`
9. Click `Review + save`
10. Verify that `Show Full Name` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.4.2 Login Window Login Items

Internal Only - General

2.4.2.1 Ensure "Disable Login Items Suppression" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting prevents users from disabling the automatic launch of login items by holding down the Shift key during login. When set to `True`, all designated login items will launch regardless of user intervention.

Rationale:

Organizations often deploy critical security software that must run at system startup to maintain security posture. Allowing users to suppress these login items could create security gaps by preventing security applications from launching, potentially leaving the system insecure.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Login` heading
6. Under the `Login Window Login Items` subheading
7. Verify that `Disable Login Items Suppression` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `loginwindow Profile`
5. Under the `Details` section
6. Confirm `Disable Login Items Suppression` is set to `True`

In some cases the above policy will not be visible on device, in this case the following command can be run:

```
sudo find /Library/Managed\ Preferences -name "*.plist" -exec
/usr/libexec/PlistBuddy -c "Print" {} \; | awk
'/DisableLoginItemsSuppression.*=.*/{p=1;c=0} p{print; if($0~/\{/) c+=1;
if($0~/\}/) c-=1; if(c<0) p=0}'
```

Expected output contains `DisableLoginItemsSuppression = true`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Login` then `Login Window Login Items`
7. Check `Disable Login Items Suppression`
8. On the left side of the page set `Disable Login Items Suppression` to `True`
9. Click `Review + save`
10. Verify that `Disable Login Items Suppression` is present and set to `True`
11. Click `Save`

Internal Only - General

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.5 Managed Settings

Internal Only - General

2.5.1 MDM Options

Internal Only - General

2.5.1.1 Ensure "Activation Lock Allowed While Supervised" is set appropriately (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

When Activation Lock is enabled, a device cannot be erased or reactivated without the associated Apple ID credentials, including after a factory reset. This setting does not enable Activation Lock directly, but instead controls if users are permitted to enable this feature through Find My.

Rationale:

When set to `Allowed`: Activation Lock provides an additional security layer beyond device passcodes and FileVault by preventing device reactivation after factory reset. While passcodes and FileVault protect data, Activation Lock specifically deters device theft by making the hardware itself unusable to thieves.

When set to `Blocked`: Ensures devices can be easily repurposed when users leave the organization. When passcode and FileVault are already providing data protection, Activation Lock may create unnecessary administrative overhead without significant additional security benefits for organization-managed devices.

Impact:

When set to `Allowed`: May complicate device management if users leave without removing their Apple ID. Requires appropriate offboarding procedures or Apple Business Manager.

When set to `Blocked`: Removes a theft deterrent from devices. Organizations should implement alternative security measures to compensate.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Managed Settings` heading
6. Under the `MDM Options` subheading
7. Verify that `Activation Lock Allowed While Supervised` is set to your organization's requirements

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Managed Settings` then `MDM Options`
7. Check `Activation Lock Allowed While Supervised`
8. On the left side of the page set `Activation Lock Allowed While Supervised` to `Allowed` or `Blocked`
9. Click `Review + save`
10. Verify that `Activation Lock Allowed While Supervised` is set to your organization's requirements
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.6 Networking

Internal Only - General

2.6.1 Content Caching

Internal Only - General

2.6.1.1 Ensure "Auto Activation" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

Content caching stores and serves various types of content from Apple, including software updates, app store purchases, iCloud data, and other downloadable content to reduce internet bandwidth usage. When "Auto Activation" is enabled, content caching automatically activates when possible and prevents manual deactivation. This capability requires macOS clients to function as P2P nodes for Apple content distribution.

Rationale:

P2P sharing services should not be enabled on endpoints using untrusted networks. Disabling content caching's auto activation reduces the attack surface by preventing automatic network service initiation. Content caching creates additional network connections and locally stored content, which may introduce security risks in managed environments.

Impact:

Disabling auto activation will increase bandwidth usage between local subnets and the Internet as devices download updates, apps, and iCloud content directly from Apple's servers rather than local caches. Organizations should ensure adequate bandwidth is available for all Apple content and services.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Networking` heading
6. Under the `Content Caching` subheading
7. Verify that `Auto Activation` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.AssetCache.managed Profile`
5. Under the `Details` section
6. Confirm `Automatically activate Content Caching` is set to `False`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Networking` then `Content Caching`
7. Check `Auto Activation`
8. On the left side of the page set `Auto Activation` to `False`
9. Click `Review + save`
10. Verify that `Auto Activation` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.6.2 Firewall

Internal Only - General

2.6.2.1 Ensure "Enable Stealth Mode" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Stealth Mode prevents the system from responding to probing requests such as ICMP ping, effectively making the system appear invisible to network scanning.

Rationale:

Enabling stealth mode helps prevent malicious actors from discovering the system through network scanning techniques. By not responding to probing attempts, the system becomes more difficult to detect and target, reducing the attack surface and reconnaissance activities.

Impact:

When stealth mode is enabled, legitimate network diagnostic tools that rely on ICMP ping responses may fail to detect or communicate with the system. Other network tools that measure activity and approved applications will work as expected.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Networking` heading
6. Under the `Firewall` subheading
7. Verify that `Enable Stealth Mode` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.security.firewall Profile`
5. Under the `Details` section
6. Confirm `Stealth mode` is set to `Enabled`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Networking` then `Firewall`
7. Check `Enable Stealth Mode`
8. On the left side of the page set `Enable Stealth Mode` to `True`
9. Click `Review + save`
10. Verify that `Enable Stealth Mode` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.5 Implement and Manage a Firewall on End-User Devices Implement and manage a host-based firewall or port-filtering tool on end-user devices, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.4 Apply Host-based Firewalls or Port Filtering Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.	●	●	●

Internal Only - General

2.6.2.2 Ensure "Enable Firewall" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The macOS firewall protects systems from unwanted network connections by blocking unauthorized incoming connections. When enabled, the firewall analyzes inbound traffic and blocks connections that don't meet the rules defined in the firewall configuration.

Rationale:

When enabled, the Firewall blocks incoming connections that haven't been authorized, reducing the attack surface from network-based threats. This is particularly important for devices that connect to untrusted networks.

Impact:

Enabling the firewall may impact legitimate applications that require incoming connections if they are not properly configured in the firewall settings. Users might experience issues with file sharing, screen sharing, or other network services until appropriate rules are established.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Networking` heading
6. Under the `Firewall` subheading
7. Verify that `Enable Firewall` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.security.firewall Profile`
5. Under the `Details` section
6. Confirm `Firewall` is set to `Enabled`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Networking` then `Firewall`
7. Check `Enable Firewall`
8. On the left side of the page set `Enable Firewall` to `True`
9. Click `Review + save`
10. Verify that `Enable Firewall` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.5 Implement and Manage a Firewall on End-User Devices Implement and manage a host-based firewall or port-filtering tool on end-user devices, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.	●	●	●
v8	13.1 Centralize Security Event Alerting Centralize security event alerting across enterprise assets for log correlation and analysis. Best practice implementation requires the use of a SIEM, which includes vendor-defined event correlation alerts. A log analytics platform configured with security-relevant correlation alerts also satisfies this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.4 Apply Host-based Firewalls or Port Filtering Apply host-based firewalls or port filtering tools on end systems, with a default-deny rule that drops all traffic except those services and ports that are explicitly allowed.	●	●	●
v7	9.5 Implement Application Firewalls Place application firewalls in front of any critical servers to verify and validate the traffic going to the server. Any unauthorized traffic should be blocked and logged.			●

Internal Only - General

2.7 Profile Removal Password

Internal Only - General

2.7.1 Ensure "Removal Password" is absent or is securely configured with restricted access (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The profile removal password setting in Intune device management controls whether a local user can remove the management profile from a macOS device. When this setting is not configured (absent) or is configured with restricted access, it prevents the unauthorized removal of management profiles that enforce organizational security policies.

Rationale:

If a profile removal password is set and becomes widely known, users could remove management profiles and circumvent organizational security policies. Either maintaining no on-device profile removal password (relying on Intune's remote unenrollment controls) or implementing a securely configured password with restricted access ensures that only authorized administrators can remove profiles when necessary.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Profile Removal Password` heading (if present)
6. Verify that `Removal Password` is absent or is securely configured with restricted access

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Verify that `com.apple.profileRemovalPassword Profile` is absent.
5. If it is visible then ensure it is securely configured with restricted access

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Profile Removal Password`
7. Uncheck/Check `Removal Password`
8. If configuring, on the left side of the page set `Removal Password` to a secure password
9. Click `Review + save`
10. Verify that `Removal Password` is absent or is securely configured
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8 Restrictions

Internal Only - General

2.8.1 Ensure "Allow Bluetooth Sharing Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Bluetooth Sharing allows users to exchange files with other Bluetooth-enabled devices. Setting "Allow Bluetooth Sharing Modification" to "False" prevents users from changing the Bluetooth sharing settings in System Settings.

Rationale:

Controlling Bluetooth Sharing capability at an organizational level prevents unauthorized data transfers between organization-managed devices and external Bluetooth-enabled devices.

Impact:

If Bluetooth Sharing was disabled before policy application (system default), it will remain disabled. If Bluetooth Sharing was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure Bluetooth Sharing is actually disabled on all systems, as this policy only restricts user control of the setting.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Bluetooth Sharing Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Bluetooth Sharing Modification` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Bluetooth Sharing Modification`
8. On the left side of the page set `Allow Bluetooth Sharing Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Bluetooth Sharing Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	3.3 Configure Data Access Control Lists Configure data access control lists based on a user's need to know. Apply data access control lists, also known as access permissions, to local and remote file systems, databases, and applications.	●	●	●
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	4.8 Log and Alert on Changes to Administrative Group Membership Configure systems to issue a log entry and alert when an account is added to or removed from any group assigned administrative privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●
v7	14.6 Protect Information through Access Control Lists Protect all information stored on systems with file system, network share, claims, application, or database specific access control lists. These controls will enforce the principle that only authorized individuals should have access to the information based on their need to access the information as a part of their responsibilities.	●	●	●

Internal Only - General

2.8.2 Ensure "Allow Password Sharing" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Password Sharing feature allows users to share passwords with nearby devices using AirDrop. When enabled, macOS users can share saved passwords from their keychain with other Apple devices in proximity.

Rationale:

Disabling password sharing via AirDrop prevents potential exposure of organizational credentials. If this feature is enabled, users could intentionally or unintentionally share sensitive passwords with unauthorized recipients.

Impact:

Users will need to use organization-approved methods for sharing credentials when required.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Password Sharing` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Password Sharing` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Password Sharing`
8. On the left side of the page set `Allow Password Sharing` to `False`
9. Click `Review + save`
10. Verify that `Allow Password Sharing` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.3 Ensure "Allow File Sharing Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

File sharing allows users to share folders and files from their Mac with other users over a network using SMB and other file sharing protocols. The "Allow File Sharing Modification" setting controls whether users can modify the file sharing configuration through System Settings. When this setting is disabled, users cannot enable or disable file sharing services or modify shared folder permissions.

Rationale:

Preventing users from modifying file sharing settings helps organizations maintain control over network resource sharing. Unrestricted file sharing can lead to unauthorized data exposure, creates additional network entry points, and may allow sensitive data to be transferred outside organizational boundaries.

Impact:

If file sharing was disabled before policy application (system default), it will remain disabled. If file sharing was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure file sharing is actually disabled on all systems, as this policy only restricts user control of the setting.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow File Sharing Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow File Sharing Modification` is set to `False`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow File Sharing Modification`
8. On the left side of the page set `Allow File Sharing Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow File Sharing Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	5.4 Restrict Administrator Privileges to Dedicated Administrator Accounts Restrict administrator privileges to dedicated administrator accounts on enterprise assets. Conduct general computing activities, such as internet browsing, email, and productivity suite use, from the user's primary, non-privileged account.	●	●	●
v7	4.3 Ensure the Use of Dedicated Administrative Accounts Ensure that all users with administrative account access use a dedicated or secondary account for elevated activities. This account should only be used for administrative activities and not internet browsing, email, or similar activities.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.4 Ensure "Allow Erase Content And Settings" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting controls whether a user can erase all content and settings (reset the device), returning the device to its factory default state.

Rationale:

Prevents unauthorized destruction of organizational data and device repurposing

Impact:

Device reset operations will require administrator intervention through management tools, ensuring proper device lifecycle management and accountability.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Erase Content And Settings` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Erase Content And Settings` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Erase Content And Settings`
8. On the left side of the page set `Allow Erase Content And Settings` to `False`
9. Click `Review + save`
10. Verify that `Allow Erase Content And Settings` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	16.7 Use Standard Hardening Configuration Templates for Application Infrastructure Use standard, industry-recommended hardening configuration templates for application infrastructure components. This includes underlying servers, databases, and web servers, and applies to cloud containers, Platform as a Service (PaaS) components, and SaaS components. Do not allow in-house developed software to weaken configuration hardening.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.5 Ensure "Allow Air Play Incoming Requests" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

AirPlay is an Apple technology that allows wireless streaming of audio, video, and screen sharing between devices. When enabled on macOS, it allows the Mac to receive AirPlay requests and function as an AirPlay receiver, permitting other Apple devices to stream content to the Mac's display.

Rationale:

Disabling AirPlay incoming requests prevents unauthorized devices from establishing AirPlay connections to organizational Macs. The feature broadcasts device presence and processes incoming connection requests, which could be leveraged for network reconnaissance or denial-of-service attacks. Although AirPlay connections require user approval on the receiving Mac, persistent connection requests may disrupt workflow, while unauthorized screen sharing could lead to exposure of sensitive information.

Impact:

Users will not be able to use their Mac as an AirPlay receiver for other Apple devices.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Air Play Incoming Requests` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow AirPlay Incoming Requests` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Air Play Incoming Requests`
8. On the left side of the page set `Allow Air Play Incoming Requests` to `False`
9. Click `Review + save`
10. Verify that `Allow Air Play Incoming Requests` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.6 Ensure "Allow Media Sharing Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Media Sharing settings in macOS allow users to share downloaded content, including music, movies, TV shows, and photos across Apple devices on the same network.

Rationale:

Preventing modification of Media Sharing settings ensures organizational control over what content can be shared across the network. When users can freely modify Media Sharing settings, they may expose media content to unauthorized devices on the network.

Impact:

If Media Sharing was disabled before policy application (system default), it will remain disabled. If Media Sharing was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure Media Sharing is actually disabled on all systems, as this policy only restricts user control of the setting.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Media Sharing Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Sharing`
4. Confirm `Media Sharing` is toggled off and the text `This service has been configured by a profile` is present

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Media Sharing Modification`
8. On the left side of the page set `Allow Media Sharing Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Media Sharing Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.7 Ensure "Allow Cloud Photo Library" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Photos (formerly known as iCloud Photo Library) is a cloud-based service that automatically stores and synchronizes photos and videos across Apple devices using Apple's iCloud infrastructure. When enabled, all photos and videos taken on the device are uploaded to iCloud storage and made available from other devices signed in with the same iCloud account.

Rationale:

Disabling iCloud Photo Library prevents the synchronization of organizational photos and videos to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures sensitive visual content remains within approved storage locations.

Impact:

Users will not be able to sync or access their photos and videos through iCloud Photos. Local device photo storage and management will continue to function normally through the Photos app.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Photo Library` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Photos` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Photo Library`
8. On the left side of the page set `Allow Cloud Photo Library` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Photo Library` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.8 Ensure "Allow Cloud Document Sync" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Document Sync is an app-level cloud-based service that enables applications to store and synchronize documents and data through iCloud. When enabled, this feature allows apps to automatically save files to iCloud storage, making these documents accessible across multiple devices using the same Apple ID.

Rationale:

Disabling iCloud Document Sync prevents applications from synchronizing organizational documents and app data to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures sensitive information remains within approved storage locations that are under organizational control.

Impact:

Applications will not be able to automatically save or sync documents with iCloud. Apps that utilize iCloud document storage capabilities will be limited to storing data locally on the device or on organization-approved storage solutions.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Document Sync` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Drive` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Document Sync`
8. On the left side of the page set `Allow Cloud Document Sync` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Document Sync` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.9 Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Enforced Software Update Delay setting controls the number of days before users are notified of available software updates on managed macOS devices. When configured, this setting prevents pending updates from appearing to users until the specified delay period has elapsed from the update's release date. The setting affects both system and app software update notifications. The optimal configuration is to leave this setting not configured (absent), allowing users to be notified of updates as soon as they become available.

Rationale:

Apple software updates almost always include security updates. By delaying update notifications, organizations increase the time systems remain vulnerable to security issues that have been patched in the available updates.

Impact:

Organizations may use a short delay period to verify compatibility with specialized software before notifications reach end users, but should minimize this delay to maintain security. Organizations should balance their testing needs against security risks associated with delayed notifications.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Enforced Software Update Delay` is absent or is set to less than or equal to 30

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Deferred Software Update Delay (Days)` is not visible or is set to `30` or less

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Uncheck/Check `Enforced Software Update Delay`
8. If configuring, on the left side of the page set `Enforced Software Update Delay` to a value less than or equal to 20
9. Click `Review + save`
10. Verify that `Enforced Software Update Delay` is absent or is set to less than or equal to 30
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●
v7	7.4 Maintain and Enforce Network-Based URL Filters Enforce network-based URL filters that limit a system's ability to connect to websites not approved by the organization. This filtering shall be enforced for each of the organization's systems, whether they are physically at an organization's facilities or not.		●	●

Internal Only - General

2.8.10 Ensure "Allow Activity Continuation" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Activity Continuation, also known as Handoff, allows users to start work on one macOS device and continue on another Apple device. This feature requires devices to be signed into the same Apple ID and uses Bluetooth and WiFi connections for nearby devices, with iCloud handling transfers between distant devices.

Rationale:

Activity Continuation transfers application state and data across devices without maintaining managed application boundaries. This could lead to organizational data being transferred devices outside the organization's control.

Impact:

Users will be unable to use Handoff functionality between their managed macOS devices and other Apple devices.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Activity Continuation` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Handoff Allowed` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Activity Continuation`
8. On the left side of the page set `Allow Activity Continuation` to `False`
9. Click `Review + save`
10. Verify that `Allow Activity Continuation` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	4.1 Maintain Inventory of Administrative Accounts Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.11 Ensure "Allow Cloud Bookmarks" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Bookmarks is a feature that synchronizes web browser bookmarks and reading list items across Apple devices using Apple's iCloud infrastructure. When enabled, bookmarks created in Safari and other compatible browsers are automatically uploaded to iCloud and made available on all devices signed into the same Apple ID.

Rationale:

Disabling iCloud Bookmarks prevents the synchronization of browser bookmarks to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures that potentially sensitive bookmark information, which may include links to organizational resources or internal sites, remains within approved environments that are under organizational control.

Impact:

Users will not be able to synchronize their browser bookmarks across multiple devices via iCloud. Bookmarks created on a device will remain local to that device only.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Bookmarks` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Bookmarks` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Bookmarks`
8. On the left side of the page set `Allow Cloud Bookmarks` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Bookmarks` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	4.1 Maintain Inventory of Administrative Accounts Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.		●	●
v7	4.8 Log and Alert on Changes to Administrative Group Membership Configure systems to issue a log entry and alert when an account is added to or removed from any group assigned administrative privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.12 Ensure "Allow Cloud Freeform" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Freeform is a collaboration application introduced in macOS 13.1 (Ventura) that provides digital whiteboard functionality across Apple devices. When enabled, iCloud Freeform allows users to create, store, and share interactive whiteboards containing text, images, videos, and other media through Apple's iCloud infrastructure.

Rationale:

Disabling iCloud Freeform prevents the synchronization of potentially sensitive organizational data to Apple's iCloud services. Whiteboards may contain proprietary information, strategic plans, or confidential data that should remain within approved organizational storage systems. This limitation helps maintain data residency requirements and ensures information remains within approved storage locations.

Impact:

Users will not be able to create, access, or share Freeform boards through iCloud services. Local creation and storage of Freeform content will remain functional on the device.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Freeform` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Freeform` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Freeform`
8. On the left side of the page set `Allow Cloud Freeform` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Freeform` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	4.1 Maintain Inventory of Administrative Accounts Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	15.3 Use a Wireless Intrusion Detection System Use a wireless intrusion detection system (WIDS) to detect and alert on unauthorized wireless access points connected to the network.		●	●

Internal Only - General

2.8.13 Ensure "Allow Cloud Calendar" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Calendar is a cloud-based service that synchronizes calendar data across Apple devices using Apple's iCloud infrastructure. When enabled, users can create, store, and access calendars, events, and appointments through their iCloud account, making this information available across multiple devices signed into the same Apple ID.

Rationale:

Disabling iCloud Calendar prevents the synchronization of organizational calendar data to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures information remains within approved storage locations.

Impact:

Users will not be able to create or access calendars through iCloud services or synchronize calendar data across devices via iCloud. They will need to use organization-approved calendar solutions for managing schedules and appointments. Local device calendars will continue to function, but will not synchronize with other devices through iCloud.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Calendar` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Calendar` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Calendar`
8. On the left side of the page set `Allow Cloud Calendar` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Calendar` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	4.1 Maintain Inventory of Administrative Accounts Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.14 Ensure "Allow ARD Remote Management Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Apple Remote Desktop (ARD) Remote Management allows administrators to remotely manage Mac systems through the Remote Management service. The Remote Management modification setting controls whether users can modify Remote Management sharing settings through System Settings. When Remote Management is enabled, it opens port 5900 and allows remote connections based on configured permissions.

Rationale:

Users with the ability to modify Remote Management settings may enable unauthorized remote access to their systems. Remote Management should be controlled through organizational management tools rather than allowing end-user modification.

Impact:

If ARD Remote Management was disabled before policy application (system default), it will remain disabled. If ARD Remote Management was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure Remote Management is actually disabled on all systems, as this policy only restricts user control of the setting.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow ARD Remote Management Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Remote Desktop Management Modification` is set to `False`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow ARD Remote Management Modification`
8. On the left side of the page set `Allow ARD Remote Management Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow ARD Remote Management Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	5.4 Restrict Administrator Privileges to Dedicated Administrator Accounts Restrict administrator privileges to dedicated administrator accounts on enterprise assets. Conduct general computing activities, such as internet browsing, email, and productivity suite use, from the user's primary, non-privileged account.	●	●	●
v7	4.3 Ensure the Use of Dedicated Administrative Accounts Ensure that all users with administrative account access use a dedicated or secondary account for elevated activities. This account should only be used for administrative activities and not internet browsing, email, or similar activities.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●
v7	14.3 Disable Workstation to Workstation Communication Disable all workstation to workstation communication to limit an attacker's ability to move laterally and compromise neighboring systems, through technologies such as Private VLANs or microsegmentation.		●	●

Internal Only - General

2.8.15 Ensure "Allow Assistant" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Siri is Apple's virtual assistant that allows users to control their macOS device and access various functions through voice commands or typing. When enabled, Siri can perform tasks such as searching the web, opening applications, sending messages, setting reminders, and accessing system features. The assistant can be activated through keyboard shortcuts, menu bar, or voice commands.

Rationale:

Disabling Siri prevents users from utilizing the assistant functionality. Siri collects and processes voice & text data, which may include sensitive organizational information, and transmits this data to Apple's servers for analysis. This creates potential data leakage risks, especially in environments that handle confidential or regulated information.

Impact:

This setting specifically disables Siri functionality but does not affect the system dictation feature, which remains available for text input.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Assistant` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Assistant` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Assistant`
8. On the left side of the page set `Allow Assistant` to `False`
9. Click `Review + save`
10. Verify that `Allow Assistant` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.16 Ensure "Allow Game Center" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

Game Center is a social gaming network provided by Apple that allows users to track achievements, compare scores on leaderboards, and connect with friends for multiplayer gaming experiences. It stores user profile data including nickname and gaming activity, and enables features such as contact discovery and nearby player detection through network/LAN/Bluetooth connections. When enabled on macOS, users can sign in to Game Center with their Apple ID.

Rationale:

Game Center introduces potential data exposure through its social networking features and automatic player discovery capabilities. The service transmits user profile information, gaming activities, and enables network discovery of nearby players, which may expose user data to unauthorized individuals and data sharing to Apple.

Impact:

Users will not be able to use Game Center functionality on their macOS devices.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Game Center` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Game Center` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Game Center`
8. On the left side of the page set `Allow Game Center` to `False`
9. Click `Review + save`
10. Verify that `Allow Game Center` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	0.0 Explicitly Not Mapped Explicitly Not Mapped			
v7	0.0 Explicitly Not Mapped Explicitly Not Mapped			

Internal Only - General

2.8.17 Ensure "Allow Auto Unlock" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Auto Unlock allows users to automatically unlock their Mac using an Apple Watch. When enabled, this feature permits users to bypass the login screen password requirement when their authenticated Apple Watch is in close proximity to the Mac.

Rationale:

Disabling Auto Unlock prevents unauthorized access to a Mac when an authenticated Apple Watch is in proximity. If a user's Apple Watch is stolen or compromised while remaining in Bluetooth range of their Mac, an attacker could potentially gain access to the device without knowledge of the user's credentials. Additionally, signal interception or replay attacks targeting the Bluetooth communication between devices could be used to bypass authentication.

Impact:

Users will be required to manually enter their password (or Touch ID if enabled) each time they need to unlock their Mac.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Auto Unlock` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow Auto Unlock` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Auto Unlock`
8. On the left side of the page set `Allow Auto Unlock` to `False`
9. Click `Review + save`
10. Verify that `Allow Auto Unlock` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.7 Manage Default Accounts on Enterprise Assets and Software Manage default accounts on enterprise assets and software, such as root, administrator, and other pre-configured vendor accounts. Example implementations can include: disabling default accounts or making them unusable.	●	●	●
v7	4.2 Change Default Passwords Before deploying any new asset, change all default passwords to have values consistent with administrative level accounts.	●	●	●

Internal Only - General

2.8.18 Ensure "Allow Startup Disk Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Startup Disk settings in System Settings allow users to select which disk is used to start up the computer. When enabled, users can change their startup disk to any compatible bootable volume connected to their device.

Rationale:

Restricting modification of the startup disk prevents users from booting from unauthorized volumes, which could be used to bypass security controls implemented on the primary operating system. An attacker or malicious user could use an alternative startup disk to gain unauthorized access to data or to install malicious software.

Impact:

This may impact users who legitimately need to boot from alternative volumes for troubleshooting or recovery purposes. In such cases, administrator intervention will be required to change the startup disk settings.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Startup Disk Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Startup Disk Modification` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Startup Disk Modification`
8. On the left side of the page set `Allow Startup Disk Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Startup Disk Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.19 Ensure "Allow UI Configuration Profile Installation" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This restriction prevents a user from intentionally or unintentionally installing additional configuration profiles through the user interface in macOS. When set to False, users are prevented from installing configuration profiles manually through System Settings or by opening profile files.

Rationale:

This adds an additional security control, so third-party and potentially malicious configuration profiles are blocked from installation. Configuration profiles can contain settings that override system security, privacy, and functionality. By restricting profile installation to managed deployment methods only, organizations maintain control over what profiles are installed on managed devices and prevent users from compromising the security posture of their devices.

Impact:

When this setting is enforced, users will be unable to install configuration profiles through the user interface and will receive a message stating "Installing profiles is restricted by a profile" when attempting to do so. Some services, such as WiFi access points that have been configured requiring a user to install a configuration profile, may be prevented from working by blocking their configuration profiles.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow UI Configuration Profile Installation` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Configuration Profile Installation` is set to `False`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow UI Configuration Profile Installation`
8. On the left side of the page set `Allow UI Configuration Profile Installation` to `False`
9. Click `Review + save`
10. Verify that `Allow UI Configuration Profile Installation` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.20 Ensure "Allow Device Name Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting prevents users from modifying the device name on macOS devices.

Rationale:

Organizations often rely on device names for identification, asset tracking, and inventory management. Allowing users to modify device names can disrupt established naming conventions, complicate device management processes, and potentially interfere with network services that depend on consistent device identification.

Impact:

Users will be unable to modify their device name. System administrators will need to ensure that devices are provisioned with appropriate names prior to deployment, as this setting will block the device renaming functionality.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Device Name Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Device Name Modification` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Device Name Modification`
8. On the left side of the page set `Allow Device Name Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Device Name Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	1.1 Establish and Maintain Detailed Enterprise Asset Inventory Establish and maintain an accurate, detailed, and up-to-date inventory of all enterprise assets with the potential to store or process data, to include: end-user devices (including portable and mobile), network devices, non-computing/IoT devices, and servers. Ensure the inventory records the network address (if static), hardware address, machine name, enterprise asset owner, department for each asset, and whether the asset has been approved to connect to the network. For mobile end-user devices, MDM type tools can support this process, where appropriate. This inventory includes assets connected to the infrastructure physically, virtually, remotely, and those within cloud environments. Additionally, it includes assets that are regularly connected to the enterprise's network infrastructure, even if they are not under control of the enterprise. Review and update the inventory of all enterprise assets bi-annually, or more frequently.	●	●	●
v7	9.1 Associate Active Ports, Services and Protocols to Asset Inventory Associate active ports, services and protocols to the hardware assets in the asset inventory.		●	●

Internal Only - General

2.8.21 Ensure "Allow Internet Sharing Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Internet Sharing allows a macOS device to share its internet connection with other devices via WiFi, Ethernet, or Bluetooth. This setting controls whether users can modify the Internet Sharing configuration in System Settings.

Rationale:

Internet Sharing creates a network access point from the macOS device, allowing other devices to connect to and route through it. This functionality can circumvent network security controls by creating unauthorized network paths and expose the organization's network to unmanaged devices.

Impact:

If Internet Sharing was disabled before policy application (system default), it will remain disabled. If Internet Sharing was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure Internet Sharing is actually disabled on all systems, as this policy only restricts user control of the setting.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Internet Sharing Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Internet Sharing Modification` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Internet Sharing Modification`
8. On the left side of the page set `Allow Internet Sharing Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Internet Sharing Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	4.1 Maintain Inventory of Administrative Accounts Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.22 Ensure "Allow Content Caching" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

Content caching stores and serves various types of content from Apple, including software updates, app store purchases, iCloud data, and other downloadable content to reduce internet bandwidth usage. When allowed, content caching enables the device to serve as a local cache server for Apple content. This capability requires macOS clients to function as P2P nodes for Apple content distribution.

Rationale:

P2P sharing services should not be enabled on endpoints using untrusted networks. Disabling content caching reduces the attack surface by preventing network service initiation. Content caching creates additional network connections and locally stored content, which may introduce security risks in managed environments.

Impact:

Disabling content caching will increase bandwidth usage between local subnets and the Internet as devices download updates, apps, and iCloud content directly from Apple's servers rather than local caches. Organizations should ensure adequate bandwidth is available for all Apple content and services.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Content Caching` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Content Caching` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Content Caching`
8. On the left side of the page set `Allow Content Caching` to `False`
9. Click `Review + save`
10. Verify that `Allow Content Caching` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.23 Ensure "Allow Find My Friends" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Find My Friends is a built-in macOS feature that enables device location sharing and tracking through Apple's Find My app. When enabled, users can share their device's real-time location with other Apple ID users and allow continuous location monitoring.

Rationale:

Unauthorized location tracking presents significant privacy and security risks for users. If the feature is enabled, a malicious actor could social engineer or gain physical access, establishing location sharing to track the device's movements without the legitimate user's knowledge. As this feature is considered normal system behavior, detecting such surveillance would be difficult. Disabling this feature prevents potential covert location tracking of company devices and their users.

Impact:

Disabling Find My Friends prevents users from sharing their location with contacts through the Find My app. This restriction does not affect other device location features such as Find My Mac that can be used for device recovery.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Find My Friends` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Find My Friends` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Find My Friends`
8. On the left side of the page set `Allow Find My Friends` to `False`
9. Click `Review + save`
10. Verify that `Allow Find My Friends` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	15.1 Maintain an Inventory of Authorized Wireless Access Points Maintain an inventory of authorized wireless access points connected to the wired network.		●	●

Internal Only - General

2.8.24 Ensure "Allow AirDrop" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When enabled, AirDrop allows users to share content with nearby Apple devices without requiring network infrastructure or internet connectivity. AirDrop uses Bluetooth for device discovery and establishes a direct, encrypted WiFi connection for the actual file transfers. The service can be configured to accept transfers from contacts only or from everyone within range.

Rationale:

Disabling AirDrop prevents unauthorized file transfers between organizational and non-organizational devices. This eliminates a potential vector for malware introduction and data exfiltration that could bypass network monitoring and other DLP controls. When AirDrop is active, users may receive unsolicited transfer requests which could contain malicious content.

Impact:

Users will be unable to use AirDrop for file transfer.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow AirDrop` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Airdrop` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow AirDrop`
8. On the left side of the page set `Allow AirDrop` to `False`
9. Click `Review + save`
10. Verify that `Allow AirDrop` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	6.7 Centralize Access Control Centralize access control for all enterprise assets through a directory service or SSO provider, where supported.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	15.4 Disable Wireless Access on Devices if Not Required Disable wireless access on devices that do not have a business purpose for wireless access.			●

Internal Only - General

2.8.25 Ensure "Allow Password Auto Fill" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

Password Auto Fill is a feature in macOS that allows automatic population of stored credentials from iCloud Keychain or third-party password managers into Safari and apps. When enabled, the system retrieves passwords from these sources and offers to automatically fill them into login forms. The feature also suggests generated passwords when creating accounts.

Rationale:

Disabling Password Auto Fill reduces the risk of unauthorized access to accounts if a device is compromised or left unattended. While password managers can enhance security through the use of unique, complex passwords, the auto-fill functionality may allow credentials to be entered without additional authentication.

Impact:

The system will no longer automatically fill stored passwords or suggest passwords when creating new accounts. This may result in users choosing weaker passwords or reusing the same password across multiple systems if not provided with an alternative organizational password management solution.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Password Auto Fill` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Password AutoFill` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Password Auto Fill`
8. On the left side of the page set `Allow Password Auto Fill` to `False`
9. Click `Review + save`
10. Verify that `Allow Password Auto Fill` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	9.1 Ensure Use of Only Fully Supported Browsers and Email Clients Ensure only fully supported browsers and email clients are allowed to execute in the enterprise, only using the latest version of browsers and email clients provided through the vendor.	●	●	●
v7	7.1 Ensure Use of Only Fully Supported Browsers and Email Clients Ensure that only fully supported web browsers and email clients are allowed to execute in the organization, ideally only using the latest version of the browsers and email clients provided by the vendor.	●	●	●

Internal Only - General

2.8.26 Ensure "Allow Cloud Notes" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Notes is a cloud-based service that synchronizes note data across Apple devices using Apple's iCloud infrastructure. When enabled, users can create, store, and access notes through their iCloud account.

Rationale:

Disabling Cloud Notes prevents the synchronization of organizational data to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures information remains within approved storage locations.

Impact:

Users will not be able to sync notes through iCloud services. Local device notes functionality will continue to operate normally, but changes will only be saved locally on the device.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Notes` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Notes` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Notes`
8. On the left side of the page set `Allow Cloud Notes` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Notes` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.27 Ensure "Allow Multiplayer Gaming" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Multiplayer gaming is a feature of Apple's Game Center service that enables users to participate in gaming sessions with other Game Center users. The feature facilitates real-time gameplay between users, and integrates with Game Center's social features for player matching and session management.

Rationale:

The multiplayer gaming functionality creates network connections through Apple's gaming services which can expose organizational devices to unauthorized peer-to-peer communications.

Impact:

Users will be unable to participate in Game Center multiplayer gaming activities.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Multiplayer Gaming` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Game Center's "Multiplayer"` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Multiplayer Gaming`
8. On the left side of the page set `Allow Multiplayer Gaming` to `False`
9. Click `Review + save`
10. Verify that `Allow Multiplayer Gaming` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.28 Ensure "Allow Local User Creation" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting controls whether users can create new local user accounts on macOS devices.

Rationale:

Unmanaged local accounts may bypass organizational authentication controls, avoid security monitoring, and potentially access sensitive data. By disabling this capability, organizations maintain control over user provisioning.

Impact:

Users will be unable to create new local user accounts.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Local User Creation` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Adding Users` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Local User Creation`
8. On the left side of the page set `Allow Local User Creation` to `False`
9. Click `Review + save`
10. Verify that `Allow Local User Creation` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	6.2 Establish an Access Revoking Process Establish and follow a process, preferably automated, for revoking access to enterprise assets, through disabling accounts immediately upon termination, rights revocation, or role change of a user. Disabling accounts, instead of deleting accounts, may be necessary to preserve audit trails.	●	●	●
v8	6.8 Define and Maintain Role-Based Access Control Define and maintain role-based access control, through determining and documenting the access rights necessary for each role within the enterprise to successfully carry out its assigned duties. Perform access control reviews of enterprise assets to validate that all privileges are authorized, on a recurring schedule at a minimum annually, or more frequently.			●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.8.29 Ensure "Allow Apple Personalized Advertising" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Apple provides a framework that allows advertisers to target macOS users with relevant advertisements through the use of a unique identifier. When personalized advertising is enabled, information about user behavior, preferences, and interests is collected and made available to advertisers to facilitate targeted ad delivery.

Rationale:

Disabling personalized advertising prevents the collection and sharing of user behavior data with advertisers, which reduces privacy risks.

Impact:

Users will receive generic advertisements rather than personalized ones in Apple apps and services.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Apple Personalized Advertising` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Apple Personalized Advertising` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Apple Personalized Advertising`
8. On the left side of the page set `Allow Apple Personalized Advertising` to `False`
9. Click `Review + save`
10. Verify that `Allow Apple Personalized Advertising` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.30 Ensure "Allow Printer Sharing Modification" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Printer Sharing allows users to share connected printers with other devices on the network. The printer sharing modification setting controls whether users can enable or disable printer sharing through System Settings. When printer sharing is enabled, other devices can discover and connect to printers attached to the Mac.

Rationale:

When printer sharing is enabled, it increases the attack surface of the device by opening network ports and services that could be exploited by malicious actors. Additionally, unauthorized printer sharing could potentially expose sensitive documents or information to others on the network.

Impact:

If printer sharing was disabled before policy application (system default), it will remain disabled. If printer sharing was enabled by the user before policy application, it will remain enabled and cannot be modified by the user. A separate script should be deployed to ensure printer sharing is actually disabled on all systems, as this policy only restricts user control of the setting.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Printer Sharing Modification` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Printer Sharing Modification` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Printer Sharing Modification`
8. On the left side of the page set `Allow Printer Sharing Modification` to `False`
9. Click `Review + save`
10. Verify that `Allow Printer Sharing Modification` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.31 Ensure "Allow Fingerprint For Unlock" is set appropriately (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

Touch ID on macOS devices enables users to unlock their devices using fingerprint authentication instead of a password. When enabled, this biometric authentication method can be used for device unlock, system preferences access, password autofill, and at other authentication points. Touch ID stores enrolled fingerprint data in the Secure Enclave, a hardware-based security component isolated from the main processor. All Touch ID operations still require the existence of a password, which must be used after device reboots or when the device has not been unlocked for more than 48 hours.

Rationale:

Organizations should evaluate their specific security requirements, threat models, and compliance needs when configuring Touch ID settings. In high-security environments or those with strict compliance requirements, disabling Touch ID may be appropriate to ensure password-based authentication. However, in many enterprise environments, enabling Touch ID can encourage users to set stronger passwords while maintaining a balance between security and usability.

Impact:

Disabling Touch ID requires users to enter their password each time they unlock their device, potentially increasing authentication friction. This may lead to behaviors such as choosing simpler passwords.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Fingerprint For Unlock` is present and set to `True` or `False` depending on organizational security guidelines

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Touch ID To Unlock Mac` is set to `True` or `False` depending on organizational security guidelines

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Fingerprint For Unlock`
8. On the left side of the page set `Allow Fingerprint For Unlock` to `True` or `False` depending on organizational security guidelines
9. Click `Review + save`
10. Verify that `Allow Fingerprint For Unlock` is present and set to `True` or `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.32 Ensure "Allow Diagnostic Submission" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

macOS devices collect and send diagnostic and usage data to Apple to help improve their products and services. This feature includes Mac Analytics, Siri & Dictation improvements, and app developer sharing. When enabled, the device automatically submits diagnostic information.

Rationale:

Automatic submission of analytics and diagnostic data may inadvertently expose internal configurations, usage patterns, or system information.

Impact:

Disabling diagnostic submission prevents Apple from receiving data that helps improve macOS functionality. Users will not contribute to Siri & Dictation improvements, and app developers won't receive crash reports. This may slightly reduce the rate at which bugs affecting the organization are identified and fixed.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Diagnostic Submission` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Diagnostic Submission` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Diagnostic Submission`
8. On the left side of the page set `Allow Diagnostic Submission` to `False`
9. Click `Review + save`
10. Verify that `Allow Diagnostic Submission` is present and set to `False`
11. Click `Save`

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.33 Ensure "Allow Cloud Reminders" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Reminders is a cloud-based service that synchronizes reminder data across Apple devices using Apple's iCloud infrastructure. When enabled, users can create, store, and access reminders through their iCloud account.

Rationale:

Disabling iCloud Reminders prevents the synchronization of organizational data to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures information remains within approved storage locations.

Impact:

Users will not be able to create or access reminders through iCloud services. Local device reminders will continue to function.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Reminders` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Reminders` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Reminders`
8. On the left side of the page set `Allow Cloud Reminders` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Reminders` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.34 Ensure "Allow Password Proximity Requests" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Allow Password Proximity Requests setting controls whether the macOS device can receive password requests from nearby Apple devices using the same Apple ID. When enabled, the Mac can receive notifications asking to share Keychain passwords with nearby Apple devices when those devices attempt to log into websites or apps.

Rationale:

Disabling password proximity requests reduces the risk of unauthorized access to credentials. If nearby devices are compromised, they could request sensitive passwords stored on the organization's Mac.

Impact:

Users will need to use organization-approved methods for sharing credentials when required.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Password Proximity Requests` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Password Proximity Requests` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Password Proximity Requests`
8. On the left side of the page set `Allow Password Proximity Requests` to `False`
9. Click `Review + save`
10. Verify that `Allow Password Proximity Requests` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.35 Ensure "Force On Device Only Dictation" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

macOS offers dictation functionality that can either process speech on-device or send audio data to Apple servers for processing. On-device dictation keeps all speech processing local on the Mac instead of transmitting voice data to Apple's servers.

Rationale:

Enabling on-device dictation prevents voice data from being transmitted to external servers, reducing the risk of sensitive information being exposed through network transmission or third-party processing. This configuration enhances privacy and security by keeping voice data local.

Impact:

On-device dictation may have reduced accuracy compared to cloud-based processing in some scenarios.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Force On Device Only Dictation` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Force On-Device Only Dictation` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Force On Device Only Dictation`
8. On the left side of the page set `Force On Device Only Dictation` to `True`
9. Click `Review + save`
10. Verify that `Force On Device Only Dictation` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.36 Ensure "Allow iPhone Mirroring" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Phone Mirroring is part of Apple's Continuity features that allows macOS devices to access iPhone functionality. When enabled, users can make and receive phone calls, send and receive SMS messages, and use their iPhone's cellular connection from their Mac. This feature requires devices to be signed into the same Apple ID and connected to the same WiFi network or in Bluetooth range.

Rationale:

iPhone Mirroring creates a communication channel between managed macOS devices and potentially unmanaged iPhones. This could allow organizational data to flow between managed and unmanaged devices without proper security controls.

Impact:

Communication activities will be limited to the iPhone device itself.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow iPhone Mirroring` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow iPhone Mirroring` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow iPhone Mirroring`
8. On the left side of the page set `Allow iPhone Mirroring` to `False`
9. Click `Review + save`
10. Verify that `Allow iPhone Mirroring` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	0.0 Explicitly Not Mapped Explicitly Not Mapped			
v7	0.0 Explicitly Not Mapped Explicitly Not Mapped			

Internal Only - General

2.8.37 Ensure "Allow Cloud Mail" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Mail is a cloud-based email service that synchronizes email data across Apple devices using Apple's iCloud infrastructure. When enabled, users can send, receive, and store emails through their iCloud account.

Rationale:

Disabling iCloud Mail prevents the possible synchronization of organizational email communications to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures sensitive communications remain within approved organizational email systems.

Impact:

Users will not be able to configure or sync the iCloud Mail service with their macOS device.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Mail` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Mail` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Mail`
8. On the left side of the page set `Allow Cloud Mail` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Mail` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	9.1 Ensure Use of Only Fully Supported Browsers and Email Clients Ensure only fully supported browsers and email clients are allowed to execute in the enterprise, only using the latest version of browsers and email clients provided through the vendor.	●	●	●
v8	9.3 Maintain and Enforce Network-Based URL Filters Enforce and update network-based URL filters to limit an enterprise asset from connecting to potentially malicious or unapproved websites. Example implementations include category-based filtering, reputation-based filtering, or through the use of block lists. Enforce filters for all enterprise assets.		●	●
v7	7.1 Ensure Use of Only Fully Supported Browsers and Email Clients Ensure that only fully supported web browsers and email clients are allowed to execute in the organization, ideally only using the latest version of the browsers and email clients provided by the vendor.	●	●	●
v7	7.4 Maintain and Enforce Network-Based URL Filters Enforce network-based URL filters that limit a system's ability to connect to websites not approved by the organization. This filtering shall be enforced for each of the organization's systems, whether they are physically at an organization's facilities or not.		●	●

Internal Only - General

2.8.38 Ensure "Allow Universal Control" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

Universal Control is a feature introduced in macOS 13 that allows users to use a single mouse and keyboard to control multiple Mac or iPad devices simultaneously. When enabled, users can move their cursor seamlessly between devices and drag and drop content across them, without additional hardware or setup.

Rationale:

Disabling Universal Control helps prevent potential unauthorized data transfers between devices. This feature could allow sensitive data to be intentionally or unintentionally shared between a managed organizational device and an unmanaged personal device. Additionally, Universal Control creates potential attack vectors where compromised devices could be used to gain access to organizational resources through the input sharing mechanism.

Impact:

Users will not be able to use Universal Control functionality between their Mac and other Apple devices. Users will need to switch input devices or transfer files through approved methods when working across multiple devices.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Universal Control` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow Universal Control` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Universal Control`
8. On the left side of the page set `Allow Universal Control` to `False`
9. Click `Review + save`
10. Verify that `Allow Universal Control` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.8.39 Ensure "Allow Cloud Address Book" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

iCloud Address Book (Contacts) is a cloud-based service that synchronizes contact information across Apple devices using Apple's iCloud infrastructure. When enabled, saved contact details including names, phone numbers, email addresses, physical addresses, and other information is synced with iCloud and made available on all devices signed into the same Apple ID.

Rationale:

Disabling iCloud Address Book prevents the synchronization of organizational contact data to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures contact information remains within approved organizational directory systems.

Impact:

Users will not be able to sync or access contacts through iCloud services. The device contacts application will continue to function locally.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Address Book` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Contacts` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Address Book`
8. On the left side of the page set `Allow Cloud Address Book` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Address Book` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.40 Ensure "Allow Cloud Desktop And Documents" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Desktop and Documents is a feature that automatically synchronizes the contents of a user's Desktop and Documents folders to iCloud storage. These files are made available across all of the user's Apple devices signed into the same Apple ID.

Rationale:

Disabling the iCloud Desktop and Documents sync feature prevents the automatic synchronization of files to Apple's iCloud services. This limitation helps maintain data residency requirements and ensures information remains within approved storage locations.

Impact:

Users will not have their Desktop and Documents folders automatically synchronized to iCloud. Files stored in these locations will remain local to the device only and will not be accessible across multiple devices via iCloud.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Desktop And Documents` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Desktop & Documents` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Desktop And Documents`
8. On the left side of the page set `Allow Cloud Desktop And Documents` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Desktop And Documents` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.41 Ensure "Allow iTunes File Sharing" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

iTunes File Sharing allows apps to share files between a Mac and iOS/iPadOS devices through iTunes. When enabled, it permits the transfer of data between macOS and mobile devices using the iTunes interface.

Rationale:

When enabled, this feature may permit users to intentionally or unintentionally transfer sensitive organizational data to personal devices, bypassing data loss prevention controls.

Impact:

Users will be unable to transfer files between macOS and iOS/iPadOS devices using the iTunes File Sharing feature.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow iTunes File Sharing` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Allow File Transfer using Finder or iTunes` is set to `False`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow iTunes File Sharing`
8. On the left side of the page set `Allow iTunes File Sharing` to `False`
9. Click `Review + save`
10. Verify that `Allow iTunes File Sharing` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.8.42 Ensure "Allow Cloud Keychain Sync" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

iCloud Keychain is a feature that synchronizes passwords, credit card information, WiFi network information, and other sensitive credentials across all of a user's Apple devices. When enabled, this data is encrypted and stored in iCloud.

Rationale:

Disabling iCloud Keychain synchronization prevents organizational credentials from being synchronized to Apple's iCloud services. Enterprise credentials stored in the device Keychain may contain sensitive information such as VPN configurations, WiFi passwords, and application credentials. When synchronized with iCloud, these credentials become stored within a user's personal Apple ID account, which may permit a user to access organizational resources from unmanaged devices, or expose data if an iCloud account becomes compromised.

Impact:

Users will not be able to synchronize their Keychain credentials across devices through iCloud. Local device Keychain functionality will remain operational, allowing credential storage on the individual device.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Restrictions` heading
6. Verify that `Allow Cloud Keychain Sync` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.applicationaccess Profile`
5. Under the `Details` section
6. Confirm `Disallow iCloud Keychain Sync` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Restrictions`
7. Check `Allow Cloud Keychain Sync`
8. On the left side of the page set `Allow Cloud Keychain Sync` to `False`
9. Click `Review + save`
10. Verify that `Allow Cloud Keychain Sync` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v8	15.3 Classify Service Providers Classify service providers. Classification consideration may include one or more characteristics, such as data sensitivity, data volume, availability requirements, applicable regulations, inherent risk, and mitigated risk. Update and review classifications annually, or when significant enterprise changes occur that could impact this Safeguard.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.9 Security

Internal Only - General

2.9.1 Passcode

Internal Only - General

2.9.1.1 Ensure "Max PIN Age In Days" is set to "365" or less (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The Max PIN Age setting enforces automatic expiration of device passcodes after a specified number of days. When configured to 365 days or less, users will be prompted to create a new passcode after the specified time period has elapsed, and must do so before being allowed to unlock the device.

Rationale:

Passwords should be changed periodically to reduce exposure. Organizations with higher security requirements may choose to implement a more frequent rotation schedule.

Impact:

Users will be required to change their device passcode when it expires.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Max PIN Age In Days` is present and set to `365` or less

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Max Age (days)` is set to `365` or less

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Max PIN Age In Days`
8. On the left side of the page set `Max PIN Age In Days` to `365` or less
9. Click `Review + save`
10. Verify that `Max PIN Age In Days` is present and set to `365` or less
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.3 Disable Dormant Accounts Delete or disable any dormant accounts after a period of 45 days of inactivity, where supported.	●	●	●
v7	16.9 Disable Dormant Accounts Automatically disable dormant accounts after a set period of inactivity.	●	●	●

Internal Only - General

2.9.1.2 Ensure "Max Grace Period" is set to "0" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The maximum grace period setting determines the duration, in minutes, during which a device can be unlocked without requiring passcode re-entry after the screen has been locked.

Rationale:

A grace period provides a window of opportunity for unauthorized access to a device when left unattended after screen lock occurs. Setting the grace period to 0 ensures immediate passcode authentication is required upon every unlock attempt.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Max Grace Period` is present and set to `0`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Lock Grace Period (minutes)` is set to `0`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Max Grace Period`
8. On the left side of the page set `Max Grace Period` to `0`
9. Click `Review + save`
10. Verify that `Max Grace Period` is present and set to `0`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.7 Manage Default Accounts on Enterprise Assets and Software Manage default accounts on enterprise assets and software, such as root, administrator, and other pre-configured vendor accounts. Example implementations can include: disabling default accounts or making them unusable.	●	●	●
v7	4.2 Change Default Passwords Before deploying any new asset, change all default passwords to have values consistent with administrative level accounts.	●	●	●

Internal Only - General

2.9.1.3 Ensure "Max Inactivity" is set to "8" or less (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting defines the maximum period of inactivity (in minutes) before screen saver is automatically initiated. When combined with the "Ask For Password" policy defined in the system configuration section of the benchmark, this will enforce a device lock after `8` minutes of inactivity.

Rationale:

Extended periods of inactivity on an unlocked device present security risks. An unattended device may permit unauthorized users to access sensitive data or perform malicious actions. Limiting inactivity to 8 minutes or less reduces the window of opportunity for unauthorized access. This control requires the "Ask For Password" policy to ensure screen saver activation triggers device locking.

While automatic locking provides a security fail-safe, users should be trained to manually lock devices when leaving them unattended and should be familiar with keyboard shortcuts for device locking.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Max Inactivity` is present and set to `8` or less

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Auto-Lock (minutes)` is set to `8` or less

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Max Inactivity`
8. On the left side of the page set `Max Inactivity` to `8` or less
9. Click `Review + save`
10. Verify that `Max Inactivity` is present and set to `8` or less
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.7 Manage Default Accounts on Enterprise Assets and Software Manage default accounts on enterprise assets and software, such as root, administrator, and other pre-configured vendor accounts. Example implementations can include: disabling default accounts or making them unusable.	●	●	●
v7	4.2 Change Default Passwords Before deploying any new asset, change all default passwords to have values consistent with administrative level accounts.	●	●	●

Internal Only - General

2.9.1.4 Ensure "Min Complex Characters" is set to "1" or more (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

This setting enforces at least one complex character to be contained within user device passcodes. Complex characters are non-alphanumeric symbols such as: &, %, $, #, !, @, and other special characters.

A space character is considered a complex character, therefore facilitating the use of passphases without symbols.

Rationale:

Complex characters make passcodes more resistant to password cracking attempts.

Impact:

If this policy is applied to current users, they may need to create new passwords on next login if their existing password does not meet this requirement.

When setting a new password, if the complex character requirement is not met, users will see that the `Contain at last one non-alphanumeric character` condition is not met when prompted to enter a new passcode.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Min Complex Characters` is present and set to `1` or more

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Min Complex Length` is set to `1` or more

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Min Complex Characters`
8. On the left side of the page set `Min Complex Characters` to `1` or more
9. Click `Review + save`
10. Verify that `Min Complex Characters` is present and set to `1` or more
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.5 Ensure "PIN History" is set to "15" or more (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The PIN history setting enforces uniqueness requirements by maintaining a record of previously used passcodes. When set to 15, users must create a passcode that differs from their last 15 used passcodes.

Rationale:

When users can cycle through a few favorite passcodes, the security benefits of periodic passcode changes are undermined.

Impact:

When setting a new password, if the passcode history uniqueness requirement is not met, users will see that the `Not be the same as the previous 15 passwords` condition is not met when prompted to enter a new passcode.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `PIN History` is present and set to `15` or more

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Max History Kept` is set to `15` or more

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `PIN History`
8. On the left side of the page set `PIN History` to `15` or more
9. Click `Review + save`
10. Verify that `PIN History` is present and set to `15` or more
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.6 Ensure "Force PIN" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting requires users to establish a device passcode (PIN) for device authentication. When enabled, users must create and use a passcode to unlock their device.

Rationale:

Without a passcode requirement, a device may remain accessible to anyone who gains physical possession of it.

Impact:

If this policy is applied to current users, they may need to create a passcode on next login if they do not currently have a passcode set.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Force PIN` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Require Password` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Force PIN`
8. On the left side of the page set `Force PIN` to `True`
9. Click `Review + save`
10. Verify that `Force PIN` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.7 Ensure "Password Content Regex" is defined (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Password Content Regex" setting enforces password complexity requirements by defining a regular expression pattern with which passwords must comply. When configured, the system evaluates new passwords against this pattern, rejecting those that fail to match. This setting utilizes ICU syntax for pattern matching and can be used to prevent passwords from containing specific words or patterns. The provided regex pattern `(?i)^(?!.*(password|cis|example)).*` blocks passwords containing defined terms regardless of case sensitivity.

Rationale:

Passwords that contain terms like company names, product names, or common industry words are significantly easier to guess through dictionary attacks and social engineering tactics. Implementing a content regex pattern prevents users from selecting passwords that include defined terms, thereby strengthening the organization's overall password security posture.

Impact:

If this policy is applied to current users, they may need to create new passwords on next login if their existing passwords contain blocked terms.

When setting a new password, if the regex requirement is not met, users will see that `ProfilePayload:<ID>:customRegex` condition is not met when prompted to enter a new passcode. This may cause some users to wonder why their password does not meet password requirements, therefore help desk staff may need to provide guidance to users on acceptable password patterns.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Password Content Regex` is present and set to `(?i)^(?!.*(password|cis|example)).*` (with appropriate words being contained within this regex)

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Password Content Regex` is set to `(?i)^(?!.*(password|cis|example)).*` (with appropriate words being contained within this regex)

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Expand `Custom Regex`
8. Check `Password Content Regex`
9. On the left side of the page set `Password Content Regex` to `(?i)^(?!.*(password|cis|example)).*` substituting an adding words as appropriate.
10. Click `Review + save`
11. Verify that `Password Content Regex` is present and set to `(?i)^(?!.*(password|cis|example)).*` (with defined appropriate words being contained within this regex)
12. Click `Save`

Internal Only - General

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.8 Ensure "Max Failed Attempts" is set to "5" or less (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting defines the maximum number of failed attempts allowed when entering a passcode at the device's lock screen.

When used in combination with the "Minutes Until Failed Login Reset" policy when the attempt threshold is reached, a time delay is imposed before another passcode attempt can be made.

Rationale:

Implementing a passcode attempt restriction mechanism protects against automated and manual password guessing attacks.

Impact:

Users who legitimately forget their passcode or make repeated typing errors may experience temporary device access delays.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Max Failed Attempts` is present and set to `5` or less

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Max Failed Attempts` is set to `5` or less

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Max Failed Attempts`
8. On the left side of the page set `Max Failed Attempts` to `5` or less
9. Click `Review + save`
10. Verify that `Max Failed Attempts` is present and set to `5` or less
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	6.2 Establish an Access Revoking Process Establish and follow a process, preferably automated, for revoking access to enterprise assets, through disabling accounts immediately upon termination, rights revocation, or role change of a user. Disabling accounts, instead of deleting accounts, may be necessary to preserve audit trails.	●	●	●
v7	16.7 Establish Process for Revoking Access Establish and follow an automated process for revoking system access by disabling accounts immediately upon termination or change of responsibilities of an employee or contractor . Disabling these accounts, instead of deleting accounts, allows preservation of audit trails.		●	●

Internal Only - General

2.9.1.9 Ensure "Allow Simple Passcode" is set to "False" (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

This setting prevents the use of simple device authentication passcodes on macOS devices by disallowing passcodes that contain two consecutive identical characters or three sequential characters.

Rationale:

Disabling simple passcodes eliminates easily predictable patterns by preventing consecutive repeating characters (such as "11") and sequential patterns (such as "123" or "abc"). This significantly increases the complexity of passcodes and enhances the security of the device against password guessing and brute force attempts.

Impact:

Users will be unable to use passcodes containing any two consecutive identical characters (such as "rr" in "corridor") or three sequential characters (such as "abc" or "123"). This restriction applies to all parts of the passcode, which means many common words and conventional password patterns will be disallowed.

If this policy is applied to current users, they may need to create new passwords on next login if their existing passcode does not meet this requirement.

When setting a new password, if the no simple passcode requirement is not met, users will see that the ``Not have two consecutive, or three sequential characters``` condition is not met when prompted to enter a new passcode.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Allow Simple Passcode` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Allow Simple` is set to `False`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Allow Simple Passcode`
8. On the left side of the page set `Allow Simple Passcode` to `False`
9. Click `Review + save`
10. Verify that `Allow Simple Passcode` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.10 Ensure "Minutes Until Failed Login Reset" is set to "15" or more (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting determines the number of minutes that must elapse before the failed login counter is reset after reaching the maximum number of unsuccessful login attempts. This policy requires that the "Max Failed Attempts" policy is also configured, and it starts a time-based delay before additional login attempts can be processed.

Rationale:

Implementing a lockout duration provides an essential control against automated and manual password guessing attempts.

Impact:

Users who exceed the maximum failed login attempts must wait for the specified duration before attempting to authenticate again, even with valid credentials.

During this waiting period, users may see the message `Your account has been disabled. Contact your system administrator for more information.` After the time period this message can be ignored and another attempt it allowed.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Minutes Until Failed Login Reset` is present and set to `15` or more

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Failed Login Reset (minutes)` is set to `15` or more

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Minutes Until Failed Login Reset`
8. On the left side of the page set `Minutes Until Failed Login Reset` to `15` or more
9. Click `Review + save`
10. Verify that `Minutes Until Failed Login Reset` is present and set to `15` or more
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	6.2 Establish an Access Revoking Process Establish and follow a process, preferably automated, for revoking access to enterprise assets, through disabling accounts immediately upon termination, rights revocation, or role change of a user. Disabling accounts, instead of deleting accounts, may be necessary to preserve audit trails.	●	●	●
v7	16.7 Establish Process for Revoking Access Establish and follow an automated process for revoking system access by disabling accounts immediately upon termination or change of responsibilities of an employee or contractor . Disabling these accounts, instead of deleting accounts, allows preservation of audit trails.		●	●

Internal Only - General

2.9.1.11 Ensure "Require Alphanumeric Passcode" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting requires that device passcodes contain at least one alphabetic character (a-z, A-Z) in addition to numerals and other required character types.

Rationale:

Alphanumeric passcodes significantly increase the possible character combinations compared to numeric-only passcodes.

Impact:

If this policy is applied to current users, they may need to create new passwords on next login if their existing passcode does not meet this requirement.

When setting a new password, if the alphanumeric requirement is not met, users will see that the `Contain at least one number and one alphabetic character` condition is not met when prompted to enter a new passcode.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Require Alphanumeric Passcode` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Require Alphanumeric` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Require Alphanumeric Passcode`
8. On the left side of the page set `Require Alphanumeric Passcode` to `True`
9. Click `Review + save`
10. Verify that `Require Alphanumeric Passcode` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.9.1.12 Ensure "Min Length" is set to "15" or more (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When configured to "15" or more, users must create passcodes that contain at least 15 characters when setting or changing their device passcode.

Rationale:

Shorter passcodes are more susceptible to brute force attacks and dictionary-based password cracking attempts. Enforcing a minimum 15-character passcode requirement exponentially increases the number of possible passcodes, making automated cracking methods significantly more difficult.

Impact:

Users may need to adapt to using longer passphrases. This presents an opportunity to encourage the use of non-common passphrases that are easier to remember but harder to guess.

If this policy is applied to current users, they may need to create new passwords on next login if their existing passcode does not meet this requirement.

When setting a new password, if the minimum length requirement is not met, users will see that the `Contain at least 15 characters` condition is not met when prompted to enter a new passcode.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Security` heading
6. Under the `Passcode` subheading
7. Verify that `Min Length` is present and set to `15` or more

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.mobiledevice.passwordpolicy Profile`
5. Under the `Details` section
6. Confirm `Min Password Length` is set to `15` or more

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Security` then `Passcode`
7. Check `Min Length`
8. On the left side of the page set `Min Length` to `15` or more
9. Click `Review + save`
10. Verify that `Min Length` is present and set to `15` or more
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	5.2 Use Unique Passwords Use unique passwords for all enterprise assets. Best practice implementation includes, at a minimum, an 8-character password for accounts using MFA and a 14-character password for accounts not using MFA.	●	●	●
v7	4.4 Use Unique Passwords Where multi-factor authentication is not supported (such as local administrator, root, or service accounts), accounts will use passwords that are unique to that system.		●	●

Internal Only - General

2.10 Software Update

Internal Only - General

2.10.1 Ensure "Automatically Install App Updates" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Automatically Install App Updates" setting controls whether macOS automatically installs updates for applications obtained from the App Store. When set to "True", the system will download and install app updates without requiring user action.

Rationale:

Application updates frequently include security patches that address known vulnerabilities.

Impact:

Automatic app updates may result in changes to application functionality or user interface without notice.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Software Update` heading
6. Verify that `Automatically Install App Updates` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.SoftwareUpdate Profile`
5. Under the `Details` section
6. Confirm `Automatically Install App Updates` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Software Update`
7. Check `Automatically Install App Updates`
8. On the left side of the page set `Automatically Install App Updates` to `True`
9. Click `Review + save`
10. Verify that `Automatically Install App Updates` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.10.2 Ensure "Automatically Install Mac OS Updates" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Automatically Install Mac OS Updates" setting controls whether macOS automatically installs operating system updates. When set to "True", the system will download and install macOS updates without requiring user initiation.

Rationale:

Operating system updates address security vulnerabilities, stability issues, and feature enhancements. By automatically installing these updates, organizations ensure that systems are protected against known security threats sooner.

Impact:

Enabling automatic macOS updates may result in system restarts outside of user control. While the system generally sends a prompt to the user requesting restart & installation, some critical updates may eventually force a restart.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Software Update` heading
6. Verify that `Automatically Install Mac OS Updates` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.SoftwareUpdate Profile`
5. Under the `Details` section
6. Confirm `Automatically Install macOS Updates` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Software Update`
7. Check `Automatically Install Mac OS Updates`
8. On the left side of the page set `Automatically Install Mac OS Updates` to `True`
9. Click `Review + save`
10. Verify that `Automatically Install Mac OS Updates` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.10.3 Ensure "Automatic Check Enabled" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Automatic Check Enabled" setting controls whether macOS automatically checks for software updates. When set to "True", the system regularly queries Apple's update servers to identify available updates for the operating system and installed applications.

Rationale:

Without automatic checking, systems may remain vulnerable to known exploits for extended periods as checks for updates would only be triggered by the user.

Additionally, if 'Automatically check for updates' is not enabled, background updates for Apple's XProtect and Gatekeeper malware definition files will not occur. These security mechanisms are critical for protecting macOS against malware and require regular definition updates to remain effective against threats.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Software Update` heading
6. Verify that `Automatic Check Enabled` is present and set to `True`

Or, from the device:

1. Open a Terminal
2. Run the following command to verify that software updates are automatically checked:

```
/usr/bin/sudo /usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SoftwareUpdate')\
.objectForKey('AutomaticCheckEnabled').js
EOS
```

3. The output of `true` is expected

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Software Update`
7. Check `Automatic Check Enabled`
8. On the left side of the page set `Automatic Check Enabled` to `True`
9. Click `Review + save`
10. Verify that `Automatic Check Enabled` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.10.4 Ensure "Critical Update Install" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When "Critical Update Install" is enabled, the system will download and install security updates without user intervention, ensuring that critical security patches are applied swiftly.

Rationale:

Automatic installation of these updates reduces the window of exposure to potential security threats and maintains system integrity.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Software Update` heading
6. Verify that `Critical Update Install` is present and set to `True`

Or, from the device:

1. Open a Terminal
2. Run the following commands to verify that system data files and security updates are automatically checked:

```
/usr/bin/sudo /usr/bin/osascript -l JavaScript << EOS
function run() {
  let pref =
ObjC.unwrap($.NSUserDefaults.alloc.initWithSuiteName('com.apple.SoftwareUpdat
e')\
  .objectForKey('CriticalUpdateInstall'))
  if (pref == 1) {
    return("true")
  } else {
    return("false")
  }
}
EOS
```

3. The output of `true` is expected

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Software Update`
7. Check `Critical Update Install`
8. On the left side of the page set `Critical Update Install` to `True`
9. Click `Review + save`
10. Verify that `Critical Update Install` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.10.5 Ensure "Automatic Download" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Automatic Download" setting controls whether macOS automatically downloads updates when they become available. When set to "True", the system will download new updates from the App Store without user initiation.

Rationale:

Pre-downloading updates ensures that security patches and critical fixes can be applied promptly when installation is initiated. This can be achieved automatically with the "Automatically Install App Updates" policy.

Impact:

Automatic downloads consume bandwidth and disk space in the background, which may affect network performance.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `Software Update` heading
6. Verify that `Automatic Download` is present and set to `True`

Or, from the device:

1. Open a Terminal
2. Run the following command to verify that software updates are automatically checked:

```
/usr/bin/sudo /usr/bin/osascript -l JavaScript << EOS
$.NSUserDefaults.alloc.initWithSuiteName('com.apple.SoftwareUpdate')\
.objectForKey('AutomaticDownload').js
EOS
```

3. The output of `true` is expected

Alternatively, from the device:

1. Open `System Settings`
2. Select `General`
3. Select `Software Update`
4. Click the `i` button
5. Verify that `Download new updates when available` is enabled and can not be disabled

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `Software Update`
7. Check `Automatic Download`
8. On the left side of the page set `Automatic Download` to `True`
9. Click `Review + save`
10. Verify that `Automatic Download` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	7.3 Perform Automated Operating System Patch Management Perform operating system updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v8	7.4 Perform Automated Application Patch Management Perform application updates on enterprise assets through automated patch management on a monthly, or more frequent, basis.	●	●	●
v7	3.4 Deploy Automated Operating System Patch Management Tools Deploy automated software update tools in order to ensure that the operating systems are running the most recent security updates provided by the software vendor.	●	●	●
v7	3.5 Deploy Automated Software Patch Management Tools Deploy automated software update tools in order to ensure that third-party software on all systems is running the most recent security updates provided by the software vendor.	●	●	●

Internal Only - General

2.11 System Configuration

Internal Only - General

2.11.1 Energy Saver

Internal Only - General

2.11.1.1 Ensure "Display Sleep Timer" is set to "10" or less, but not 0 (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "Display Sleep Timer" controls the duration of inactivity before the display enters sleep mode. This setting is required for reliable System Sleep Timer functionality. Display sleep only turns off the screen and does not trigger system re-authentication.

Rationale:

Setting an appropriate display sleep timer ensures the System Sleep Timer functions reliably, which is critical for FileVault security.

Impact:

Users will need to reactivate displays after inactivity periods. Additional screen saver passcode controls defined in this benchmark will enforce passcode re-entry when implemented.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Energy Saver` subheading
7. Under `Desktop Power`
8. Verify that `Display Sleep Timer` is present and set to `10` or less, but not 0
9. Under `Laptop Battery Power`
10. Verify that `Display Sleep Timer` is present and set to `10` or less, but not 0
11. Under `Laptop Power`
12. Verify that `Display Sleep Timer` is present and set to `10` or less, but not 0

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.MCX Profile`
5. Under the `Details` section
6. Confirm `Desktop Power Settings` is set to `Display Sleep Timer = 10` or `Not Applicable For This Computer`
7. Confirm `Portable Power Settings` is set to `Display Sleep Timer = 10` or `Not Applicable For This Computer`
8. Confirm `Portable Battery Settings` is set to `Display Sleep Timer = 10` or `Not Applicable For This Computer`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Energy Saver`
7. Expand `Desktop Power`
8. Check `Display Sleep Timer`
9. Expand `Laptop Battery Power`
10. Check `Display Sleep Timer`
11. Expand `Laptop Power Power`
12. Check `Display Sleep Timer`
13. On the left side of the page set all instances of `Display Sleep Timer` to `10` or less, but not 0
14. Click `Review + save`
15. Verify that `Display Sleep Timer` is present three times and is set to `10` or less, but not 0
16. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	16.11 Lock Workstation Sessions After Inactivity Automatically lock workstation sessions after a standard period of inactivity.	●	●	●

Internal Only - General

2.11.1.2 Ensure "System Sleep Timer" is set to "15" or less, but not 0 (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

The "System Sleep Timer" controls the duration of inactivity before system sleep activation. This operates independently from the display sleep timer but requires "Display Sleep Timer" configuration to function consistently.

Rationale:

This setting ensures unattended devices enter sleep mode promptly. When the "Destroy FV Key On Standby" recommendation is applied, this will ensure FileVault encryption keys are effectively destroyed on sleep, requiring re-authentication to access encrypted data.

Impact:

Users must wake the device up from sleep, causing a minor delay.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Energy Saver` subheading
7. Under `Desktop Power`
8. Verify that `System Sleep Timer` is present and set to `15` or less, but not 0
9. Under `Laptop Battery Power`
10. Verify that `System Sleep Timer` is present and set to `15` or less, but not 0
11. Under `Laptop Power`
12. Verify that `System Sleep Timer` is present and set to `15` or less, but not 0

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.MCX Profile`
5. Under the `Details` section
6. Confirm `Desktop Power Settings` is set to `System Sleep Timer = 15` or `Not Applicable For This Computer`
7. Confirm `Portable Power Settings` is set to `System Sleep Timer = 15` or `Not Applicable For This Computer`
8. Confirm `Portable Battery Settings` is set to `System Sleep Timer = 15` or `Not Applicable For This Computer`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Energy Saver`
7. Expand `Desktop Power`
8. Check `System Sleep Timer`
9. Expand `Laptop Battery Power`
10. Check `System Sleep Timer`
11. Expand `Laptop Power Power`
12. Check `System Sleep Timer`
13. On the left side of the page set all instances of `System Sleep Timer` to `15` or less, but not 0
14. Click `Review + save`
15. Verify that `System Sleep Timer` is present three times and is set to `15` or less, but not 0
16. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	16.11 Lock Workstation Sessions After Inactivity Automatically lock workstation sessions after a standard period of inactivity.	●	●	●

Internal Only - General

2.11.1.3 Ensure "Wake on LAN" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting controls whether a Mac can be awakened from sleep through network access. When enabled, the system can be remotely activated by wake packets sent over the network, allowing the computer to be accessed when it would otherwise be in sleep mode.

Rationale:

Disabling Wake on LAN prevents unauthorized users from remotely waking the system, which could be used in an attempt to gain access to an secured or unattended device.

Impact:

In modern computing environments, disabling Wake on LAN has minimal operational impact. Modern MDM solutions like Intune do not rely on Wake on LAN functionality for management operations, instead communicating with devices when they are online and applying policies when devices check in.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Energy Saver` subheading
7. Under `Desktop Power`
8. Verify that `Wake on LAN` is present and set to `False`
9. Under `Laptop Battery Power`
10. Verify that `Wake on LAN` is present and set to `False`
11. Under `Laptop Power`
12. Verify that `Wake on LAN` is present and set to `False`

Or, from the device:

1. Open a Terminal
2. Run the following command to verify that a profile is installed that disables Wake On Lan is installed:

```
/usr/bin/sudo /usr/bin/profiles -P -o stdout | /usr/bin/grep "Wake On LAN"
```

3. The following output is expected:

```
"Wake On LAN" = 0;
"Wake On LAN" = 0;
"Wake On LAN" = 0;
```


Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Energy Saver`
7. Expand `Desktop Power`
8. Check `Wake on LAN`
9. Expand `Laptop Battery Power`
10. Check `Wake on LAN`
11. Expand `Laptop Power Power`
12. Check `Wake on LAN`
13. On the left side of the page set all instances of `Wake on LAN` to `False`
14. Click `Review + save`
15. Verify that `Wake on LAN` is present three times and is set to `False`
16. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.11.1.4 Ensure "Wake On Modem Ring" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting controls whether a Mac can be awakened from sleep when it detects a signal from a modem connected to the system. When enabled, an incoming call to a connected modem will cause the system to wake from sleep mode.

Rationale:

Disabling Wake on Modem Ring prevents unauthorized users from remotely waking the system via a modem, which could be used in an attempt to gain access to an secured or unattended device.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Energy Saver` subheading
7. Under `Desktop Power`
8. Verify that `Wake on Modem Ring` is present and set to `False`
9. Under `Laptop Battery Power`
10. Verify that `Wake on Modem Ring` is present and set to `False`
11. Under `Laptop Power`
12. Verify that `Wake on Modem Ring` is present and set to `False`

Or, from the device:

1. Open a Terminal
2. Run the following command to verify that a profile is installed that disables Wake On Lan is installed:

```
/usr/bin/sudo /usr/bin/profiles -P -o stdout | /usr/bin/grep "Wake On Modem
Ring"
```

3. The following output is expected:

```
"Wake On Modem Ring" = 0;
"Wake On Modem Ring" = 0;
"Wake On Modem Ring" = 0;
```


Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Energy Saver`
7. Expand `Desktop Power`
8. Check `Wake on Modem Ring`
9. Expand `Laptop Battery Power`
10. Check `Wake on Modem Ring`
11. Expand `Laptop Power Power`
12. Check `Wake on Modem Ring`
13. On the left side of the page set all instances of `Wake on Modem Ring` to `False`
14. Click `Review + save`
15. Verify that `Wake on Modem Ring` is present three times and is set to `False`
16. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.11.1.5 Ensure "Destroy FV Key On Standby" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When enabled, the FileVault keys are completely destroyed from the SMC or RAM when the system enters sleep, requiring the user to re-enter their password upon wakeup to decrypt the disk.

Rationale:

FileVault keys temporarily stored in SMC or RAM during standby could be vulnerable to extraction through cold boot attacks or memory analysis. By destroying these keys during standby, an additional layer of protection is provided for encrypted data, even if an attacker gains physical access to the device while in standby mode.

Impact:

This may slightly increase the time required for a system to wake from standby, as the user must re-authenticate to decrypt the FileVault volume.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Energy Saver` subheading
7. Verify that `Destroy FV Key On Standby` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.MCX Profile`
5. Under the `Details` section
6. Confirm `Remove FileVault Key on Standby` is set to `True`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Energy Saver`
7. Check `Destroy FV Key On Standby`
8. On the left side of the page set `Destroy FV Key On Standby` to `True`
9. Click `Review + save`
10. Verify that `Destroy FV Key On Standby` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v8	4.8 Uninstall or Disable Unnecessary Services on Enterprise Assets and Software Uninstall or disable unnecessary services on enterprise assets and software, such as an unused file sharing service, web application module, or service function.		●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●
v7	9.2 Ensure Only Approved Ports, Protocols and Services Are Running Ensure that only network ports, protocols, and services listening on a system with validated business needs, are running on each system.		●	●

Internal Only - General

2.11.2 Screensaver

Internal Only - General

2.11.2.1 Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

When enabled, the system will prompt for authentication whenever the screen saver is deactivated. When combined with the "Max Inactivity" policy defined in the passcode subsection of the benchmark, this will enforce a device lock when the screen saver is triggered.

Rationale:

Requiring password authentication after screen saver activation ensures that only authorized users can regain access to the system.

The "Ask For Password Delay" should be absent or set to "0" (seconds), to ensure that a passcode is required immediately after the screen saver has started.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `Screensaver` subheading
7. Verify that `Ask For Password` is present and set to `True`
8. Verify that `Ask For Password Delay` is absent or set to `0`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.screensaverProfile`
5. Under the `Details` section
6. Confirm `Ask For Password` is set to `True`
7. Confirm `Ask For Password Delay` is absent or set to `0`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `Screensaver`
7. Check `Ask For Password`
8. On the left side of the page set `Ask For Password` to `True` (a module name must also be provided)
9. Click `Review + save`
10. Verify that `Ask For Password` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.7 Manage Default Accounts on Enterprise Assets and Software Manage default accounts on enterprise assets and software, such as root, administrator, and other pre-configured vendor accounts. Example implementations can include: disabling default accounts or making them unusable.	●	●	●
v7	4.2 Change Default Passwords Before deploying any new asset, change all default passwords to have values consistent with administrative level accounts.	●	●	●

Internal Only - General

2.11.3 System Extensions

Internal Only - General

2.11.3.1 Ensure "Allow User Overrides" is set to "False" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting controls whether users can approve system extensions that aren't explicitly allowed by configuration profiles. System extensions are software components that extend the functionality of macOS by integrating with the kernel or other system services without requiring kernel extensions (kexts).

Rationale:

System extensions can access sensitive system resources and function. Examples include network content filters that can intercept traffic, endpoint security tools that can monitor system events, and DNS proxies that can redirect queries. When users can approve such extensions, they may authorize potentially malicious components that compromise security or violate organizational policies. This restriction ensures only administrator-vetted system extensions run on managed devices.

Impact:

Users will be unable to approve system extensions. Legitimate system extensions that are needed but not pre-approved via configuration profiles will be blocked until administrators explicitly allow them. Some previously approved third-party system extensions may cease to function after this policy is applied.

To allow specific system extensions to operate, administrators must add entries to the "Allowed Team Identifiers" list within the "System Extensions" configuration. Team IDs can be discovered on devices using the Terminal command `systemextensionsctl list`, or found within the application's Info.plist file. The Team ID remains consistent across all devices and through software updates, enabling efficient management of approved extensions. Once added to the allowed list, the application will function normally, requesting necessary extension permissions that can be granted.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Configuration` heading
6. Under the `System Extensions` subheading
7. Verify that `Allow User Overrides` is present and set to `False`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.system-extension-policy Profile`
5. Under the `Details` section
6. Confirm `User approvals allowed?` is set to `No`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Configuration` then `System Extensions`
7. Check `Allow User Overrides`
8. On the left side of the page set `Allow User Overrides` to `False`
9. Click `Review + save`
10. Verify that `Allow User Overrides` is present and set to `False`
11. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.12 System Policy Control

Internal Only - General

2.12.1 System Policy Control

Internal Only - General

2.12.1.1 Ensure "Enable XProtect Malware Upload" is set to "Disabled" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

XProtect Malware Upload is a feature that allows Gatekeeper to upload suspicious files to Apple's servers for analysis when malware is detected.

Rationale:

While this feature contributes to Apple's malware detection improvements, it may result in sensitive organizational data being transmitted to external servers.

Impact:

This may marginally reduce Apple's ability to detect new malware variants across their product ecosystem.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Policy Control` heading
6. Under the `System Policy Control` subheading
7. Verify that `Enable XProtect Malware Upload` is present and set to `Disabled`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.systempolicy.control Profile`
5. Under the `Details` section
6. Confirm `XProtect Malware Upload` is set to `Disallow`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Policy Control` then `System Policy Control`
7. Check `Enable XProtect Malware Upload`
8. On the left side of the page set `Enable XProtect Malware Upload` to `Disabled`
9. Click `Review + save`
10. Verify that `Enable XProtect Malware Upload` is present and set to `Disabled`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	10.1 Deploy and Maintain Anti-Malware Software Deploy and maintain anti-malware software on all enterprise assets.	●	●	●
v8	10.2 Configure Automatic Anti-Malware Signature Updates Configure automatic updates for anti-malware signature files on all enterprise assets.	●	●	●
v8	10.5 Enable Anti-Exploitation Features Enable anti-exploitation features on enterprise assets and software, where possible, such as Microsoft® Data Execution Prevention (DEP), Windows® Defender Exploit Guard (WDEG), or Apple® System Integrity Protection (SIP) and Gatekeeper™.		●	●
v7	8.2 Ensure Anti-Malware Software and Signatures are Updated Ensure that the organization's anti-malware software updates its scanning engine and signature database on a regular basis.	●	●	●
v7	8.4 Configure Anti-Malware Scanning of Removable Devices Configure devices so that they automatically conduct an anti-malware scan of removable media when inserted or connected.	●	●	●

Internal Only - General

2.12.1.2 Ensure Gatekeeper is configured for application installs from Identified Developers only (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This recommendation configures Gatekeeper to allow application installations only from the Mac App Store and identified developers with valid code signatures.

It requires both the "Enable Assessment" setting to be set to "True" (enabling Gatekeeper) and the "Allow Identified Developers" setting to be set to "True".

Rationale:

Gatekeeper helps protect systems from malicious applications by verifying that applications are from trusted sources before allowing them to run. By enabling "Allow Identified Developers," the system permits applications from both the Mac App Store and developers who have registered with Apple and digitally signed their applications.

Impact:

Users will be unable to install or run applications that are not from the Mac App Store or from identified developers with valid code signatures. Some legitimate but unsigned applications may not launch until the developer obtains proper signing credentials from Apple.

If this policy is applied to machines with software already installed from unidentified developers, those applications will not launch.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Policy Control` heading
6. Under the `System Policy Control` subheading
7. Verify that `Enable Assessment` is present and set to `True`
8. Verify that `Allow Identified Developers` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.systempolicy.control Profile`
5. Under the `Details` section
6. Confirm `Policies` is set to `Enable`
7. Confirm `Identified Developers` is set to `Allow`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Policy Control` then `System Policy Control`
7. Check `Enable Assessment`
8. Check `Allow Identified Developers`
9. On the left side of the page set `Enable Assessment` to `True`
10. On the left side of the page set `Allow Identified Developers` to `True`
11. Click `Review + save`
12. Verify that `Enable Assessment` is present and set to `True`
13. Verify that `Allow Identified Developers` is present and set to `True`
14. Click `Save`

Default Value:

Not configured

Internal Only - General

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	10.1 Deploy and Maintain Anti-Malware Software Deploy and maintain anti-malware software on all enterprise assets.	●	●	●
v8	10.2 Configure Automatic Anti-Malware Signature Updates Configure automatic updates for anti-malware signature files on all enterprise assets.	●	●	●
v8	10.5 Enable Anti-Exploitation Features Enable anti-exploitation features on enterprise assets and software, where possible, such as Microsoft® Data Execution Prevention (DEP), Windows® Defender Exploit Guard (WDEG), or Apple® System Integrity Protection (SIP) and Gatekeeper™.		●	●
v7	8.2 Ensure Anti-Malware Software and Signatures are Updated Ensure that the organization's anti-malware software updates its scanning engine and signature database on a regular basis.	●	●	●
v7	8.4 Configure Anti-Malware Scanning of Removable Devices Configure devices so that they automatically conduct an anti-malware scan of removable media when inserted or connected.	●	●	●

Internal Only - General

2.12.1.3 Ensure Gatekeeper is configured to block all user application installs (Manual)

Profile Applicability:

- Level 2 - Supervised Devices

Description:

This setting, when implemented in conjunction with the "Restrict Store Software Update Only" policy, will block all user software installation methods. It requires "Enable Assessment" to be set to "True" (enabling Gatekeeper) and "Allow Identified Developers" to be set to "False", restricting installations to Mac App Store applications only. Setting "Restrict Store Software Update Only" to "True" prevents the Mac App Store from launching and installing applications, effectively preventing all user-initiated application installations.

Rationale:

Restricting application installation to approved deployment methods ensures maximum control over software running on organizational devices, eliminating the risk of unauthorized installations. All software deployments will occur through managed distribution channels.

Impact:

Users will be unable to install any applications directly. All applications must be deployed through organizational software distribution methods such as MDM or approved deployment tools.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Policy Control` heading
6. Under the `System Policy Control` subheading
7. Verify that `Enable Assessment` is present and set to `True`
8. Verify that `Allow Identified Developers` is present and set to `False`

For this to be effective, control (Ensure "Restrict Store Software Update Only" is set to "True") must be set.
Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.systempolicy.control Profile`
5. Under the `Details` section
6. Confirm `Policies` is set to `Enable`
7. Confirm `Identified Developers` is set to `Disallow`

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Policy Control` then `System Policy Control`
7. Check `Enable Assessment`
8. Check `Allow Identified Developers`
9. On the left side of the page set `Enable Assessment` to `True`
10. On the left side of the page set `Allow Identified Developers` to `False`
11. Click `Review + save`
12. Verify that `Enable Assessment` is present and set to `True`
13. Verify that `Allow Identified Developers` is present and set to `False`
14. Click `Save`

For this to be effective, control (Ensure "Restrict Store Software Update Only" is set to "True") must be set.

Internal Only - General

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	10.1 Deploy and Maintain Anti-Malware Software Deploy and maintain anti-malware software on all enterprise assets.	●	●	●
v8	10.2 Configure Automatic Anti-Malware Signature Updates Configure automatic updates for anti-malware signature files on all enterprise assets.	●	●	●
v8	10.5 Enable Anti-Exploitation Features Enable anti-exploitation features on enterprise assets and software, where possible, such as Microsoft® Data Execution Prevention (DEP), Windows® Defender Exploit Guard (WDEG), or Apple® System Integrity Protection (SIP) and Gatekeeper™.		●	●
v7	8.2 Ensure Anti-Malware Software and Signatures are Updated Ensure that the organization's anti-malware software updates its scanning engine and signature database on a regular basis.	●	●	●
v7	8.4 Configure Anti-Malware Scanning of Removable Devices Configure devices so that they automatically conduct an anti-malware scan of removable media when inserted or connected.	●	●	●

Internal Only - General

2.12.2 System Policy Managed

Internal Only - General

2.12.2.1 Ensure "Disable Override" is set to "True" (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This setting disables the contextual menu option in Finder that allows users to bypass Gatekeeper application verification by right-clicking and selecting "Open" on unsigned applications.

Rationale:

When users can bypass Gatekeeper verification, it may permit the execution of unsigned or maliciously crafted applications that haven't been approved.

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Under `Configuration settings` heading
5. Expand the `System Policy Control` heading
6. Under the `System Policy Managed` subheading
7. Verify that `Disable Override` is present and set to `True`

Or, from the device:

1. Open `System Settings`
2. Click `General`
3. Click `Device Management`
4. Double-click `com.apple.systempolicy.managed Profile`
5. Under the `Details` section
6. Confirm `Open untrusted apps via Finder` is set to `Disallow`

Internal Only - General

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `Configuration`
3. Select the profile which applies to the macOS device
4. Click edit, next to `Configuration settings`
5. Click `Add settings`
6. Select `System Policy Control` then `System Policy Managed`
7. Check `Disable Override`
8. On the left side of the page set `Disable Override` to `True`
9. Click `Review + save`
10. Verify that `Disable Override` is present and set to `True`
11. Click `Save`

Default Value:

Not configured

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

2.13 Profile Implementation

Internal Only - General

2.13.1 Ensure Configuration Profile Can Not be Removed by an End User (Manual)

Profile Applicability:

- Level 1 - Supervised Devices

Description:

This recommendation focuses on preventing end users from removing management profiles from organizational macOS devices. When properly implemented, the option to remove a management profile in System Settings should be grayed out (disabled), which indicates the device is enrolled via Apple Business Manager (ABM). If the removal button is clickable but requires authentication, this represents an alternative implementation. The ABM enrollment method is preferred and the most effective method to ensure management profiles remain locked to devices and cannot be removed, even by users with administrative privileges.

Rationale:

If users can remove configuration profiles, they may intentionally or unintentionally circumvent security controls, potentially exposing the organization to security risks. Using Apple Business Manager enrollment creates a stronger binding between the management system (Intune MDM) and the device that persist when administrative users attempt to remove management profiles, ensuring continuous enforcement of policies.

Impact:

Organizations must establish an ABM account and register devices before deployment.

Internal Only - General

Audit:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `MacOS`
3. Select `Enrollment`
4. Select `Enrollment program tokens`
5. Select the organizations token with devices synced to it
6. Under the `Manage` heading, select `profiles`
7. Select the macOS profile assigned to organization macOS machines
8. Under the `Manage` heading, select `Properties`
9. Ensure `Locked enrollment` is set to `Yes`
10. Under the `Monitor` heading, select `Assigned devices`
11. Ensure that this profile is assigned to all organization macOS devices

From the macOS device:

1. Open System Settings
2. Click General
3. Click Device Management
4. Select `Management Profile`
5. Click the `–` symbol
6. Ensure this cannot be clicked (grayed out)
7. If the button can be clicked, ensure that a password is required before the profile can be removed

Remediation:

From the Microsoft Intune admin center:

1. Select `Devices`
2. Select `MacOS`
3. Select `Enrollment`
4. Select `Enrollment program tokens`
5. If no token exists, select `Create token` and follow the ABM/ASM token creation workflow
6. Select the token for your organization
7. Under the `Manage` heading, select `Profiles`
8. Either select an existing profile or select `Create profile`
9. Configure the profile and ensure `Locked enrollment` is set to `Yes`
10. Under `Assignment`, ensure the profile is assigned to appropriate device groups
11. Click `Review + create`
12. Click `Create`

Internal Only - General

Default Value:

Enrollment method dependant

CIS Controls:

Controls Version	Control	IG 1	IG 2	IG 3
v8	4.1 Establish and Maintain a Secure Configuration Process Establish and maintain a secure configuration process for enterprise assets (end-user devices, including portable and mobile, non-computing/IoT devices, and servers) and software (operating systems and applications). Review and update documentation annually, or when significant enterprise changes occur that could impact this Safeguard.	●	●	●
v7	5.1 Establish Secure Configurations Maintain documented, standard security configuration standards for all authorized operating systems and software.	●	●	●

Internal Only - General

Appendix: Summary Table

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
1	**Benchmark Guidance**		
2	**Recommendations for Supervised (Organization) Devices**		
2.1	**Accounts**		
2.1.1	**Accounts**		
2.1.1.1	Ensure "Disable Guest Account" is set to "True" (Manual)	☐	☐
2.2	**App Store**		
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True" (Manual)	☐	☐
2.3	**Full Disk Encryption**		
2.3.1	**FIleVault**		
2.3.1.1	Ensure "User Enters Missing Info" is set to "True" (Manual)	☐	☐
2.3.1.2	Ensure "Enable" is set to "On" (Manual)	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0" (Manual)	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled" (Manual)	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True" (Manual)	☐	☐
2.3.2	**FileVault Options**		
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True" (Manual)	☐	☐

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.3.3	**Endpoint Disk Encryption**		
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy (Manual)	☐	☐
2.4	**Login**		
2.4.1	**Login Window Behavior**		
2.4.1.1	Ensure "Show Full Name" is set to "True" (Manual)	☐	☐
2.4.2	**Login Window Login Items**		
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True" (Manual)	☐	☐
2.5	**Managed Settings**		
2.5.1	**MDM Options**		
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately (Manual)	☐	☐
2.6	**Networking**		
2.6.1	**Content Caching**		
2.6.1.1	Ensure "Auto Activation" is set to "False" (Manual)	☐	☐
2.6.2	**Firewall**		
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True" (Manual)	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True" (Manual)	☐	☐
2.7	**Profile Removal Password**		
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access (Manual)	☐	☐
2.8	**Restrictions**		

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False" (Manual)	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False" (Manual)	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False" (Manual)	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False" (Manual)	☐	☐
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False" (Manual)	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False" (Manual)	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False" (Manual)	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False" (Manual)	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days (Manual)	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False" (Manual)	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False" (Manual)	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False" (Manual)	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False" (Manual)	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False" (Manual)	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False" (Manual)	☐	☐

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.8.16	Ensure "Allow Game Center" is set to "False" (Manual)	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False" (Manual)	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False" (Manual)	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False" (Manual)	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False" (Manual)	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False" (Manual)	☐	☐
2.8.22	Ensure "Allow Content Caching" is set to "False" (Manual)	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False" (Manual)	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False" (Manual)	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False" (Manual)	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False" (Manual)	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False" (Manual)	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False" (Manual)	☐	☐
2.8.29	Ensure "Allow Apple Personalized Advertising" is set to "False" (Manual)	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False" (Manual)	☐	☐

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately (Manual)	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False" (Manual)	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False" (Manual)	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False" (Manual)	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True" (Manual)	☐	☐
2.8.36	Ensure "Allow iPhone Mirroring" is set to "False" (Manual)	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False" (Manual)	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False" (Manual)	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False" (Manual)	☐	☐
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False" (Manual)	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False" (Manual)	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False" (Manual)	☐	☐
2.9	**Security**		
2.9.1	**Passcode**		
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less (Manual)	☐	☐

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.9.1.2	Ensure "Max Grace Period" is set to "0" (Manual)	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less (Manual)	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more (Manual)	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more (Manual)	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True" (Manual)	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined (Manual)	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less (Manual)	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False" (Manual)	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more (Manual)	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True" (Manual)	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more (Manual)	☐	☐
2.10	**Software Update**		
2.10.1	Ensure "Automatically Install App Updates" is set to "True" (Manual)	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True" (Manual)	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True" (Manual)	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True" (Manual)	☐	☐
2.10.5	Ensure "Automatic Download" is set to "True" (Manual)	☐	☐

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.11	**System Configuration**		
2.11.1	**Energy Saver**		
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0 (Manual)	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0 (Manual)	☐	☐
2.11.1.3	Ensure "Wake on LAN" is set to "False" (Manual)	☐	☐
2.11.1.4	Ensure "Wake On Modem Ring" is set to "False" (Manual)	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True" (Manual)	☐	☐
2.11.2	**Screensaver**		
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0" (Manual)	☐	☐
2.11.3	**System Extensions**		
2.11.3.1	Ensure "Allow User Overrides" is set to "False" (Manual)	☐	☐
2.12	**System Policy Control**		
2.12.1	**System Policy Control**		
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled" (Manual)	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only (Manual)	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs (Manual)	☐	☐
2.12.2	**System Policy Managed**		

Internal Only - General

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
2.12.2.1	Ensure "Disable Override" is set to "True" (Manual)	☐	☐
2.13	**Profile Implementation**		
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User (Manual)	☐	☐

Internal Only - General

Appendix: CIS Controls v7 IG 1 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False"	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False"	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False"	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False"	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v7 IG 2 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.1.1.1	Ensure "Disable Guest Account" is set to "True"	☐	☐
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.1.1	Ensure "Auto Activation" is set to "False"	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False"	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False"	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False"	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False"	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False"	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False"	☐	☐
2.8.22	Ensure "Allow Content Caching" is set to "False"	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False"	☐	☐
2.8.29	Ensure "Allow Apple Personalized Advertising" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True"	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False"	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True"	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.3	Ensure "Wake on LAN" is set to "False"	☐	☐
2.11.1.4	Ensure "Wake On Modem Ring" is set to "False"	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v7 IG 3 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.1.1.1	Ensure "Disable Guest Account" is set to "True"	☐	☐
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.1.1	Ensure "Auto Activation" is set to "False"	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False"	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False"	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False"	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False"	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False"	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False"	☐	☐
2.8.22	Ensure "Allow Content Caching" is set to "False"	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False"	☐	☐
2.8.29	Ensure "Allow Apple Personalized Advertising" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True"	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False"	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True"	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.3	Ensure "Wake on LAN" is set to "False"	☐	☐
2.11.1.4	Ensure "Wake On Modem Ring" is set to "False"	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v7 Unmapped Recommendations

Recommendation		Set Correctly	
		Yes	No
	No unmapped recommendations to CIS Controls v7	☐	☐

Internal Only - General

Appendix: CIS Controls v8 IG 1 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.1.1.1	Ensure "Disable Guest Account" is set to "True"	☐	☐
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False"	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True"	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False"	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True"	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v8 IG 2 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.1.1.1	Ensure "Disable Guest Account" is set to "True"	☐	☐
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.1.1	Ensure "Auto Activation" is set to "False"	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False"	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False"	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False"	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False"	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False"	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False"	☐	☐
2.8.22	Ensure "Allow Content Caching" is set to "False"	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False"	☐	☐
2.8.29	Ensure "Allow Apple Personalized Advertising" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True"	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False"	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True"	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.3	Ensure "Wake on LAN" is set to "False"	☐	☐
2.11.1.4	Ensure "Wake On Modem Ring" is set to "False"	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v8 IG 3 Mapped Recommendations

Recommendation		Set Correctly	
		Yes	No
2.1.1.1	Ensure "Disable Guest Account" is set to "True"	☐	☐
2.2.1	Ensure "Restrict Store Software Update Only" is set to "True"	☐	☐
2.3.1.1	Ensure "User Enters Missing Info" is set to "True"	☐	☐
2.3.1.2	Ensure "Enable" is set to "On"	☐	☐
2.3.1.3	Ensure "Defer Force At User Login Max Bypass Attempts" is set to "0"	☐	☐
2.3.1.4	Ensure "Show Recovery Key" is set to "Disabled"	☐	☐
2.3.1.5	Ensure "Force Enable In Setup Assistant" is set to "True"	☐	☐
2.3.2.1	Ensure "Prevent FileVault From Being Disabled" is set to "True"	☐	☐
2.3.3.1	Ensure There is a Disk Encryption FileVault Policy	☐	☐
2.4.1.1	Ensure "Show Full Name" is set to "True"	☐	☐
2.4.2.1	Ensure "Disable Login Items Suppression" is set to "True"	☐	☐
2.5.1.1	Ensure "Activation Lock Allowed While Supervised" is set appropriately	☐	☐
2.6.1.1	Ensure "Auto Activation" is set to "False"	☐	☐
2.6.2.1	Ensure "Enable Stealth Mode" is set to "True"	☐	☐
2.6.2.2	Ensure "Enable Firewall" is set to "True"	☐	☐
2.7.1	Ensure "Removal Password" is absent or is securely configured with restricted access	☐	☐
2.8.1	Ensure "Allow Bluetooth Sharing Modification" is set to "False"	☐	☐
2.8.2	Ensure "Allow Password Sharing" is set to "False"	☐	☐
2.8.3	Ensure "Allow File Sharing Modification" is set to "False"	☐	☐
2.8.4	Ensure "Allow Erase Content And Settings" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.5	Ensure "Allow Air Play Incoming Requests" is set to "False"	☐	☐
2.8.6	Ensure "Allow Media Sharing Modification" is set to "False"	☐	☐
2.8.7	Ensure "Allow Cloud Photo Library" is set to "False"	☐	☐
2.8.8	Ensure "Allow Cloud Document Sync" is set to "False"	☐	☐
2.8.9	Ensure "Enforced Software Update Delay" is absent or less than or equal to 30 days	☐	☐
2.8.10	Ensure "Allow Activity Continuation" is set to "False"	☐	☐
2.8.11	Ensure "Allow Cloud Bookmarks" is set to "False"	☐	☐
2.8.12	Ensure "Allow Cloud Freeform" is set to "False"	☐	☐
2.8.13	Ensure "Allow Cloud Calendar" is set to "False"	☐	☐
2.8.14	Ensure "Allow ARD Remote Management Modification" is set to "False"	☐	☐
2.8.15	Ensure "Allow Assistant" is set to "False"	☐	☐
2.8.17	Ensure "Allow Auto Unlock" is set to "False"	☐	☐
2.8.18	Ensure "Allow Startup Disk Modification" is set to "False"	☐	☐
2.8.19	Ensure "Allow UI Configuration Profile Installation" is set to "False"	☐	☐
2.8.20	Ensure "Allow Device Name Modification" is set to "False"	☐	☐
2.8.21	Ensure "Allow Internet Sharing Modification" is set to "False"	☐	☐
2.8.22	Ensure "Allow Content Caching" is set to "False"	☐	☐
2.8.23	Ensure "Allow Find My Friends" is set to "False"	☐	☐
2.8.24	Ensure "Allow AirDrop" is set to "False"	☐	☐
2.8.25	Ensure "Allow Password Auto Fill" is set to "False"	☐	☐
2.8.26	Ensure "Allow Cloud Notes" is set to "False"	☐	☐
2.8.27	Ensure "Allow Multiplayer Gaming" is set to "False"	☐	☐
2.8.28	Ensure "Allow Local User Creation" is set to "False"	☐	☐
2.8.29	Ensure "Allow Apple Personalized Advertising" is set to "False"	☐	☐
2.8.30	Ensure "Allow Printer Sharing Modification" is set to "False"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.8.31	Ensure "Allow Fingerprint For Unlock" is set appropriately	☐	☐
2.8.32	Ensure "Allow Diagnostic Submission" is set to "False"	☐	☐
2.8.33	Ensure "Allow Cloud Reminders" is set to "False"	☐	☐
2.8.34	Ensure "Allow Password Proximity Requests" is set to "False"	☐	☐
2.8.35	Ensure "Force On Device Only Dictation" is set to "True"	☐	☐
2.8.37	Ensure "Allow Cloud Mail" is set to "False"	☐	☐
2.8.38	Ensure "Allow Universal Control" is set to "False"	☐	☐
2.8.39	Ensure "Allow Cloud Address Book" is set to "False"	☐	☐
2.8.40	Ensure "Allow Cloud Desktop And Documents" is set to "False"	☐	☐
2.8.41	Ensure "Allow iTunes File Sharing" is set to "False"	☐	☐
2.8.42	Ensure "Allow Cloud Keychain Sync" is set to "False"	☐	☐
2.9.1.1	Ensure "Max PIN Age In Days" is set to "365" or less	☐	☐
2.9.1.2	Ensure "Max Grace Period" is set to "0"	☐	☐
2.9.1.3	Ensure "Max Inactivity" is set to "8" or less	☐	☐
2.9.1.4	Ensure "Min Complex Characters" is set to "1" or more	☐	☐
2.9.1.5	Ensure "PIN History" is set to "15" or more	☐	☐
2.9.1.6	Ensure "Force PIN" is set to "True"	☐	☐
2.9.1.7	Ensure "Password Content Regex" is defined	☐	☐
2.9.1.8	Ensure "Max Failed Attempts" is set to "5" or less	☐	☐
2.9.1.9	Ensure "Allow Simple Passcode" is set to "False"	☐	☐
2.9.1.10	Ensure "Minutes Until Failed Login Reset" is set to "15" or more	☐	☐
2.9.1.11	Ensure "Require Alphanumeric Passcode" is set to "True"	☐	☐
2.9.1.12	Ensure "Min Length" is set to "15" or more	☐	☐
2.10.1	Ensure "Automatically Install App Updates" is set to "True"	☐	☐
2.10.2	Ensure "Automatically Install Mac OS Updates" is set to "True"	☐	☐
2.10.3	Ensure "Automatic Check Enabled" is set to "True"	☐	☐
2.10.4	Ensure "Critical Update Install" is set to "True"	☐	☐

Internal Only - General

Recommendation		Set Correctly	
		Yes	No
2.10.5	Ensure "Automatic Download" is set to "True"	☐	☐
2.11.1.1	Ensure "Display Sleep Timer" is set to "10" or less, but not 0	☐	☐
2.11.1.2	Ensure "System Sleep Timer" is set to "15" or less, but not 0	☐	☐
2.11.1.3	Ensure "Wake on LAN" is set to "False"	☐	☐
2.11.1.4	Ensure "Wake On Modem Ring" is set to "False"	☐	☐
2.11.1.5	Ensure "Destroy FV Key On Standby" is set to "True"	☐	☐
2.11.2.1	Ensure "Ask For Password" is set to "True" and "Ask For Password Delay" is absent or set to "0"	☐	☐
2.11.3.1	Ensure "Allow User Overrides" is set to "False"	☐	☐
2.12.1.1	Ensure "Enable XProtect Malware Upload" is set to "Disabled"	☐	☐
2.12.1.2	Ensure Gatekeeper is configured for application installs from Identified Developers only	☐	☐
2.12.1.3	Ensure Gatekeeper is configured to block all user application installs	☐	☐
2.12.2.1	Ensure "Disable Override" is set to "True"	☐	☐
2.13.1	Ensure Configuration Profile Can Not be Removed by an End User	☐	☐

Internal Only - General

Appendix: CIS Controls v8 Unmapped Recommendations

Recommendation		Set Correctly	
		Yes	No
	No unmapped recommendations to CIS Controls v8	☐	☐

Internal Only - General

Appendix: Change History

Date	Version	Changes for this version
Apr 21, 2025	1.0.0	Initial Draft Released (Ticket 24647)
May 30, 2025	1.0.0	Initial Release

Internal Only - General