

# **Object-oriented design: Interfaces, Subtyping and Polymorphism**

CS 115

---

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong, and Dr. Howard Hamilton

Last updated: February 6, 2025

## **Polymorphism, dynamic binding, hidden functions & operators**

---

## Interface inheritance

- Rather than reusing implementation, reuse interface!

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface
- Key idea:

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface
- Key idea:
  - introduce abstract interface (the base class)



# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface
- Key idea:
  - introduce abstract interface (the base class)
  - write the function in terms of this interface

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface
- Key idea:
  - introduce abstract interface (the base class)
  - write the function in terms of this interface
  - develop 3 derived classes that extend this base class and implements (virtual) functions of the base class

# Interface inheritance

- Rather than reusing implementation, reuse interface!
  - program to an interface, not an implementation
- Say we want to develop 3 similar functions; how to rather implement one?
  - via a common interface
- Key idea:
  - introduce abstract interface (the base class)
  - write the function in terms of this interface
  - develop 3 derived classes that extend this base class and implements (virtual) functions of the base class
  - C++ compiler will do the rest via *dynamic binding*

## Example: Summing All Elements in a List-like structure

- Array version:

## Example: Summing All Elements in a List-like structure

- Array version:

## Example: Summing All Elements in a List-like structure

- Array version:

```
int sumArray(const int A[], unsigned int n) {  
    int sum = 0;  
    unsigned int i = 0;  
    while (i < n) {  
        sum += A[i];  
        i++;  
    }  
    return sum;  
}
```



# ManagedArray Version

```
int sumManagedArray(const ManagedArray &A) {  
    int sum = 0;  
    unsigned i = 0;  
    while (i < A.length()) {  
        sum += A.retrieve(i);  
        i++;  
    }  
    return sum;  
}
```



## Standard Input Stream Version

# Standard Input Stream Version

```
int sumStandardInputStream() {  
    int sum = 0;  
    int next;  
    cin >> next;  
    while (cin) {  
        sum += next;  
        cin >> next;  
    }  
    return sum;  
}
```

## Reducing Redundancy

- All the examples were doing essentially the same thing

# Reducing Redundancy

- All the examples were doing essentially the same thing
- In Pseudocode:

# Reducing Redundancy

- All the examples were doing essentially the same thing
- In Pseudocode:

# Reducing Redundancy

- All the examples were doing essentially the same thing
- In Pseudocode:

```
int sumDataSource(a data source) {  
    int sum = 0;  
    while (data source has not been exhausted) {  
        sum += next entry in the data source;  
        exclude the retrieved entry from future consideration;  
    }  
    return sum;  
}
```

- How can we make this concrete code?

## Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class

## Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class
  - Give a dummy value of 0



## Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class
  - Give a dummy value of 0
- An *abstract class* has at least one virtual method

## Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class
  - Give a dummy value of 0
- An *abstract class* has at least one virtual method
  - Gives *interface* without an implementation

## Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class
  - Give a dummy value of 0
- An *abstract class* has at least one virtual method
  - Gives *interface* without an implementation

# Abstract Classes and the Virtual keyword

- When we declare a method as virtual, it *must be overridden* in some child class
  - Give a dummy value of 0
- An *abstract class* has at least one virtual method
  - Gives *interface* without an implementation

```
class DataSource {  
public:  
    // exhausted  
    virtual bool exhausted() const = 0; // pure virtual function  
    // next  
    virtual int next() = 0; // pure virtual function  
};
```

- Abstract class can't be instantiated (but can be referenced or extended)

# Generic Code via Abstract Classes

# Generic Code via Abstract Classes

```
int sumDataSource(DataSource &ds) {  
    int sum = 0;  
    while (! ds.exhausted()) {  
        sum += ds.next();  
    }  
    return sum;  
}
```

- What's new: can be applied to instances of any derived class of DataSource

# Generic Code via Abstract Classes

```
int sumDataSource(DataSource &ds) {  
    int sum = 0;  
    while (! ds.exhausted()) {  
        sum += ds.next();  
    }  
    return sum;  
}
```

- What's new: can be applied to instances of any derived class of DataSource
- Called a **polymorphic function**

## Extending the Interface

- Array Version



## Extending the Interface

- Array Version
  - Has the same methods as DataSource

# Extending the Interface

- Array Version
  - Has the same methods as DataSource
  - BUT we specify the concrete representation

## Extending the Interface

- Array Version
  - Has the same methods as DataSource
  - BUT we specify the concrete representation
    - `private` fields

## Extending the Interface

- Array Version
  - Has the same methods as DataSource
  - BUT we specify the concrete representation
    - `private` fields

# Extending the Interface

- Array Version
  - Has the same methods as DataSource
  - BUT we specify the concrete representation
    - private fields

```
const unsigned ARRAY_DATA_SOURCE_CAPACITY = 10000;

class ArrayDataSource : public DataSource {
public:
    ArrayDataSource(const int A[], unsigned int n);
    virtual bool exhausted() const;
    virtual int next();
private:
    int data[ARRAY_DATA_SOURCE_CAPACITY];
    unsigned length;
    unsigned i;
};
```

## Implementing the Interface

- Must give implementation of each unspecified method from DataSource

## Implementing the Interface

- Must give implementation of each unspecified method from DataSource

# Implementing the Interface

- Must give implementation of each unspecified method from DataSource

```
ArrayDataSource::ArrayDataSource(const int A[], unsigned int n) {  
    assert(n < ARRAY_DATA_SOURCE_CAPACITY);  
    for (unsigned int k = 0; k < n; k++)  
        data[k] = A[k];  
    length = n;  
    i = 0;  
}  
  
bool ArrayDataSource::exhausted() const {  
    return i == length;  
}  
  
int ArrayDataSource::next() {  
    assert(! exhausted());  
    i++;  
    return data[i - 1];  
}
```





# Dynamic Binding

```
// set up and initialize managed array data source  
int A[ ] = { 1, 3, 9, -2 };  
ArrayDataSource ads(A, 4);  
  
// call sumDataSource to add up entries  
int sum = sumDataSource(ads);
```

- Which version of `exhausted()` and `next()` to use in `sumDataSource(ads)`?

# Dynamic Binding

```
// set up and initialize managed array data source  
int A[ ] = { 1, 3, 9, -2 };  
ArrayDataSource ads(A, 4);  
  
// call sumDataSource to add up entries  
int sum = sumDataSource(ads);
```

- Which version of `exhausted()` and `next()` to use in `sumDataSource(ads)`?
  - determined **at runtime**

# Dynamic Binding

```
// set up and initialize managed array data source  
int A[ ] = { 1, 3, 9, -2 };  
ArrayDataSource ads(A, 4);  
  
// call sumDataSource to add up entries  
int sum = sumDataSource(ads);
```

- Which version of `exhausted()` and `next()` to use in `sumDataSource(ads)`?
  - determined **at runtime**
  - depends on the exact type of object `ads` is bound to

# Dynamic Binding

```
// set up and initialize managed array data source  
int A[ ] = { 1, 3, 9, -2 };  
ArrayDataSource ads(A, 4);  
  
// call sumDataSource to add up entries  
int sum = sumDataSource(ads);
```

- Which version of `exhausted()` and `next()` to use in `sumDataSource(ads)`?
  - determined **at runtime**
  - depends on the exact type of object `ads` is bound to
    - In this case, `ArrayDataSource`

## A Different Instance

- For `ManagedArray`

## A Different Instance

- For `ManagedArray`

# A Different Instance

- For ManagedArray

```
class ManagedArrayDataSource : public DataSource {
public:
    ManagedArrayDataSource(const ManagedArray &A);
    virtual bool exhausted() const;
    virtual int next();
private:
    ManagedArray array;
    unsigned int i;
};
```





# Implementation

```
ManagedArrayDataSource::ManagedArrayDataSource(const ManagedArray& A)
: array(A.length()) {
    for (unsigned int k = 0; k < A.length(); k++)
        array.store(k, A.retrieve(k));
    i = 0;
}

bool ManagedArrayDataSource::exhausted() const {
    return i == array.length();
}

int ManagedArrayDataSource::next() {
    assert(! exhausted());
    i++;
    return array.retrieve(i - 1);
}
```

## Dynamic Binding for the Managed Array Version

# Dynamic Binding for the Managed Array Version

```
// set up and initialize managed array data source  
int A[] = { 1, 3, 9, -2 };  
ManagedArray ma;  
for (unsigned int i = 0; i < 4; i++)  
    ma.store(i, A[i]);  
ManagedArrayDataSource mads(ma);  
  
// call sumDataSource to add up entries  
int sum = sumDataSource(mads);
```

- The code of `sumDataSource` *has not changed!*

# Dynamic Binding for the Managed Array Version

```
// set up and initialize managed array data source
int A[] = { 1, 3, 9, -2 };
ManagedArray ma;
for (unsigned int i = 0; i < 4; i++)
    ma.store(i, A[i]);
ManagedArrayDataSource mads(ma);

// call sumDataSource to add up entries
int sum = sumDataSource(mads);
```

- The code of `sumDataSource` *has not changed!*
  - But next and exhausted functions it was provided have

# Static Binding Example

- Static means “at compile time”

## Static Binding Example

- Static means “at compile time”
- C++ uses static by default

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)



# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

```
class C {  
public:  
    void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    void f() { /* impl 2*/}  
    ...  
};
```

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

```
class C {  
public:  
    void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    void f() { /* impl 2*/}  
    ...  
};
```

# Static Binding Example

- Static means “at compile time”
- C++ uses static by default
  - Not true in other languages (Java, Python)

```
class C {  
public:  
    void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    void f() { /* impl 2*/}  
    ...  
};
```

```
void g(C &c) {  
    c.f( );  
}  
  
int main() {  
    D d;  
    // static binding: impl.2 invoked  
    d.f();  
    // static binding: impl.1 invoked  
    g(d);  
    return 0;  
}
```

## Dynamic Binding Example

- Dynamic means “at run time”

## Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding



## Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

## Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

## Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

# Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

```
class C {  
public:  
    virtual void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    // implicitly virtual  
    void f() { /* impl 2*/}  
    ...  
};
```

# Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

```
class C {  
public:  
    virtual void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    // implicitly virtual  
    void f() { /* impl 2*/}  
    ...  
};
```

# Dynamic Binding Example

- Dynamic means “at run time”
  - `virtual` keyword tells C++ to use dynamic binding

```
class C {  
public:  
    virtual void f() { /* impl 1*/}  
    ...  
};  
  
class D : public C {  
public:  
    // implicitly virtual  
    void f() { /* impl 2*/}  
    ...  
};
```

```
void g(C &c) {  
    c.f( );  
}  
  
int main() {  
    D d;  
    // static binding:  
    //     impl.2 invoked  
    d.f();  
    // dynamic binding: impl.2 invoked  
    g(d);  
    return 0;  
}
```

## Overloading is Static

- Overloading, *not overriding*

## Overloading is Static

- Overloading, *not overriding*



# Overloading is Static

- Overloading, *not overriding*

```
class E : public C {  
public:  
    // This does not override f() in class C  
    // so it is not implicitly virtual  
    void f(int i) { /* implementation 3 */ }  
    ...  
};  
  
int main() {  
    E e;  
    e.f(); // static binding: impl.1 invoked  
    e.f(4); // static binding: impl.3 invoked  
    return 0;  
}
```

- From the Greek

# Polymorphism

- From the Greek
  - *Poly* : many

# Polymorphism

- From the Greek
  - *Poly* : many
  - *Morphos* : forms

# Polymorphism

- From the Greek
  - *Poly* : many
  - *Morphos* : forms
- OOP lets us write one function that works on many types

# Polymorphism

- From the Greek
  - *Poly* : many
  - *Morphos* : forms
- OOP lets us write one function that works on many types
- This is *subtyping polymorphism*

# Polymorphism

- From the Greek
  - *Poly* : many
  - *Morphos* : forms
- OOP lets us write one function that works on many types
- This is *subtyping polymorphism*
  - We'll see another kind later

- From the Greek
  - *Poly* : many
  - *Morphos* : forms
- OOP lets us write one function that works on many types
- This is *subtyping polymorphism*
  - We'll see another kind later
  - If A extends B, you can use a B object anywhere an A is expected



- From the Greek
  - *Poly* : many
  - *Morphos* : forms
- OOP lets us write one function that works on many types
- This is *subtyping polymorphism*
  - We'll see another kind later
  - If A extends B, you can use a B object anywhere an A is expected
  - If A extends B, we say A is a *subtype* of B

# What Actually Are Objects?

- We can finally say what an object *is*:

# What Actually Are Objects?

- We can finally say what an object *is*:
  - An instance of a class

# What Actually Are Objects?

- We can finally say what an object *is*:
  - An instance of a class
  - Containing a value for each field of that class

# What Actually Are Objects?

- We can finally say what an object *is*:
  - An instance of a class
  - Containing a value for each field of that class
  - *and* containing a pointer to the implementation of each virtual method of that class

# What Actually Are Objects?

- We can finally say what an object *is*:
  - An instance of a class
  - Containing a value for each field of that class
  - *and* containing a pointer to the implementation of each virtual method of that class
- Objects package data and operations together

## Subtyping as a Safer Alternative to Unions

- Recall our library code

## Subtyping as a Safer Alternative to Unions

- Recall our library code



# Subtyping as a Safer Alternative to Unions

- Recall our library code

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    CatalogEntryType tag;  
    union {  
        struct { unsigned int pages; } book;  
        struct { unsigned int discs, minutes; } dvd;  
    } variant;  
};
```

- Can do better with OOP

## CatalogEntry Abstract Class

- Base class with all of the shared fields

## CatalogEntry Abstract Class

- Base class with all of the shared fields

# CatalogEntry Abstract Class

- Base class with all of the shared fields

```
class CatalogEntry {  
public:  
    // e.g. an operation we want to do for any entry  
    virtual void printInfo() = 0;  
protected:  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    // No tag or variant-specific info  
};
```

## A Book Subtype

## A Book Subtype

```
//Book.h
class BookEntry : public CatalogEntry {
public:
    void printInfo();
private:
    int pages;
}

// Book.cpp
void BookEntry::printInfo(){
    // Have all CatalogEntry fields
    // plus pages
    cout << title << author ...
        << pages;
}
```

## A DVD Subtype

## A DVD Subtype

```
//Book.h
class DVDEntry : public CatalogEntry {
public:
    void printInfo();
private:
    int discs;
    int minutes;
}

// Book.cpp
void DVDEntry::printInfo(){
    // Have all CatalogEntry fields
    // plus pages
    cout << title << author ...
        << discs << minutes;
}
```



## Hidden functions and operators

- A function or operator in the base class with the same name and parameters as a function in the derived class

## Hidden functions and operators

- A function or operator in the base class with the same name and parameters as a function in the derived class
  - can access using the base-class type qualifier

## Hidden functions and operators

- A function or operator in the base class with the same name and parameters as a function in the derived class
  - can access using the base-class type qualifier

# Hidden functions and operators

- A function or operator in the base class with the same name and parameters as a function in the derived class
  - can access using the base-class type qualifier

```
void Derived1::func() {  
    // func() is defined in both  
    // the base and the child class Derived1  
    Base1::func();  
    // ...  
}  
  
// same for operators  
Derived1 &Derived1::operator=(const Derived1 &original) {  
    if (this != &original) {  
        // = is defined in both the base and the child class  
        Base1::operator=(original);  
        field1 = original.field1;  
    }  
    return *this;  
}
```

# Hidden Function Example

# Hidden Function Example

## Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation

## Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation



# Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation

```
void CatalogEntry::printInfo(){  
    cout << title << author <<  
        ... << callNumber;  
}
```

- BookEntry and DVDEntry  
then only need to deal with  
their specific fields

# Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation

```
void CatalogEntry::printInfo(){  
    cout << title << author <<  
        ... << callNumber;  
}
```

- BookEntry and DVDEntry  
then only need to deal with  
their specific fields
  - Can call the base type  
version for the rest;

# Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation

```
void CatalogEntry::printInfo(){  
    cout << title << author <<  
        ... << callNumber;  
}
```

- BookEntry and DVDEntry  
then only need to deal with  
their specific fields
  - Can call the base type  
version for the rest;

# Hidden Function Example

- Leave  
CatalogEntry::printInfo()  
as virtual, but give it an  
implementation

```
void CatalogEntry::printInfo(){  
    cout << title << author <<  
        ... << callNumber;  
}
```

- BookEntry and DVDEntry  
then only need to deal with  
their specific fields
  - Can call the base type  
version for the rest;

# Hidden Function Example

- Leave `CatalogEntry::printInfo()` as virtual, but give it an implementation

```
void CatalogEntry::printInfo(){  
    cout << title << author <<  
        ... << callNumber;  
}
```

- `BookEntry` and `DVDEntry` then only need to deal with their specific fields
  - Can call the base type version for the rest;

```
void BookEntry::printInfo() {  
    // Call the base class version  
    // to print the shared fields  
    CatalogEntry::printInfo();  
    // Print our specific fields  
    cout << pages;  
}
```

```
void DVDEntry::printInfo() {  
    CatalogEntry::printInfo();  
    cout << discs << minutes;  
}
```