

Records

CS 115

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong, and Dr. Howard Hamilton

Last updated: January 8, 2025

Structs and unions

Motivation

Motivation

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

```
string titles[N];  
string authors[N];  
string publishers[N];  
unsigned int publishingYears[N];  
string callNumbers[N];  
double Price[N];
```

- Poor choice of interface!

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

```
string titles[N];  
string authors[N];  
string publishers[N];  
unsigned int publishingYears[N];  
string callNumbers[N];  
double Price[N];
```

- Poor choice of interface!
- (many arguments to pass for functions)

Use a record instead!

Use a record instead!

Use a record instead!

- Data can be heterogenous

Use a record instead!

- Data can be heterogenous
- Define:

Use a record instead!

- Data can be heterogenous
- Define:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

Use a record instead!

- Data can be heterogenous
- Define:
- Only 1 argument needs to be passed

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

```
c.title = "Peter Pan";  
c.author = "J. M. Barrie";  
c.publisher = "Scribner";  
c.publishingYear = 1980;  
c.callNumber = "B2754 1980";
```

Initializing a Record

- As with arrays

Initializing a Record

- As with arrays

Initializing a Record

- As with arrays

```
CatalogEntry c = {"Peter Pan",  
                  "J. M. Barrie",  
                  "Scribner",  
                  1980,  
                  "B2754 1980"};
```

Copying a Record

Copying a Record

```
// initialization list  
CatalogEntry c = { ... };  
  
// initialization by copying  
CatalogEntry c1 = c;  
  
// default initialization  
CatalogEntry c2;  
// assignment operator  
c2 = c;
```

Functions operating on records

Functions operating on records

```
void printCatalogEntry(CatalogEntry c){  
    cout << "Title: " << c.title << endl;  
    cout << "Author: " << c.author << endl;  
    cout << "Publisher: " << c.publisher << endl;  
    cout << "Publishing Year: " << c.publishingYear << endl;  
    cout << "Call Number: " << c.callNumber << endl;  
}
```

- As usual, by default arguments are passed by value (call by value)

Functions operating on records

- For efficiency, call by reference is also supported

Functions operating on records

- For efficiency, call by reference is also supported

Functions operating on records

- For efficiency, call by reference is also supported

```
void printCatalogEntry(const CatalogEntry &c){  
    cout << "Title: " << c.title << endl;  
    cout << "Author: " << c.author << endl;  
    cout << "Publisher: " << c.publisher << endl;  
    cout << "Publishing Year: " << c.publishingYear << endl;  
    cout << "Call Number: " << c.callNumber << endl;  
}
```

Equality checking

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&
- c1.author == c2.author &&

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&
- c1.author == c2.author &&
- c1.publisher == c2.publisher &&

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&
- c1.author == c2.author &&
- c1.publisher == c2.publisher &&
- c1.publishingYear == c2.publishingYear &&

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&
- c1.author == c2.author &&
- c1.publisher == c2.publisher &&
- c1.publishingYear == c2.publishingYear &&

Equality checking

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry& c1, const CatalogEntry& c2){
```

- return
- c1.title == c2.title &&
- c1.author == c2.author &&
- c1.publisher == c2.publisher &&
- c1.publishingYear == c2.publishingYear &&

```
c1.callNumber == c2.callNumber;  
}
```

Complex record data structures

Complex record data structures

```
CatalogEntry A[3];
```

- CatalogEntry A[] =

Complex record data structures

```
CatalogEntry A[3];
```

- CatalogEntry A[] =

Complex record data structures

```
CatalogEntry A[3];
```

- CatalogEntry A[] =

```
{  
  {"Peter Pan",  
    "J. M. Barrie",//  
    "Scribner",//  
    1980,//  
    "B2754 1980"},  
  
  {"C++ Primer",  
    "Stanley B. Lippman",//  
    "Addison-Wesley",//  
    1998, //
```

Practise!

- See the very first announcement in UR Courses

Practise!

- See the very first announcement in UR Courses
- Try the exercises there

Practise!

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system

Practise!

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system
 - declare a C++ struct to represent a hexagon

Practise!

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system
 - declare a C++ struct to represent a hexagon
 - declare a C++ struct to represent a circle

Complex record data structures

Complex record data structures

```
const int MAX_NAMES = 100;  
  
struct FullName {  
    string name_component[MAX_NAMES];  
    int name_count;  
};
```

Complex record data structures

Complex record data structures

```
const int SCREEN_HEIGHT = 768, SCREEN_WIDTH = 1024;
struct Screen{
    char screen_array[SCREEN_HEIGHT][SCREEN_WIDTH];
};

...

Screen my_screen;
for (int i = 0; i < SCREEN_HEIGHT; i++){
    my_screen.screen_array[i][0] = '*';
}
```


Complex record data structures

Complex record data structures

```
struct str1 {  
    int a[2];  
    int b;  
};  
  
void func1(str1 A[ ]){  
    A[0].a[0] = 10;  
    A[0].a[1] = 20;  
    A[0].b = 30;  
}  
  
int main( ) {  
    str1 A[ ] = {{{1,0},2}, {{3,0},4},{{0,0},9}};  
    func1(A);  
  
    std::cout << A[0].b<<"\n";  
    std::cout << A[0].a[1]<<"\n";  
}
```

Enumerations

- User-defined data type that consists of integral constants

Enumerations

- User-defined data type that consists of integral constants

Enumerations

- User-defined data type that consists of integral constants

```
enum day {  
    Friday = 99, //  
    Saturday, //  
    Sunday = 90, //  
    ...,  
    Thursday //  
};  
  
day d;  
d = Thursday;  
  
if (d == Saturday || d == Sunday)  
    cout << "Enjoy the weekend!" ;  
  
cout << d+1 ;
```

Variant records

- Multiple component fields can be defined

Variant records

- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

```
union Coordinates {  
    int a, //  
    double b, //  
    char c //  
};  
  
Coordinates x;  
  
x.a = 5;  
cout << x.a;           // works, prints 5  
  
x.b = 416.905;          // destroys the value of x.a  
x.c = 'p';              // destroys the value of x.a and x.b  
cout << x.a;           // invalid!
```

Example

Example

```
enum CatalogEntryType {  
    BookEntry, //  
    DVDEntry //  
};  
  
struct BookSpecificInfo {  
    unsigned int pages;  
};  
  
struct DVDSpecificInfo {  
    unsigned int discs;  
    unsigned int minutes;  
};  
  
union CatalogEntryVariantPart {  
    BookSpecificInfo book;
```

Example (cont'd)

Example (cont'd)

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    CatalogEntryType tag;  
    CatalogEntryVariantPart variant;  
};
```

Example (cont'd)

Example (cont'd)

```
void printCatalogEntry(const CatalogEntry& c) {
    cout << "Title: " << c.title << endl;
    ...
    cout << "Call Number: " << c.callNumber << endl;
    switch (c.tag) {
        case BookEntry:
            cout << "Pages: " << c.variant.book.pages << endl;
            break;
        case DVDEntry:
            cout << "Discs: " << c.variant.dvd.discs << endl;
            cout << "Minutes: " << c.variant.dvd.minutes << endl;
            break;
    }
}
```

Anonymous declaration of records and variant-records

- Earlier:

Anonymous declaration of records and variant-records

- Earlier:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

```
union CatalogEntryVariantPart {  
    struct BookSpecificInfo { unsigned int pages; } book;  
    struct DVDSpecificInfo { unsigned int discs, minutes; } dvd;  
};
```

Anonymous declaration of records and variant-records

- Can also anonymize:

Anonymous declaration of records and variant-records

- Can also anonymize:

Anonymous declaration of records and variant-records

- Can also anonymize:

```
union CatalogEntryVariantPart {  
    struct { unsigned int pages; } book;  
    struct { unsigned int discs, minutes; } dvd;  
};
```

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    CatalogEntryType tag;  
    union {  
        struct { unsigned int pages; } book;  
        struct { unsigned int discs, minutes; } dvd;  
    } variant;  
};
```