

Dynamic memory management using Pointers

CS 115

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong,
and Dr. Howard Hamilton

Last updated: March 21, 2025

Pointers and New

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time
 - we can allocate memory of size MAX (a constant)

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time
 - we can allocate memory of size MAX (a constant)
- Problems with this model:

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time
 - we can allocate memory of size MAX (a constant)
- Problems with this model:
 - might run out of space (despite having a lot of unused memory)

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time
 - we can allocate memory of size MAX (a constant)
- Problems with this model:
 - might run out of space (despite having a lot of unused memory)
 - can be under-utilized (e.g. if we only use a small part of MAX)

Static vs Dynamic allocation

- So far used pointers for allocating space during compile-time only
 - error-prone and might be difficult to understand
 - could have avoided by using arrays and references
- But what if we don't know the size of required memory at compile-time
 - we can allocate memory of size MAX (a constant)
- Problems with this model:
 - might run out of space (despite having a lot of unused memory)
 - can be under-utilized (e.g. if we only use a small part of MAX)
- Solution: allocate memory on demand at run-time!

Run-time Allocation

- Allocates memory in *heap* (in contrast to .text, .data, and stack)

Run-time Allocation

- Allocates memory in *heap* (in contrast to `.text`, `.data`, and `stack`)
- Uses keyword `new` to allocate memory

Run-time Allocation

- Allocates memory in *heap* (in contrast to .text, .data, and stack)
- Uses keyword `new` to allocate memory

Run-time Allocation

- Allocates memory in *heap* (in contrast to `.text`, `.data`, and `stack`)
- Uses keyword `new` to allocate memory

```
int *px = new int;  
*px = 777;  
cout << *px;
```

- Must free-up space when done, using keyword `delete` (otherwise memory leak can happen!)

Run-time Allocation

- Allocates memory in *heap* (in contrast to *.text*, *.data*, and *stack*)
- Uses keyword `new` to allocate memory

```
int *px = new int;  
*px = 777;  
cout << *px;
```

- Must free-up space when done, using keyword `delete` (otherwise memory leak can happen!)
 - also clean up any dangling pointers using `nullptr`

Run-time Allocation

- Allocates memory in *heap* (in contrast to *.text*, *.data*, and *stack*)
- Uses keyword `new` to allocate memory

```
int *px = new int;  
*px = 777;  
cout << *px;
```

- Must free-up space when done, using keyword `delete` (otherwise memory leak can happen!)
 - also clean up any dangling pointers using `nullptr`

Run-time Allocation

- Allocates memory in *heap* (in contrast to `.text`, `.data`, and `stack`)
- Uses keyword `new` to allocate memory

```
int *px = new int;  
*px = 777;  
cout << *px;
```

- Must free-up space when done, using keyword `delete` (otherwise memory leak can happen!)
 - also clean up any dangling pointers using `nullptr`

```
...  
delete px;  
px = nullptr;
```

Simple example: Book Record

Simple example: Book Record

```
struct Book {
    string title;
    string author;
    string call_number;
};


void printBook(const Book *pBook){
    cout << "title: " << pBook->title << endl;
    cout << "author: " << pBook->author << endl;
    cout << "call number: " << pBook->call_number;
    cout << endl;
}

int main(){
    // allocate a Book from heap
    Book *pb = new Book;
    pb->title = "Security";
    pb->author = "Matt Bishop";
    pb->call_number = "QA.420";
    printBook(pb);
    delete pb; // explicit deallocation
    return 0;}
```

Pictorial representation: Run-time Allocation

Pictorial representation: Run-time Allocation


```
Book *p;  
p = new Book;  
p -> title = "Emma";
```



Safely Allocating Memory

Safely Allocating Memory

```
Book *pb[10];  
  
for (int i = 0; i < 10; I++){  
    pb[i] = new Book;  
    pb[i] -> title = "Emma";  
}
```




Safely Deallocating Memory

Safely Deallocating Memory

Safely Deallocating Memory


Safely Deallocating Memory

```
for (int i = 0; i < 10; i++)  
    delete pb[i];
```



Safely Deallocating Memory


```
for (int i = 0; i < 10; i++)  
    delete pb[i];
```



- Dangling pointers!

Safely Deallocating Memory


```
for (int i = 0; i < 10; i++)  
    delete pb[i];
```



- Dangling pointers!
- assign `nullptr` to indicate this

Safely Deallocating Memory


```
for (int i = 0; i < 10; i++)  
    delete pb[i];
```



- Dangling pointers!
- assign `nullptr` to indicate this

Safely Deallocating Memory

```
for (int i = 0; i < 10; i++)  
    delete pb[i];
```



- Dangling pointers!
- assign nullptr to indicate this

```
for (int i = 0; i < 10; i++)  
    pb[i] = nullptr;
```


The Null Pointer

- If you ever try to dereference `nullptr`, your program will immediately crash

The Null Pointer

- If you ever try to dereference `nullptr`, your program will immediately crash
 - This is *good!*

The Null Pointer

- If you ever try to dereference `nullptr`, your program will immediately crash
 - This is *good!*
 - Crashes right at the point of failure

The Null Pointer

- If you ever try to dereference `nullptr`, your program will immediately crash
 - This is *good!*
 - Crashes right at the point of failure
 - Doesn't silently fail and access garbage memory


Pointer to dynamic array: Allocation

Pointer to dynamic array: Allocation

Pointer to dynamic array: Allocation


Pointer to dynamic array: Allocation

```
Book *parray = new Book[10];
```



Pointer to dynamic array: Allocation


```
Book *parray = new Book[10];
```



Pointer to dynamic array: Allocation

```
Book *parray = new Book[10];
```


parray



```
for (int i = 0; i < 10; i++)  
    parray[i].title = "Emma";
```

```
// could have also used:  
// (parray+i)->title = "Emma";  
// (*(parray+i)).title = "Emma";
```

parray



Pointer to dynamic array: Deallocation

Pointer to dynamic array: Deallocation

```
Book *parray = new Book[10];  
  
for (int i = 0; i < 10; i++)  
    parray[i].title = "Emma";  
  
...  
  
delete [ ] parray;  
  
parray = nullptr;
```

Arrays are just pointers

- An array *A* is actually just a pointer to the start of the array in memory

Arrays are just pointers

- An array *A* is actually just a pointer to the start of the array in memory
 - This is why arrays are always pass-by-reference

Arrays are just pointers

- An array A is actually just a pointer to the start of the array in memory
 - This is why arrays are always pass-by-reference
- $A[i]$ is the same as $*(A + i)$

Arrays are just pointers

- An array A is actually just a pointer to the start of the array in memory
 - This is why arrays are always pass-by-reference
- $A[i]$ is the same as $*(A + i)$
 - Get the value i places after the start of the array

Arrays are just pointers

- An array A is actually just a pointer to the start of the array in memory
 - This is why arrays are always pass-by-reference
- $A[i]$ is the same as $*(A + i)$
 - Get the value i places after the start of the array
- Why we always need to pass the length of the array

Arrays are just pointers

- An array `A` is actually just a pointer to the start of the array in memory
 - This is why arrays are always pass-by-reference
- `A[i]` is the same as `*(A + i)`
 - Get the value `i` places after the start of the array
- Why we always need to pass the length of the array
 - Address tells us where it starts, not where it ends


Pointer to array of pointers (double pointer): Allocating

Pointer to array of pointers (double pointer): Allocating

Pointer to array of pointers (double pointer): Allocating


Pointer to array of pointers (double pointer): Allocating

```
Book **pparray = new Book*[10];
```



Pointer to array of pointers (double pointer): Allocating



```
Book **pparray = new Book*[10];
```



Pointer to array of pointers (double pointer): Allocating

```
Book **pparray = new Book*[10];
```

```
for (int i = 0; i < 10; i++){  
    parray[i] = new Book;  
    parray[i] -> title = "Emma";  
}
```



Pointer to array of pointers (double pointer): Deallocating

Pointer to array of pointers (double pointer): Deallocating

```
Book **pparray = new Book * [10];  
  
for (int i = 0; i < 10; i++){  
    pparray[i] = new Book;  
    pparray[i] -> title = "Emma";  
}
```

- Deallocation must be done in the reverse order of allocation

Pointer to array of pointers (double pointer): Deallocating

```
Book **pparray = new Book * [10];  
  
for (int i = 0; i < 10; i++){  
    pparray[i] = new Book;  
    pparray[i] -> title = "Emma";  
}
```

- Deallocation must be done in the reverse order of allocation

Pointer to array of pointers (double pointer): Deallocating

```
Book **pparray = new Book * [10];

for (int i = 0; i < 10; i++){
    pparray[i] = new Book;
    pparray[i] -> title = "Emma";
}
```

- Deallocation must be done in the reverse order of allocation

```
for (int i = 0; i < 10; i++){
    delete pparray[i];
    // following is redundant, since we
    // are about to delete parray
    pparray[i] = nullptr;
}

delete [] pparray;
pparray = nullptr;
```

Collection data structures with maximum capacity

- Example: print in reverse order

Collection data structures with maximum capacity

- Example: print in reverse order

Collection data structures with maximum capacity

- Example: print in reverse order

```
const int CAPACITY = 1000;  
  
int main(){  
    int A[CAPACITY];  
    int length;  
  
    cin >> length;  
  
    for (int i = 0; i < length; i++)  
        cin >> A[i];  
  
    for (int i = length - 1; i >= 0; i--)  
        cout << A[i] << endl;  
  
    return 0;  
}
```

Collection data structures w/o maximum capacity

- Example: print in reverse order

Collection data structures w/o maximum capacity

- Example: print in reverse order

Collection data structures w/o maximum capacity

- Example: print in reverse order

```
int main(){
    int length;
    int *A;

    // Read length of sequence
    cin >> length;

    // Allocate enough memory to hold
    // sequence
    A = new int[length];

    for (int i = 0; i < length; i++)
        cin >> A[i];

    // Write sequence in rev. order
    for (int i = length - 1; i >= 0; i--)
        cout << A[i] << endl;

    // Deallocate memory
    delete [] A;
```

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:
- allocate a bigger array

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:
 - allocate a bigger array
 - copy the contents of the old array to the new one

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:
 - allocate a bigger array
 - copy the contents of the old array to the new one
 - deallocate the old array

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:
 - allocate a bigger array
 - copy the contents of the old array to the new one
 - deallocate the old array
- use the new array to store incoming integers until it is filled up again

Dynamically Expanding and Shrinking: IDea

- Initialize the array with some arbitrary capacity
- Insert integers into the array as usual
- When the array is filled up, expand the capacity of the array as follows:
 - allocate a bigger array
 - copy the contents of the old array to the new one
 - deallocate the old array
- use the new array to store incoming integers until it is filled up again
- Deallocate the array when it is no longer needed

Expand/Shrink main function

Expand/Shrink main function

```
int main(){
    // Initialize encapsulated array
    init();

    // Read sequence
    int x;
    cin >> x;
    while (cin){
        append(x);
        cin >> x;
    }

    // Write sequence in reverse order
    for (unsigned int i = length(); i > 0; i--){
        cout << retrieve(i - 1) << endl;
    }

    // Deallocate encapsulated array
    cleanup();

    return 0;
}
```


Initializing

```
// Amount of memory available
unsigned int array_capacity = 0;
// Amount of memory used
unsigned int array_length = 0;
// Actual memory resource
int *array = nullptr;

bool isInitialized(){
    return (array != nullptr);
}

void init(){
    assert(! isInitialized());
    // Default initial capacity
    array_capacity = 4;
    // Array is empty initially
    array_length = 0;
    // Allocate array
    array = new int[array_capacity];
    assert(isInitialized());
} // end init()
```

Example: Append for shrinking/growing

Example: Append for shrinking/growing

```
void append(int x) {  
    assert(isInitialized());  
  
    // Expand capacity if full  
    if (array_length == array_capacity)  
        expand();  
  
    // Append to the end  
    array[array_length] = x;  
    // Update array length  
    array_length++;  
}
```


Expand for Shrinking/Growing

Expand for Shrinking/Growing

```
void expand() {
    assert(isInitialized());
    assert(array_capacity > 0);
    assert(array_length == array_capacity);

    // Calculate new capacity
    int new_array_capacity = array_capacity * 2;
    // Allocate bigger array
    int *new_array = new int[new_array_capacity];

    // Copy contents
    for (unsigned int i = 0; i < array_length; i++)
        new_array[i] = array[i];
    // Deallocate old array
    delete[] array;

    // Use new array and update capacity
    array = new_array;
    array_capacity = new_array_capacity;
    assert(array_length < array_capacity);
}
```

Shrinking/Growing: Retrieve and Cleanup

Shrinking/Growing: Retrieve and Cleanup

```
unsigned int length(){
    assert(isInitialized());
    return array_length;
}


int retrieve(unsigned int i){
    assert(isInitialized());
    assert(i < length());
    return array[i];
}

void cleanup(){
    assert(isInitialized());
    // Deallocate memory resource
    delete [] array;
    // Establish postconditions
    array = nullptr;
    array_capacity = 0;
    array_length = 0;
    assert(! isInitialized());
}
```

Dynamically allocated 2d arrays

Dynamically allocated 2d arrays


```
// allocate the 2D array  
int** parray;
```




Dynamically allocated 2d arrays

```
// allocate the 2D array
```

```
int** parray;
```




```
parray = nullptr;
```




Dynamically allocated 2d arrays

```
// allocate the 2D array
```


```
int** parray;
```



```
parray = nullptr;
```




```
parray = new int*[10];
```



Allocating the Second Dimension

Allocating the Second Dimension

```
// allocate the 2D array  
int** parray = nullptr;  
parray = new int*[10];  
  
for (unsigned int i = 0; i < 10; i++){  
    parray[i] = new int[20];  
}
```



Using Dynamic 2D arrays

Using Dynamic 2D arrays

```
// store 7 in position 6 of row 2  
pparray[2][6] = 7;
```

- How about using pointers?

Using Dynamic 2D arrays

```
// store 7 in position 6 of row 2  
pparray[2][6] = 7;
```

- How about using pointers?

Using Dynamic 2D arrays

```
// store 7 in position 6 of row 2  
pparray[2][6] = 7;
```

- How about using pointers?

```
*(*(parray + 2) + 6) = 7;  
// when done:  
// deallocate in reverse order  
for (unsigned int i = 0; i < 10; i++)  
    delete [] parray[i];  
delete [] parray;
```

