

Review: Types and Values

CS 115

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong,
and Dr. Howard Hamilton

Last updated: February 14, 2025

Leading Towards Polymorphism and Generics

Midterm Details

- **March 7** in-class

Midterm Details

- **March 7** in-class
- Covers all topics up-to and including constructors/overloading

Midterm Details

- **March 7** in-class
- Covers all topics up-to and including constructors/overloading
- May cover both conceptual and practical (code)

The Road Ahead

- Next unit has a significant increase in the complexity of what we're learning

- Next unit has a significant increase in the complexity of what we're learning
 - Powerful but complex features of C++

The Road Ahead

- Next unit has a significant increase in the complexity of what we're learning
 - Powerful but complex features of C++
- To lead to that, we're going to review some more of the basics

The Road Ahead

- Next unit has a significant increase in the complexity of what we're learning
 - Powerful but complex features of C++
- To lead to that, we're going to review some more of the basics
 - Help catch up

What is a value?

- The result of running some computation

What is a value?

- The result of running some computation
 - E.g. 2, true, {1,2,3,4}, 3.1415926535

What is a value?

- The result of running some computation
 - E.g. 2, true, {1,2,3,4}, 3.1415926535
- An *expression* has a value

What is a value?

- The result of running some computation
 - E.g. 2, true, {1, 2, 3, 4}, 3.1415926535
- An *expression* has a value
 - e.g. 2+2 and 1+3 are different expressions that produce the same value

Things that have values

- Variables have values while we're running our program

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$
 - Exception: void return type

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$
 - Exception: void return type
- Array access

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$
 - Exception: `void` return type
- Array access
 - $A[3] + 2$

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$
 - Exception: `void` return type
- Array access
 - $A[3] + 2$
- Class/struct field access

Things that have values

- Variables have values while we're running our program
 - But we might not know what that value is ahead of time
- Arithmetic expressions/using operators $3+4$, $x/9$,
 $2*3*4*5*6$
- Function calls
 - $f(x)$, $\text{sqrt}(2)$, $\text{Counter}(2, 10)$
 - Exception: `void` return type
- Array access
 - $A[3] + 2$
- Class/struct field access
 - `point.x * -1`

Weird things that have values

- The value of $x = y$ is y 's value

Weird things that have values

- The value of $x = y$ is y 's value
 - So can do $x = y = z$ to set all to z

Weird things that have values

- The value of `x = y` is `y`'s value
 - So can do `x = y = z` to set all to `z`
- The value of `stream << "hello"` is another stream

Weird things that have values

- The value of `x = y` is `y`'s value
 - So can do `x = y = z` to set all to `z`
- The value of `stream << "hello"` is another stream
 - So can chain them together

Weird things that have values

- The value of `x = y` is `y`'s value
 - So can do `x = y = z` to set all to `z`
- The value of `stream << "hello"` is another stream
 - So can chain them together
- The value of `i++` is `i`'s original value

Weird things that have values

- The value of `x = y` is `y`'s value
 - So can do `x = y = z` to set all to `z`
- The value of `stream << "hello"` is another stream
 - So can chain them together
- The value of `i++` is `i`'s original value
 - But `++i` has the value of `i` *after* adding one

Where you can use values

- Right hand side of an assignment

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`
 - `A[3] = foo.x`

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`
 - `A[3] = foo.x`
- Argument to a function/operation

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`
 - `A[3] = foo.x`
- Argument to a function/operation
 - `printEntry({1, 2, 3, 4})`

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`
 - `A[3] = foo.x`
- Argument to a function/operation
 - `printEntry({1, 2, 3, 4})`
- return in a function definition

Where you can use values

- Right hand side of an assignment
 - `x = f(3);`
 - `A[3] = foo.x`
- Argument to a function/operation
 - `printEntry({1, 2, 3, 4})`
- return in a function definition
- If a value has a certain type, you can use it *anywhere* that is expecting that type

What is a type?

- A type is a way of classifying values

What is a type?

- A type is a way of classifying values
- Tells you

What is a type?

- A type is a way of classifying values
- Tells you
 - What operations you can perform on a value

What is a type?

- A type is a way of classifying values
- Tells you
 - What operations you can perform on a value
 - Which functions can accept that value as an argument

What is a type?

- A type is a way of classifying values
- Tells you
 - What operations you can perform on a value
 - Which functions can accept that value as an argument
 - What you can do with the return value of a function

Values and Types

- Every value in C++ has a type

Values and Types

- Every value in C++ has a type
 - Some values have more than one type

Values and Types

- Every value in C++ has a type
 - Some values have more than one type
 - e.g. 1 can be `int`, `unsigned int`, `double` etc.

- Every value in C++ has a type
 - Some values have more than one type
 - e.g. 1 can be `int`, `unsigned int`, `double` etc.
 - More examples after the break

Values are NOT types

- `struct`, `class`, and `enum` are all ways of *defining a new type*

Values are NOT types

- `struct`, `class`, and `enum` are all ways of *defining a new type*
- They don't create any values in your program

Values are NOT types

- `struct`, `class`, and `enum` are all ways of *defining a new type*
- They don't create any values in your program
 - They create a whole collection of values that you can use in your program

Example: Struct

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field
- Example values:

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field
- Example values:
 - {"Alice", 1234, 75.2}

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field
- Example values:
 - {"Alice", 1234, 75.2}
 - {"Bob", 5678, 68.99}

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field
- Example values:
 - {"Alice", 1234, 75.2}
 - {"Bob", 5678, 68.99}
 - {"Eve", 2468, 92.45}

Example: Struct

```
struct Student{  
    string name;  
    int studentNum;  
    float average;  
}
```

- This defines a new type named Student
 - Doesn't create any specific values
 - Just tells us what they might look like
- Each Student value contains a value for *each* field
- Example values:
 - {"Alice", 1234, 75.2}
 - {"Bob", 5678, 68.99}
 - {"Eve", 2468, 92.45}
- Each Student contains a string AND an int AND a float

Types are Interchangeable

- Any type can be used as:

Types are Interchangeable

- Any type can be used as:
 - The type of a variable

Types are Interchangeable

- Any type can be used as:
 - The type of a variable
 - The return type of a function

Types are Interchangeable

- Any type can be used as:
 - The type of a variable
 - The return type of a function
 - The type of a function argument

Types are Interchangeable

- Any type can be used as:
 - The type of a variable
 - The return type of a function
 - The type of a function argument
 - Type type of things inside an array

Types are Interchangeable

- Any type can be used as:
 - The type of a variable
 - The return type of a function
 - The type of a function argument
 - Type type of things inside an array
 - The type of a class/struct field

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types
 - `int x;`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types
 - `int x;`
 - `Quadrant q;`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types
 - `int x;`
 - `Quadrant q;`
 - `Point2D p;`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types
 - `int x;`
 - `Quadrant q;`
 - `Point2D p;`
- May need constructor arguments, e.g. `Counter (3,4);`

Example: Declaring Variables

- Every time we declare (create a new) variable, it has the form `TypeName variableName;`
- E.g. `Counter c;`
 - `Counter` is the name of the type;
 - `c` is a name that we pick for the variable to have
- Works with any types
 - `int x;`
 - `Quadrant q;`
 - `Point2D p;`
- May need constructor arguments, e.g. `Counter (3,4);`
- C++ (usually) requires that we specify the type of every variable

Example: Enums

Example: Enums

```
enum Direction{  
North, South, East, West};
```

- Direction is a type

Example: Enums

```
enum Direction{  
North, South, East, West};
```

- `Direction` is a type
- There are exactly 4 values with type `Direction`

Example: Enums

```
enum Direction{  
    North, South, East, West};
```

- `Direction` is a type
- There are exactly 4 values with type `Direction`
 - North, South, East, and West

Types are Static

- **Static:** defined/checked at compile-time

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time
- C++ Types are static

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time
- C++ Types are static
 - Defined at compile-time

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time
- C++ Types are static
 - Defined at compile-time
- Values are dynamic

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time
- C++ Types are static
 - Defined at compile-time
- Values are dynamic
 - They exist in memory at run-time

Types are Static

- **Static:** defined/checked at compile-time
- **Dynamic:** defined/checked at run-time
- C++ Types are static
 - Defined at compile-time
- Values are dynamic
 - They exist in memory at run-time
 - Many values of a particular type may exist throughout the run of a program

- A *class* is a special kind of type

- A *class* is a special kind of type
 - Like a struct: specific fields with values

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*
 - Functions that are attached to a particular object

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*
 - Functions that are attached to a particular object
 - Call using field-access dot notation

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*
 - Functions that are attached to a particular object
 - Call using field-access dot notation
 - `point.print()`

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*
 - Functions that are attached to a particular object
 - Call using field-access dot notation
 - `point.print()`
- Methods can access fields of the object called on

Types in OOP

- A *class* is a special kind of type
 - Like a struct: specific fields with values
- An *object* is a value of some class
- Additionally: class has *methods*
 - Functions that are attached to a particular object
 - Call using field-access dot notation
 - `point.print()`
- Methods can access fields of the object called on
 - Even private

- A constructor creates an object of a given class

- A constructor creates an object of a given class
- There may be more than one constructor

- A constructor creates an object of a given class
- There may be more than one constructor
 - e.g. They can be *overloaded*

- A constructor creates an object of a given class
- There may be more than one constructor
 - e.g. They can be *overloaded*
- We *define* each constructor once

- A constructor creates an object of a given class
- There may be more than one constructor
 - e.g. They can be *overloaded*
- We *define* each constructor once
 - In the class declaration

- A constructor creates an object of a given class
- There may be more than one constructor
 - e.g. They can be *overloaded*
- We *define* each constructor once
 - In the class declaration
- A constructor is called each time we *create* a variable of


```
Counter c;  
...  
c.increment();
```

- For a call `c.increment()`, the program:

```
Counter c;  
...  
c.increment();
```

- For a call `c.increment()`, the program:
 - Looks up the type of `c`

```
Counter c;  
...  
c.increment();
```

- For a call `c.increment()`, the program:
 - Looks up the type of `c`
 - e.g. `Counter`


```
Counter c;  
...  
c.increment();
```

- For a call `c.increment()`, the program:
 - Looks up the type of `c`
 - e.g. `Counter`
 - Looks at the `Counter` class definition for a `Counter::increment()` method

```
Counter c;  
...  
c.increment();
```

- For a call `c.increment()`, the program:
 - Looks up the type of `c`
 - e.g. `Counter`
 - Looks at the `Counter` class definition for a `Counter::increment()` method
 - Calls that method as a function

What's Different in OOP

- Without OOP, functions exist separately from values

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value
 - Most operations act on at least one value

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value
 - Most operations act on at least one value
 - So we treat the operation as if it is a part of that value

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value
 - Most operations act on at least one value
 - So we treat the operation as if it is a part of that value
- What this means?

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value
 - Most operations act on at least one value
 - So we treat the operation as if it is a part of that value
- What this means?
 - Different classes can have different methods of the same name

What's Different in OOP

- Without OOP, functions exist separately from values
 - Can only access its arguments and globals
- With OOP, a method belongs to a particular value
 - Most operations act on at least one value
 - So we treat the operation as if it is a part of that value
- What this means?
 - Different classes can have different methods of the same name
 - When you call `foo.bar()`, it looks at the type of `foo` to know which code to use

Abstract Data Types

- A type where we *don't know exactly what values look like*

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type
 - A collection of operations defining a specific *interface*

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type
 - A collection of operations defining a specific *interface*
 - Can only interact with the type through the interface

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type
 - A collection of operations defining a specific *interface*
 - Can only interact with the type through the interface
- Classes are the realization of the concept of an ADT

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type
 - A collection of operations defining a specific *interface*
 - Can only interact with the type through the interface
- Classes are the realization of the concept of an ADT
 - The interface is the public methods of the class

Abstract Data Types

- A type where we *don't know exactly what values look like*
 - We just know what operations are supported for the type
 - A collection of operations defining a specific *interface*
 - Can only interact with the type through the interface
- Classes are the realization of the concept of an ADT
 - The interface is the public methods of the class
 - Can only interact with an object of a class through the interface