

Arrays

CS 115

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong, and Dr. Howard Hamilton

Last updated: January 7, 2025

One, two, and multi-dimensional arrays

Motivation

- Print 1000 numbers in reverse order

Motivation

- Print 1000 numbers in reverse order

Motivation

- Print 1000 numbers in reverse order

```
int value0;  
int value1;  
int value2;  
// ...  
int value999;  
  
cin >> value0;  
cin >> value1;  
// ...  
cin >> value999;  
  
cout << value999 << endl;  
cout << value998 << endl;  
// ...  
cout << value0 << endl;
```

Motivation (cont'd)

- How about 10000000 numbers?

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components
 - indexing support

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components
 - indexing support
 - constant time access

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components
 - indexing support
 - constant time access
 - random access

Motivation (cont'd)

- How about 10000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components
 - indexing support
 - constant time access
 - random access

Motivation (cont'd)

- How about 1000000 numbers?
- Tedious, not scalable, and error prone
- Solution: use aggregate data type
 - homogenous components
 - indexing support
 - constant time access
 - random access

```
int a[1200000];    // Array declaration

for (int i = 0; i < 1200000; i++)
    cin >> a[i];    // Array access
for (int i = 1199999; i >= 0; i--)
    cout << a[i] << endl;
```

Array Operations

- Call the things we store in the array *elements*

Array Operations

- Call the things we store in the array *elements*
- Get the *i*th element's value: `array[i]`

Array Operations

- Call the things we store in the array *elements*
- Get the *i*th element's value: `array[i]`
- Set the *i*th element: `array[i] = someValue;`

Simple arrays

Simple arrays

```
const int N = 120000;  
int a[N];    // Array declaration  
  
for (int i = 0; i < N; i++)  
    cin >> a[i];    // Array access  
for (int i = N-1; i >= 0; i--)  
    cout << a[i] << endl;
```

- Array size must be a constant expression

Simple arrays

```
const int N = 120000;  
int a[N];    // Array declaration  
  
for (int i = 0; i < N; i++)  
    cin >> a[i];    // Array access  
for (int i = N-1; i >= 0; i--)  
    cout << a[i] << endl;
```

- Array size must be a constant expression
- Easy to change size: just update N (the rest of the program remains intact)

Passing arrays as arguments

Passing arrays as arguments

```
int sumArray(int a[], unsigned int n) // Array argument
{
    int sum = 0;
    for (int i = 0; i < n; i++)
        sum += a[i];
    return sum;
}

int main()
{
    // Array initialization
    int a[] = { 3, 24, -88, 17, -1 };
    cout << sumArray(a, 5) << endl;
}
```

- Array size can be left unspecified in array initialization syntax

Passing arrays as arguments

- Array arguments are always automatically passed by reference

Passing arrays as arguments

- Array arguments are always automatically passed by reference
- no special notation is require

Passing arrays as arguments

- Array arguments are always automatically passed by reference
- no special notation is require

Passing arrays as arguments

- Array arguments are always automatically passed by reference
- no special notation is require

```
// int sumArray(int& a[], unsigned int n) - INCORRECT  
int sumArray(int a[], unsigned int n)    // CORRECT  
{  
    ...  
}
```

- Works for arrays of all sizes (size is passed as a separate argument)

Passing arrays as arguments

- Array arguments are always automatically passed by reference
- no special notation is require

```
// int sumArray(int& a[], unsigned int n) - INCORRECT  
int sumArray(int a[], unsigned int n)    // CORRECT  
{  
    ...  
}
```

- Works for arrays of all sizes (size is passed as a separate argument)
- Interface not safe: can modify the content of A

A Safer Interface

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

```
int sumArray(const int a[], unsigned int n)
```

- How to figure out array size when passing n if the size was left unspecified when declaring it?

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

```
int sumArray(const int a[], unsigned int n)
```

- How to figure out array size when passing n if the size was left unspecified when declaring it?
- use sizeof function:

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

```
int sumArray(const int a[], unsigned int n)
```

- How to figure out array size when passing n if the size was left unspecified when declaring it?
- use sizeof function:

A Safer Interface

```
int sumArray(int a[], unsigned int n)  
// not safe, sumArray can modify A!
```

- Use the following instead:

```
int sumArray(const int a[], unsigned int n)
```

- How to figure out array size when passing n if the size was left unspecified when declaring it?
- use sizeof function:

```
int a[] = {1,2,6,3,8};  
int x = sumArray(a, sizeof(a) / sizeof(int));
```

Play time

- Check if integer array sorted

Play time

- Check if integer array sorted

Play time

- Check if integer array sorted

```
bool arrayIsSorted(const int a[], unsigned int n){  
    for (int i = 0; i < n-1; i++){  
        if (a[i] > a[i+1])  
            return false;  
    }  
    return true;  
}
```

Play time

- Reversing items in integer array

Play time

- Reversing items in integer array

Play time

- Reversing items in integer array

```
void swap(int &a, int &b) {  
    int tmp = a;  
    a = b;  
    b = tmp;  
}  
  
// below a[] is not a constant as want to produce side-effect  
void reverseArray(int a[], unsigned int n) {  
    for (int i = 0; i < n/2; i++)  
        swap(a[i], a[n - i - 1]);  
}
```


Processing subarrays

- Compute the sum of an array segment

Processing subarrays

- Compute the sum of an array segment

Processing subarrays

- Compute the sum of an array segment

```
// pos   : index of the first component in the subarray  
// count: total number of components in the subarray  
int sumSubarray(const int a[],  
                unsigned int pos,  
                unsigned int count){  
    int sum = 0;  
    for (int i = pos; i < pos + count; i++)  
        sum += a[i];  
  
    return sum;  
}
```

Processing subarrays

- Another way to do the same thing

Processing subarrays

- Another way to do the same thing

Processing subarrays

- Another way to do the same thing

```
// begin: index of first component in the subarray  
// end   : index of the last component in the subarray  
int sumSubarray(const int a[],  
                unsigned int begin,  
                unsigned int end){  
    assert(begin <= end);  
    int sum = 0;  
    for (int i = begin; i <= end; i++)  
        sum += a[i];  
  
    return sum;  
}
```

Subtleties

- C++ does not check if array indices are within bound

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility
- Array Copying

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility
- Array Copying

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility
- Array Copying

```
a = b // invalid
```

- copy cell by cell:

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility
- Array Copying

```
a = b // invalid
```

- copy cell by cell:

Subtleties

- C++ does not check if array indices are within bound
- it's your responsibility
- Array Copying

```
a = b // invalid
```

- copy cell by cell:

```
a[6]=b[9] // works!
```

- Array Comparison

- Array Comparison

- Array Comparison

```
if(a == b) // invalid
```

- compare each pair of cells at a time

- Array Comparison

```
if(a == b) // invalid
```

- compare each pair of cells at a time
- No need to return array as function output, uses call by reference anyway!

Prof's Aside

- C++ arrays are *unsafe*

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler
- C++ will never change

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler
- C++ will never change
 - Backwards compatibility

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler
- C++ will never change
 - Backwards compatibility
 - `std::array` is safe but isn't the default

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler
- C++ will never change
 - Backwards compatibility
 - `std::array` is safe but isn't the default
- Languages like Rust make sure that these errors are *impossible*

Prof's Aside

- C++ arrays are *unsafe*
- This is *terrible* language design
 - Billions of dollars and many security incidents caused by unsafe memory access
 - Error cost outweighs performance cost of checking array bounds
 - Most checks can be optimized out by the compiler
- C++ will never change
 - Backwards compatibility
 - `std::array` is safe but isn't the default
- Languages like Rust make sure that these errors are *impossible*
 - Unless you explicitly disable safety

Example

Example

```
#include <iostream>
using namespace std;
int main(){
    char passwd[8] = "secret";
    char username[8] = "bob101";
    string toPrint = "";
    // Oops reading past end of array!
    for (int i = 0; i < 16; i++){
        toPrint += username[i];
    }
    cout << toPrint << endl;
}
```

Example

```
#include <iostream>
using namespace std;
int main(){
    char passwd[8] = "secret";
    char username[8] = "bob101";
    string toPrint = "";
    // Oops reading past end of array!
    for (int i = 0; i < 16; i++){
        toPrint += username[i];
    }
    cout << toPrint << endl;
}
```

bob101secret

Two Dimensional Arrays

Motivation

- Want to store quantity of different products sold in a store

Motivation

- Want to store quantity of different products sold in a store
- but for multiple locations/regions

Motivation

- Want to store quantity of different products sold in a store
- but for multiple locations/regions
- Conceptually can store as a matrix, where rows represent different locations and columns represent different products

Motivation

- Want to store quantity of different products sold in a store
- but for multiple locations/regions
- Conceptually can store as a matrix, where rows represent different locations and columns represent different products
- `sales[2][1]` are the total number of items sold for location 2 and product 1

Motivation

- Want to store quantity of different products sold in a store
- but for multiple locations/regions
- Conceptually can store as a matrix, where rows represent different locations and columns represent different products
- `sales[2][1]` are the total number of items sold for location 2 and product 1
- recall item n is the $(n+1)$ -th item

Motivation

- Want to store quantity of different products sold in a store
- but for multiple locations/regions
- Conceptually can store as a matrix, where rows represent different locations and columns represent different products
- `sales[2][1]` are the total number of items sold for location 2 and product 1
- recall item n is the $(n+1)$ -th item
 - index starts from 0!

Declaration and Access

Declaration and Access

```
const unsigned int NUM_OF_REGIONS = 4;  
const unsigned int NUM_OF_PRODUCTS = 3;  
  
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- To access sales figure for first product in second region, use:

Declaration and Access

```
const unsigned int NUM_OF_REGIONS = 4;  
const unsigned int NUM_OF_PRODUCTS = 3;  
  
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- To access sales figure for first product in second region, use:

Declaration and Access

```
const unsigned int NUM_OF_REGIONS = 4;  
const unsigned int NUM_OF_PRODUCTS = 3;  
  
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- To access sales figure for first product in second region, use:

```
sales[1][0] // recall, indices start from 0
```

- e.g., want to set sales figure for first product in second region to 500

Declaration and Access

```
const unsigned int NUM_OF_REGIONS = 4;  
const unsigned int NUM_OF_PRODUCTS = 3;  
  
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- To access sales figure for first product in second region, use:

```
sales[1][0] // recall, indices start from 0
```

- e.g., want to set sales figure for first product in second region to 500

Declaration and Access

```
const unsigned int NUM_OF_REGIONS = 4;  
const unsigned int NUM_OF_PRODUCTS = 3;  
  
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- To access sales figure for first product in second region, use:

```
sales[1][0] // recall, indices start from 0
```

- e.g., want to set sales figure for first product in second region to 500

```
sales[1][0] = 500;
```

Populating and Accessing

Populating and Accessing

```
// Read input stream
for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)
    for (unsigned int product = 0; product < NUM_OF_PRODUCTS; product++)
        cin >> sales[region][product];

// total sales for a particular product (product 0)
unsigned int total_sales = 0;

for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)
    // add up sales from all regions for product 0
    total_sales += sales[region][0];
```

- Can you compute total sales from region 1?

Passing 2D Arrays

Passing 2D Arrays

```
unsigned int sumProductSales(  
    unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS],  
    unsigned int product)  
{  
    unsigned int total_sales = 0;  
    for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)  
        total_sales += sales[region][product];  
  
    return total_sales;  
}
```

- Can you implement a safer interface?

Passing 2D Arrays

```
unsigned int sumProductSales(  
    unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS],  
    unsigned int product)  
{  
    unsigned int total_sales = 0;  
    for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)  
        total_sales += sales[region][product];  
  
    return total_sales;  
}
```

- Can you implement a safer interface?
- As usual, can leave size of first dimension unspecified, e.g. `int F(int arr[][SIZE])`

Passing 2D Arrays

```
unsigned int sumProductSales(  
    unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS],  
    unsigned int product)  
{  
    unsigned int total_sales = 0;  
    for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)  
        total_sales += sales[region][product];  
  
    return total_sales;  
}
```

- Can you implement a safer interface?
- As usual, can leave size of first dimension unspecified, e.g. `int F(int arr[][SIZE])`
- but not the second one (why?)

Making things more modular

- So we can change internal representation without changing interface

Making things more modular

- So we can change internal representation without changing interface

Making things more modular

- So we can change internal representation without changing interface

```
// Implement a function that returns  
// the value of one element from the sales array  
unsigned int getSales(  
    const unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS],  
    unsigned int r, unsigned int p){  
    return sales[r][p];  
}  
  
// Implement a function that sets the value  
// of one element from the sales array  
void setSales(unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS],  
    unsigned int r, unsigned int p, unsigned int v){  
    sales[r][p] = v;  
}
```

Using typedef

Using typedef

```
// too lazy to write long types? Use typedef instead!  
  
typedef unsigned int Sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];  
  
unsigned int sumSales(const Sales sales){  
    ...  
}
```

Simulating Two-dimensional Arrays by One-dimensional Ones

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?
 - row-major vs. column-major order

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?
 - row-major vs. column-major order
 - e.g. `sales[i][j]`

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?
 - row-major vs. column-major order
 - e.g. `sales[i][j]`
 - same as `_sales[i * NUM_OF_PRODUCTS + j]` in row-major

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?
 - row-major vs. column-major order
 - e.g. `sales[i][j]`
 - same as `_sales[i * NUM_OF_PRODUCTS + j]` in row-major
- Now you know why the size of the 2nd dimension can't be left unspecified!

Simulating Two-dimensional Arrays by One-dimensional Ones

```
unsigned int sales[NUM_OF_REGIONS][NUM_OF_PRODUCTS];
```

- versus

```
unsigned int _sales[NUM_OF_REGIONS * NUM_OF_PRODUCTS];
```

- Issue: how to map between these two?
 - row-major vs. column-major order
 - e.g. `sales[i][j]`
 - same as `_sales[i * NUM_OF_PRODUCTS + j]` in row-major
- Now you know why the size of the 2nd dimension can't be left unspecified!
 - Can you write the formula for column-major order?

Using Row-Major Order

Using Row-Major Order

```
unsigned int totalSales = 0;

for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)
    for (unsigned int product = 0;
         product < NUM_OF_PRODUCTS;
         product++){
        totalSales += _sales[region * NUM_OF_PRODUCTS + product];
    }
```

- This is why we need to know the size of the second dimension

Using Row-Major Order

```
unsigned int totalSales = 0;

for (unsigned int region = 0; region < NUM_OF_REGIONS; region++)
    for (unsigned int product = 0;
         product < NUM_OF_PRODUCTS;
         product++){
        totalSales += _sales[region * NUM_OF_PRODUCTS + product];
    }
```

- This is why we need to know the size of the second dimension
 - To calculate offset

Multi-dimensional Arrays

Multi-dimensional Arrays

```
const unsigned int NUM_YEARS = 2;
const unsigned int NUM_REGIONS = 4;
const unsigned int NUM_PRODUCTS = 3;

typedef unsigned int Sales[NUM_YEARS][NUM_REGIONS][NUM_PRODUCTS];

unsigned int total_sales = 0;
for (unsigned int year = 0; year < NUM_YEARS; year++)
    for (unsigned int region = 0; region < NUM_REGIONS; region++)
        for (unsigned int product = 0; product < NUM_PRODUCTS; product++)
            total_sales += sales[year][region][product];
```

Simulating 3d with 1d

- `Sales[year][region][product]`

Simulating 3d with 1d

- `Sales[year][region][product]`
- `vs_Sales[(year * NUM_REGS * NUM_PRODS) + (region * NUM_OF_PRODS) + product]`

Multi-dimensional Arrays

- In general for a d-dimensional array with dimensions S_1, S_2, \dots, S_d , the element at `Item[n_1][n_2]...[n_d]` can be represented as a single dimensional array with the following index

Multi-dimensional Arrays

- In general for a d-dimensional array with dimensions S_1, S_2, \dots, S_d , the element at `Item[n_1][n_2]...[n_d]` can be represented as a single dimensional array with the following index

Multi-dimensional Arrays

- In general for a d-dimensional array with dimensions S_1, S_2, \dots, S_d , the element at $\text{Item}[n_1][n_2] \dots [n_d]$ can be represented as a single dimensional array with the following index

```
_Item[n_d + S_d * (n_{d-1} + S_{d-1} *  
  * (n_{d-2} + S_{d-2} * (...+S_2*n_1) ... ))]
```