

# **Program Organization Principles**

CS 115

---

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong,  
and Dr. Howard Hamilton

Last updated: January 21, 2025

**Terminology concerning program organization, interface vs. implementation, data encapsulation, information hiding, modularity, layering, design by contract, abstract data types**

---

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern
- concern = a set of information that affects code

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern
- concern = a set of information that affects code
- can be realized via layering and modularity

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern
- concern = a set of information that affects code
- can be realized via layering and modularity
- Layering: use separate layers in the software, each of which addresses a different concern (e.g., presentation layer, business logic layer, data access layer, etc.)

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern
- concern = a set of information that affects code
- can be realized via layering and modularity
- Layering: use separate layers in the software, each of which addresses a different concern (e.g., presentation layer, business logic layer, data access layer, etc.)
- **Modularity:** the degree to which a system's components can be separated and recombined

# Separation of Concerns

- is a design principle for separating a computer program into distinct sections such that each section addresses a separate concern
- concern = a set of information that affects code
- can be realized via layering and modularity
- Layering: use separate layers in the software, each of which addresses a different concern (e.g., presentation layer, business logic layer, data access layer, etc.)
- **Modularity:** the degree to which a system's components can be separated and recombined
- break system into parts and to hide the complexity of each part behind an abstraction and interface



# Modularity

- Why bother?

# Modularity

- Why bother?
- Simplifies development and maintenance of computer programs

# Modularity

- Why bother?
- Simplifies development and maintenance of computer programs
- Promote software reuse

- Why bother?
- Simplifies development and maintenance of computer programs
- Promote software reuse
- Modules can be developed and updated independently (can improve on one section of code without changing other sections)

# Modularity

- Why bother?
- Simplifies development and maintenance of computer programs
- Promote software reuse
- Modules can be developed and updated independently (can improve on one section of code without changing other sections)
- How to realize modularity?

# Modularity

- Why bother?
- Simplifies development and maintenance of computer programs
- Promote software reuse
- Modules can be developed and updated independently (can improve on one section of code without changing other sections)
- How to realize modularity?
  - procedural programming: via functions and top-down design

# Modularity

- Why bother?
- Simplifies development and maintenance of computer programs
- Promote software reuse
- Modules can be developed and updated independently (can improve on one section of code without changing other sections)
- How to realize modularity?
  - procedural programming: via functions and top-down design
- OOP: via classes and objects

- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour



- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour
- Perhaps older version was poorly written due to time constraints etc.

- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour
- Perhaps older version was poorly written due to time constraints etc.
  - e.g., replace 306 with the constant SK\_CODE1

- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour
- Perhaps older version was poorly written due to time constraints etc.
  - e.g., replace 306 with the constant SK\_CODE1
  - replace long if-then-else branches with switch/case statements

- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour
- Perhaps older version was poorly written due to time constraints etc.
  - e.g., replace 306 with the constant SK\_CODE1
  - replace long if-then-else branches with switch/case statements
  - divide overly complex implementation into smaller functions

- **Refactoring** is to rewrite code in order to improve its readability, reusability, or structure without affecting its meaning or behaviour
- Perhaps older version was poorly written due to time constraints etc.
  - e.g., replace 306 with the constant SK\_CODE1
  - replace long if-then-else branches with switch/case statements
  - divide overly complex implementation into smaller functions
  - replace with efficient code, etc.

# Layers of Abstraction

- Each level represents an increasingly detailed model of the software system and its processes

# Layers of Abstraction

- Each level represents an increasingly detailed model of the software system and its processes
- at each level, the model is described using concepts appropriate to a certain domain

# Layers of Abstraction

- Each level represents an increasingly detailed model of the software system and its processes
- at each level, the model is described using concepts appropriate to a certain domain
- each higher, more abstract level builds on a lower, less abstract level



# Layers of Abstraction

- Each level represents an increasingly detailed model of the software system and its processes
- at each level, the model is described using concepts appropriate to a certain domain
- each higher, more abstract level builds on a lower, less abstract level
- To understand levels of abstraction better, see optional slides on Layering

# Interface vs. Implementation

- **Interface:** How to use your code (type signature, precondition, postcondition, description of return value)

# Interface vs. Implementation

- **Interface:** How to use your code (type signature, precondition, postcondition, description of return value)
  - Modular programming: developing software where each section of code is a module with a carefully specified interface

# Interface vs. Implementation

- **Interface:** How to use your code (type signature, precondition, postcondition, description of return value)
  - Modular programming: developing software where each section of code is a module with a carefully specified interface
  - makes the purpose of your code clear

# Interface vs. Implementation

- **Interface:** How to use your code (type signature, precondition, postcondition, description of return value)
  - Modular programming: developing software where each section of code is a module with a carefully specified interface
  - makes the purpose of your code clear
  - client software can focus on the interface

# Interface vs. Implementation

- **Interface:** How to use your code (type signature, precondition, postcondition, description of return value)
  - Modular programming: developing software where each section of code is a module with a carefully specified interface
  - makes the purpose of your code clear
  - client software can focus on the interface
    - *and ignore its implementation*

- A crucial aspect of modular programming is mentally separating the interface from the implementation

- A crucial aspect of modular programming is mentally separating the interface from the implementation
  - Do you know how `cin` and `cout` are implemented?



- A crucial aspect of modular programming is mentally separating the interface from the implementation
  - Do you know how `cin` and `cout` are implemented?
  - You don't need to know to use them

- A crucial aspect of modular programming is mentally separating the interface from the implementation
  - Do you know how `cin` and `cout` are implemented?
  - You don't need to know to use them
- We will specify the interfaces in `.h` files (as well-documented prototypes)

## Interfaces ctd.

- A crucial aspect of modular programming is mentally separating the interface from the implementation
  - Do you know how `cin` and `cout` are implemented?
  - You don't need to know to use them
- We will specify the interfaces in `.h` files (as well-documented prototypes)
- We will specify the implementation in `.cpp` files (primarily as functions)

## Interfaces ctd.

- A crucial aspect of modular programming is mentally separating the interface from the implementation
  - Do you know how `cin` and `cout` are implemented?
  - You don't need to know to use them
- We will specify the interfaces in `.h` files (as well-documented prototypes)
- We will specify the implementation in `.cpp` files (primarily as functions)
- Some functions and variables are not (directly) accessible!

# Separating interface and implementation

- Two Approaches

# Separating interface and implementation

- Two Approaches
  - via data encapsulation

# Separating interface and implementation

- Two Approaches
  - via data encapsulation
    - hide variables describing state of the module inside the module

# Separating interface and implementation

- Two Approaches
  - via data encapsulation
    - hide variables describing state of the module inside the module
    - (static variables/functions and namespaces)



# Separating interface and implementation

- Two Approaches
  - via data encapsulation
    - hide variables describing state of the module inside the module
    - (static variables/functions and namespaces)
  - by defining new abstract data types (ADT) using records and classes

# The Static Keyword

- On global variables and functions

# The Static Keyword

- On global variables and functions

# The Static Keyword

- On global variables and functions

# The Static Keyword

- On global variables and functions

# The Static Keyword

- On global variables and functions

# The Static Keyword

- On global variables and functions

```
// whatever.cpp  
  
static int foo = 5;  
int bar = 6;  
  
static void doh(int var1) {  
    // do something  
}  
  
void yay(char c){  
    // do something  
}
```

# The Static Keyword

- On global variables and functions

```
// whatever.cpp  
  
static int foo = 5;  
int bar = 6;  
  
static void doh(int var1) {  
    // do something  
}  
  
void yay(char c){  
    // do something  
}
```



# The Static Keyword

- On global variables and functions

```
// whatever.cpp

static int foo = 5;
int bar = 6;

static void doh(int var1) {
    // do something
}

void yay(char c){
    // do something
}
```

# The Static Keyword

- On global variables and functions

```
// whatever.cpp
```

```
static int foo = 5;
```

```
int bar = 6;
```

```
static void doh(int var1) {  
    // do something  
}
```

```
void yay(char c){  
    // do something  
}
```

```
// main.cpp
```

```
int main ( ){
```

```
    extern int foo; // invalid
```

```
    extern int bar; // works!
```

```
    doh(13); // invalid
```

```
    yay('a'); // works!
```

```
}
```

## Local Variables and static

## Local Variables and static

## Local Variables and static

## Local Variables and static

# Local Variables and static

```
void fun(int var1) {  
    int x1=0;  
    x1+=var1;  
    cout << x1 << endl;  
}  
void funS(int var1) {  
    static int x2=0;  
    x2+=var1;  
    cout << x2 << endl;  
}  
int main ( ){  
    fun(5);  
    fun(5);  
    fun(7);  
  
    funS(5);  
    funS(5);  
    funS(7);  
}
```

# Local Variables and static

```
void fun(int var1) {  
    int x1=0;  
    x1+=var1;  
    cout << x1 << endl;  
}  
void funS(int var1) {  
    static int x2=0;  
    x2+=var1;  
    cout << x2 << endl;  
}  
int main ( ){  
    fun(5);  
    fun(5);  
    fun(7);  
  
    funS(5);  
    funS(5);  
    funS(7);  
}
```

**Variable value persists across multiple calls to the function**

5  
5  
7  
5  
10



# Local Variables and static

```
void fun(int var1) {  
    int x1=0;  
    x1+=var1;  
    cout << x1 << endl;  
}  
void funS(int var1) {  
    static int x2=0;  
    x2+=var1;  
    cout << x2 << endl;  
}  
int main ( ){  
    fun(5);  
    fun(5);  
    fun(7);  
  
    funS(5);  
    funS(5);  
    funS(7);  
}
```

## Variable value persists across multiple calls to the function

- Like a global, but can only be accessed from inside the function

5  
5  
7  
5  
10

# Local Variables and static

```
void fun(int var1) {  
    int x1=0;  
    x1+=var1;  
    cout << x1 << endl;  
}  
void funS(int var1) {  
    static int x2=0;  
    x2+=var1;  
    cout << x2 << endl;  
}  
int main ( ){  
    fun(5);  
    fun(5);  
    fun(7);  
  
    funS(5);  
    funS(5);  
    funS(7);  
}
```

## Variable value persists across multiple calls to the function

- Like a global, but can only be accessed from inside the function
- So other things can't mess it up!

5  
5  
7  
5  
10





# Namespaces

- Scope for identifiers

# Namespaces

- Scope for identifiers
- Avoids name collisions

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from



# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

```
// myProg.h

#pragma once

namespace myNSpace{
    void Foo();
    int Bar();
}
```

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

```
// myProg.h

#pragma once

namespace myNSpace{
    void Foo();
    int Bar();
}
```

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

```
// myProg.h

#pragma once

namespace myNSpace{
    void Foo();
    int Bar();
}
```

# Namespaces

- Scope for identifiers
- Avoids name collisions
- Makes it clear where a name is coming from

```
// myProg.h
```

```
#pragma once
```

```
namespace myNSpace{  
    void Foo();  
    int Bar();  
}
```

```
#include "myProg.h"
```

```
using namespace myNSpace;
```

```
// use fully-qualified name here
```

```
void myNSpace::Foo(){
```

```
    // no qualification needed for Bar()
```

```
    Bar();
```

```
}
```

```
int ContosoDataServer::Bar(){
```

```
    return 0;
```

```
}
```

# Anonymous namespaces

# Anonymous namespaces

# Anonymous namespaces

- Used for hiding identifiers



## Anonymous namespaces

- Used for hiding identifiers

## Anonymous namespaces

- Used for hiding identifiers

# Anonymous namespaces

- Used for hiding identifiers

```
// myProg.h

#pragma once

namespace {
    float foo;
    double pi(){
        return 3.141592653;
    }
}

char bar;
```

# Anonymous namespaces

- Used for hiding identifiers

```
// myProg.h

#pragma once

namespace {
    float foo;
    double pi(){
        return 3.141592653;
    }
}

char bar;
```

# Anonymous namespaces

- Used for hiding identifiers

```
// myProg.h

#pragma once

namespace {
    float foo;
    double pi(){
        return 3.141592653;
    }
}

char bar;
```

# Anonymous namespaces

- Used for hiding identifiers

```
// myProg.h

#pragma once

namespace {
    float foo;
    double pi(){
        return 3.141592653;
    }
}

char bar;
```

```
// myProg.cpp

#include "myProg.h"

int main(){
    foo = 2.718281828; // invalid!
    double y = pi();    // invalid!
    char c = bar;       // works

    return 0;
}
```

- Can declare the same namespace over multiple sections

- Can declare the same namespace over multiple sections
- Have to be careful about usage of identifiers



- Can declare the same namespace over multiple sections
- Have to be careful about usage of identifiers
- Can have nested namespaces, inline namespaces, namespace aliases, etc.

- Can declare the same namespace over multiple sections
- Have to be careful about usage of identifiers
- Can have nested namespaces, inline namespaces, namespace aliases, etc.
- Also check out the global namespace

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code
- can be achieved via static variables

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code
- can be achieved via static variables
- (restricts variable/function scope to file)

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code
- can be achieved via static variables
- (restricts variable/function scope to file)
- hides implementation details

# Data encapsulation

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code
- can be achieved via static variables
- (restricts variable/function scope to file)
- hides implementation details
- clients are forced to use interface to access data

- to place a barrier around the variables that represent the internal state of a software component so that these variables cannot be accessed directly by client code
- can be achieved via static variables
- (restricts variable/function scope to file)
- hides implementation details
- clients are forced to use interface to access data
- similar effects can be achieved using namespaces



# Separating interface and implementation

- e.g. A Bounded Counter

## Separating interface and implementation

- e.g. A Bounded Counter
- Start by specifying the interface of the module

## Separating interface and implementation

- e.g. A Bounded Counter
- Start by specifying the interface of the module

## Separating interface and implementation

- e.g. A Bounded Counter
- Start by specifying the interface of the module

# Separating interface and implementation

- e.g. A Bounded Counter
- Start by specifying the interface of the module

```
// initializeCounter
//
// Purpose: Initialize the bounded counter module.
// Parameter(s):
//   <1> value1: Initial value for the counter
//               expressed as an unsigned integer.
//   <2> upper1: Upper bound for counter value
//               expressed as an unsigned integer.
// Precondition(s): value1 < upper1
// Returns: N/A
// Side effect: The counter is initialized, with value1 as the current
// upper bound of counter values.
```

## Separating interface and implementation

# Separating interface and implementation

# Separating interface and implementation

```
// getCounterValue
//
// Purpose: Retrieve the current value of
// the counter.
// Parameter(s): N/A
// Precondition(s): N/A
// Returns: The unsigned integer value of
// the counter.
// Side effect: N/A
```

```
// incrementCounter
//
// Purpose: Increment the value of the
// counter.
// Parameter(s): N/A
// Precondition(s): N/A
// Returns: N/A
// Side effect: The counter value is
// incremented by one. If the incremented
```







# Complete Interface

```
// encapsulated_counter.h
//
// This module provides ...
// Data encapsulation is used to
// protect the state of the bounded
// counter from manipulation by client
// code, except via the functions in
// the interface.

#pragma once
//initializeCounter
//...
void initializeCounter(unsigned int value1, unsigned int upper1);
// getCountValue
//...
unsigned int getCountValue();
// incrementCounter
//...
void incrementCounter();
```





# Client Code

```
#include <iostream>
using namespace std;
#include "encapsulated_counter.h"

int main() {
    initializeCounter(0, 3);
    cout << getCounterValue() << endl;
    incrementCounter();
    cout << getCounterValue() << endl;
    incrementCounter();
    incrementCounter();
    cout << getCounterValue() << endl;
    return 0;
}
```

- Output:

# Client Code

```
#include <iostream>
using namespace std;
#include "encapsulated_counter.h"

int main() {
    initializeCounter(0, 3);
    cout << getCounterValue() << endl;
    incrementCounter();
    cout << getCounterValue() << endl;
    incrementCounter();
    incrementCounter();
    cout << getCounterValue() << endl;
    return 0;
}
```

- Output:

- 0

# Client Code

```
#include <iostream>
using namespace std;
#include "encapsulated_counter.h"

int main() {
    initializeCounter(0, 3);
    cout << getCounterValue() << endl;
    incrementCounter();
    cout << getCounterValue() << endl;
    incrementCounter();
    incrementCounter();
    cout << getCounterValue() << endl;
    return 0;
}
```

- Output:

- 0
- 1



# Client Code

```
#include <iostream>
using namespace std;
#include "encapsulated_counter.h"

int main() {
    initializeCounter(0, 3);
    cout << getCounterValue() << endl;
    incrementCounter();
    cout << getCounterValue() << endl;
    incrementCounter();
    incrementCounter();
    cout << getCounterValue() << endl;
    return 0;
}
```

- Output:

- 0
- 1
- 0

# Implementing the Interface

# Implementing the Interface

# Implementing the Interface

```
// encapsulated_counter.cpp
//
static unsigned int counter_value;
static unsigned int counter_upper;

void initializeCounter(unsigned int value1, unsigned int upper1) {
    counter_value = value1;
    counter_upper = upper1;
}

unsigned int getCounterValue(){
    return counter_value;
}

void incrementCounter(){
    ++counter_value;
    if (counter_value == counter_upper)
        counter_value = 0;
}
```

## Design by contract

- Allows for clean division of labour

## Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)

## Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying

## Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable



## Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable
  - Client's POV: how much is expected

# Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable
  - Client's POV: how much is expected
- Usually specified using

## Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable
  - Client's POV: how much is expected
- Usually specified using
  - preconditions

# Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable
  - Client's POV: how much is expected
- Usually specified using
  - preconditions
  - postconditions

# Design by contract

- Allows for clean division of labour
- Specifies the usage convention for a module is captured in a contract between the supplier (the developer of the module) and the client (the user of the module)
- Protects all parties by specifying
  - supplier's POV: how little is acceptable
  - Client's POV: how much is expected
- Usually specified using
  - preconditions
  - postconditions
  - invariants

## Design By Contract in our Counter

## Design By Contract in our Counter

# Design By Contract in our Counter

```
// initializeCounter
//
// Purpose: Initialize the bounded counter module.
// Parameter(s):
//   <1> value1: Initial value for the counter
//               expressed as an unsigned integer.
//   <2> upper1: Upper bound for counter value
//               expressed as an unsigned integer.
// Precondition(s):
//   <1>: value1 < upper1
// Returns: N/A
// Side Effect: The global counter is initialized, with value1 as
//               the current counter value, and upper1 as the upper
//               bound of counter values.
```



# Preconditions and Posconditions

# Preconditions and Posconditions

# Preconditions and Posconditions

```
// encapsulated_counter.cpp
#include <cassert>

void initializeCounter(unsigned int value1, unsigned int upper1){
    assert(value1 < upper1); // encapsulated_counter.cpp
    counter_value = value1;
    counter_upper = upper1;
}
```





# Invariants

```
// initializeCounter
//
// Module invariant: Current counter value is
// always strictly less than the upper bound
//

static bool isInvariantTrue(){
    return counter_value < counter_upper;
}
```







## Invariants ctd.

```
void initializeCounter(unsigned int value1, unsigned int upper1){
    assert(value1 < upper1);
    counter_value = value1;
    counter_upper = upper1;
    assert(isInvariantTrue());
}

unsigned int getCounterValue(){
    assert(isInvariantTrue());
    return counter_value;
}

void incrementCounter(){
    assert(isInvariantTrue());
    ++counter_value;
    if (counter_value == counter_upper)
        counter_value = 0;
    assert(isInvariantTrue());
}
```

## Another Example (see the notes)

- Consider designing a timer that represents the accumulated time in [hh:mm:ss] format

## Another Example (see the notes)

- Consider designing a timer that represents the accumulated time in [hh:mm:ss] format
- Internally can be implemented in many ways

## Another Example (see the notes)

- Consider designing a timer that represents the accumulated time in [hh:mm:ss] format
- Internally can be implemented in many ways
- e.g., only store seconds

## Another Example (see the notes)

- Consider designing a timer that represents the accumulated time in [hh:mm:ss] format
- Internally can be implemented in many ways
- e.g., only store seconds
- e.g., store all hours, minutes, and seconds

## Another Example (see the notes)

- Consider designing a timer that represents the accumulated time in [hh:mm:ss] format
- Internally can be implemented in many ways
- e.g., only store seconds
- e.g., store all hours, minutes, and seconds
- But if interface remains the same, changing implementation does not require changing client code

## Abstract data types (ADT)

- Motivation: returning to our example, we want to have multiple counters

## Abstract data types (ADT)

- Motivation: returning to our example, we want to have multiple counters
- ADT: data type defined by its possible values and operations, e.g.: counters



## Abstract data types (ADT)

- Motivation: returning to our example, we want to have multiple counters
- ADT: data type defined by its possible values and operations, e.g.: counters

## Abstract data types (ADT)

- Motivation: returning to our example, we want to have multiple counters
- ADT: data type defined by its possible values and operations, e.g.: counters

# Abstract data types (ADT)

- Motivation: returning to our example, we want to have multiple counters
- ADT: data type defined by its possible values and operations, e.g.: counters

```
// counter.h
//
// This module defines an abstract data type named Counter.
// A counter value is maintained by
// each instance of the Counter type.
// Users may increment or retrieve the value of the counter.
// Data type invariant: Current value of a counter instance
// must be strictly smaller than its
// upper bound
struct Counter{
    // ... details to be filled out later
};
```

# Abstract data types (ADT)

# Abstract data types (ADT)

# Abstract data types (ADT)

```
// counterInitialize
//
// Purpose: Initialize a counter instance.
// Parameter(s):
//   <1> counter: A counter instance to be initialized.
//   <2> value1: Initial value for the counter
//               specified as an unsigned integer.
//   <3> upper1: Upper bound for counter value
//               specified as an unsigned integer.
// Precondition:
//   <1> value1 < upper1
// Side Effect: The counter instance is initialized, with value1 as
//               the current counter value, and upper1 as the upper
//               bound of counter values.
//
void counterInitialize(Counter& counter,
                      unsigned int value1,
                      unsigned int upper1);
```

# Abstract data types (ADT)

# Abstract data types (ADT)



## Abstract data types (ADT)

```
// counterGetValue
//
// Purpose: Retrieve the current value of a
// counter instance.
// Parameter(s):
//   <1> counter: A counter instance
// Returns: The unsigned integer value of the
// counter instance.

unsigned counterGetValue(const Counter& counter);
```

# Abstract data types (ADT)

# Abstract data types (ADT)

## Abstract data types (ADT)

```
// counterIncrement
//
// Purpose: Increment a given counter
// instance.
// Parameter(s):
//   <1> counter: counter instance to be
//   incremented
// Side Effect: The counter value of the
// parameter is incremented by one. If the
// incremented value reaches the upper
// bound, then the counter value is reset to
// zero.
void counterIncrement(Counter& counter);
```





# Client Code

```
int main( ){
    Counter c, d;
    counterInitialize(c, 0, 3);
    counterInitialize(d, 0, 10);
    counterIncrement(c); counterIncrement(c); counterIncrement(c);
    counterIncrement(d); counterIncrement(d); counterIncrement(d);
    cout << counterGetValue(c) << endl;
    cout << counterGetValue(d) << endl;
    return 0;
}
```

# Data Representation, Implementation, Issues



# Data Representation, Implementation, Issues

# Data Representation, Implementation, Issues

# Data Representation, Implementation, Issues

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees



# Data Representation, Implementation, Issues

- No encapsulation

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

# Data Representation, Implementation, Issues

- No encapsulation

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

# Data Representation, Implementation, Issues

- No encapsulation

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

- No encapsulation

```
Counter c;  
counterInitialize(c, 0, 3);  
c.value = 999; // allowed!
```

- No initialization guarantees

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

- No encapsulation

```
Counter c;  
counterInitialize(c, 0, 3);  
c.value = 999; // allowed!
```

- No initialization guarantees

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

- No encapsulation

```
Counter c;  
counterInitialize(c, 0, 3);  
c.value = 999; // allowed!
```

- No initialization guarantees

# Data Representation, Implementation, Issues

```
struct Counter {  
    unsigned int value;  
    unsigned int upper;  
};
```

- Can implement as before
- Problems:
  - no data encapsulation
  - no initialization guarantees

- No encapsulation

```
Counter c;  
counterInitialize(c, 0, 3);  
c.value = 999; // allowed!
```

- No initialization guarantees

```
// Precondition:  
// <1> The counter module must  
// have been properly initialized  
Counter c;  
cout << counterGetValue(c) << endl;
```