

Records

CS 115

Dr. Joseph Eremondi, adapted from Dr. Shakil Khan, Dr. Philip Fong,
and Dr. Howard Hamilton

Last updated: January 17, 2025

Structs and unions

Motivation

Motivation

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
 - Data in collection is heterogenous
- Solution using arrays:

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
 - Data in collection is heterogenous
- Solution using arrays:

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
 - Data in collection is heterogenous
- Solution using arrays:

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

```
string titles[N];  
string authors[N];  
string publishers[N];  
unsigned int publishingYears[N];  
string callNumbers[N];  
double Price[N];
```

- Poor choice of interface!

Motivation

- E.g. Catalog information in a library
- Data in collection is heterogenous

Title	string
Author	string
Publisher	string
Year	unsigned int
Call Number	string
Price	double

- Solution using arrays:

```
string titles[N];  
string authors[N];  
string publishers[N];  
unsigned int publishingYears[N];  
string callNumbers[N];  
double Price[N];
```

- Poor choice of interface!
- (many arguments to pass for functions)

Use a record instead!

Use a record instead!

Use a record instead!

- Data can be heterogenous

Use a record instead!

- Data can be heterogenous
- Define:

Use a record instead!

- Data can be heterogenous
- Define:

Use a record instead!

- Data can be heterogenous
- Define:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

Use a record instead!

- Only 1 argument needs to be passed
- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

Use a record instead!

- Data can be heterogenous
- Define:

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
};
```

- Only 1 argument needs to be passed
- Declare:

```
struct CatalogEntry c;  
// or, equivalently this:  
CatalogEntry c;
```

- Initialize:

```
c.title = "Peter Pan";  
c.author = "J. M. Barrie";  
c.publisher = "Scribner";  
c.publishingYear = 1980;  
c.callNumber = "B2754 1980";
```

Initializing a Record

- As with arrays

Initializing a Record

- As with arrays

Initializing a Record

- As with arrays

Initializing a Record

- As with arrays

```
CatalogEntry c = {"Peter Pan",  
                  "J. M. Barrie",  
                  "Scribner",  
                  1980,  
                  "B2754 1980"};
```

Copying a Record

Copying a Record

Copying a Record

```
// initialization list  
CatalogEntry c = { ... };  
  
// initialization by copying  
CatalogEntry c1 = c;  
  
// default initialization  
CatalogEntry c2;  
// assignment operator  
c2 = c;
```

Functions operating on records

Functions operating on records

Functions operating on records

```
void printCatalogEntry(CatalogEntry c){  
    cout << "Title: " << c.title << endl;  
    cout << "Author: " << c.author << endl;  
    cout << "Publisher: " << c.publisher << endl;  
    cout << "Publishing Year: " << c.publishingYear << endl;  
    cout << "Call Number: " << c.callNumber << endl;  
}
```

- As usual, by default arguments are passed by value (call by value)

Passing References

- For efficiency, call by reference is also supported

Passing References

- For efficiency, call by reference is also supported

Passing References

- For efficiency, call by reference is also supported

Passing References

- For efficiency, call by reference is also supported

```
void printCatalogEntry(const CatalogEntry &c){  
    cout << "Title: " << c.title << endl;  
    cout << "Author: " << c.author << endl;  
    cout << "Publisher: " << c.publisher << endl;  
    cout << "Publishing Year: " << c.publishingYear << endl;  
    cout << "Call Number: " << c.callNumber << endl;  
}
```

Equality checking

- Not supported by default

Equality checking

- Not supported by default

Equality checking

- Not supported by default

Equality checking

- Not supported by default

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

Equality checking

- Not supported by default

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

Equality checking

- Not supported by default

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

Equality checking

- Not supported by default

```
if (c1 == c2) // invalid
```

- As in the case for arrays, must do this each field at a time

```
bool CatalogEntryEquals(const CatalogEntry &c1, const CatalogEntry &c2)
{
    return c1.title == c2.title && c1.author == c2.author &&
        c1.publisher == c2.publisher &&
        c1.publishingYear == c2.publishingYear &&
        c1.callNumber == c2.callNumber;
}
```


Complex record data structures

- Arrays of records

Complex record data structures

- Arrays of records

Complex record data structures

- Arrays of records

Complex record data structures

- Arrays of records

```
CatalogEntry A[3];  
CatalogEntry A[] = {{"Peter Pan",  
                    "J. M. Barrie",  
                    "Scribner",  
                    1980,  
                    "B2754 1980"},  
{"C++ Primer",  
 "Stanley B. Lippman",  
 "Addison-Wesley",  
 1998,  
 "QA 76.73 C15 L57 1998"},  
{"Anatomy of LISP",  
 "John Allen",  
 "McGraw-Hill",  
 1978,  
 "QA 76.73 L23A44"}}};
```

Practise!

- See the very first announcement in UR Courses

Practise!

- See the very first announcement in UR Courses
- Try the exercises there

Practise!

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system
 - declare a C++ struct to represent a hexagon

- See the very first announcement in UR Courses
- Try the exercises there
 - declare a C++ struct to represent a point in the Cartesian coordinate system
 - declare a C++ struct to represent a hexagon
 - declare a C++ struct to represent a circle

Arrays inside of records

- Can put arrays as fields of records

Arrays inside of records

- Can put arrays as fields of records

Arrays inside of records

- Can put arrays as fields of records

Arrays inside of records

- Can put arrays as fields of records

```
const int MAX_NAMES = 100;  
  
struct FullName {  
    string name_component[MAX_NAMES];  
    int name_count;  
};
```

Multi-Dimensional Arrays in Records

Multi-Dimensional Arrays in Records

Multi-Dimensional Arrays in Records

```
const int SCREEN_HEIGHT = 768, SCREEN_WIDTH = 1024;
struct Screen{
    char screen_array[SCREEN_HEIGHT][SCREEN_WIDTH];
};

...

Screen my_screen;
for (int i = 0; i < SCREEN_HEIGHT; i++){
    my_screen.screen_array[i][0] = '*';
}
```


Mix and Match

Mix and Match

Mix and Match

Mix and Match

Mix and Match

```
#include <iostream>
using namespace std;
struct str1 {
    int a[2];
    int b;
};

void func1(str1 A[ ]){
    A[0].a[0] = 10;
    A[0].a[1] = 20;
    A[0].b = 30;
}

int main( ) {
    str1 A[3] = {{{1,0},2}, {{3,0},4},{{0,0},9}};
    func1(A);

    std::cout << A[0].b<<"\n";
    std::cout << A[0].a[1]<<"\n";
}
```

Mix and Match

```
#include <iostream>
using namespace std;
struct str1 {
    int a[2];
    int b;
};

void func1(str1 A[ ]){
    A[0].a[0] = 10;
    A[0].a[1] = 20;
    A[0].b = 30;
}

int main( ) {
    str1 A[3] = {{{1,0},2}, {{3,0},4},{{0,0},9}};
    func1(A);

    std::cout << A[0].b<<"\n";
    std::cout << A[0].a[1]<<"\n";
}
```

- What will the output be?

Enumerations

Enumerations

Enumerations

```
enum day {  
    Friday = 99, //  
    Saturday, //  
    Sunday = 90, //  
    ...,  
    Thursday //  
};  
  
day d;  
d = Thursday;  
  
if (d == Saturday || d == Sunday)  
    cout << "Enjoy the weekend!" ;  
  
cout << d+1 ;
```

Enumerations

```
enum day {  
    Friday = 99, //  
    Saturday, //  
    Sunday = 90, //  
    ...,  
    Thursday //  
};  
  
day d;  
d = Thursday;  
  
if (d == Saturday || d == Sunday)  
    cout << "Enjoy the weekend!" ;  
  
cout << d+1 ;
```

- User-defined data type that consists of integral constants

Enumerations

```
enum day {  
    Friday = 99, //  
    Saturday, //  
    Sunday = 90, //  
    ...,  
    Thursday //  
};  
  
day d;  
d = Thursday;  
  
if (d == Saturday || d == Sunday)  
    cout << "Enjoy the weekend!" ;  
  
cout << d+1 ;
```

- User-defined data type that consists of integral constants
- What will the output be?

Variant records

Variant records

Variant records

- Called union in C++

Variant records

- Called union in C++
- Multiple component fields can be defined

Variant records

- Called union in C++
- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Called union in C++
- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Called union in C++
- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Called union in C++
- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

Variant records

- Called union in C++
- Multiple component fields can be defined
- At most one field can be in use at one time (fields share the same memory)

```
union Coordinates {  
    int a,  
    double b,  
    char c  
};  
  
Coordinates x;  
  
x.a = 5;  
cout << x.a; // works, prints 5  
  
x.b = 416.905; // destroys the value of x.a  
x.c = 'p'; // destroys the value of x.a and  
cout << x.a; // invalid!  
cout << x.b; // invalid!  
cout << x.c; // works, prints p
```

Example

Example

Example

Example

Example

```
enum CatalogEntryType {  
    BookEntry, //  
    DVDEntry //  
};  
  
struct BookSpecificInfo {  
    unsigned int pages;  
};
```

Example

```
enum CatalogEntryType {  
    BookEntry, //  
    DVDEntry //  
};  
  
struct BookSpecificInfo {  
    unsigned int pages;  
};
```

Example

```
enum CatalogEntryType {  
    BookEntry, //  
    DVDEntry //  
};  
  
struct BookSpecificInfo {  
    unsigned int pages;  
};
```

Example

```
enum CatalogEntryType {  
    BookEntry, //  
    DVDEntry //  
};  
  
struct BookSpecificInfo {  
    unsigned int pages;  
};
```

```
struct DVDSpecificInfo {  
    unsigned int discs;  
    unsigned int minutes;  
};  
  
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

Example (cont'd)

Example (cont'd)

Example (cont'd)

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    CatalogEntryType tag;  
    CatalogEntryVariantPart variant;  
};
```

Example (cont'd)

Example (cont'd)

Example (cont'd)

```
void printCatalogEntry(const CatalogEntry& c) {
    cout << "Title: " << c.title << endl;
    ...
    cout << "Call Number: " << c.callNumber << endl;
    switch (c.tag) {
    case BookEntry:
        cout << "Pages: " << c.variant.book.pages << endl;
        break;
    case DVDEntry:
        cout << "Discs: " << c.variant.dvd.discs << endl;
        cout << "Minutes: " << c.variant.dvd.minutes << endl;
        break;
    }
}
```

- C++ unions are unsafe

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there
 - You have to make sure the tag actually matches the data

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there
 - You have to make sure the tag actually matches the data
- Other languages have safe combinations of tags and unions

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there
 - You have to make sure the tag actually matches the data
- Other languages have safe combinations of tags and unions
 - enum in Rust and Swift

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there
 - You have to make sure the tag actually matches the data
- Other languages have safe combinations of tags and unions
 - enum in Rust and Swift
 - Sealed Classes in Java/Kotlin

- C++ unions are unsafe
 - Without the tag, there's no way to know which type a union contains
 - C++ doesn't require the tag to be there
 - You have to make sure it's there
 - You have to make sure the tag actually matches the data
- Other languages have safe combinations of tags and unions
 - enum in Rust and Swift
 - Sealed Classes in Java/Kotlin
 - Algebraic datatypes in functional languages (CS 350)

Anonymous declaration of records and variant-records

- Earlier:

Anonymous declaration of records and variant-records

- Earlier:

Anonymous declaration of records and variant-records

- Earlier:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

Anonymous declaration of records and variant-records

- Earlier:

```
union CatalogEntryVariantPart {  
    BookSpecificInfo book;  
    DVDSpecificInfo dvd;  
};
```

- Could have actually declared them in-line:

```
union CatalogEntryVariantPart {  
    struct BookSpecificInfo { unsigned int pages; } book;  
    struct DVDSpecificInfo { unsigned int discs, minutes; } dvd;  
};
```

Anonymous declaration of records and variant-records

- Can also anonymize:

Anonymous declaration of records and variant-records

- Can also anonymize:

Anonymous declaration of records and variant-records

- Can also anonymize:

Anonymous declaration of records and variant-records

- Can also anonymize:

```
union CatalogEntryVariantPart {  
    struct { unsigned int pages; } book;  
    struct { unsigned int discs, minutes; } dvd;  
};
```


Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

Anonymous declaration of records and variant-records

- In fact, we could have done the same with the union

```
struct CatalogEntry {  
    string title;  
    string author;  
    string publisher;  
    unsigned int publishingYear;  
    string callNumber;  
    CatalogEntryType tag;  
    union {  
        struct { unsigned int pages; } book;  
        struct { unsigned int discs, minutes; } dvd;  
    } variant;  
};
```