

# **Final Exam Review: Interpreters**

CS 350

---

Dr. Joseph Eremondi

Last updated: August 14, 2024

# Interpreters

---

## What We've Learned

- Syntax trees to represent programs

# What We've Learned

- Syntax trees to represent programs
- Evaluation (interp)

## What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively

## What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying

# What We've Learned

- Syntax trees to represent programs
- Evaluation (interp)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features



# What We've Learned

- Syntax trees to represent programs
- Evaluation (interp)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters



# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters
  - Boxes

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters
  - Boxes
  - Mutable Variables

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters
  - Boxes
  - Mutable Variables
  - Recursion via mutation

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters
  - Boxes
  - Mutable Variables
  - Recursion via mutation
- OOP

# What We've Learned

- Syntax trees to represent programs
- Evaluation (`interp`)
  - Compute the value for an expression recursively
- Desugaring
  - E.g. Substitution, Currying
- Language features
  - Conditionals
  - Top-level function definitions
  - Local variable definitions (`let var`)
  - First-class functions via substitution
- Environment-based interpreters
  - Variables via environments
  - Lambdas via environments: closures
- Store-passing interpreters
  - Boxes
  - Mutable Variables
  - Recursion via mutation
- OOP
- Lazy evaluation

# **Syntax and the Language Pipeline**

---

# Life of a program

- The Language Pipeline:



# The Pipeline

- Start with source code



# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input



# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input
- Interpreter/Evaluation

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input
- Interpreter/Evaluation
  - Actually run the code

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input
- Interpreter/Evaluation
  - Actually run the code
  - Get a value and/or side-effects

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input
- Interpreter/Evaluation
  - Actually run the code
  - Get a value and/or side-effects
- Value type

# The Pipeline

- Start with source code
- Parser translates it into a *syntax tree*
  - I won't ask about parsers on the exam
- Surface Syntax Tree (SurfaceExpr)
  - Direct representation of the syntax of the program
- Desugaring/Elaboration
  - Translate the surface syntax tree into core syntax
- Core syntax (Expr)
  - The type that the interpreter takes as input
- Interpreter/Evaluation
  - Actually run the code
  - Get a value and/or side-effects
- Value type
  - Whatever the result of the computation is

- Every expression has a *value*

# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value

# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value
  - Can view it as *defining* the semantics of the language



# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value
  - Can view it as *defining* the semantics of the language
- Recursively compute sub-expression values

# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value
  - Can view it as *defining* the semantics of the language
- Recursively compute sub-expression values
  - Use to compute value for the whole expression

# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value
  - Can view it as *defining* the semantics of the language
- Recursively compute sub-expression values
  - Use to compute value for the whole expression
  - Once have a value, then we can use the features of the implementation language

# Interpreter Basics

- Every expression has a *value*
- Interpreter computes this value
  - Can view it as *defining* the semantics of the language
- Recursively compute sub-expression values
  - Use to compute value for the whole expression
  - Once have a value, then we can use the features of the implementation language
    - e.g. We can't use `Plait +` on an `Expr`, but once we apply `interp` and get a `Number` we can

# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized

# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized
- We use `Symbol` as a Plait type to represent variable names

# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized
- We use `Symbol` as a Plait type to represent variable names
- Add variant (`Var [x : Symbol]`) to `Expr`

# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized
- We use `Symbol` as a Plait type to represent variable names
- Add variant (`Var [x : Symbol]`) to `Expr`
- New operation: substitution



# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized
- We use `Symbol` as a Plait type to represent variable names
- Add variant `(Var [x : Symbol])` to `Expr`
- New operation: substitution
  - Replace all *free* occurrences of the variable `x` with some expression in another expression

# Variables and Substitution

- To implement functions, we need a way to specify a program that's parameterized
- We use `Symbol` as a Plait type to represent variable names
- Add variant `(Var [x : Symbol])` to `Expr`
- New operation: substitution
  - Replace all *free* occurrences of the variable `x` with some expression in another expression
    - Ignoring bound occurrences gives us *shadowing*

- To implement a function call with substitution:

# Function Calls

- To implement a function call with substitution:
  - Evaluate the function to a value

# Function Calls

- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body

# Function Calls

- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body
  - Evaluate the argument to a value

- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body
  - Evaluate the argument to a value
    - (If doing strict semantics)

# Function Calls

- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body
  - Evaluate the argument to a value
    - (If doing strict semantics)
  - Replace the parameter symbol with the argument value in the body



- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body
  - Evaluate the argument to a value
    - (If doing strict semantics)
  - Replace the parameter symbol with the argument value in the body
  - Interpret the replaced body

# Function Calls

- To implement a function call with substitution:
  - Evaluate the function to a value
    - Gives us a parameter symbol and a body
  - Evaluate the argument to a value
    - (If doing strict semantics)
  - Replace the parameter symbol with the argument value in the body
  - Interpret the replaced body
    - This is how we say “run the body”

## Local Definitions: Intuition

- Consider this C++ program

## Local Definitions: Intuition

- Consider this C++ program

# Local Definitions: Intuition

- Consider this C++ program

```
if (someCondition){  
    cout >> "hello";  
    int x = 10;  
    while (x > 0){  
        cout >> x;  
        x = x - 1;  
    }  
}  
cout >> "goodbye";
```

- Declaring `int x = 10` creates a new variable **whose scope is not obvious from the code**

# Local Definitions: Intuition

- Consider this C++ program

```
if (someCondition){  
    cout >> "hello";  
    int x = 10;  
    while (x > 0){  
        cout >> x;  
        x = x - 1;  
    }  
}  
cout >> "goodbye";
```

- Declaring `int x = 10` creates a new variable **whose scope is not obvious from the code**
  - We can use `x` anywhere from where it's declared until the end of the `if` block

# Local Definitions: Intuition

- Consider this C++ program

```
if (someCondition){  
    cout >> "hello";  
    int x = 10;  
    while (x > 0){  
        cout >> x;  
        x = x - 1;  
    }  
}  
cout >> "goodbye";
```

- Declaring `int x = 10` creates a new variable **whose scope is not obvious from the code**
  - We can use `x` anywhere from where it's declared until the end of the `if` block
- The assignment in the `while` does **not** affect the scope

# Local Definitions: Intuition

- Consider this C++ program

```
if (someCondition){  
    cout >> "hello";  
    int x = 10;  
    while (x > 0){  
        cout >> x;  
        x = x - 1;  
    }  
}  
cout >> "goodbye";
```

- Declaring `int x = 10` creates a new variable **whose scope is not obvious from the code**
  - We can use `x` anywhere from where it's declared until the end of the `if` block
- The assignment in the `while` does **not** affect the scope
  - No equivalent in a purely functional language



## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of x is body

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of x is body
- The value of x in body is the value of xExpr

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $\text{body}$
- The value of  $x$  in  $\text{body}$  is the value of  $\text{xExpr}$
- To interpret with substitution, we:

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $\text{body}$
- The value of  $x$  in  $\text{body}$  is the value of  $\text{xExpr}$
- To interpret with substitution, we:
  - Evaluate  $\text{xExpr}$  to  $\text{xVal}$

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $\text{body}$
- The value of  $x$  in  $\text{body}$  is the value of  $\text{xExpr}$
- To interpret with substitution, we:
  - Evaluate  $\text{xExpr}$  to  $\text{xVal}$
  - Replace  $x$  with  $\text{xVal}$  in  $\text{body}$

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $\text{body}$
- The value of  $x$  in  $\text{body}$  is the value of  $\text{xExpr}$
- To interpret with substitution, we:
  - Evaluate  $\text{xExpr}$  to  $\text{xVal}$
  - Replace  $x$  with  $\text{xVal}$  in  $\text{body}$
  - Interpret the replaced version of  $\text{body}$



## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $body$
- The value of  $x$  in  $body$  is the value of  $xExpr$
- To interpret with substitution, we:
  - Evaluate  $xExpr$  to  $xVal$
  - Replace  $x$  with  $xVal$  in  $body$
  - Interpret the replaced version of  $body$
- Similar to:

## Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $body$
- The value of  $x$  in  $body$  is the value of  $xExpr$
- To interpret with substitution, we:
  - Evaluate  $xExpr$  to  $xVal$
  - Replace  $x$  with  $xVal$  in  $body$
  - Interpret the replaced version of  $body$
- Similar to:

# Local Definitions

- In an expression based language, the scope of a variable is *explicit*

```
{letvar x xExpr body}
```

- The scope of  $x$  is  $body$
- The value of  $x$  in  $body$  is the value of  $xExpr$
- To interpret with substitution, we:
  - Evaluate  $xExpr$  to  $xVal$
  - Replace  $x$  with  $xVal$  in  $body$
  - Interpret the replaced version of  $body$
- Similar to:

```
if (true){ // make the scope explicit
  int x = xExpr;
  body;
}
```

- When we have functions as values, we need a way to

# Environments

---

- What is the *meaning* of the program  $\{+ \ x \ 1\}$

- What is the *meaning* of the program  $\{+ \ x \ 1\}$ 
  - With substitution, the program has no meaning until we replace  $x$  with a value

# Why Environments

- What is the *meaning* of the program  $\{ + \ x \ 1 \}$ 
  - With substitution, the program has no meaning until we replace  $x$  with a value
- Environments *give meaning to programs with free variables*



# Why Environments

- What is the *meaning* of the program  $\{+ \ x \ 1\}$ 
  - With substitution, the program has no meaning until we replace  $x$  with a value
- Environments *give meaning to programs with free variables*
  - The program has a value *parameterized over* values for the free variables

# Why Environments

- What is the *meaning* of the program  $\{+ \ x \ 1\}$ 
  - With substitution, the program has no meaning until we replace  $x$  with a value
- Environments *give meaning to programs with free variables*
  - The program has a value *parameterized over* values for the free variables
- Performance:

# Why Environments

- What is the *meaning* of the program  $\{+ \ x \ 1\}$ 
  - With substitution, the program has no meaning until we replace  $x$  with a value
- Environments *give meaning to programs with free variables*
  - The program has a value *parameterized over* values for the free variables
- Performance:
  - Instead of traversing the entire body of the function, just push a binding onto the front of a list

- Environment is a list of symbol-value pairs

- Environment is a list of symbol-value pairs
  - For purely functional language

- Environment is a list of symbol-value pairs
  - For purely functional language
- Operations:

- Environment is a list of symbol-value pairs
  - For purely functional language
- Operations:
  - Make empty environment

- Environment is a list of symbol-value pairs
  - For purely functional language
- Operations:
  - Make empty environment
  - Look up the most recent value for a given symbol



- Environment is a list of symbol-value pairs
  - For purely functional language
- Operations:
  - Make empty environment
  - Look up the most recent value for a given symbol
  - Add a new binding (e.g. add a new value for a given symbol)

- Environment is a list of symbol-value pairs
  - For purely functional language
- Operations:
  - Make empty environment
  - Look up the most recent value for a given symbol
  - Add a new binding (e.g. add a new value for a given symbol)
    - Like a low-tech hashtable/dictionary/key-value store

## Letvar with environments

## Letvar with environments

```
{letvar x xExpr body}
```

- Interpret xExpr to a value

## Letvar with environments

```
{letvar x xExpr body}
```

- Interpret xExpr to a value
- Make a new environment with x bound to the value of xExpr

- Lambdas let us create functions at any point in the program

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values



- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**
- Functions evaluate to closures

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**
- Functions evaluate to closures
- Data structure with:

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**
- Functions evaluate to closures
- Data structure with:
  - Parameter variable

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**
- Functions evaluate to closures
- Data structure with:
  - Parameter variable
  - Body (where parameter is in scope)

# Closures

- Lambdas let us create functions at any point in the program
  - Can refer to any in-scope variables
- When those variables get values, the lambda should use those values
  - Happens automatically with substitution
- In an environment-based interpreter, we must **include the environment from when a function was created**
- Functions evaluate to closures
- Data structure with:
  - Parameter variable
  - Body (where parameter is in scope)
  - Environment from when the function was **created**

# Static vs. Dynamic Scope

- Closures implement static scope



# Static vs. Dynamic Scope

- Closures implement static scope
  - In a lambda, free variables get their values from where the function was *created*

# Static vs. Dynamic Scope

- Closures implement static scope
  - In a lambda, free variables get their values from where the function was *created*
- Dynamic scope:

# Static vs. Dynamic Scope

- Closures implement static scope
  - In a lambda, free variables get their values from where the function was *created*
- Dynamic scope:
  - In a lambda, free variables get their values from where the function is *called*

# Mutable State

---

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*



# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store
  - `interp` now produces a value *and a store*

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store
  - `interp` now produces a value *and a store*
    - State of memory after interpreting some expression

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store
  - `interp` now produces a value *and a store*
    - State of memory after interpreting some expression
    - Gets passed to the next interpreter call

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variables value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store
  - `interp` now produces a value *and a store*
    - State of memory after interpreting some expression
    - Gets passed to the next interpreter call
  - Sequence of states we pass along determines the execution order

# Generative Recursion

- Recall how we used generative/tail recursion to implement loops
  - Updated a variable's value by passing the new value as a parameter to the recursive call
- Implementing mutable state in a purely functional language works the same way
  - Take an extra argument for the *current state of memory*
    - Called the **store**
  - Each recursive call is explicitly passed a store
  - `interp` now produces a value *and a store*
    - State of memory after interpreting some expression
    - Gets passed to the next interpreter call
  - Sequence of states we pass along determines the execution order
- We can now view programs as functions from the current environment *and the current state of memory* to values *and states of memory*

- Value representing a location in memory



- Value representing a location in memory
  - Kind of like pointer

- Value representing a location in memory
  - Kind of like pointer
- Create a box

- Value representing a location in memory
  - Kind of like pointer
- Create a box
  - Add a **new** location to the store

- Value representing a location in memory
  - Kind of like pointer
- Create a box
  - Add a **new** location to the store
- Unbox a value

- Value representing a location in memory
  - Kind of like pointer
- Create a box
  - Add a **new** location to the store
- Unbox a value
  - Look up the value for the box's location in the store

- Value representing a location in memory
  - Kind of like pointer
- Create a box
  - Add a **new** location to the store
- Unbox a value
  - Look up the value for the box's location in the store
- Set a box's value

- Value representing a location in memory
  - Kind of like pointer
- Create a box
  - Add a **new** location to the store
- Unbox a value
  - Look up the value for the box's location in the store
- Set a box's value
  - Update the store to have a new value *for the box's existing location*

# Mutable Variables

- One big change:



# Mutable Variables

- One big change:
  - Environments store *locations*, not values

# Mutable Variables

- One big change:
  - Environments store *locations*, not values
- Each variable lookup now gets a location from the env, and a value from that location in the store

# Mutable Variables

- One big change:
  - Environments store *locations*, not values
- Each variable lookup now gets a location from the env, and a value from that location in the store
- Can mutate a variable's value by producing a store with a different value at the variable's location

- Can define values self-referentially with mutable state

- Can define values self-referentially with mutable state
- Interpret the value for a variable in an environment extended with that variable

- Can define values self-referentially with mutable state
- Interpret the value for a variable in an environment extended with that variable
  - Dummy value at the variable's location in the store

- Can define values self-referentially with mutable state
- Interpret the value for a variable in an environment extended with that variable
  - Dummy value at the variable's location in the store
- After interpreting the value, put that value at the variable's location in the store

- Can define values self-referentially with mutable state
- Interpret the value for a variable in an environment extended with that variable
  - Dummy value at the variable's location in the store
- After interpreting the value, put that value at the variable's location in the store
- Works as long as all recursive uses of the variable are in the body of a lambda



- Can define values self-referentially with mutable state
- Interpret the value for a variable in an environment extended with that variable
  - Dummy value at the variable's location in the store
- After interpreting the value, put that value at the variable's location in the store
- Works as long as all recursive uses of the variable are in the body of a lambda
  - Closures don't evaluate their bodies until called

## **Alternate Models of Execution**

---

- Pair data (members) with operations on that data (fields)

- Pair data (members) with operations on that data (fields)
- Self reference

- Pair data (members) with operations on that data (fields)
- Self reference
- Adding new variants of an interface is an easy (local) change

- Pair data (members) with operations on that data (fields)
- Self reference
- Adding new variants of an interface is an easy (local) change
- Adding new operations is a hard (global) change