

Midterm Review

CS 350

Dr. Joseph Eremondi

Last updated: July 23, 2024

Overview

The Road So Far

- Functional programming

The Road So Far

- Functional programming
 - Recursion and datatypes

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables
 - Let via substitution

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables
 - Let via substitution
 - Let via environment extension

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables
 - Let via substitution
 - Let via environment extension
 - First-class functions

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables
 - Let via substitution
 - Let via environment extension
 - First-class functions
 - Dynamic typing

The Road So Far

- Functional programming
 - Recursion and datatypes
 - Higher-order functions and lambdas
- Interpreters
 - Parsing basics and syntax trees
 - Arithmetic via recursion on the AST
 - Adding conditionals: If0
 - Adding syntactic sugar
 - Now have Surface AST and Core AST
 - eLab translates from surface to core
 - Expresses some features in terms of other ones
 - Adding functions
 - Substitution
 - Environments
 - Adding variables
 - Let via substitution
 - Let via environment extension
 - First-class functions
 - Dynamic typing
 - Closures and environments

Part 1: Functional Programming Concepts

- Functions *in the mathematical sense*

- Functions *in the mathematical sense*
 - Same input always produces same output

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*
 - Once a variable has a value, it keeps that value for its entire scope

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*
 - Once a variable has a value, it keeps that value for its entire scope
- The main method of iteration/repetition is recursion

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*
 - Once a variable has a value, it keeps that value for its entire scope
- The main method of iteration/repetition is recursion
 - Not loops

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*
 - Once a variable has a value, it keeps that value for its entire scope
- The main method of iteration/repetition is recursion
 - Not loops
 - Explicit recursion: a function calling itself on different (smaller) arguments

Functional Programming

- Functions *in the mathematical sense*
 - Same input always produces same output
- Variables are *immutable*
 - Once a variable has a value, it keeps that value for its entire scope
- The main method of iteration/repetition is recursion
 - Not loops
 - Explicit recursion: a function calling itself on different (smaller) arguments
 - Higher-order functions: capture patterns of recursion that can be re-used many times

Programming With Recursion 1: Shape

- Identify the shape of the problem

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs
 - Types of outputs

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs
 - Types of outputs
 - Other assumptions not expressible with types

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs
 - Types of outputs
 - Other assumptions not expressible with types
 - e.g. Can we assume numbers are integers? Positive? etc.

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs
 - Types of outputs
 - Other assumptions not expressible with types
 - e.g. Can we assume numbers are integers? Positive? etc.
 - e.g. Can we assume a list is non-empty

Programming With Recursion 1: Shape

- Identify the shape of the problem
 - Types of inputs
 - Types of outputs
 - Other assumptions not expressible with types
 - e.g. Can we assume numbers are integers? Positive? etc.
 - e.g. Can we assume a list is non-empty
- Now you can write tests, since you know what valid inputs are

Programming With Recursion: Template

- What are the cases you have to handle?

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. $(+ \ n \ 1)$

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?
 - List: head and tail for cons case

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?
 - List: head and tail for cons case
 - Datatype: fields for that constructor

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?
 - List: head and tail for cons case
 - Datatype: fields for that constructor
- Write a template that looks at the input and has a placeholder for each case

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?
 - List: head and tail for cons case
 - Datatype: fields for that constructor
- Write a template that looks at the input and has a placeholder for each case
 - Numbers: branch using if or cond

Programming With Recursion: Template

- What are the cases you have to handle?
 - Numbers: 0 vs. (+ n 1)
 - List: empty vs. (cons h t)
 - Datatype: each constructor
- What are the sub-values for each case?
 - List: head and tail for cons case
 - Datatype: fields for that constructor
- Write a template that looks at the input and has a placeholder for each case
 - Numbers: branch using if or cond
 - Lists or datatype: branch using type-case

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype
 - E.g. in `Expr`, `Var x` and `NumLit n` are both base cases

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype
 - E.g. in `Expr`, `Var x` and `NumLit n` are both base cases
- For the base case, figure out the solution for that case

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype
 - E.g. in `Expr`, `Var x` and `NumLit n` are both base cases
- For the base case, figure out the solution for that case
 - Depends on the problem you're looking at

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype
 - E.g. in `Expr`, `Var x` and `NumLit n` are both base cases
- For the base case, figure out the solution for that case
 - Depends on the problem you're looking at
 - E.g. "If my input is \emptyset , what should `f` be?"

Programming With Recursion: Base vs Recursive Case

- Figure out which cases are base cases and which are recursive cases
 - Recursive case has a sub-value of input
 - Might be many base cases for datatype
 - E.g. in `Expr`, `Var x` and `NumLit n` are both base cases
- For the base case, figure out the solution for that case
 - Depends on the problem you're looking at
 - E.g. "If my input is \emptyset , what should `f` be?"
 - E.g. "If my list is empty, how do I apply a function to each element in it?"

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call
 - Figure out values for other arguments

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call
 - Figure out values for other arguments
 - Problem dependent

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call
 - Figure out values for other arguments
 - Problem dependent
 - E.g. What env do we pass in `interp`?

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call
 - Figure out values for other arguments
 - Problem dependent
 - E.g. What env do we pass in `interp`?
 - Might be helpful to use `let*` to store results of recursive calls in variables

Programming With Recursion: Recursive Calls

- Figure out what recursive calls you can make in the recursive cases
 - If a sub-value has the same type, can definitely use it as argument to recursive call
 - Figure out values for other arguments
 - Problem dependent
 - E.g. What env do we pass in `interp`?
 - Might be helpful to use `let*` to store results of recursive calls in variables
 - Can always delete if you don't end up using them in the solution

Programming With Recursion: Putting It Together

- Look at what you have in scope

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together
- If you don't have what you need, ask:

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together
- If you don't have what you need, ask:
 - Could I make a helper function to get what I need?

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together
- If you don't have what you need, ask:
 - Could I make a helper function to get what I need?
 - Helper could also be recursive

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together
- If you don't have what you need, ask:
 - Could I make a helper function to get what I need?
 - Helper could also be recursive
- Compute the result you need for the recursive cases

Programming With Recursion: Putting It Together

- Look at what you have in scope
 - Fields/sub-values of the input
 - Results of recursive calls
 - Other arguments
- Look at the types
 - Lets you know what you have, and what you need build things together
- If you don't have what you need, ask:
 - Could I make a helper function to get what I need?
 - Helper could also be recursive
- Compute the result you need for the recursive cases
 - Problem-specific

Constructing a value of a given type

- Look at the type of the thing you're trying to produce

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant
 - e.g. 4 or #t or "hello"

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant
 - e.g. 4 or #t or "hello"
 - A function or constructor application

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant
 - e.g. 4 or #t or "hello"
 - A function or constructor application
 - Each argument to the function must then be provided

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant
 - e.g. 4 or #t or "hello"
 - A function or constructor application
 - Each argument to the function must then be provided
 - Look at their types and repeat this process

Constructing a value of a given type

- Look at the type of the thing you're trying to produce
 - Some take arguments, some don't
- You must build it using one of:
 - A variable that is in scope
 - A literal/constant
 - e.g. 4 or #t or "hello"
 - A function or constructor application
 - Each argument to the function must then be provided
 - Look at their types and repeat this process
- Which you choose depends on what you're trying to do

Higher Order Functions

Designing Higher Order Functions

- The process is the exact same

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype
- Might not

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype
- Might not
 - e.g. If you're writing `comp : (('b -> 'c) ('a -> 'b) -> ('a -> 'c))` there's nothing to deconstruct/recur on, so you just build the solution directly

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype
- Might not
 - e.g. If you're writing `comp : (('b -> 'c) ('a -> 'b) -> ('a -> 'c))` there's nothing to deconstruct/recur on, so you just build the solution directly
- Same advice applies:

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype
- Might not
 - e.g. If you're writing `comp : (('b -> 'c) ('a -> 'b) -> ('a -> 'c))` there's nothing to deconstruct/recur on, so you just build the solution directly
- Same advice applies:
 - Look at the types of what's in scope

Designing Higher Order Functions

- The process is the exact same
 - Except sometimes you have inputs or outputs that are functions
- Might use recursion if your input is recursive data
 - e.g. List or datatype
- Might not
 - e.g. If you're writing `comp : (('b -> 'c) ('a -> 'b) -> ('a -> 'c))` there's nothing to deconstruct/recur on, so you just build the solution directly
- Same advice applies:
 - Look at the types of what's in scope
 - Look at what you can build using what's in scope