

# Mutable Variables

CS 350

---

Dr. Joseph Eremondi

Last updated: August 1, 2024

## Outline

---

- Learning goals

- Learning goals
  - To interpret a language where variables can change values (mutate)

- Learning goals
  - To interpret a language where variables can change values (mutate)
  - To understand the design choices around functions in such a language

- Learning goals
  - To interpret a language where variables can change values (mutate)
  - To understand the design choices around functions in such a language
- Key concepts

- Learning goals
  - To interpret a language where variables can change values (mutate)
  - To understand the design choices around functions in such a language
- Key concepts
  - Pass-by-reference vs. Pass-by-value

# Identifiers vs Variables

- Until now, a variable denoted a *value*



# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment

# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment
- They didn't really ever vary

# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment
- They didn't really ever vary
  - Except between different function calls

# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment
- They didn't really ever vary
  - Except between different function calls
- To allow variables values to change, we can make one simple change:

# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment
- They didn't really ever vary
  - Except between different function calls
- To allow variables values to change, we can make one simple change:
  - **Keep locations instead of values in the environment**

# Identifiers vs Variables

- Until now, a variable denoted a *value*
  - In a given environment
- They didn't really ever vary
  - Except between different function calls
- To allow variables values to change, we can make one simple change:
  - **Keep locations instead of values in the environment**
  - Then each variable refers to a single store location, whose value can change

# Pass-by-value

# Pass-by-reference