

Implementing Recursion via State

CS 350

Dr. Joseph Eremondi

Last updated: August 3, 2024

Recursion via State

- Goals

- Goals
 - To see how to implement an interpreter for a language with recursion

- Goals
 - To see how to implement an interpreter for a language with recursion
 - To see how recursion interacts with environments and stores

- Goals
 - To see how to implement an interpreter for a language with recursion
 - To see how recursion interacts with environments and stores
- Key Concepts

- Goals
 - To see how to implement an interpreter for a language with recursion
 - To see how recursion interacts with environments and stores
- Key Concepts
 - Landin's Knot

Recursion in Curly-Rec

- When we are allowed to refer to x while defining the value that is assigned to x

Recursion in Curly-Rec

- When we are allowed to refer to `x` while defining the value that is assigned to `x`
- We'll do this with a special `let` form

Recursion in Curly-Rec

- When we are allowed to refer to `x` while defining the value that is assigned to `x`
- We'll do this with a special `let` form
 - `{letrec x <expr> <expr>}`

Recursion in Curly-Rec

- When we are allowed to refer to `x` while defining the value that is assigned to `x`
- We'll do this with a special `let` form
 - `{letrec x <expr> <expr>}`
 - Gives `{letrec x e1 e2}` gives `x` the value `e1` then evaluates `e2` with `x` in scope

Recursion in Curly-Rec

- When we are allowed to refer to `x` while defining the value that is assigned to `x`
- We'll do this with a special `let` form
 - `{letrec x <expr> <expr>}`
 - Gives `{letrec x e1 e2}` gives `x` the value `e1` then evaluates `e2` with `x` in scope
 - Exactly like `letvar`, except **`x` is also in scope in `e1`**

Bad Recursion

- We can't give x a value if we need to evaluate x to get that value

Bad Recursion

- We can't give x a value if we need to evaluate x to get that value
- E.g.

Bad Recursion

- We can't give x a value if we need to evaluate x to get that value
- E.g.
 - `{letrec x {+ x 1}}`

Bad Recursion

- We can't give x a value if we need to evaluate x to get that value
- E.g.
 - `{letrec x {+ x 1}}`
 - Should raise an error or loop forever

Bad Recursion

- We can't give x a value if we need to evaluate x to get that value
- E.g.
 - `{letrec x {+ x 1}}`
 - Should raise an error or loop forever
 - In a later lecture we'll see a way to give this semantics

- What can we define with recursion?

- What can we define with recursion?
 - Definitions that refer to x but don't try to evaluate it

- What can we define with recursion?
 - Definitions that refer to x but don't try to evaluate it
 - **Recursive occurrences of the variable must be in the body of a lambda**

- What can we define with recursion?
 - Definitions that refer to x but don't try to evaluate it
 - **Recursive occurrences of the variable must be in the body of a lambda**
 - Lambda bodies aren't evaluated until call time

Interpreting Recursion: The Problem

- To interpret `{letrec x e1 e2}` recursively

Interpreting Recursion: The Problem

- To interpret `{letrec x e1 e2}` recursively
 - Need `x` in scope when interpreting `e1`

Interpreting Recursion: The Problem

- To interpret `{letrec x e1 e2}` recursively
 - Need `x` in scope when interpreting `e1`
 - Can't put `e1`'s value because we haven't computed it yet

Interpreting Recursion: The Problem

- To interpret `{letrec x e1 e2}` recursively
 - Need `x` in scope when interpreting `e1`
 - Can't put `e1`'s value because we haven't computed it yet
 - Can't compute `e1`'s value because we need something for

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it
 - Interpret e1 in the environment extended with x's location

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it
 - Interpret e1 in the environment extended with x's location
 - If ever fetch from that location, get the dummy value and raise an error

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it
 - Interpret e1 in the environment extended with x's location
 - If ever fetch from that location, get the dummy value and raise an error
 - Shouldn't ever fetch if self-references are in the bodies of functions

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it
 - Interpret e1 in the environment extended with x's location
 - If ever fetch from that location, get the dummy value and raise an error
 - Shouldn't ever fetch if self-references are in the bodies of functions
 - Then, **update the store to contain the value of e1 at the location of x**

Interpreting Recursion: Idea

- With Mutable Variables, the environment stores *locations*, not values
- For `{letrec x e1 e2}`
 - Generate a new location for the recursive x being defined
 - Put a dummy value at it
 - Interpret e1 in the environment extended with x's location
 - If ever fetch from that location, get the dummy value and raise an error
 - Shouldn't ever fetch if self-references are in the bodies of functions
 - Then, **update the store to contain the value of e1 at the location of x**
 - Then, interpret the body e2 with this updated store

Interpreting Recursion: Code

Interpreting Recursion: Code

```
(define (interp [env : Env]
               [e : Expr]
               [sto : Store]) : Result
  (type-case Expr e
    [(LetRec x xexpr body)
     (let* ([x-loc (new-loc sto)] ;; Location for x
            [dummy-sto ;; Put a dummy value at x's location
              (override-store (cell x-loc
                                   (Var 'recursionError)))]
            (with ([x-val x-sto]
                   ;; Interpret xexpr in env with x's location
                   (interp (extendEnv (bind x x-loc) env)
                           xexpr
                           dummy-sto))
                     ;; Interpret body in env with x's location
                     ;; and store with x's newly computed value
                     ;; plus any side-effects from xexpr
                     (interp (extendEnv (bind x x-loc) env) body
                             (override-store (cell x-loc x-val) x-sto)))))]
```

Example

Example

```
{letrec fact {fun {x}
                  {if0 x
                     1
                     {* x {fact {- x 1}}}}}
  {fact 3}}
```

- To evaluate letrec we:

Example

```
{letrec fact {fun {x}
                  {if0 x
                     1
                     {* x {fact {- x 1}}}}}
  {fact 3}}
```

- To evaluate letrec we:
 - Make a new location Θ for fact

Example

```
{letrec fact {fun {x}
                  {if0 x
                     1
                     {* x {fact {- x 1}}}}}
  {fact 3}}
```

- To evaluate letrec we:
 - Make a new location Θ for fact
 - Evaluate the value for fact

Example

```
{letrec fact {fun {x}
                  {if0 x
                     1
                     {* x {fact {- x 1}}}}}
  {fact 3}}
```

- To evaluate letrec we:
 - Make a new location Θ for fact
 - Evaluate the value for fact
 - Env: fact := Θ

Example

```
{letrec fact {fun {x}
                  {if0 x
                     1
                     {* x {fact {- x 1}}}}}
  {fact 3}}
```

- To evaluate letrec we:
 - Make a new location Θ for fact
 - Evaluate the value for fact
 - Env: fact := Θ
 - Store: $\Theta \Rightarrow (\text{Var } \text{'recursionError}) \sim\sim$

Example (ctd)

- Evaluating function produces closure:

Example (ctd)

- Evaluating function produces closure:

Example (ctd)

- Evaluating function produces closure:

```
(ClosureV
  (Fun 'x (If0 (Var 'x)
    (NumLit 1)
    (Times (Var 'x)
      (Call (Var 'fact)
        (Plus (Var 'x)
          (Times (NumLit 1) (NumLit -1)))))))
  (fact := 0))
```

- Never fetch from location 0

Example (ctd)

- Evaluating function produces closure:

```
(ClosureV
  (Fun 'x (If0 (Var 'x)
    (NumLit 1)
    (Times (Var 'x)
      (Call (Var 'fact)
        (Plus (Var 'x)
          (Times (NumLit 1) (NumLit -1)))))))
  (fact := 0))
```

- Never fetch from location 0
 - Interp of function doesn't interp body of function

Example (ctd)

- Evaluating function produces closure:

```
(ClosureV
  (Fun 'x (If0 (Var 'x)
    (NumLit 1)
    (Times (Var 'x)
      (Call (Var 'fact)
        (Plus (Var 'x)
          (Times (NumLit 1) (NumLit -1)))))))
  (fact := 0))
```

- Never fetch from location 0
 - Interp of function doesn't interp body of function
- Closure captures environment with `fact := 0`

Example (ctd)

- Evaluating function produces closure:

```
(ClosureV
  (Fun 'x (If0 (Var 'x)
               (NumLit 1)
               (Times (Var 'x)
                      (Call (Var 'fact)
                            (Plus (Var 'x)
                                   (Times (NumLit 1) (NumLit -1)))))))
  (fact := 0))
```

- Never fetch from location 0
 - Interp of function doesn't interp body of function
- Closure captures environment with `fact := 0`
 - Only captures environment, **not store**

Example (ctd)

- Then tie the knot

Example (ctd)

- Then tie the knot
 - Env: fact := 0

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`
- Cyclic data structure:

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`
- Cyclic data structure:
 - Store contains closure at location `0`

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`
- Cyclic data structure:
 - Store contains closure at location `0`
 - Closure stores environment (`fact := 0`)

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`
- Cyclic data structure:
 - Store contains closure at location `0`
 - Closure stores environment (`fact := 0`)
 - That environment points to `0` in store

Example (ctd)

- Then tie the knot
 - Env: `fact := 0`
 - Store: `0 ==> (ClosureV (Fun 'x) (fact := 0))`
 - Updated with value for `fact`
- Cyclic data structure:
 - Store contains closure at location `0`
 - Closure stores environment (`fact := 0`)
 - That environment points to `0` in store
 - Store contains closure at location `0`

Example (ct)

Example (ct)

```
{letrec fact {fun {x}
                  {if0 x
                      1
                      {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store

Example (ct)

```
{letrec fact {fun {x}
  {if0 x
    1
    {* x {fact {- x 1}}}}}
{fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0

Example (ct)

```
{letrec fact {fun {x}
                    {if0 x
                        1
                        {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0

Example (ct)

```
{letrec fact {fun {x}
                    {if0 x
                        1
                        {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body

Example (ct)

```
{letrec fact {fun {x}
                    {if0 x
                        1
                        {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0

Example (ct)

```
{letrec fact {fun {x}
                  {if0 x
                      1
                      {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0
 - Store 0 ==> (ClosureV), 1 ==> (NumV 3)

Example (ct)

```
{letrec fact {fun {x}
                    {if0 x
                        1
                        {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0
 - Store 0 ==> (ClosureV), 1 ==> (NumV 3)
- If0 in closure body goes to branch with call

Example (ct)

```
{letrec fact {fun {x}
                  {if0 x
                      1
                      {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0
 - Store 0 ==> (ClosureV), 1 ==> (NumV 3)
- If0 in closure body goes to branch with call
- fact in call evaluates to *the same closure* at location 0

Example (ct)

```
{letrec fact {fun {x}
                  {if0 x
                      1
                      {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0
 - Store 0 ==> (ClosureV), 1 ==> (NumV 3)
- If0 in closure body goes to branch with call
- fact in call evaluates to *the same closure* at location 0
 - Evaluation repeats, but with x bound to location with NumV 2

Example (ct)

```
{letrec fact {fun {x}
                    {if0 x
                        1
                        {* x {fact {- x 1}}}}}
  {fact 3}}
```

- Finally evaluate body in updated store
 - Env: fact := 0
- 3 evaluates to (NumLit 3), fact evaluates to closure from location 0
- Call evaluates closure body
 - Environment x := 1, fact := 0
 - Store 0 ==> (ClosureV), 1 ==> (NumV 3)
- If0 in closure body goes to branch with call
- fact in call evaluates to *the same closure* at location 0
 - Evaluation repeats, but with x bound to location with NumV 2
 - Etc. until we reach 0 and don't have a recursive call

Landin's Knot

- This trick is general

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming
 - Early version of algebraic datatypes

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming
 - Early version of algebraic datatypes
- You can simulate recursion in any language with

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming
 - Early version of algebraic datatypes
- You can simulate recursion in any language with
 - First-class functions/closures

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming
 - Early version of algebraic datatypes
- You can simulate recursion in any language with
 - First-class functions/closures
 - Mutable references/variables

Landin's Knot

- This trick is general
 - Known as *Landin's Knot*
 - British Computer Scientist Peter Landin
 - Pioneer of functional programming
 - Inventor of *offside rule* for whitespace-sensitive languages
 - Invented the term *syntactic sugar*
 - Saw the connection between lambda calculus and programming
 - Early version of algebraic datatypes
- You can simulate recursion in any language with
 - First-class functions/closures
 - Mutable references/variables
- Useful in typed languages that can't give the Y-combinator a type