

Mutable Variables

CS 350

Dr. Joseph Eremondi

Last updated: August 1, 2024

Curly-Mutvar

- Learning goals

- Learning goals
 - To interpret a language where variables can change values (mutate)

- Learning goals
 - To interpret a language where variables can change values (mutate)
 - To understand the design choices around functions in such a language

- Learning goals
 - To interpret a language where variables can change values (mutate)
 - To understand the design choices around functions in such a language
- Key concepts

- Learning goals
 - To interpret a language where variables can change values (mutate)
 - To understand the design choices around functions in such a language
- Key concepts
 - Pass-by-reference vs. Pass-by-value

Identifiers vs Variables

- Until now, a variable denoted a *value*

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment
- They didn't really ever vary

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment
- They didn't really ever vary
 - Except between different function calls

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment
- They didn't really ever vary
 - Except between different function calls
- To allow variables values to change, we can make one simple change:

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment
- They didn't really ever vary
 - Except between different function calls
- To allow variables values to change, we can make one simple change:
 - **Keep locations instead of values in the environment**

Identifiers vs Variables

- Until now, a variable denoted a *value*
 - In a given environment
- They didn't really ever vary
 - Except between different function calls
- To allow variables values to change, we can make one simple change:
 - **Keep locations instead of values in the environment**
 - Then each variable refers to a single store location, whose value can change

Bindings with mutable variables

- Each binding associates a symbol with a *location*

Bindings with mutable variables

- Each binding associates a symbol with a *location*

Bindings with mutable variables

- Each binding associates a symbol with a *location*

```
(define-type Binding
  (bind [name : Symbol]
        [loc : Location]))
```

- All other environment operations are the same

Bindings with mutable variables

- Each binding associates a symbol with a *location*

```
(define-type Binding  
  (bind [name : Symbol]  
        [loc : Location]))
```

- All other environment operations are the same
- Lookup now has type:

Bindings with mutable variables

- Each binding associates a symbol with a *location*

```
(define-type Binding  
  (bind [name : Symbol]  
        [loc : Location]))
```

- All other environment operations are the same
- Lookup now has type:

Bindings with mutable variables

- Each binding associates a symbol with a *location*

```
(define-type Binding  
  (bind [name : Symbol]  
        [loc : Location]))
```

- All other environment operations are the same
- Lookup now has type:

```
(define (lookup [n : Symbol] [env : Env]) : Location ....)
```

Interpreting Variables

Interpreting Variables

```
(define (interp [env : Env]
               [e : Expr]
               [sto : Store]) : Result
  (type-case Expr e
    [(Var x)
     (v*s (fetch (lookup x env) sto) sto)]
    ....))
```

- Previously, we just looked up a value with `lookup`

Interpreting Variables

```
(define (interp [env : Env]
               [e : Expr]
               [sto : Store]) : Result
  (type-case Expr e
    [(Var x)
     (v*s (fetch (lookup x env) sto) sto)]
    ....))
```

- Previously, we just looked up a value with `lookup`
- Now we lookup a *location*

Interpreting Variables

```
(define (interp [env : Env]
                [e : Expr]
                [sto : Store]) : Result
  (type-case Expr e
    [(Var x)
     (v*s (fetch (lookup x env) sto) sto)]
    ....))
```

- Previously, we just looked up a value with `lookup`
- Now we lookup a *location*
 - Have to use `fetch` to get its value from the store

Interpreting Variables

```
(define (interp [env : Env]
                [e : Expr]
                [sto : Store]) : Result
  (type-case Expr e
    [(Var x)
     (v*s (fetch (lookup x env) sto) sto)]
    ....))
```

- Previously, we just looked up a value with `lookup`
- Now we lookup a *location*
 - Have to use `fetch` to get its value from the store
- Produce that value, along with the unchanged store

Adding mutation: Curly-Mutvar

- Curly syntax: `{setvar! SYMBOL <expr>}`

Adding mutation: Curly-Mutvar

- Curly syntax: `{setvar! SYMBOL <expr>}`
 - `{setvar! x e}` changes the value of in-scope variable `x` to be the value of `e`

Adding mutation: Curly-Mutvar

- Curly syntax: `{setvar! SYMBOL <expr>}`
 - `{setvar! x e}` changes the value of in-scope variable `x` to be the value of `e`
- Interpreting

Adding mutation: Curly-Mutvar

- Curly syntax: `{setvar! SYMBOL <expr>}`
 - `{setvar! x e}` changes the value of in-scope variable `x` to be the value of `e`
- Interpreting
 - Just like `SetBox` except we get the location from the environment, instead of by evaluating a box

Adding mutation: Curly-Mutvar

- Curly syntax: `{setvar! SYMBOL <expr>}`
 - `{setvar! x e}` changes the value of in-scope variable `x` to be the value of `e`
- Interpreting
 - Just like `SetBox` except we get the location from the environment, instead of by evaluating a box

Adding mutation: Curly-Mutvar

- Curly syntax: {setvar! SYMBOL <expr>}
 - {setvar! x e} changes the value of in-scope variable x to be the value of e
- Interpreting
 - Just like SetBox except we get the location from the environment, instead of by evaluating a box

```
(define (interp [env : Env]
               [e : Expr]
               [sto : Store]) : Result
  (type-case Expr e
    [(Setvar! x e)
     (with ([e-val e-sto] (interp env e sto))
       (v*s e-val
            ; Get the location from the environment
            (override-store (cell (lookup x env) e-val)
                           e-sto))))]
    ....))
```

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*
 - Need a location to associate with the new variable

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*
 - Need a location to associate with the new variable
 - Need to make sure the argument value ends up at that location

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*
 - Need a location to associate with the new variable
 - Need to make sure the argument value ends up at that location
- If the argument is e.g. a number, then we have to make a new location for it

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*
 - Need a location to associate with the new variable
 - Need to make sure the argument value ends up at that location
- If the argument is e.g. a number, then we have to make a new location for it
- *What if the argument is already a variable?*

Function Calls

- To call a function, we evaluate the body in the environment extended with the argument value
 - Environment now takes *locations*
 - Need a location to associate with the new variable
 - Need to make sure the argument value ends up at that location
- If the argument is e.g. a number, then we have to make a new location for it
- *What if the argument is already a variable?*
 - Have a design decision

- If we implement function calls using pass-by-value, then:

- If we implement function calls using pass-by-value, then:
 - **Each function call generates a new location where its argument values are stored**

- If we implement function calls using pass-by-value, then:
 - **Each function call generates a new location where its argument values are stored**
 - If the arguments are variables, their values are looked up and copied to the new location

Pass-by-value interp

```
[(Call funExpr argExpr)
 (with ([fun-v fun-sto] (interp env funExpr sto))
  (with ([arg-v arg-sto] (interp env argExpr fun-sto))
   (let* (
    [funPair (checkAndGetClosure fun-v)] ;; Function might be
    [argVar (fst (fst funPair))]
    [funBody (snd (fst funPair))]
    [funEnv (snd funPair)]
    ;; Allocate a new location for the argument value
    [argLoc (new-location arg-sto)]
    ;; new store with the arg value at the new location
    ;; Use most recent store from arg
    [body-sto (override-store (cell argLoc arg-v) arg-sto)])
    ;; Evaluate the body in the extended *closure* env
    ;; with the new location bound to the parameter name,
    ;; using the new store with the argument value
    (interp (extendEnv (bind argVar argLoc) funEnv)
             funBody
             body-sto)))))]
```

- Pass-by-reference means that, when a function argument is a variable, the function's body is evaluated in an environment *where the argument variable is bound to the input variable's location*

Pass-by-reference

- Pass-by-reference means that, when a function argument is a variable, the function's body is evaluated in an environment *where the argument variable is bound to the input variable's location*
- Changes to one will be seen in the other

Interpreting

```
;; Everything the same as pass-by-value  
;; except we check if the argument is a variable  
;; and use its location instead of the new one if it is  
(type-case Expr argExpr  
  [(Var x)  
    (interp (extendEnv (bind argVar (lookup x env)) funEnv)  
              funBody  
              arg-sto)))  
  ; Otherwise do the same as call-by-value  
[else ....])
```

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference
- Pass by value means that a function can only mutate locations that it is *explicitly given*

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference
- Pass by value means that a function can only mutate locations that it is *explicitly given*
 - i.e. as box parameters

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference
- Pass by value means that a function can only mutate locations that it is *explicitly given*
 - i.e. as box parameters
- Pass by reference allows you to abstract over patterns of mutation

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference
- Pass by value means that a function can only mutate locations that it is *explicitly given*
 - i.e. as box parameters
- Pass by reference allows you to abstract over patterns of mutation
 - e.g. Write a function that says “change these variables in this way” that can be used over and over again

The Difference

- Any changes made to the parameter variable are lost in pass-by-value, but kept in pass-by-reference
- Pass by value means that a function can only mutate locations that it is *explicitly given*
 - i.e. as box parameters
- Pass by reference allows you to abstract over patterns of mutation
 - e.g. Write a function that says “change these variables in this way” that can be used over and over again
 - e.g. swap two variable’s values

Example

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}}
  {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}}
  {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}
    {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)
 - The final addition adds the value of {f y} to the value of y, which did not change

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}}
  {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)
 - The final addition adds the value of {f y} to the value of y, which did not change
 - {+ 6 2}, result of 8

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}
    {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)
 - The final addition adds the value of {f y} to the value of y, which did not change
 - {+ 6 2}, result of 8
- In pass-by-reference, x refers to the same store location as y

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                        {setvar! x {* x 3}}
                        x}}
    {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)
 - The final addition adds the value of {f y} to the value of y, which did not change
 - {+ 6 2}, result of 8
- In pass-by-reference, x refers to the same store location as y
 - Setting the value of x changes y because they both refer to the same location

Example

```
{letvar y 2
  {letvar f {fun {x} {begin
                    {setvar! x {* x 3}}
                    x}}
    {+ {f y} y}}}
```

- In both pass-by-value and pass-by-reference, the call to {f y} produces 6
- In pass-by-value, x has a different location than y, that started off with 2 (the value of y)
 - The final addition adds the value of {f y} to the value of y, which did not change
 - {+ 6 2}, result of 8
- In pass-by-reference, x refers to the same store location as y
 - Setting the value of x changes y because they both refer to the same location
 - Result is 12, since both the call and y have the value of 6

Which to Choose?

- We will use pass-by-value, since it's simpler

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference
- However, we can replicate pass-by-reference using Boxes

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference
- However, we can replicate pass-by-reference using Boxes
 - This is what e.g. Python does

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference
- However, we can replicate pass-by-reference using Boxes
 - This is what e.g. Python does
 - Most objects are implicitly boxed, so it seems like pass by reference

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference
- However, we can replicate pass-by-reference using Boxes
 - This is what e.g. Python does
 - Most objects are implicitly boxed, so it seems like pass by reference
 - Actually passing a value, but the value is (something like) a box

Which to Choose?

- We will use pass-by-value, since it's simpler
 - C++ is pass by value, but sometimes that value is a pointer/reference
- However, we can replicate pass-by-reference using Boxes
 - This is what e.g. Python does
 - Most objects are implicitly boxed, so it seems like pass by reference
 - Actually passing a value, but the value is (something like) a box
 - Immutable types (like tuples) are passed by value

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator & in C++

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator `&` in C++
- `{getloc SYMBOL}` produces a box whose location is the same location as whatever in-scope symbol it is given

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator `&` in C++
- `{getloc SYMBOL}` produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. `{getloc x}` would produce `{BoxV l}` where `l` is the location in the environment for `x`

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator `&` in C++
- `{getloc SYMBOL}` produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. `{getloc x}` would produce `{BoxV l}` where `l` is the location in the environment for `x`
- Interpreting:

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator `&` in C++
- `{getloc SYMBOL}` produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. `{getloc x}` would produce `{BoxV l}` where `l` is the location in the environment for `x`
- Interpreting:
 - Like `new-box`, except we look up the location in the environment instead of getting a new one

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator `&` in C++
- `{getloc SYMBOL}` produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. `{getloc x}` would produce `{BoxV l}` where `l` is the location in the environment for `x`
- Interpreting:
 - Like `new-box`, except we look up the location in the environment instead of getting a new one

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator & in C++
- {getloc SYMBOL} produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. {getloc x} would produce {BoxV l} where l is the location in the environment for x
- Interpreting:
 - Like new-box, except we look up the location in the environment instead of getting a new one

```
[(GetLoc x)
 (v*s (BoxV (lookup x env))
  ;; No changes to the store
 sto)]
```

- Now the box and the variable point to the *same location*

Aliasing

- To enable passing by reference, we add an *aliasing expression* to Curly-Mutvar
 - Like “address-of” operator & in C++
- {getloc SYMBOL} produces a box whose location is the same location as whatever in-scope symbol it is given
 - e.g. {getloc x} would produce {BoxV l} where l is the location in the environment for x
- Interpreting:
 - Like new-box, except we look up the location in the environment instead of getting a new one

```
[(GetLoc x)
 (v*s (BoxV (lookup x env))
  ;; No changes to the store
 sto)]
```

- Now the box and the variable point to the *same location*
- Changes to one are seen in the other

Example

```
{letvar doublebox! {fun {x} {set-box! x {* 2 {unbox x}}}}  
  letvar y 3  
  {begin {doublebox {getloc y}}  
    y}}
```

- Function takes in a box, gets its value, doubles it, and writes it to the same location

Example

```
{letvar doublebox! {fun {x} {set-box! x {* 2 {unbox x}}}}  
  letvar y 3  
  {begin {doublebox {getloc y}}  
    y}}
```

- Function takes in a box, gets its value, doubles it, and writes it to the same location
- The `getloc` makes a new box whose location is the same as `y`

Example

```
{letvar doublebox! {fun {x} {set-box! x {* 2 {unbox x}}}}  
  letvar y 3  
  {begin {doublebox {getloc y}}  
    y}}
```

- Function takes in a box, gets its value, doubles it, and writes it to the same location
- The `getloc` makes a new box whose location is the same as `y`
- When `doublebox!` runs it alters the value at the location of its box, which was the location of `y`

Example

```
{letvar doublebox! {fun {x} {set-box! x {* 2 {unbox x}}}}  
  letvar y 3  
  {begin {doublebox {getloc y}}  
    y}}
```

- Function takes in a box, gets its value, doubles it, and writes it to the same location
- The `getloc` makes a new box whose location is the same as `y`
- When `doublebox!` runs it alters the value at the location of its box, which was the location of `y`
- The final result is 6, since the value of `y` was changed