

# **Environments, Binding, and Scope**

CS 350

---

Dr. Joseph Eremondi

Last updated: July 13, 2024

# Overview

---

# The Road to Midterm

- Today: Environments in Curly

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait
- Thurs: Implementing Lambda in Curly

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait
- Thurs: Implementing Lambda in Curly
- Mon: Closures and Environments in Curly

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait
- Thurs: Implementing Lambda in Curly
- Mon: Closures and Environments in Curly
- Tues/Wed: lectures (not included on midterm)



# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait
- Thurs: Implementing Lambda in Curly
- Mon: Closures and Environments in Curly
- Tues/Wed: lectures (not included on midterm)
- Thurs: **MIDTERM**

# The Road to Midterm

- Today: Environments in Curly
- Tues: Lambda and First-class Functions in Plait
- Wed: Replacements for Recursion in Plait
- Thurs: Implementing Lambda in Curly
- Mon: Closures and Environments in Curly
- Tues/Wed: lectures (not included on midterm)
- Thurs: **MIDTERM**

**Everything up to and including Closures may appear on the midterm**

# Environments

---

- Evaluate their argument

# Functions Review

- Evaluate their argument
- Lookup the function body

# Functions Review

- Evaluate their argument
- Lookup the function body
- Replace the parameter variable with the

# Functions Review

- Evaluate their argument
- Lookup the function body
- Replace the parameter variable with the
- Evaluate the result

# Functions Review

- Evaluate their argument
- Lookup the function body
- Replace the parameter variable with the
- Evaluate the result
- If we ever interpret a variable, raise an error



# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!
- Want a way to have  $\mathcal{O}(1)$  function calls

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!
- Want a way to have  $\mathcal{O}(1)$  function calls
  - Not including the time to evaluate the function body

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!
- Want a way to have  $\mathcal{O}(1)$  function calls
  - Not including the time to evaluate the function body
- Substitution is forgetful

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!
- Want a way to have  $\mathcal{O}(1)$  function calls
  - Not including the time to evaluate the function body
- Substitution is forgetful
  - Just replaces function variable with expression

# The Problem

- Each substitution is  $\mathcal{O}(n)$  where  $n$  is the number of nodes in the function body AST
- This is *in addition* to the cost of actually evaluating the function
  - Very slow!
- Want a way to have  $\mathcal{O}(1)$  function calls
  - Not including the time to evaluate the function body
- Substitution is forgetful
  - Just replaces function variable with expression
  - Not very useful for debugging



# The Solution: Environments

- Data structure for *deferred substitution*

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:
  - Instead of replacing all  $x$  with value  $v$ , keep a list of replacements you need to do

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:
  - Instead of replacing all  $x$  with value  $v$ , keep a list of replacements you need to do
  - When you interpret  $x$ , check the environment before raising an error

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:
  - Instead of replacing all  $x$  with value  $v$ , keep a list of replacements you need to do
  - When you interpret  $x$ , check the environment before raising an error
  - If there's an entry for  $x$  in the environment, return that

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:
  - Instead of replacing all  $x$  with value  $v$ , keep a list of replacements you need to do
  - When you interpret  $x$ , check the environment before raising an error
  - If there's an entry for  $x$  in the environment, return that
    - Error otherwise

# The Solution: Environments

- Data structure for *deferred substitution*
  - List of variable/value pairs
- Intuition:
  - Instead of replacing all  $x$  with value  $v$ , keep a list of replacements you need to do
  - When you interpret  $x$ , check the environment before raising an error
  - If there's an entry for  $x$  in the environment, return that
    - Error otherwise
    - Means reference to undefined variable



# The Environment Data Structure: Bindings

# The Environment Data Structure: Bindings

```
;; Just a pair, but we get better names than fst and snd  
(define-type Binding  
  (bind [name : Symbol]  
        [val : Number]))
```

# The Environment Data Structure: Bindings

```
;; Just a pair, but we get better names than fst and snd  
(define-type Binding  
  (bind [name : Symbol]  
        [val : Number]))
```

```
;; Get helper functions from the type-def  
(bind-name (bind 'x 3))  
(bind-val (bind 'x 3))
```

# The Environment Data Structure: Bindings

```
;; Just a pair, but we get better names than fst and snd  
(define-type Binding  
  (bind [name : Symbol]  
        [val : Number]))
```

```
;; Get helper functions from the type-def  
(bind-name (bind 'x 3))  
(bind-val (bind 'x 3))
```

```
'x  
3
```

# The Environment Data Structure: Environments

# The Environment Data Structure: Environments

```
;; Lets us write Env instead of (Listof Binding)  
;; But it's not defining a new type,  
;; just a new name for the same type.  
(define-type-alias Env (Listof Binding))  
;; Environment is either empty or extended env  
(define emptyEnv : Env  
  empty)  
(define (extendEnv [bnd : Binding]  
                [env : Env])  
  : Env  
  (cons bnd env))  
  
emptyEnv  
(extendEnv (bind 'x 3) (extendEnv (bind 'y 4) empty))
```

# The Environment Data Structure: Environments

```
;; Lets us write Env instead of (Listof Binding)  
;; But it's not defining a new type,  
;; just a new name for the same type.  
(define-type-alias Env (Listof Binding))  
;; Environment is either empty or extended env  
(define emptyEnv : Env  
  empty)  
(define (extendEnv [bnd : Binding]  
               [env : Env])  
  : Env  
  (cons bnd env))  
  
emptyEnv  
(extendEnv (bind 'x 3) (extendEnv (bind 'y 4) empty))
```

```
'()  
(list (bind 'x 3) (bind 'y 4))
```

## Looking up variables

- Find the **first** binding in the environment



# Looking up variables

- Find the **first** binding in the environment
  - This is important for shadowing

## Looking up variables

- Find the **first** binding in the environment
  - This is important for shadowing
- Just a linear search, like we've seen lots already

## Looking up variables

- Find the **first** binding in the environment
  - This is important for shadowing
- Just a linear search, like we've seen lots already

# Looking up variables

- Find the **first** binding in the environment
  - This is important for shadowing
- Just a linear search, like we've seen lots already

```
(define (lookup [n : Symbol] [env : Env]) : Number
  (type-case (Listof Binding) env
    ;; Can't find a variable in an empty env
    [empty (error 'lookup "undefined variable")]
    ;; Cons: check if the first binding is the var
    ;; we're looking for.
    ;; Return its value if it is, otherwise
    ;; keep looking in the rest of the list
    [(cons b rst-env) (cond
                        [(symbol=? n (bind-name b))
                         (bind-val b)]
                        [else (lookup n rst-env)]))])
```

## Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*

## Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*
- Programs should run the exact same in both interpreters

## Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*
- Programs should run the exact same in both interpreters
- Strategy: add an extra context argument for Environment

## Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*
- Programs should run the exact same in both interpreters
- Strategy: add an extra context argument for Environment
  - Unlike fundefs, this will *change across recursive calls*



## Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*
- Programs should run the exact same in both interpreters
- Strategy: add an extra context argument for Environment
  - Unlike fundefs, this will *change across recursive calls*

# Intepreting CurlyFundef with Environments

- We can change the implementation *without changing the surface language*
- Programs should run the exact same in both interpreters
- Strategy: add an extra context argument for Environment
  - Unlike fundefs, this will *change across recursive calls*

```
(define (interp [env : Env]
               [defs : (Listof FunDef)]
               [e : Expr] ) : Number
  (type-case Expr e
    ....))
```

## Case: Plus etc.

- Exactly like before, except we have to pass the environment in the recursive call

## Case: Plus etc.

- Exactly like before, except we have to pass the environment in the recursive call
- Other operations are similar

## Case: Plus etc.

- Exactly like before, except we have to pass the environment in the recursive call
- Other operations are similar

## Case: Plus etc.

- Exactly like before, except we have to pass the environment in the recursive call
- Other operations are similar

```
;; {+ e1 e2} evaluates e1 and e2, then adds the results together  
[(Plus l r)  
 (+ (interp env defs l) (interp env defs r))]
```

## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment

## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment
- So we look in the environment and see if there's a value *bound* to  $x$



## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment
- So we look in the environment and see if there's a value *bound* to  $x$
- If there is return it

## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment
- So we look in the environment and see if there's a value *bound* to  $x$
- If there is return it
  - Otherwise, variable not found error

## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment
- So we look in the environment and see if there's a value *bound* to  $x$
- If there is return it
  - Otherwise, variable not found error

## Case: Variable

- Can't return an error, because we might have added a deferred substitution to the environment
- So we look in the environment and see if there's a value *bound* to  $x$
- If there is return it
  - Otherwise, variable not found error

```
[(Var x)  
 (lookup x env)]
```

## Case: Function call

- Just like before, we get the function body + variable, and value for argument

## Case: Function call

- Just like before, we get the function body + variable, and value for argument
- Still interpret body

## Case: Function call

- Just like before, we get the function body + variable, and value for argument
- Still interpret body
- Instead of replacing in body, add variable-value pair to the environment

## Case: Function call

- Just like before, we get the function body + variable, and value for argument
- Still interpret body
- Instead of replacing in body, add variable-value pair to the environment
  - Called *binding* the variable to its value



## Case: Function call

- Just like before, we get the function body + variable, and value for argument
- Still interpret body
- Instead of replacing in body, add variable-value pair to the environment
  - Called *binding* the variable to its value

## Case: Function call

- Just like before, we get the function body + variable, and value for argument
- Still interpret body
- Instead of replacing in body, add variable-value pair to the environment
  - Called *binding* the variable to its value

```
[(Call funName argExpr)
  (let* ([argVal (interp env defs argExpr)]
        [def (get-fundef funName defs)]
        [argVar (mkFunDef-arg def)]
        [funBody (mkFunDef-body def)])
    (interp (extendEnv (bind argVar argVal) emptyEnv) ;;<-----
            defs
            funBody)))]
```

- We evaluated the body of the function in the empty environment, plus a value for its variable

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment

# Static Scoping

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*

# Static Scoping

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*
  - Should be able to predict how a function behaves from how it's called

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*
  - Should be able to predict how a function behaves from how it's called
  - Don't want result to depend on context, just arguments

# Static Scoping

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*
  - Should be able to predict how a function behaves from how it's called
  - Don't want result to depend on context, just arguments
- Gives the same results as substitution.



# Static Scoping

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*
  - Should be able to predict how a function behaves from how it's called
  - Don't want result to depend on context, just arguments
- Gives the same results as substitution.
- We call this *static scoping*

# Static Scoping

- We evaluated the body of the function in the empty environment, plus a value for its variable
  - Didn't extend the additional environment
- Want functions to be *abstractions*
  - Should be able to predict how a function behaves from how it's called
  - Don't want result to depend on context, just arguments
- Gives the same results as substitution.
- We call this *static scoping*
- If we extend the environment from the call site, we get *dynamic scoping*

## Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error

## Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error
  - No value for y in body of f

## Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error
  - No value for y in body of f
- Dynamic scoping produces 6

## Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error
  - No value for y in body of f
- Dynamic scoping produces 6
  - Looks up y from g when evaluating f

## Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error
  - No value for y in body of f
- Dynamic scoping produces 6
  - Looks up y from g when evaluating f
- Dynamic scoping is **WRONG**

# Static Scoping Exapmple

```
{define {f x} {+ x y}}  
{define {g y} {f y}}  
{g 3}
```

- Static scoping says this is an error
  - No value for y in body of f
- Dynamic scoping produces 6
  - Looks up y from g when evaluating f
- Dynamic scoping is **WRONG**
  - You should understand it, but know that static scoping is what we want



## Implementing Let

---

- New language: Curly-Let

- New language: Curly-Let
- Curly-Fundef, but with one new feature

- New language: Curly-Let
- Curly-Fundef, but with one new feature
  - `{letvar x e1 e2}`

- New language: Curly-Let
- Curly-Fundef, but with one new feature
  - `{letvar x e1 e2}`
    - Gives x the value e1 in the expression e2

- New language: Curly-Let
- Curly-Fundef, but with one new feature
  - `{letvar x e1 e2}`
    - Gives x the value e1 in the expression e2
    - Called letvar so we don't confuse with plait

- New language: Curly-Let
- Curly-Fundef, but with one new feature
  - `{letvar x e1 e2}`
    - Gives x the value e1 in the expression e2
    - Called letvar so we don't confuse with plait
- We'll implement with both substitution and environments





```
(type-def Expr
  ....
  [(Letvar [x : Symbol]
           [xval : Expr]
           [body : Expr]])
)
```

- Parsing and Desugaring are the same as usual

```
(type-def Expr
  ....
  [(Letvar [x : Symbol]
           [xval : Expr]
           [body : Expr]])
  )
```

- Parsing and Desugaring are the same as usual
  - See Curly-Let.rkt

## Interpreting: Substitution

- Want variable to have the given value in the body

## Interpreting: Substitution

- Want variable to have the given value in the body
  - So just substitute the value for the variable in the body

## Interpreting: Substitution

- Want variable to have the given value in the body
  - So just substitute the value for the variable in the body
- Key detail: expression only evaluated once

## Interpreting: Substitution

- Want variable to have the given value in the body
  - So just substitute the value for the variable in the body
- Key detail: expression only evaluated once
  - Can have exponential speedup in some algorithms

## Interpreting: Substitution

- Want variable to have the given value in the body
  - So just substitute the value for the variable in the body
- Key detail: expression only evaluated once
  - Can have exponential speedup in some algorithms

# Interpreting: Substitution

- Want variable to have the given value in the body
  - So just substitute the value for the variable in the body
- Key detail: expression only evaluated once
  - Can have exponential speedup in some algorithms

```
(define (interp [defs : (Listof FunDef)] ;;NEW
          [e : Expr] ) : Number
  (type-case Expr e
    ;; ....
    [(Letvar x xexp body)
     (interp defs (subst x (interp defs xexp) body))])
```



## Interpreting: Environments

- Interpret the variable's value in the current environment

## Interpreting: Environments

- Interpret the variable's value in the current environment
- Interpret the let body in the *extended* environment

## Interpreting: Environments

- Interpret the variable's value in the current environment
- Interpret the let body in the *extended* environment
- When we hit *x* we'll look in the env

## Interpreting: Environments

- Interpret the variable's value in the current environment
- Interpret the let body in the *extended* environment
- When we hit *x* we'll look in the env

# Interpreting: Environments

- Interpret the variable's value in the current environment
- Interpret the let body in the *extended* environment
- When we hit x we'll look in the env

```
(define (interp [env : Env]
                [defs : (Listof FunDef)]
                [e : Expr] ) : Number
  (type-case Expr e
    ;; ....
    [(Letvar x xexp body)
     (let ([xval (interp env defs xexp)])
       (interp (extendEnv (bind x xval) env)
                defs body))])])
```

- Notice that we only add to the env to interp body, not xexp

- Notice that we only add to the env to interp body, not xexp
- This is because x is *in scope* for body but not xexp

- Notice that we only add to the env to interp body, not xexp
- This is because x is *in scope* for body but not xexp
- We say the **scope of a variable** is the part of the program in which its value is either substituted or bound



- Notice that we only add to the env to interp body, not xexp
- This is because x is *in scope* for body but not xexp
- We say the **scope of a variable** is the part of the program in which its value is either substituted or bound
- Let *extends* scope by adding a variable, while calls *transfer* scope to the function

- Notice that we only add to the env to interp body, not xexp
- This is because x is *in scope* for body but not xexp
- We say the **scope of a variable** is the part of the program in which its value is either substituted or bound
- Let *extends* scope by adding a variable, while calls *transfer* scope to the function
- Later we'll see more complex examples of scope

- Notice that we only add to the env to interp body, not xexp
- This is because x is *in scope* for body but not xexp
- We say the **scope of a variable** is the part of the program in which its value is either substituted or bound
- Let *extends* scope by adding a variable, while calls *transfer* scope to the function
- Later we'll see more complex examples of scope
  - e.g. in Plait, `let` and `let*` have different rules for what's in scope

# The Stack

- Environments have a *stack* structure

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding



# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages
  - Every time we call a function or define a variable we push onto the call stack

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages
  - Every time we call a function or define a variable we push onto the call stack
- Curly-Let and others have an *implicit* call stack

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages
  - Every time we call a function or define a variable we push onto the call stack
- Curly-Let and others have an *implicit* call stack
  - We don't keep the data structure ourselves

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages
  - Every time we call a function or define a variable we push onto the call stack
- Curly-Let and others have an *implicit* call stack
  - We don't keep the data structure ourselves
  - Instead, call `interp` recursively to add to the *Plait* call stack

# The Stack

- Environments have a *stack* structure
  - Push on new bindings when variables are defined
  - Don't directly pop, but will sometimes interpret in the unextended environment
- If we bind a value to a variable that's already in the environment, we say we *shadow* the old binding
  - Lookup always takes the most recent binding
- Part of the *call stack*
  - Theoretical in Curly
  - Actually implemented for most languages
  - Every time we call a function or define a variable we push onto the call stack
- Curly-Let and others have an *implicit* call stack
  - We don't keep the data structure ourselves
  - Instead, call `interp` recursively to add to the *Plait* call stack
  - When finished eval, `plait` returns is to part waiting for the result