

Qualification Round 2022 - Code Jam 2022

Punched Cards

Attempts

2

Penalties

0

Penalty Time

22:52:49

Points



Problem

A secret team of programmers is plotting to disrupt the programming language landscape and bring punched cards back by introducing a new language called *Punched Card Python* that lets people code in Python using punched cards! Like good disrupters, they are going to launch a viral campaign to promote their new language before even having the design for a prototype. For the campaign, they want to draw punched cards of different sizes in ASCII art.



The ASCII art of a punched card they want to draw is similar to an $\mathbf{R} \times \mathbf{C}$ matrix without the top-left cell. That means, it has $(\mathbf{R} \cdot \mathbf{C}) - 1$ cells in total. Each cell is drawn in ASCII art as a period (.) surrounded by dashes (-) above and below, pipes (|) to the left and right, and plus signs (+) for each corner. Adjacent cells share the common characters in the border. Periods (.) are used to align the cells in the top row.

For example, the following is a punched card with $\mathbf{R} = 3$ rows and $\mathbf{C} = 4$ columns:

```

. . + - + - + - +
. . | . | . | . |
+ - + - + - + - +
| . | . | . | . |

```

```

+--+--+--+
|. |. |. |. |
+--+--+--+

```

There are more examples with other sizes in the samples below. Given the integers **R** and **C** describing the size of a punched card, print the ASCII art drawing of it as described above.

Input

The first line of the input gives the number of test cases, **T**. **T** lines follow, each describing a different test case with two integers **R** and **C**: the number of rows and columns of the punched card that must be drawn.

Output

For each test case, output one line containing Case #*x* :, where *x* is the test case number (starting from 1). Then, output $(2 \cdot \mathbf{R}) + 1$ additional lines with the ASCII art drawing of a punched card with **R** rows and **C** columns.

Limits

Time limit: 5 seconds.

Memory limit: 1 GB.

Test Set 1 (Visible Verdict)

$$1 \leq \mathbf{T} \leq 81.$$

$$2 \leq \mathbf{R} \leq 10.$$

$$2 \leq \mathbf{C} \leq 10.$$

Sample

Sample Input



```

3
3 4
2 2
2 3

```

Sample Output



```

Case #1:
..+--+--+
..|. |. |. |
+--+--+--+
|. |. |. |
+--+--+--+
|. |. |. |
+--+--+--+

```

Case #2:

..+-+

..|. |

+--+

|. |.

+--+

Case #3:

..+--+

..|. |.

+--+

|. |.

+--+

Sample Case #1 is the one described in the problem statement. Sample Cases #2 and #3 are additional examples. Notice that the output for each case contains exactly $R \cdot C + 3$ periods.