

Consider the **Boston** data set from *R*. This example shows how to build tree models to predict the median price of houses **medv** in the Boston area. All other variables in the data set are considered predictors. It is of interest to identify which variables are most useful to predict the price of houses. Divide the dataset into a training (50%) and a test set as needed.

Single trees

- a) Use function **tree** from library **tree** to fit a regression tree. Use the full dataset. Plot the resulting tree. Plot the regions defined by the terminal nodes.
- b) Fit a regression tree on the training set. Plot the resulting tree. Prune the tree to five terminal nodes. Use cross validation to find the best number of terminal nodes.
- c) Which predictors are found most important? Report the test MSPE. Fit a tree with 5 splits. Compare MSPE.

Bagging

- d) Use function **randomForest** from library **randomForest** to fit regression trees with bagging. How many trees are bagged?
- e) Which predictors are found most important? Report the test MSPE. Fit regression trees limiting the number of trees to 25. Compare MSPE.
- f) Fit a random forest model to the training set. Compare the test MSPE with that of the bagging tree model.

Boosting

- g) Use function **gbm** from library **gbm** to fit 5000 boosted regression trees. Limit the depth of each tree to 4 using the option **interaction.depth=4**. Use option **distribution="gaussian"** since this is a *regression* tree.
- h) Which predictors are found most important? Report the test MSPE.

```

# trees.r    p328
library(MASS)      # Boston dataset
library(tree)      # tree()
setwd("C:/Users/USC Guest/Downloads") # to save eps files

# regression trees
#=====
dim(Boston)
# [1] 506  14
# medv is response, p=13 predictors

set.seed(1)
n = nrow(Boston)
train = sample(1:n,n/2) # 253 train rows
dtrain = Boston[train,]
dtest = Boston[-train,]

# tree - 2 predictors, full dataset
#=====
tree0=tree(medv~lstat+rm,Boston)

# scatterplot
plot(lstat~rm,Boston,pch=19,cex=0.6,col="red")
# regions
partition.tree(tree0,add = T,col="blue")

# tree plot
plot(tree0)
text(tree0,cex=0.75)
# inequality at split is for left arm
# $16950 is house prediction for rm < 6.94, and 14.4 < lstat < 19.83

# all predictors - train set
#=====
tree1=tree(medv~.,Boston,subset=train)
summary(tree1)

# Regression tree:
# tree(formula = medv ~ ., data = Boston, subset = train)
# Variables actually used in tree construction:
# [1] "lstat" "rm"    "dis"
# Number of terminal nodes:  8
# Residual mean deviance:  12.65 = 3099 / 245
# Distribution of residuals:
#      Min.    1st Qu.    Median      Mean    3rd Qu.      Max.
# -14.10000  -2.04200  -0.05357   0.00000   1.96000  12.60000

# "lstat" "rm"    "dis"    best classifiers
# RSS is 3099
# tree with 8 terminal nodes

```

```
# 253 - 8 = 245 dof

plot(tree1)
text(tree1,cex=0.75)
# partition.tree() does not apply for 3 classifiers

names(tree1)
# [1] "frame"      "where"      "terms"      "call"       "y"          "weights"

tree1$frame
#      var    n      dev      yval splits.cutleft splits.cutright
# 1  lstat 253 20894.6572 22.67312      <9.715      >9.715
# 2    rm 103  7764.5843 30.13204      <7.437      >7.437
# 4    rm  89 3310.1604 27.57640      <6.7815     >6.7815
# 8   dis  61 1994.6223 25.52131      <2.6221     >2.6221
# 16 <leaf>  5   615.7800 37.40000
# 17    rm  56  610.3336 24.46071      <6.4755     >6.4755
# 34 <leaf> 31   136.3555 22.54194
# 35 <leaf> 25   218.3200 26.84000
# 9  <leaf> 28   496.6496 32.05357
# 5  <leaf> 14   177.8436 46.37857
# 3  lstat 150 3464.7147 17.55133      <21.49     >21.49
# 6  lstat 120 1593.6987 19.16333      <14.48     >14.48
# 12 <leaf> 62   398.4892 21.04032
# 13 <leaf> 58   743.2822 17.15690
# 7  <leaf> 30   311.8897 11.10333

# 22.67312 is mean response (medv) in training set
# dev = deviance (square distance to the mean of that region)
# <leaf> rows are terminal nodes
#      sum of deviance of terminal nodes is 3099
#      sum of deviance decreases with large n. splits
# y val of terminal nodes are means of regions
# leftmost column is order of splitting
# 1st row splits into rows 2 and 3
# 2nd row splits into row 4 and 5
# n number of obs in terminal nodes

# pruning tree to 5 terminal nodes
#=====

pruned1=prune.tree(tree1,best=5)
pruned1$frame
#      var    n      dev      yval splits.cutleft splits.cutright
# 1  lstat 253 20894.6572 22.67312      <9.715      >9.715
# 2    rm 103  7764.5843 30.13204      <7.437      >7.437
# 4    rm  89 3310.1604 27.57640      <6.7815     >6.7815
# 8 <leaf>  61 1994.6223 25.52131
# 9 <leaf>  28  496.6496 32.05357
# 5 <leaf>  14  177.8436 46.37857
```

```
# 3  lstat 150  3464.7147 17.55133          <21.49          >21.49
# 6 <leaf> 120  1593.6987 19.16333
# 7 <leaf>  30   311.8897 11.10333
```

```
summary(pruned1)
# Regression tree:
# snip.tree(tree = tree1, nodes = c(6L, 8L))
# Variables actually used in tree construction:
# [1] "lstat" "rm"
# Number of terminal nodes:  5
# Residual mean deviance:  18.45 = 4575 / 248
# Distribution of residuals:
#      Min.  1st Qu.  Median      Mean 3rd Qu.      Max.
# -9.56300 -2.86300 -0.06333  0.00000  2.69700 24.48000
```

```
# Residual mean deviance larger than that of non-pruned
```

```
plot(pruned1)
text(pruned1)
```

```
# regions
plot(rm~lstat,Boston,pch=19,cex=0.6,col="red")
partition.tree(pruned1,add = T,col="blue")
# most important predictor goes in X-axis
```

```
# this way is wrong!
plot(lstat~rm,Boston,pch=19,cex=0.6,col="red")
partition.tree(pruned1,add = T,col="blue")
```

```
# cross validation - best n. terminal nodes
#=====
cv.boston=cv.tree(tree1)
plot(cv.boston)                                # 8 nodes is best tree
```

```
# test error rate
y.test= Boston[-train,"medv"]                  # y values in test set
newval= Boston[-train,]
yhat  = predict(tree1,newval)
```

```
# plot means of terminal regions (yhat) vs y
plot(yhat~y.test,pch=19,cex=0.5,ylim=c(10,50))
abline(0,1)
grid()
```

```
# identify houses with large residuals
```

```
res = y.test - yhat
# yhat is vector
# vector has no rownames
a = rownames(as.matrix(yhat))  # as.matrix required
```

```
text(yhat~y.test,labels=ifelse(res>10,a,""),pos=1,offset=0.25,cex=0.4)

# houses with res>5
a[res>5]
# [1] "8" "9" "124" "149" "180" "183" "185" "209" "210" "215"
# [11] "223" "264" "267" "292" "369" "370" "371" "409" "413" "474"

text(yhat~y.test,labels=ifelse(res>15|res<(-15),a,""),pos=1,offset=0.25,cex=0.4)

# only 8 different predictions (shown in the tree plot)
unique(yhat)
# 26.84000 22.54194 32.05357 17.15690 11.10333 21.04032 37.40000 46.37857

# test MSE
mspe = mean((yhat-y.test)^2) # 25.05
sqrt(mspe) # [1] 5.004557

# predictions are within $5005 of true median home value
```




Figure 1: Regions for the tree with 2 predictors *lstat* and *rm*, full dataset




Figure 2: Tree with 2 predictors *lstat* and *rm*, full dataset




Figure 3: Tree1 considering all predictors (but using only 3, lstat, rm, dis), training set




Figure 4: Pruned Tree with 5 terminal nodes, training set




Figure 5: Regions of pruned tree with 5 terminal nodes, training set




Figure 6: MSPE for different number of terminal nodes, from plotting output of `cv.tree()`




Figure 7: Output of `cv.tree()` from Tree with all predictors , training set

```

# bagging.r
# all 13 predictors should be considered at each split (mtry=p)

library(MASS)      # Boston dataset
library(randomForest)
setwd("C:/Users/Cesar/Favorites/Downloads") # to save eps files

dim(Boston) # [1] 506 14
# medv is response, p=13 predictors
n = nrow(Boston)
train = sample(1:n,n/2) # 253 train rows

# Bagging and Random Forests
#=====
set.seed(1)
bag1=randomForest(medv~.,data=Boston,subset=train,mtry=13,importance = T)
bag1
# randomForest(formula = medv ~ ., data = Boston, mtry = 13, importance = T,subset = train)
#
#           Type of random forest: regression
#           Number of trees: 500
# No. of variables tried at each split: 13
#           Mean of squared residuals: 10.54712
#           % Var explained: 87.23

# 10.54 is train MSE
# p = 13 predictors
# how to plot one of the 500 trees?
# n. terminal nodes?
# ask to find importance of predictors needed for: importance(bag1)

names(bag1)
# [1] "call"           "type"           "predicted"       "mse"
# [5] "rsq"            "oob.times"      "importance"       "importanceSD"
# [9] "localImportance" "proximity"      "ntree"           "mtry"
# [13] "forest"         "coefs"          "y"               "test"
# [17] "inbag"          "terms"
summary(bag1)
#           Length Class  Mode
# call           6    -none- call
# type           1    -none- character
# predicted      253    -none- numeric
# mse            500    -none- numeric
# rsq            500    -none- numeric
# oob.times      253    -none- numeric
# importance      26    -none- numeric
# importanceSD    13    -none- numeric
# localImportance 0     -none- NULL
# proximity       0     -none- NULL
# ntree           1     -none- numeric
# mtry            1     -none- numeric

```

```

# forest          11    -none- list
# coefs           0    -none- NULL
# y              253    -none- numeric
# test           0    -none- NULL
# inbag          0    -none- NULL
# terms          3    terms  call

# 500 train MSEs

# times train obs was OOB
table(bag1$oob.times)
# 144 153 158 160 161 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181
#   1   1   1   1   1   3   1   2   3   2   4   2   2   3   9   6   9   9   6  11  12  10  11   7
# 186 187 188 189 190 191 192 193 194 195 196 197 198 200 201 202 203 204 205 206 207 211 212 215
#   6   9   8   9   6   8   5   1   7   6   3   5   2   1   3   5   2   2   2   2   1   1   1   1

head(bag1$predicted)
#      175      410      307      222      391      344
# 21.90482 16.87879 34.48303 17.70609 14.03278 29.22515
head(bag1$y)
# 175 410 307 222 391 344
# 22.6 27.5 33.4 21.7 15.1 23.9
head(Boston[train,"medv"])
# [1] 22.6 27.5 33.4 21.7 15.1 23.9

# test set performance
y.test=Boston[-train,"medv"]          # y values in test set
yhat.bag = predict(bag1,newdata=Boston[-train,])

# residuals and row numbers
res = y.test - yhat.bag
a = rownames(as.matrix(yhat.bag))    # as.matrix is required

# plot means of terminal regions (yhat) vs y
plot(yhat.bag~y.test,pch=19,cex=0.5,ylim=c(10,50))
abline(0,1)
grid()
text(yhat.bag~y.test,labels=ifelse(res>5,a,""),pos=1,offset=0.25,cex=0.4)
# dots seem to cluster around 45 degree line

# MSEP
mean((yhat.bag-y.test)^2)    #[1] 12.81118    (this value changes)
# half of CV best tree MSEP -good!

# limit n. of trees to 25
bag2=randomForest(medv~.,data=Boston,subset=train,mtry=13,ntree=25)
yhat.bag = predict(bag2,newdata=Boston[-train,])
mean((yhat.bag-y.test)^2)    #[1] 14.29294    (this value changes)

```

```
# random forest (mtry < p)
#=====
set.seed(1)
forest1=randomForest(medv~.,data=Boston,subset=train,mtry=6,importance=T)
forest1
# randomForest(formula = medv ~ ., data = Boston, mtry = 6, importance = T,subset = train)
#           Type of random forest: regression
#           Number of trees: 500
# No. of variables tried at each split: 6
#           Mean of squared residuals: 11.64401
#           % Var explained: 85.9

# test set performance
yhat.rf = predict(forest1,newdata=Boston[-train,])
mean((yhat.rf-y.test)^2)      #[1] 11.20823
# little improvement over bagging

# importance of each predictor

importance(forest1)
#           %IncMSE IncNodePurity
# crim      12.4532926    1025.78688
# zn         2.7950457      52.75363
# indus     10.8424427    982.29679
# chas       0.9750709      67.04497
# nox       11.9825575   1264.03961
# rm        34.0973035   6667.19323
# age        9.6228463    458.13995
# dis       14.4846189   1280.22577
# rad        4.0478715    106.03032
# tax        7.6757169    481.81702
# ptratio   12.6021811   1030.07392
# black      6.7831663    373.05591
# lstat     27.4485257   6825.52957

# IncMSE - avg increase in MSE when predictor is excluded from model
# IncNodePurity - avg increase in RSS from splits using this predictor

# plot these two columns - for convenience
varImpPlot(forest1,main="")

# rm & lstat most important predictors
```





Figure 8: Predictors sorted by importance, rm and lstat, best predictors

```
# boosting.r    p331

library(MASS)      # Boston dataset
library(gbm)       # gbm()
setwd("C:/Users/Cesar/Favorites/Downloads") # to save eps files

dim(Boston)
# [1] 506 14
# medv is response, p=13 predictors
n = nrow(Boston)
set.seed(1)
train = sample(1:n,n/2) # 253 train rows

set.seed(1)
boost1=gbm(medv~.,data=Boston[train,],distribution="gaussian",n.trees=5000,interaction.depth=4)
# for categorical response use distribution="bernoulli"
# we limit the depth of each tree to 4 splits
# we want 5000 trees (default is 100 trees)

names(boost1)
# [1] "initF"           "fit"             "train.error"     "valid.error"
# [5] "oobag.improve"   "trees"           "c.splits"        "bag.fraction"
# [9] "distribution"    "interaction.depth" "n.minobsinnode"  "num.classes"
# [13] "n.trees"         "nTrain"          "train.fraction"  "response.name"
# [17] "shrinkage"       "var.levels"      "var.monotone"    "var.names"
# [21] "var.type"        "verbose"         "data"            "Terms"
# [25] "cv.folds"        "call"            "m"

# lambda -default value
boost1$shrinkage # [1] 0.001

# importance of predictors
summary(boost1); grid()
#           var      rel.inf
# lstat    lstat 45.96758091
# rm       rm   31.22024973
# dis      dis   6.80540085
# crim     crim  4.06995214
# nox      nox   2.55687077
# ptratio  ptratio 2.27547427
# black    black  1.79481300
# age      age   1.65100042
# tax      tax   1.36245454
# indus    indus  1.26933836
# chas     chas   0.80150463
# rad      rad   0.21054835
# zn       zn    0.01481202

# creates a plot
# lstat and rm best predictors
```

```
# test MSPE
y.test=Boston[-train,"medv"]      # y values in test set
yhat.boost=predict(boost1,newdata=Boston[-train,],n.trees=5000)
mean((yhat.boost-y.test)^2)       # [1] 11.84445
# similar to Random Forest MSPE

# lambda = 0.2   (shrinkage)
boost2=gbm(medv~.,data=Boston[train,],distribution="gaussian",n.trees=5000,
           interaction.depth=4,shrinkage=0.2,verbose=F)

yhat.boost=predict(boost2,newdata=Boston[-train,],n.trees=5000)
mean((yhat.boost-y.test)^2)       # [1] 11.51109

# n.trees in predict function cannot exceed
# n.trees in gbm()
```