

Project 6: Bacterial growth and parameter fitting

MCSB Bootcamp — Mathematical and Computational Track

Jun Allard

Model simulation

Given the parameters of a model, we can use ODE solvers to predict the behavior of a model, $x(t)$.

Given data, can we find which model parameters are the best fit?

- a. Write code to simulate the following model

$$\frac{dN}{dt} = \lambda N(1 - (N/\theta)^\alpha) \quad (1)$$

where the user (you) specifies the parameter values $\lambda = 1$, $\theta = 10^3$, $\alpha = 2$, and the initial condition $N(0) = 200$. Plot a time series of $N_{\text{sim}}(t)$.

```
# Your code here.
```

Data analysis

- b. Write code that loads bacterial growth experimental data into two arrays: one for the amount of bacteria $N_{\text{exp}}(t_i)$ and the other for the measurement time points t_i . Plot the time series $N_{\text{exp}}(t_i)$.

```
# Your code here.
```

- c. Plot the solution $N(t)$ and the experimental data $N_{\text{exp}}(t)$ on the same axes. Set $N(0)$ to match the experimental data exactly. Manually explore different parameter values of λ, θ, α to see which values best fit the data.

```
# Your code here.
```

Parameter learning

- d. Write code that computes the sum of squared error (SSE), which is

$$\text{SSE} = \sum_i (N_{\text{sim}}(t_i) - N_{\text{exp}}(t_i))^2$$

Hint: The Matlab solver `ode45` can take a time vector as an input argument. If the time vector has more than two elements, it will return the solution only at those elements. This is useful if you only need the solution at certain times t_i .

```
# Your code here.
```

- e. Using the code from the previous part, create a *function* that takes parameters and returns the SSE. Hint: A function can be defined in a separate m-file.

```
# Your code here.
```

- f. Use an automated minimization algorithm like Matlab's `fminsearch` to find the parameters that minimize the sum of squared error. These parameters are the “best fit” or “maximum likelihood” parameters $\hat{\lambda}, \hat{\theta}, \hat{\alpha}$. Plot, on the same axes, the experimental and best-fit model time series, $N_{\text{exp}}(t)$ and $N_{\text{sim}}(t)$.

```
# Your code here.
```

Model learning

- g. Now repeat the above, but use the model with $\alpha = 1$. Did the fit improve, or worsen?

```
# Your code here.
```

- h. Now repeat the above, but with

$$\frac{dN}{dt} = \lambda N.$$

Note this is numerically the same as Equation 1 with $\theta \gg N$. Did the fit improve, or worsen?

```
# Your code here.
```