

Cost Analysis: LoRaWAN vs. Mesh Network (ZAR)

1. Introduction

LoRaWAN (Standard)

LoRaWAN requires a star-topology where all sensors speak directly to a Gateway. This usually requires expensive, high-performance gateways but allows for cheap, standardized sensor modules.

- **CAPEX:** High (Gateways) / Low (Nodes)
- **OPEX:** Moderate (Recurring Network Server fees)

Mesh Network (Proprietary/Dual-Band)

Mesh allows cheap, standardized nodes to relay data to each other, forming a dynamic network that funnels to a simple, low-cost gateway.

- **CAPEX:** Low (Gateways) / High (Nodes)
- **OPEX:** Low (Self-managed, no external LNS fees assumed)

2. Assumptions & Scope

Currency Exchange: \$1 = R16.16 | €1 = R19.16

Exclusions

- Backhaul Connectivity (SIM/Ethernet cost).
- Sensor Manufacturing Base Cost (Housing/Battery/PCB).

Inclusions

- **Hardware:** Radio Modules & Gateways.
- **Software:** LoRaWAN Network Server (LNS) is included as a **monthly recurring cost**.

3. Cost Parameters

Component	Standard LoRaWAN	Mesh	Notes
Radio Module (CAPEX)	R120.00	R422.00 (€22)	Mesh module is ~R300 more expensive per unit.
Gateway (CAPEX)	R2,297.00	R950.00	LoRaWAN Gateway is ~R1,350 more expensive.
Solar Panel (CAPEX)	R 2,000.00		Solar panels (100W) are needed for remote LoRaWAN gateways
Battery (CAPEX)	R 8,000.00		Battery is needed for remote LoRaWAN gateways.
Charger Controller (CAPEX)	R 1,000.00		Charger controller is needed for remote LoRaWAN gateways.
LNS Fee (OPEX)		R0.00	Based on R 3716,80 (\$230)/1000 devices/month. Mesh is zero-rated for local routing.

4. Total Cost of Ownership (TCO) & Projections

Since LoRaWAN has an ongoing cost, we must compare Total Cost over time (M months).

Formula

LoRaWAN

Cost CAPEX = (Gateway Cost * Gateway Quantity) + (Radio Module Cost * Radio Module) +

Cost OPEX = LNS/1000* Node Quantity

Mesh

Cost CAPEX = (Gateway Cost * Gateway Quantity) + (Radio Module Cost * Radio Module)

Scenario A: Large Scale (1000 Sensors, 5 Gateways)

Context: A large commercial deployment.

- **LoRaWAN CAPEX:** $(R2,297.00 * 5) + (R120.00 * 1000) = R11485.00 + R120,00.00 = R131,485.00$

- **Mesh CAPEX:** $(R950.00 * 5) + (R422.00 * 1000) = R4,750.00 + R422,00.00 = R 426,750.00$
- **Initial Diff:** LoRaWAN is **R295,265 cheaper** upfront.
- **LoRaWAN OPEX:** $1000 * R3.76188 = R3716,80$
- **Break Even Time:** $R295,265.00 / R3716.80 \sim 79 \text{ months}$

Result: LoRaWAN is cheaper for the first **6.6 Years**. After 6.7 years, the cumulative monthly fees exceed the one-time savings on modules.

Scenario B: Medium Scale (100 Sensors, 2 Gateway one solar powered)

Context: A typical smart-farm.

- **LoRaWAN CAPEX:** $(R2,297.00 * 2 + (R2,000.00 + R8,000.00 R1,000.00)) + (100 * R120.00) = R15,594.00 + R12,000.00 = R 27,594.00$
- **Mesh CAPEX:** $(R950.00 * 2) + (R422 * 100) = R1,900.00 + R 42,200.00 = R 44,100.00$
- **Initial Diff:** LoRaWAN is **R 16,506.00 cheaper**.
- **LoRaWAN OPEX:** $R3.7168 * 100 = R 371.68$
- **Break Even Time:** $R25,606.00 / R 3771.68 \sim 44 \text{ months}$

Result: Consistent with the large sale; LoRaWAN wins for any project shorter than ~3.6 years.

Scenario C: Small & Complex (10 Sensors, 5 Gateways four solar powered)

Context: A confusing layout (tunnels/basements/ hills) requiring many gateways for few devices.

- **LoRaWAN CAPEX:** $(R2,276.00 * 5 + (R2,000.00 + R8,000.00 R1,000.00)*4) + (R 120.00 * 10) = R 11,380.00 + R44,000.00 + R 1,200.00 = R 56,580.00$
- **Mesh CAPEX:** $(R 950.00 * 5) + (R 422.00 * 10) = R 4,750.00 + R 4,220.00 = R 8,970.00$
- **Initial Diff:** Mesh is **R 47,610.00 cheaper** upfront.
- **LoRaWAN OPEX:** R45.30 / month.
- **Result:** Mesh starts cheaper and **stays cheaper forever**. LoRaWAN never catches up because it has higher CAPEX *and* higher OPEX in this scenario.

Exact Break-Even Point (5 Gateways four solar powered, 60 Months)

- To find the exact number of nodes N where LoRaWAN and Mesh costs are equal over a 5-year (60 month) period with 5 Gateways:

The Variables

- **Gateway Cost Diff:** $R 55,380.00 - R950.00 = R54,430.00$ (Infrastructure debt of LoRaWAN)
- **Module Cost Diff:** $R422 - R120 = R302$ (Upfront unit saving of LoRaWAN)
- **Operational Cost (60 mo):** $R3.7167 * 60 = R223.00$ (Recurring cost per LoRaWAN node)
- **Net Unit Saving (60 mo):** $R302 - R223.00 = R 78.99$

The Calculation:

$$N = R54,430/R78.99 = 642.3$$

- **Conclusion:** For 5 gateways over 5 years, the break-even point is exactly 642 sensors.
- **Below 642 sensors:** Mesh is cheaper due to avoiding R50,735 in gateway costs.
- **Above 642 sensors:** LoRaWAN is cheaper as the R302 unit saving eventually offsets the infrastructure and LNS costs.

5. Conclusion

The updated LNS fee of **R3.7167 per device/month** further solidifies LoRaWAN's position as the most cost-effective solution for scaled deployments.

1. For Standard Deployments (>50 sensors): LoRaWAN is the winner.

- * The significant CAPEX savings on radio modules (**R120 vs R422**) create a massive financial cushion.
- * LoRaWAN remains cheaper for a minimum of **6 to 6.6 years** (74-79 months) depending on scale. This duration likely exceeds the operational battery life of the sensors themselves.
- * *Recommendation*: For any commercial or agricultural project where sensor volume is the primary driver, LoRaWAN offers the lowest Total Cost of Ownership (TCO) over the device lifecycle.

2. For Complex/Niche Deployments (<20 sensors): Mesh is the winner.

- * In environments requiring many gateways for few devices (e.g., mine shafts, extremely hilly terrain), Mesh's lower gateway cost (**R950 vs R2297**) and zero monthly fees make it the superior choice.
- * Mesh starts cheaper and stays cheaper because the infrastructure savings are never eroded by recurring fees.

Final Recommendation

Standardize on LoRaWAN for general-purpose IoT sensor networks. The "break-even" point has moved out to over 6 years, making the initial investment in higher-cost gateways more than justified by the long-term module savings. Use Mesh only as a tactical solution for extreme coverage gaps that cannot be economically reached via LoRaWAN.