Author: J Scheepers

Cost Analysis: LoRaWAN vs. Mesh Network (ZAR)

1. Introduction

LoRaWAN (Standard)

LoRaWAN requires a star-topology where all sensors speak directly to a Gateway. This usually requires expensive, high-performance gateways but allows for cheap, standardized sensor modules.

- **CAPEX**: High (Gateways) / Low (Nodes)
- **OPEX**: Moderate (Recurring Network Server fees)

Mesh Network (Proprietary/Dual-Band)

Mesh allows cheap, standardized nodes to relay data to each other, forming a dynamic network that funnels to a simple, low-cost gateway.

- **CAPEX**: Low (Gateways) / High (Nodes)
- **OPEX**: Low (Self-managed, no external LNS fees assumed)

---

2. Assumptions & Scope

Currency Exchange: $1 = R16.16 | €1 = R19.16

Exclusions

- Backhaul Connectivity (SIM/Ethernet cost).
- Sensor Manufacturing Base Cost (Housing/Battery/PCB).

Inclusions

- **Hardware**: Radio Modules & Gateways.
- **Software**: LoRaWAN Network Server (LNS) is included as a **monthly recurring cost**.

---

3. Cost Parameters

Component	Standard LoRaWAN	Mesh	Notes
Radio Module (CAPEX)	R120.00	R422.00 (€22)	Mesh module is ~R300 more expensive per unit.
Gateway (CAPEX)	R2,297.00	R950.00	LoRaWAN Gateway is ~R1,350 more expensive.
Solar Panel (CAPEX)	R 2,000.00		Solar panels (100W) are needed for remote LoRaWAN gateways
Battery (CAPEX)	R 8,000.00		Battery is needed for remote LoRaWAN gateways.
Charger Controller (CAPEX)	R 1,000.00		Charger controller is needed for remote LoRaWAN gateways.
LNS Fee (OPEX)		R0.00	Based on R 3716,80 ($230)/1000 devices/month. Mesh is zero-rated for local routing.

---

4. Total Cost of Ownership (TCO) & Projections

Since LoRaWAN has an ongoing cost, we must compare Total Cost over time (M months).

Formula

LoRaWAN

Cost CAPEX = (Gateway Cost * Gateway Quantity) + (Radio Module Cost * Radio Module) +

Cost OPEX = LNS/1000* Node Quantity

Mesh

Cost CAPEX = (Gateway Cost * Gateway Quantity) + (Radio Module Cost * Radio Module)

Scenario A: Large Scale (1000 Sensors, 5 Gateways)

Context: A large commercial deployment.

- **LoRaWAN CAPEX**: (R2,297.00 * 5) + (R120.00 * 1000) = R11485.00 + R120,00.00 = R 131,485.00

- **Mesh CAPEX**: (R950.00 * 5) + (R422.00 * 1000) = R4,750.00+R422,00.00 = R 426,750.00
- **Initial Diff**: LoRaWAN is **R295,265 cheaper** upfront.
- **LoRaWAN OPEX**: 1000 * R3.76188 = R3716,80
- **Break Even Time**: R295,265.00 / R3716.80 ~ 79 months

Result: LoRaWAN is cheaper for the first **6.6 Years**. After 6.7 years, the cumulative monthly fees exceed the one-time savings on modules.

Scenario B: Medium Scale (100 Sensors, 2 Gateway one solar powered)
Context: A typical smart-farm.

- **LoRaWAN CAPEX**: (R2,297.00 * 2 + (R2,000.00 + R8,000.00 R1,000.00)) + (100 * R120.00) = R15,594.00 + R12,000.00 = R 27,594.00
- **Mesh CAPEX:** (R950.00 *2) + (R422*100)= R1,900.00 + R 42,200.00 = R 44,100.00
- **Initial Diff:** LoRaWAN is R 16,506.00 cheaper.
- **LoRaWAN OPEX**: R3.7168 *100 = R 371.68
- **Break Even Time**: R25,606.00 / R 3771.68 ~ 44 months

Result: Consistent with the large sale; LoRaWAN wins for any project shorter than ~3.6 years.

Scenario C: Small & Complex (10 Sensors, 5 Gateways four solar powered)
Context: A confusing layout (tunnels/basements/ hills) requiring many gateways for few devices.

- **LoRaWAN CAPEX**: (R2,276.00 * 5 + (R2,000.00 + R8,000.00 R1,000.00)*4) + (R 120.00 * 10) = R 11,380.00 + R44,000.00 + R 1,200.00 = R 56,580.00
- **Mesh CAPEX**: (R 950.00 * 5) + (R 422.00 * 10) = R 4,750.00 + R 4,220.00 = R 8,970.00
- Initial Diff: Mesh is **R 47,610.00** cheaper upfront.
- **LoRaWAN OPEX**: R45.30 / month.
- **Result**: Mesh starts cheaper and **stays cheaper forever**. LoRaWAN never catches up because it has higher CAPEX *and* higher OPEX in this scenario.

Exact Break-Even Point (5 Gateways four solar powered, 60 Months)
- To find the exact number of nodes N where LoRaWAN and Mesh costs are equal over a 5-year (60 month) period with 5 Gateways:

The Variables
- **Gateway Cost Diff:** R 55,380.00 - R950.00 = R54,430.00 (Infrastructure debt of LoRaWAN)
- **Module Cost Diff:** R422 - R120 = R302 (Upfront unit saving of LoRaWAN)
- **Operational Cost (60 mo):** R3.7167 * 60 = R223.00 (Recurring cost per LoRaWAN node)
- **Net Unit Saving (60 mo):** R302 - R223.00 = R 78.99

The Calculation:

N = R54,430/R78.99 = 642.3

- **Conclusion:** For 5 gateways over 5 years, the break-even point is exactly 642 sensors.
- **Below 642 sensors:** Mesh is cheaper due to avoiding R50,735 in gateway costs.
- **Above 642 sensors:** LoRaWAN is cheaper as the R302 unit saving eventually offsets the infrastructure and LNS costs.

The inclusion of the **R 3.7167 LNS fee** and high-capacity **Solar Infrastructure (R 11,000 per remote site)** shifts the financial viability significantly based on deployment topology and density.

1. **High-Density / Grid-Powered (Scenario A/B): LoRaWAN is the winner**. If grid power is available (eliminating solar costs) OR if density exceeds **650 sensors** per 5 gateways, the R 120 module cost provides an unbeatable TCO.
   Recommendation: Use LoRaWAN for large commercial hubs or sites with pre-existing power infrastructure.

2. **Distributed / Solar-Powered (Scenario B/4.4): Mesh is the winner.** When solar/battery kits (R 11,000 each) are required for gateways, the "Infrastructure Debt" scales to R 13,297 per site.
   In a typical farm layout (e.g., 100 sensors across 5 solar gateways), the R 302 module saving is not enough to offset the R 50,000+ infrastructure premium and recurring LNS fees.
   Recommendation: Use Mesh for typical agricultural deployments where sensor density per gateway is low to moderate.

3. **Small & Complex (Scenario C): Mesh is the definitive winner.** In environments requiring many gateways for very few devices (e.g., mine shafts, extremely hilly terrain, small remote outposts), Mesh's R 950 gateway cost and zero monthly fees make it the only logical choice. LoRaWAN in this scenario starts R 47,000 more expensive and the gap widens every month due to LNS fees.
   Recommendation: Use Mesh as a tactical solution for coverage gaps and low-density remote monitoring.

Final Recommendation

Standardize on Mesh for small-to-medium agricultural deployments (under 600 nodes) where solar-powered gateways are required for coverage. The "Infrastructure Debt" created by solar-powered LoRaWAN gateways (R13,297/site) and the LNS fees only make sense at extreme scale.

Use LoRaWAN only as a tactical solution for high-density industrial clusters or locations with existing grid-powered gateways where the CAPEX savings on the R120 modules can be realized without the solar infrastructure overhead.