

GE23131-Programming Using C-2024

Quiz navigation



[Show one page at a time](#)

[Finish review](#)

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Friday, 1 November 2024, 7:57 PM
Duration	51 days 21 hours

Question **1**

Correct

Marked out of
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false
Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main ()
3 {
4     int a, b, one, two;
5     scanf ("%d %d", &a, &b);
6     one = a%10;
7     two = b%10;
8     one == two ? printf ("true") : printf ("false");
9     return 0;
10 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print *Weird*
- If ***n*** is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If ***n*** is even and in the inclusive range of **6** to **20**, print ***Weird***
- If ***n*** is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

A single line containing a positive integer, ***n***.

Constraints

· $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main ()
3 {
4     int n;
5     scanf ("%d", &n);
6     if (n%2 != 0)
7         printf ("Weird");
8     else if (n%2 == 0 && n <= 5)
9         printf ("Not Weird");
10    else if (n%2 == 0 && n <= 20)
11        printf ("Weird");
12    else if (n%2 == 0 && n > 20)
13        printf ("Not Weird");
14    return 0;
15 }
```

✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 [Flag question](#)

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3*3 + 4*4 = 25 = 5*5$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main ()
3  {
4      int a, b, c;
5      scanf ("%d %d %d", &a, &b, &c);
6      if (a*a + b*b == c*c || a*a + c*c == b*b || b*b + c*c == a*a)
7          printf ("yes");
8      else
9          printf ("no");
10     return 0;
11 }
```

	Input	Expected	Got	
✓	3	yes	yes	✓
	5			
	4			
✓	5	no	no	✓
	8			
	2			

Passed all tests! ✓

Finish review